

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	OmicSync: Reliability-Aware Spatial Multi-Omics Clustering with Evidence-Constrained LLM Reasoning	[Paper] [Paper: PDF p. 1]
Authors	Rabeya Tus Sadia, Qiang Ye, Qiang Cheng	[Paper] [Paper: PDF p. 1]
Venue	arXiv (preprint)	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Core task	Spatial domain clustering + per-spot reliability auditing via evidence-constrained LLM reasoning	[Paper] [Paper: PDF p. 1–2]
Key innovation	Coupling of uncertainty-aware MoE routing, multi-strategy LLM reasoning, and REINFORCE-guided latent space refinement — all grounded in model-derived per-spot signals	[Paper] [Paper: PDF p. 2, 7, 9–10]
Target modalities	RNA (gene expression), ADT (surface proteins), histology (H&E image patches), spatial coordinates	[Paper] [Paper: PDF p. 3–5]
Datasets	Four 10x CytAssist FFPE spatial proteomics datasets: Human Tonsil, Human Breast Cancer, Human Glioblastoma, Human Tonsil with Add-on Antibodies	[Paper] [Paper: PDF p. 11]
Baselines	GROVER, MISO, SpatialGlue, COSMOS	[Paper] [Paper: PDF p. 11]
Evaluation metrics (Task A)	ARI, NMI, FMI, SiLC, AMI, Jaccard, CHI, Purity, DBI	[Paper] [Paper: PDF p. 11]
Evaluation metrics (Task C)	Grounding Rate (GR), Confidence Alignment (CA), Spatial Consistency (SC)	[Paper] [Paper: PDF p. 9, 13]
Code/data availability	Not stated in text; no URL or repository mentioned	Not assessable from supplied material

02 一句话总结

OmicSync 是首个将空间多组学聚类、模型内生可靠性信号提取（软分配置信度、模态路由权重、MC-Dropout 路由不确定性）、五策略证据约束型 LLM 推理、以及基于 REINFORCE 的推理质量反馈闭环训练（OmicSync-R）统一于单框架的可信空间域发现方法；它不追求“黑箱聚类+后验解释”，而是构建从聚类头输出到自然语言审计的可追溯证据链，使每个空间点的域分配具备可验证的分子依据、模态归因与空间支持；其局限在于推理不可微、奖励设计对 k 敏感、且仅在 Human Breast Cancer 上验证了闭环有效性。

03 研究问题

现有空间多组学聚类方法（如 GROVER、SpatialGlue）仅输出扁平化域划分，无法回答三个关键临床/分析级问题：（1）哪些spot的分配是可靠的？（2）哪个模态（RNA/ADT/图像）主导了该分配决策？（3）为何应信任该分配？——这导致下游分析（如差异表达、配体-受体推断）可能被边界spot或低质量数据引入的错误分配系统性污染。作者洞察到：可靠性不能仅靠聚类指标（如ARI）全局评估，而需在spot粒度上耦合**可计算的内部信号**（confidence, routing uncertainty, modality weight）与**可审计的外部表达**（LLM生成的自然语言报告）。因此，论文路径不是改进聚类算法本身，而是构建一个“聚类-信号提取-证据构造-推理生成-（可选）反馈优化”的全栈式可靠性增强范式。

04 研究背景与发展路径

空间多组学分析已从单模态（RNA-only）[9] → 图神经网络整合空间邻域（STAGATE, GraphST）[10–11] → 多模态融合（GROVER, SpatialGlue, COSMOS）[5–8]，但所有阶段均止步于“聚类结果输出”。解释性仍停留在注意力热图或SHAP等特征归因层面[12]，缺乏spot级、多信号协同、自然语言可读的因果性解释。LLM在单细胞中已有应用（细胞类型注释、通路摘要）[13–15]，但未与空间聚类模型耦合。OmicSync的发展路径是：以GROVER的KAN-GCN骨干为基线[5]，在其上叠加五大新组件——空间位置编码、跨模态Transformer、不确定性MoE路由、ClusteringHead/CellTypeHead/ImputationHeads三头结构、以及证据约束推理模块——从而将“鲁棒表征学习”升级为“鲁棒+可审计+可反馈”的闭环分析。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Opaque clustering outputs	Downstream analyses treat all spot assignments as equally reliable, propagating errors into biological conclusions [Paper] [Paper: PDF p. 1]	Existing methods return only flat partitions without reliability indicators [Paper] [Paper: PDF p. 1]	[Paper] [Paper: PDF p. 1]: “most spatial domain discovery methods provide only cluster assignments, without indicating assignment reliability, modality contributions, or why a domain decision should be trusted.”

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Lack of spot-level interpretability	No mechanism to explain <i>why</i> a specific spot is assigned to domain k , nor which molecular evidence supports it	Explainability remains underdeveloped; attention/SHAP reveal influential features but not spot-specific, multi-signal grounded explanations [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 3]: “they generally do not provide spot-specific explanations of clustering assignments grounded in multiple internal reliability signals.”
Modality contribution ambiguity	Cannot quantify how much RNA vs. ADT vs. histology contributed to a given assignment	Prior multimodal methods lack interpretable modality-routing mechanisms [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 4]: “modality-routing weights that indicate the relative weighting of RNA, ADT, and histology in the fused representation.”
Uncertainty unquantified per spot	No estimate of epistemic uncertainty for individual spot assignments, hindering trust calibration	Epistemic uncertainty estimation is computationally challenging in deep models [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 2]: “Quantifying how confident the model is in each assignment [...] is therefore not merely desirable but crucial [...]”

06 核心理念

OmicSync 的核心理念是：**将聚类模型自身产生的中间信号（而非原始输入）作为唯一证据源，构造结构化证据字典，并以此严格约束LLM生成spot级可靠性报告；再将报告的质量（faithfulness）作为非可微奖励，通过REINFORCE反向塑造聚类头的latent representation。**这不是“用LLM解释黑箱”，而是“让聚类头显式产出可解释信号 → 让LLM只消费这些信号 → 让LLM的输出质量反过来优化聚类头”。其哲学基础是：**可审计性（auditability）必须源于信号可追溯性（traceability），而可追溯性要求证据源与推理目标在计算图中同构。**Figure 1 的架构图即体现此思想：所有箭头最终汇聚于“structured evidence dictionary”这一枢纽，再单向流向reasoning module。

07 方法总览

OmicSync 是端到端可训练框架，包含六大核心组件：（1）**预处理**：RNA（log-normalized PCA）、ADT（CLR-normalized PCA）、Histology（UNI ViT-L/16 embedding）；（2）**空间位置编码**：2D正弦位置编码注入坐标先验；（3）**KAN-GCN模态编码器**：对每个模态分别施加空间图卷积与特征图卷积，再经intra-modality attention融合；（4）**CrossModalTransformer**：将三模态token堆叠为序列，通过self-attention实现跨模态上下文富集；（5）**UncertaintyMoE**：MC-Dropout下评估gating network，输出mean routing vector（模态权重）与epistemic uncertainty（方差）；（6）**多头输出**：ClusteringHead（Student’s t-distribution soft assignment）、CellTypeHead（Leiden伪标签监督）、ImputationHeads（掩码重建自监督）。OmicSync-R在此基础上，将ClusteringHead的soft assignment分布采样后送入reasoning module，用GR/CA/SC加权得分作为REINFORCE reward，更新ClusteringHead参数。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
SpatialPositionEncoder	将2D坐标映射为4F维正弦编码并投影，加至各模态特征前	解决“相同分子谱但不同空间位置”（如生发中心边缘vs中心）的表示歧义，注入组织架构先验	Input: spot coordinate $q \in \mathbb{R}^2$; Output: $PE_m(q) \in \mathbb{R}^{dm}$	[Paper] [Paper: PDF p. 5]: “This design allows the model to incorporate spatial context and tissue architecture that are not captured by molecular composition alone.”	移除将导致空间同质区域（如tonsil germinal center）内spot区分能力下降，ARI/SilC在homogeneous dataset上显著恶化 [Paper] [Paper: PDF p. 7]
UncertaintyModule	MC-Dropout下运行gating network，输出mean routing vector $\bar{g}$ 和epistemic uncertainty u_i	提供两个关键可靠性信号：模态贡献可解释性（ $\bar{g}$ ）与路由决策稳定性（ u_i ），二者均为Task C证据源	Input: averaged cross-modal token $\tilde{e}$; Output: $\bar{g} \in [0,1]^3, u_i \in \mathbb{R}_{\geq 0}$	[Paper] [Paper: PDF p. 6–7]: “The mean gate values $\bar{g} \in [0,1]^3$ are thresholded [...] The scalar u_i [...] is defined as the epistemic routing uncertainty [...] Both u_i and $\bar{g}$ are provided as interpretable model outputs and used by Task C.”	移除将丢失模态归因与不确定性估计，Task C无法生成modality-routing/uncertainty-focused解释；Table 3显示Uncertainty策略CA=1.00，证明其必要性 [Paper] [Paper: PDF p. 13]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal		
ClusteringHead	Student’ s t- kernel soft assignment + self- sharpening KL loss	实现无监督域 聚类，同时输出soft assignment q_{ik} ，用于计算 confidence q 和runner-up margin Δ_i ——二者为 Task C核心证据	Input: L2- normalized latent $\hat{z}_i$; Output: $q_i \in$ $[0,1]^K$, $q =$ $\max_k q_{ik}$, $R_i =$ $\operatorname{argmax}_k q_{ik}$	[Paper] [Paper: PDF p. 7]: “The predicted domain for spot i is $R_i =$ $\operatorname{argmax}_k q_{ik}$, and the assignment confidence is defined as q $= \max_k q_{ik}$.”	移除则无聚类 输出，整个框架失效； Table 5显示 q 与 u 负相关 ($r=-0.42$)， 证明其作为独立可靠性维度的价值 [Paper] [Paper: PDF p. 15]		
Evidence- Constrained Reasoning Module	将Task A信号 组装为结构化 字典，驱动 Llama-3.3- 70B生成5种 策略的自然语言报告	将量化信号转化为人类可理解、可审计的spot级理由，实现“从数字到叙事”的可信跃迁	Input: R_i , q , Δ_i , $\bar{g}$, u_i , top markers, 5- nearest neighbourhood; Output: $J^G \in \mathbb{N}^L$	[Paper] [Paper: PDF p. 8]: “This coupling is designed to make the explanations auditable, so that each generated justification can be traced back to the model- derived evidence supporting the corresponding spatial- domain assignment.”	移除则退化为 传统聚类； Figure 2与 Table 2证明其能生成空间一致的pseudo-cell-type maps，表明信号有效 [Paper] [Paper: PDF p. 13–14]		
OmicSync-R (REINFORCE loop)	以GR/CA/SC 加权得 R_i ，作为reward优化ClusteringHead的 q 分布	解决base OmicSync中reasoning与clustering解耦问题，使LLM的“好理由”能正向塑造latent space	Input: q_i , sampled $a_i \sim$ Categorical(q_i); Output: $L_{reinforce} =$ $-\sum_i \operatorname{sg}(R_i - b_i) \log q_{i,a_i}$	[Paper] [Paper: PDF p. 9–10]: “The REINFORCE loss applied to the assignment distribution is $L_{reinforce} = -1/$	S_R	$\sum_i \in S_R$ $\operatorname{sg}(R_i - b_i) \log q_{i,a_i} [\dots]$ allowing reasoning coherence to shape the learned latent structure.”	移除则无闭环；Table 7显示OmicSync-R在Human Breast Cancer上8/9指标提升，证明其有效性 [Paper] [Paper: PDF p. 17]

09 关键公式与符号

论文未提供完整可核验的单一主公式，但明确定义了以下关键符号与公式（全部可溯源至PDF页码）：

- **Soft assignment & confidence:** $q_{ik} = (1 + \| \hat{z}_i - \mu_k \|^2)^{-1} / \sum_k (1 + \| \hat{z}_i - \mu_k \|^2)^{-1}$ [Equation 15, p.7]; $q = \max_k q_{ik}$ [Equation 3, p.4]
- **Modality routing & uncertainty:** $\bar{g} = (1/T) \sum_t g_{i,t}$, $u_i = \sum_m \text{Var}_t[g_{i,m,t}]$ [Equations 12–13, p.6]
- **Grounding Rate (GR):** $GR_i = |M_i \cap J_i| / |M_i|$, where M_i = supplied marker set, J_i = markers mentioned in J_i [Equation 18, p.9]
- **Confidence Alignment (CA):** Binary metric assessing match between u_i tier (LOW/MEDIUM/HIGH) and hedging language in J_i [Paper] [Paper: PDF p.9]
- **Spatial Consistency (SC):** Binary metric assessing whether J_i correctly references dominant neighbourhood composition [Paper] [Paper: PDF p.9]
- **REINFORCE reward:** $R_i = w_1 GR_i + w_2 CA_i + w_3 SC_i$, with $w_1=0.5$, $w_2=0.3$, $w_3=0.2$ [Equation 20, p.9]
- **OmicSync-R objective:** $L_{\text{OmicSync-R}} = L_{\text{OmicSync}} + \lambda_R L_{\text{reinforce}}$ [Equation 24, p.10]
- **Key variables:** $Z \in \mathbb{R}^{N \times d}$ (shared latent), $Q \in [0,1]^{N \times K}$ (soft assignment), $G \in [0,1]^{N \times 3}$ (modality-routing matrix), $u \in \mathbb{R}^N$ (epistemic uncertainty vector), $c \in [0,1]^N$ (confidence vector) [Paper] [Paper: PDF p.3–4]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Table 1 (Clustering rank)	OmicSync achieves superior clustering quality across heterogeneous benchmarks	Compared against GROVER, MISO, SpatialGlue, COSMOS on 4 CytAssist FFPE datasets using same K range (6–10) and pseudo-reference labels	Best avg. rank on Tonsil (1.44), Glioblastoma (1.78), Tonsil Add-on (1.22); 2nd on Breast Cancer (2.33); best ARI on all four	OmicSync learns more biologically coherent latent representations than baselines, especially on datasets with richer protein panels (Add-on) or homogeneous structure (Tonsil)	Not that OmicSync is universally superior — its Purity < GROVER on Tonsil suggests trade-off between cluster compactness and label purity	[Paper] [Paper: PDF p.12]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Figure 2 & Table 2 (Task B)	CellTypeHead with Leiden pseudo-labels regularises latent space to preserve local cell-type organisation	Qualitative visualisation of pseudo-cell-type maps; no external ground-truth used	Maps show locally structured patterns (e.g., large coherent regions in Glioblastoma, fine-grained mixing in Tonsil)	Semi-supervised pseudo-label regularisation encourages latent space to retain local cellular hierarchy, even without true annotations	Not that CellTypeHead achieves accurate cell-type classification — authors explicitly state it's not a benchmark [Paper] [Paper: PDF p.13]	[Paper] [Paper: PDF p.13–14]
Table 3 & Figure 3A (Reasoning strategy)	Stepwise prompting yields highest joint faithfulness	Five strategies (Standard, Stepwise, Counterfactual, Contrastive, Uncertainty) evaluated on same 40 spots	Stepwise: GR=1.00, CA=1.00, SC=0.975; Uncertainty: GR=0.074, CA=1.00	Structured, stage-wise prompting maximally leverages all supplied evidence types; Uncertainty strategy trades GR for CA by design	Not that Stepwise is optimal for all use cases — e.g., Uncertainty strategy is best when confidence calibration is primary goal	[Paper] [Paper: PDF p.13, 21]
Table 4 & Figure 3B,C (Dataset-level reasoning)	Reasoning quality correlates with dataset properties (e.g., antibody panel size, tissue homogeneity)	Aggregated GR/CA/SC across 5 strategies per dataset	Tonsil Add-on: highest SC (0.84), lowest u (0.0526); Tonsil: highest CA (0.94); Breast Cancer: lowest SC (0.58)	Dataset-level reasoning fidelity reflects underlying data quality and biological heterogeneity — e.g., richer ADT panel reduces routing uncertainty	Not that reasoning quality directly measures biological truth — it measures alignment with <i>model's own evidence</i> , which may contain upstream bias	[Paper] [Paper: PDF p.13, 21]
Table 5 (Reliability audit)	High-confidence spots exhibit lower uncertainty and higher spatial homogeneity	Three-tier split ($c \geq 0.35$, $0.20 < c < 0.35$, $c < 0.20$) on 40 explained spots	High- c : $\bar{u}=0.034$, spatial hom.=75.6%; Low- c : $\bar{u}=0.111$ ($3.3\times$), spatial hom.=60.0%	The two core reliability signals (c , u_i) capture meaningful, complementary aspects of assignment stability and local support	Not that c and u_i are interchangeable — they're moderately anti-correlated ($r=-0.42$), confirming distinct roles	[Paper] [Paper: PDF p.15, 21]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Table 6 & 7 (OmicSync-R)	REINFORCE reward improves clustering metrics on challenging dataset	OmicSync-R vs base OmicSync on Human Breast Cancer ($k=10$); 22 reasoning updates over epochs 50–575	ARI +0.99 (45.73→46.72); 8/9 metrics improved; GR≈0.98, CA peaked at 0.775	Reasoning-quality feedback can serve as effective auxiliary signal for latent space refinement, particularly on datasets where base model underperforms	Not that OmicSync-R is robust across k — benefit is concentrated at $k=10$; $k=6-9$ yield ARI <28 [Paper] [Paper: PDF p.17]	[Paper] [Paper: PDF p.16–17]

11 对结论的正确理解

OmicSync 的核心贡献是**构建了一个从聚类输出到自然语言审计的可追溯证据链**，而非宣称其聚类性能绝对最优。其“best rank”是相对于所选四个基线在特定评估协议（ $K=6-10$, pseudo-reference labels）下的相对优势，且存在trade-off（如Tonsil上Purity更低）。Task C的“faithfulness”指标（GR/CA/SC）衡量的是LLM生成文本与**模型自身输出信号**的一致性，而非与ground-truth生物学事实的一致性——例如GR=1.00仅表示LLM提到了所有供给的marker名，不保证这些marker确为生物学关键驱动因子。OmicSync-R的成功（+0.99 ARI）证明了“reasoning coherence”可作为latent space的有用正则项，但其效果受限於reward设计（ k -sensitive）、计算开销（220 LLM calls）和dataset scope（仅1/4验证）。Figure 2的pseudo-cell-type maps是**定性正则化效果的间接证据**，而非细胞类型预测的定量结果——作者反复强调Task B是semi-supervised regulariser，非benchmark [Paper] [Paper: PDF p.8,13]。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Post-hoc nature of base Task C	“does not backpropagate into the clustering objective; it explains rather than optimises the partition” [Paper] [Paper: PDF p.18]	Addressed by OmicSync-R via REINFORCE [Paper] [Paper: PDF p.18]	[Paper] [Paper: PDF p.18]
OmicSync-R resource intensity	“requires repeated LLM-based explanation generation and reward evaluation during training [...] more resource-intensive than base OmicSync” [Paper] [Paper: PDF p.10,11]	Explore “amortised reward models, cached reasoning evaluations, and smaller verifier models” [Paper] [Paper: PDF p.18]	[Paper] [Paper: PDF p.10,11,18]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Reward sensitivity to k	“The benefit [...] is concentrated at $k = 10$. For $k = 6-9$, OmicSync-R yields ARI values [...] substantially below its ARI of 46.72 at $k = 10$ ” [Paper] [Paper: PDF p.17]	Investigate “reward annealing or multi- k training to reduce k -sensitivity” [Paper] [Paper: PDF p.18]	[Paper] [Paper: PDF p.17,18]
Task B pseudo-label limitation	“Task B pseudo-labels are RNA-derived, so the reported analysis evaluates the regularisation benefit [...] rather than external classification accuracy” [Paper] [Paper: PDF p.18]	Not explicitly proposed, but implies need for multi-modal ground-truth or better pseudo-label strategies	[Paper] [Paper: PDF p.18]
Reasoning module scope constraint	“its explanations are limited to the five supplied evidence types [...] and inherit any upstream uncertainty in those signals” [Paper] [Paper: PDF p.18]	Extend to “additional modalities, such as ATAC-seq chromatin accessibility and spatial metabolomics” [Paper] [Paper: PDF p.18]	[Paper] [Paper: PDF p.18]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The “Stepwise” strategy achieves perfect GR/CA but $SC = 0.975 < 1.00$, while “Contrastive” has $SC = 0.650$ — yet both use identical evidence dictionary. This suggests SC metric may conflate <i>neighbourhood composition reporting</i> with <i>correct interpretation of its relevance</i> .	SC evaluates whether J_i “correctly references” neighbourhood composition, but does not assess whether that reference is <i>biologically meaningful</i> . E.g., stating “5 neighbours are Vascular” is $SC = 1.00$, but failing to link it to vascular biology is undetected.	Over-reliance on SC could mislead: high SC may reflect rote copying of evidence, not insightful reasoning. This undermines the claim that Stepwise is “most faithful” overall.	Redesign SC to require <i>causal linking</i> : e.g., “Vascular neighbours support vascular assignment because...” — scored by biomedical expert or LLM verifier. Compare SC scores before/after adding this requirement.	[Paper] [Paper: PDF p.9,13]: SC definition is purely referential (“correctly references”), not inferential. Table 3 shows Stepwise $SC = 0.975$, not 1.00, implying some failures in referencing.

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
OmicSync-R’ s reward weights ($w_1=0.5$, $w_2=0.3$, $w_3=0.2$) are fixed and unvalidated. GR dominates, yet Table 3 shows Uncertainty strategy has GR=0.074 by design — meaning its reward is almost entirely driven by CA/SC, which are less stable (see Table 6: CA drops to 0.313 at epoch 425).	Fixed weights may over-prioritise GR (easily gamed by LLM listing all markers) while under-weighting harder-to-optimize SC, whose late-training decline (mean SC=0.21 after epoch 400) suggests fundamental misalignment between neighbourhood evidence and final assignments.	If reward is skewed, OmicSync-R may optimize for “marker-listing ability” rather than true reasoning coherence, limiting generalizability. This questions the validity of using R_t as a proxy for holistic “reasoning quality” .	Conduct ablation: train OmicSync-R with $w_1=0.2$, $w_2=0.4$, $w_3=0.4$; compare final ARI and SC trajectory. Also, correlate R_t with human expert rating of J_t faithfulness on subset.	[Paper] [Paper: PDF p.9]: weights are stated without justification. Table 6 shows SC degrades late, suggesting it’ s the bottleneck. Equation 20 fixes weights.
The adaptive n_{hops} mechanism uses RNA neighbour similarity >0.6 to define “homogeneous tissue” , but this threshold is arbitrary and dataset-specific. Figure 3C shows Tonsil Add-on has lowest u (0.053) and best rank (1.22), yet its n_{hops} is 2 — same as standard Tonsil (rank 1.44, $u=0.088$). This weakens the claimed causal link between n_{hops} and performance.	n_{hops} may be a proxy for other factors (e.g., ADT panel richness), not tissue homogeneity per se. Using RNA similarity to decide spatial exclusion for <i>all</i> modalities ignores modality-specific spatial scales (e.g., protein gradients may be sharper than RNA).	If n_{hops} is not the true driver, the “adaptive spatial smoothing” contribution is overstated, and the mechanism may not generalize to non-RNA-centric modalities like ATAC or metabolomics.	Replace RNA-based n_{hops} selection with modality-agnostic graph metrics (e.g., spatial entropy of G), or learn n_{hops} per modality. Compare ARI on Breast Cancer (where $n_{hops}=1$) under both schemes.	[Paper] [Paper: PDF p.7]: n_{hops} threshold is ad hoc. Figure 3C shows Add-on’ s superiority correlates with ADT panel, not n_{hops} .

14 学到的知识

- **可靠性信号必须可计算、可分离、可组合**：OmicSync 显式定义了三种正交信号——assignment confidence（分布锐度）、epistemic routing uncertainty（MC-Dropout方差）、modality-routing weights（gating均值）——它们分别捕获不同维度的不确定性，且均可直接用于Task C证据构造。这提示我们在设计single-cell foundation models时，应避免单一“confidence score”，而应解耦出distributional、epistemic、aleatoric等分量。
- **LLM推理必须被证据严格约束，而非自由发挥**：OmicSync 的“evidence-constrained”设计（禁止引入未供给的基因名/蛋白名/文献）确保了审计可追溯性。这对perturbation prediction任务极具启发：可将扰动响应预测（如 Δ gene expression）作为证据，约束LLM生成“why this gene changes”而非泛泛而谈。
- **REINFORCE是连接不可微LLM与可微模型的务实桥梁**：OmicSync-R 不尝试微调LLM，而是将其视为black-box reward generator。这为multi-omics中使用大模型（如BioMedLM）提供范式：用其输出质量

（而非梯度）指导foundation model训练。

- **模态路由（MoE）不仅是融合工具，更是可解释性接口：**UncertaintyMoE 输出的 g_i 直接成为Task C的“which modality drove this?” 答案，且Figure 3E显示不同疾病有不同模态偏好（Glioblastoma RNA-dominant），这比attention权重更易解读。
- **空间邻域一致性（SC）是最难优化的指标：**Table 6显示SC在训练后期崩溃，暗示当前spot-level reward不足以建模空间图结构。这提示在spatial transcriptomics中，graph-level rewards（如subgraph homogeneity）可能比spot-level更有效。
- **伪标签（pseudo-label）的正则化价值不亚于真标签：**Task B虽无ground-truth，但Leiden RNA pseudo-labels成功引导latent space产生空间连贯的pseudo-cell-type maps（Figure 2），证明高质量unsupervised signals可作为强归纳偏置。

15 与既有知识的连接

- **候选连接/方法论连接：**OmicSync 的“KAN-GCN backbone + spatial position encoding”与 STAGATE/GraphST 一脉相承，但前者将空间信息注入各模态特征层（而非仅图卷积），更契合multi-omics异构性。
- **候选连接/方法论连接：**UncertaintyMoE 的MC-Dropout设计直接受 Gal & Ghahramani (2016) [17] 启发，但将其应用于模态路由（而非全网络），创造了新的可解释性维度。
- **候选连接/方法论连接：**REINFORCE loop 与 Williams (1992) [18] 经典policy gradient一致，但创新在于reward由自动faithfulness metrics构成，规避了人工reward engineering。
- **候选连接/方法论连接：**Evidence dictionary 构造逻辑类似 SHAP 的“feature attribution + context”，但扩展至多信号（confidence + uncertainty + modality + neighbourhood），更适配spatial omics的复杂因果。
- **弱连接/方法论连接：**与single-cell foundation models（如scGPT, scFoundation）相比，OmicSync 未使用大规模预训练，而是聚焦于小样本、多模态、空间约束下的联合学习，其“reliability-aware”设计可迁移至scGPT的cell state representation微调中。
- **弱连接/方法论连接：**cross-modal alignment 思路与 SpatialGlue 的cross-attention相似，但OmicSync 用CrossModalTransformer在token级融合，再经UncertaintyMoE路由，提供了更细粒度的模态控制。
- **弱连接/方法论连接：**perturbation prediction 可借鉴其证据构造：将扰动前后表达变化 ΔX 、关键TF活性、chromatin accessibility变化作为证据字典，约束LLM生成机制解释。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** SpatialGraph-REINFORCE

originating limitation/observation: SC metric degrades late in OmicSync-R training (Table 6), suggesting spot-level rewards fail to capture spatial graph coherence [Analysis]. **core hypothesis:** A graph-level reward, computed over k-hop neighbourhood subgraphs, will better align latent space with tissue topology than spot-level SC. **delta from paper:** Replaces spot-level SC_i with $SC_subgraph =$ fraction of nodes in k-hop subgraph assigned to same domain as center node, averaged over all subgraphs. **initial method:** For each reasoning update, sample 10 subgraphs; compute $SC_subgraph$; use as reward component in R_t . **validation:** Compare SC trajectory and final ARI on Human Breast Cancer

vs. base OmicSync-R. **failure modes:** Subgraph sampling may be noisy; k must be tuned per dataset.

innovation status: unverified

- **name:** MultiModal-PseudoLabel Fusion

originating limitation/observation: Task B uses RNA-only Leiden pseudo-labels, ignoring ADT/histology signals for supervision [Paper] [Paper: PDF p.18]. **core hypothesis:** Fusing pseudo-labels from all three modalities (e.g., ensemble Leiden on RNA/ADT/histology embeddings) will yield more robust CellTypeHead regularization. **delta from paper:** Replace single RNA-derived Y with $Y_{fused} = \text{argmax}$ over ensemble soft assignments from modality-specific Leiden. **initial method:** Run Leiden on X_1, X_2, X_3 separately; average soft assignments; threshold to get pseudo-labels. **validation:** Compare pseudo-cell-type map coherence (Figure 2) and Task A ARI on all four datasets. **failure modes:** Modality imbalance (e.g., sparse ADT) may dominate fusion; requires modality-specific resolution tuning. **innovation status:** unverified

- **name:** PerturbReasoner

originating limitation/observation: OmicSync's evidence dictionary includes "top evidence features" — directly transferable to perturbation contexts where Δ features are known [Paper] [Paper: PDF p.8]. **core hypothesis:** Constraining LLM to reason *only* about supplied perturbation-induced Δ features, modality weights, and neighbourhood shifts will yield more actionable mechanistic hypotheses than free-form prediction. **delta from paper:** Input to reasoning module includes: perturbed gene set, Δ expression vector, dominant modality post-perturbation, pre/post neighbourhood composition shift. **initial method:** Apply OmicSync pipeline to perturbation datasets (e.g., CROP-seq); construct evidence dictionary with perturbation-specific signals. **validation:** Human expert assessment of generated hypotheses' biological plausibility vs. baseline (e.g., scGPT + prompt). **failure modes:** Requires high-quality perturbation response data; may not generalize to partial/indirect perturbations. **innovation status:** unverified