

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	MARC: Morphology-Aware Regression of Consensus for Cell Segmentation in Subcellular Spatial Transcriptomics	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.CV)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-12	[Paper meta]
Authors	Xinyu Shu, Andrew Zhang, Jean Yang, Jinman Kim	[Paper] [Paper: PDF p. 1]
Core task	Pixel-level consensus-support regression for SST cell segmentation quality estimation	[Paper] [Paper: PDF p. 1–2, Fig 1b]
Input modalities	Candidate mask F_k , DAPI morphology D , transcript-density map T	[Eq. 2, Paper: PDF p. 3]
Output	Dense consensus-support map $\hat{C}_k \in [0,1]^{H \times W} \rightarrow$ cell-level score $S_{\{k,c\}}$	[Eq. 3, Eq. 8, Paper: PDF p. 3, 5]
Training supervision	Leave-one-method-out mean consensus $C^{(-k)}$ (pseudo-target)	[Eq. 5, Paper: PDF p. 3]
Loss function	Foreground-Union Consensus Loss (FUCL)	[Eq. 7, Paper: PDF p. 4]
Evaluation dataset	Xenium FFPE human renal cell carcinoma (spatially held-out tiles)	[Paper] [Paper: PDF p. 5]
Candidate methods	Cellpose-SAM, BIDCell, ProSeg, Xenium 10x onboard	[Paper] [Paper: PDF p. 5, Table 1]
Key metrics	Pixel-level Dice $\uparrow$ / L1 $\downarrow$; Cell-level Spearman $\rho \uparrow$	[Table 1, Paper: PDF p. 4]
Code/data availability	Not reported in text; “未开源代码” noted in selection reason	[Selection reason]

02 一句话总结

该论文提出 MARC (Morphology-Aware Regression of Consensus)，一个无需多方法集成推理即可预测亚细胞空间转录组 (SST) 中候选细胞分割掩码的跨方法共识支持度的回归框架。它通过将候选掩码、DAPI形态与转录密度三通道融合输入 U-Net 架构，以 leave-one-method-out 平均共识为伪标签、Foreground-Union Consensus Loss (FUCL) 为监督目标进行训练，在 Xenium 肾癌数据上实现了像素级 Dice 0.90 和细胞级 Spearman 相关性 0.79，显著优于仅用候选掩码或单模态输入的基线。其核心价值在于将原本计算密集的显式共识构建 (需运行全部4种分割流程) 压缩为单次前向推理，为大规模 SST 分析提供了可扩展的质量控制范式；但该共识仍是代理指标 (surrogate)，不等价于生物学真值边界。

03 研究问题

SST 细胞分割质量评估缺乏可靠 ground truth：手动标注成本过高且边界本身存在生物学模糊性 [Paper] [Paper: PDF p. 1]；而现有监督/不确定性方法依赖专家标注或模型内部状态，无法泛化至外部生成的异构候选掩码 [Paper] [Paper: PDF p. 1-2]。因此，如何在**无真值、无模型访问权限、跨方法异构输入**条件下，对任意 SST 分割结果进行**高效、一致、空间可解释的质量量化**？论文将此问题重构为：能否从单一候选掩码及其配套形态与分子信号中，直接回归出该掩码在多方法共识空间中的像素级支持强度？

04 研究背景与发展路径

传统图像分割质量评估依赖人工标注（如 SegQC [19]）或模型内不确定性估计（如 Bayesian dropout [7,12]），但二者均不适用于 SST 场景：前者因细胞密度过高、标注主观性强而不可扩展 [Paper] [Paper: PDF p. 1-2]；后者要求访问生成该掩码的原始模型参数与推理路径，而实际中用户常仅持有黑盒输出掩码 [Paper] [Paper: PDF p. 2]。共识方法（如 STAPLE [21]、多数投票）虽能规避真值依赖，却需完整执行所有参与方法的 pipeline（含各自 SST 输入预处理），导致计算开销随方法数线性增长，难以用于千级 tile 的常规质控 [Paper] [Paper: PDF p. 2, Fig 1a]。MARC 的发展路径是：**放弃“运行共识” → 转向“学习共识”**：将共识视为可建模的隐变量，利用 leave-one-method-out 伪标签将其蒸馏为一个轻量回归任务，使共识能力内化于单模型中。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
No scalable ground truth	Manual annotation is prohibitively time-consuming for large SST datasets; boundaries are biologically ambiguous even for experts	SST boundaries must be inferred from incomplete morphological and transcript signals; dense packing and weak contrast exacerbate ambiguity	[Paper] [Paper: PDF p. 1, "However, reliable ground-truth boundaries are unavailable..."]
Incompatibility of existing QC methods	Supervised QC requires expert masks; uncertainty-based QC requires internal model access	Existing approaches were not developed specifically for SST; they assume either full annotation access or white-box model deployment	[Paper] [Paper: PDF p. 1-2, "Conventional segmentation quality-assessment approaches were not developed specifically for SST..."]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Computational bottleneck of explicit consensus	Multi-method consensus construction is computationally intensive and difficult to scale	Requires configuring and running all contributing pipelines with their method-specific SST inputs (e.g., different preprocessing, alignment)	[Paper] [Paper: PDF p. 2, Fig 1a caption; "making consensus construction computationally intensive"]
Lack of spatially resolved, cross-method quality signal	Candidate masks lack per-pixel reliability estimates; cell-level scores cannot prioritize ambiguous regions for review	Prior work focuses on generating better masks, not evaluating externally generated candidates; no framework produces dense consensus-support maps usable for spatial filtering	[Paper] [Paper: PDF p. 2, "Most existing work focuses on generating improved masks rather than evaluating the reliability of an externally generated candidate mask."]

06 核心思想

论文的核心洞察是：**共识不是必须被“计算”的结果，而是可以被“感知”的上下文模式**。当多个互补的 SST 分割方法（如 morphology-driven Cellpose-SAM 与 transcript-aware ProSeg）对同一组织区域产生分歧时，其分歧模式本身携带了关于局部信号质量（如核形态清晰度、转录富集强度、邻近细胞重叠程度）的强判别信息。MARC 的核心思想即：将候选掩码 F_k 视为查询（query），将 DAPI 形态 D 与转录密度 T 视为支撑证据（evidence），联合建模三者之间的几何-分子一致性关系，从而在像素级预测该候选区域获得其余 $K-1$ 种方法共同支持的概率。这本质上是将共识建模为一种**跨模态、跨方法的条件置信度场**，而非离散的二值集成输出。

07 方法总览

MARC 将 SST 分割质量评估解耦为两个阶段：**(1) 像素级共识支持回归**：以三通道输入 $X_k = \text{concat}(D, T, F_k)$ 经 U-Net 编码-解码，输出连续值 $\hat{C}_k \in [0,1]^{H \times W}$ ，表示每个像素属于跨方法共识前景的概率；**(2) 细胞级分数聚合**：利用原始标签掩码 M_k 对 $\hat{C}_k$ 进行实例平均，得到每个候选细胞 c 的标量支持分 $S_{\{k,c\}}$ 。训练目标为 Foreground-Union Consensus Loss (FUCL)，仅在候选前景 F_k 或 leave-one-method-out 共识前景 $C^{(-k)}$ 覆盖的并集区域 U_k 内计算 L1 误差，强制模型聚焦于最具判别力的争议区域（如候选延伸至背景、或遗漏真实核区）。整个流程完全避免在推理时调用其他分割方法，实现 $O(1)$ 推理复杂度。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Three-channel input fusion	Concatenate s DAPI morphology D , transcript density T , and candidate foreground F_k into X_k in $\mathbb{R}^{3 \times H \times W}$	Enables joint modeling of geometric, structural, and molecular cues; avoids modality silos that would miss cross-signal inconsistencies	Input: D, T, F_k (all $H \times W$); Output: X_k	[Eq. 2, Paper: PDF p. 3]; Ablation in Table 2 shows +DAPI/+trans cripts boost Dice & ρ	Removal reduces Dice by $\sim 4.4\%$ (mask-only $\rightarrow$ mask+DAPI) and ρ by ~ 0.33 (mask-only $\rightarrow$ mask+DAPI), proving morphology is critical for ranking [Paper] [Paper: PDF p. 6, Table 2]
U-Net encoder-decoder backbone	Extracts hierarchical features and regresses dense $\hat{C}_k$ via skip connections	Captures multi-scale context (e.g., nuclear shape at high-res, tissue architecture at low-res); skip connections preserve boundary detail crucial for pixel-level support	Input: X_k ; Output: logit map $Z_k \rightarrow \hat{C}_k = \sigma(Z_k)$	[Sec 3.2, Paper: PDF p. 3]; Fig 2 shows architecture	Without skip connections, boundary localization degrades $\rightarrow$ lower Dice/IoU; FUCL' s foreground focus would under-constrain such a model

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Foreground-Union Consensus Loss (FUCL)	Computes L1 loss only over union $U_k = F_k \cup C^{(-k)}$ of candidate and consensus foreground	Focuses gradient updates on regions where candidate and consensus disagree (i.e., ambiguous boundaries), preventing background noise from dominating training	Input: $\hat{C}_k, C^{(-k)}, U_k$; Output: scalar loss $L^{(k)}_{\text{FU}}$	[Eq. 6–7, Paper: PDF p. 4]; Defined as mean absolute error clamped to U_k	Using full-image L1 would dilute gradients on critical disagreement pixels → lower Dice & poorer cell-level correlation (as implied by FUCL’s design rationale [Paper] [Paper: PDF p. 4])
Cell-level aggregation (Eq. 8)	Averages $\hat{C}_k$ over pixels assigned to each instance c in M_k : $S_{k,c} = \frac{1}{ M_k(c) } \sum_{(x,y) \in M_k(c)} \hat{C}_k(x,y)$	$M_k = c \setminus \{(x,y) : M_k(x,y) = c\}$	$\sum_{(x,y) \in M_k(c)} \hat{C}_k(x,y)$	Converts dense spatial support into actionable, instance-level QC scores for manual review or downstream filtering	Input: $\hat{C}_k, M_k$; Output: vector $S_{k,c}$ [Eq. 8, Paper: PDF p. 5]; Used for Spearman ρ calculation and Fig 3/4 visualization Without aggregation, no cell-level ranking possible; candidate-copy baseline has constant $S_{k,c} \rightarrow$ undefined ρ [Table 2, *]

09 关键公式与符号

论文未给出显式“算法公式”，但明确定义了以下关键符号与可核验公式：

- M_k : 候选方法 k 输出的带标签掩码 ($H \times W$ 整数矩阵), $M_k(x,y)=c$ 表示像素 (x,y) 属于细胞实例 c [Eq. 1, Paper: PDF p. 3]。
- F_k : M_k 的二值前景图, $F_k(x,y)=1$ iff $M_k(x,y)>0$ [Eq. 1]。
- D, T : 对齐的 DAPI 形态图与转录密度图 (均为 $H \times W$ 实值图) [Paper] [Paper: PDF p. 3]。
- $X_k = \text{concat}(D, T, F_k)$: 三通道模型输入 [Eq. 2]。
- $\hat{C}_k = f_{\theta}(X_k) = \sigma(Z_k)$: 模型输出的连续共识支持图, 经 sigmoid 映射至 $[0,1]$ [Eq. 3–4]。
- $C^{(-k)} = \frac{1}{K-1} \sum_{j \neq k} F_j$: leave-one-method-out 共识伪目标 ($K=4$, 故为其余3法平均) [Eq. 5]。
- $U_k(x,y) = \mathbb{I}[F_k(x,y)=1 \vee C^{(-k)}(x,y)>0]$: 前景并集掩码, 定义 FUCL 作用域 [Eq. 6]。

- $L^{\{k\}}_{\text{FU}} = \frac{1}{|U_k|} \sum_{x,y} U_k(x,y) \cdot |\hat{C}_k(x,y) - C^{\{-k\}}(x,y)|$:
Foreground-Union Consensus Loss [Eq. 7]。
- $S_{k,c} = \frac{1}{|\{(x,y): M_k(x,y)=c\}|} \sum_{(x,y): M_k(x,y)=c} \hat{C}_k(x,y)$: 细胞 c 的共识支持分 [Eq. 8]。

Note: 无公式 (7) 在文本中缺失 (跳过编号7)，但 FUCL 定义完整见 Eq. 7；Equation 8 是唯一明确写出的聚合公式。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Main evaluation (Table 1)	MARC predicts explicit consensus targets ($C^{\{-k\}}$) with high fidelity	MARC vs. explicit $C^{\{-k\}}$ across 4 candidate methods; metrics: L1, Dice, IoU, Sensitivity, Precision, Cell Spearman ρ	Avg. Dice=0.9002, Avg. ρ =0.7905; best per-metric bolded	MARC closely approximates explicit cross-method consensus at both pixel and cell levels	MARC recovers biological ground truth (not claimed; authors explicitly state consensus is a surrogate [Paper] [Paper: PDF p. 7])	[Table 1, Paper: PDF p. 4]; [Paper] [Paper: PDF p. 5, "MARC achieved mean...indicating that MARC closely reproduces the explicit consensus"]
Input ablation (Table 2)	DAPI morphology and transcript density provide complementary, non-redundant signals beyond candidate geometry	MARC variants: mask-only, mask+DAPI, mask+DAPI+transcripts; all trained/tested on same $C^{\{-k\}}$ targets	Adding DAPI boosts avg. Dice from 0.8565→0.8866 and ρ from 0.4228→0.7564; adding transcripts further to 0.9002/0.7905	Morphology is the primary driver for cell-level ranking; transcripts add molecular specificity for pixel-level refinement	DAPI alone suffices for high-quality ranking (false: ρ =0.7564 < 0.7905 with transcripts)	[Table 2, Paper: PDF p. 6]; [Paper] [Paper: PDF p. 6, "The substantial increase in cell-level correlation after adding DAPI indicates that morphology provides the main additional signal..."]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Target ablation (Sec 4.3)	Mean-consensus supervision is more effective than STAPLE for preserving cell-level rankings	Two MARC models: mean- $C^{\{-k\}}$ vs. STAPLE- $C^{\{-k\}}$ targets; identical inputs/architecture/loss	Mean target: higher sensitivity (0.9168 vs 0.8860) and p (0.7905 vs 0.7491); STAPLE: higher precision (0.9128 vs 0.8843)	Mean consensus better captures fraction-of-support intuition and preserves ordering; STAPLE trades recall for precision	STAPLE is objectively more accurate (not supported: models evaluated against different targets)	[Paper] [Paper: PDF p. 5–6, "Mean-consensus and STAPLE supervision produced similar average Dice scores...but different trade-offs"]
Qualitative analysis (Fig 4)	MARC localises weakly supported regions spatially	Visual inspection of predicted $\hat{C}_k$ and $S_{\{k,c\}}$ on held-out test tiles	Bright $\hat{C}_k$ aligns with nuclear morphology & transcript density; dim regions correspond to candidate extensions into background or method-specific artifacts	MARC produces spatially varying, interpretable support maps that highlight ambiguity for review	MARC' s low-score regions perfectly match biological ground truth errors (Not assessable from supplied material; no ground truth provided)	[Fig 4, Paper: PDF p. 6]; [Paper] [Paper: PDF p. 7, "Lower consensus was observed where candidate masks extended into the background..."]

11 对结论的正确理解

MARC 的核心结论是：在 SST 场景下，跨方法共识支持度是一个可被 U-Net 从候选掩码+形态+转录三元组中有效回归的稠密场，且该回归结果在像素重叠（Dice 0.90）和细胞排序（ p 0.79）上高度逼近显式计算的 leave-one-method-out 共识。这意味着：（1）共识蕴含的可靠性信号具有足够强的统计规律性，能被端到端模型捕获；（2）形态与分子上下文是解码该信号的关键，远超候选掩码自身几何信息；（3）FUCL 的前景并集约束是有效的训练偏置，引导模型关注歧义边界。但必须强调：该共识是方法论共识（methodological agreement），非生物学共识（biological truth）；其价值在于提供一种可扩展、可解释、与下游分析解耦的质量代理指标，而非替代真值。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Consensus as surrogate, not ground truth	Failure modes common to multiple segmentation methods may be reinforced in the consensus target, leading to systematic bias	Acknowledge it's a pragmatic alternative to manual annotation; suggest orthogonal validation with membrane/protein markers	[Paper] [Paper: PDF p. 7, "A key limitation...failure modes across segmentation methods may be reinforced...incorporate orthogonal membrane or protein markers for validation"]
Limited generalisability	Evaluated only on Xenium renal cell carcinoma data; candidate methods share inputs from same assay, reducing independence	Future work will evaluate on additional tissues, platforms, and segmentation methods	[Paper] [Paper: PDF p. 7, "Another limitation is that the MARC was evaluated on a single Xenium renal cell carcinoma dataset...evaluate additional tissues, platforms, and segmentation methods"]
Platform/method dependence	Current setup assumes aligned DAPI and transcript maps; performance may degrade with poor registration or noisy transcript data	Not explicitly stated, but implied by reliance on "aligned" inputs in Methods [Sec 3.1] and ablation showing transcript density improves performance	[Paper] [Paper: PDF p. 3, "Let $D \in \mathbb{R}^{H \times W}$ denote the aligned DAPI morphology image and $T \in \mathbb{R}^{H \times W}$ the transcript-density image."; Table 2 shows transcript addition improves metrics]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
MARC' s high cell-level Spearman ρ (0.79) relies on the <i>same</i> leave-one-method-out protocol for both training targets ($\mathcal{S}^{\{-k\}}$) and evaluation reference ($\mathcal{S}^{\{-k\}}$)	This creates an optimistic bias: the model is optimized to mimic a target defined by the very ensemble it' s meant to replace; real-world utility requires generalisation to unseen method combinations or new assays	Overstates practical deployability; if a new segmentation method is added, retraining MARC with updated $\mathcal{S}^{\{-k\}}$ may be needed, reintroducing computational cost	Train MARC on subset of methods (e.g., 3 out of 4), then test its prediction against consensus including the held-out method; measure ρ drop	[Paper] [Paper: PDF p. 3, "For candidate method k , the consensus target is calculated as the mean binary foreground prediction of the remaining $K-1$ methods"; Table 1 evaluates exactly this same setup]

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
FUCL restricts loss to foreground union $\mathcal{U}_k$, but $\mathcal{C}^{(-k)}$ is a soft probability map (mean of binaries), while $\hat{\mathcal{C}}_k$ is a sigmoid output — the L1 loss treats them as equally calibrated continuous values	The soft target $\mathcal{C}^{(-k)}$ in $[0,1]$ represents fractional support, but FUCL’s L1 assumes linear correspondence; a KL divergence or focal loss might better handle the confidence calibration mismatch	Poor calibration could harm downstream tasks like active learning where absolute $\hat{\mathcal{C}}_k$ thresholds matter (e.g., filtering cells with $\hat{\mathcal{C}}_k < 0.3$)	Compare FUCL with KL-divergence loss on same setup; calibrate $\hat{\mathcal{C}}_k$ using isotonic regression against $\mathcal{C}^{(-k)}$; report ECE (Expected Calibration Error)	[Eq. 5 defines $\mathcal{C}^{(-k)}$ as arithmetic mean; Eq. 4 defines $\hat{\mathcal{C}}_k$ as sigmoid; FUCL uses L1 without calibration discussion]
Input ablation shows transcript density boosts performance, but Table 2 reports lower ρ for BIDCell (0.6251) vs others (>0.81) despite using same transcript input	BIDCell itself is transcript-aware [Paper] [Paper: PDF p. 3], so its candidate mask $\mathcal{F}_k$ may already encode transcript information, making the additional transcript channel $\mathcal{T}$ redundant or even conflicting for this method	Suggests MARC’s modality fusion isn’t universally optimal; method-specific input gating or attention might improve robustness across heterogeneous candidates	Implement modality-gating modules per candidate method; ablate $\mathcal{T}$ only for BIDCell input and compare to full model	[Paper] [Paper: PDF p. 3, "BIDCell uses biologically informed self-supervised learning to integrate morphological and transcript information"; Table 2 shows BIDCell row has lowest $\rho=0.6251$]

14 学到的知识

- **共识可学习性**：跨方法分割共识并非必须显式计算的刚性集成，而是一种可被深度网络从多模态上下文中回归的稠密语义场，其可学习性源于方法间错误的互补性（morphology vs. transcript errors）。
- **FUCL 的设计智慧**：聚焦前景并集的损失函数是处理“弱监督代理目标”的关键——它将优化目标锚定在最具信息量的歧义区域（candidate-background boundary, candidate-overlap zone），避免背景噪声稀释梯度。
- **形态的不可替代性**：在 SST 中，DAPI 形态对细胞级质量排序的贡献（ $\Delta\rho\approx0.33$ ）远超转录密度（ $\Delta\rho\approx0.03$ ），证实核结构仍是细胞身份与边界的最稳健先验，分子信号起校准与细化作用。
- **伪标签的脆弱性**：leave-one-method-out 协议虽巧妙规避真值需求，但其有效性高度依赖候选方法的独立性；当方法共享底层假设（如均基于 Xenium 数据）时，共识可能收敛至局部最优而非全局可靠解。
- **空间可解释性即生产力**：dense $\hat{\mathcal{C}}_k$ 图不仅用于打分，其像素级热图可直接指导人工校正（如 Fig 4 中红框细胞的低支持区域），将 QC 从“整体可信度判断”升级为“精准干预定位”。

15 与既有知识的连接

- **候选连接/方法论连接**：MARC 的 leave-one-method-out 伪标签范式与 self-training、noisy student 等半监督方法同源，但创新点在于将“student”目标定义为跨方法共识而非单模型自治；FUCL 的前景聚焦策略与医学图像分割中常用的 foreground-weighted Dice loss [18] 一脉相承，但更进一步限定于“candidate $\cup$ consensus”交集。

- **候选连接/方法论连接**: 其三通道输入 (mask+DAPI+transcripts) 与 multi-omics 表征学习中常见的模态拼接 (如 scRNA+ATAC) 思路一致, 但 SST 的 spatial alignment 约束使其更接近 spatial omics 特定架构 (如 SPATA [16]); U-Net 结构选择印证了 biomedical AI 中编码器-解码器对空间关系建模的普适优势。
- **候选连接/方法论连接**: cell-level aggregation (Eq. 8) 本质是 instance-aware pooling, 与 graph neural networks 中的 readout 函数 (如 sum/mean pooling over node features) 功能相似, 暗示可将候选细胞视为图节点, $\hat{C}_k$ 像素为邻居特征, 探索 GNN-based consensus refinement。
- **弱连接/方法论连接**: single-cell foundation models 通常面向 profile-level embedding, 而 MARC 聚焦 segmentation-level spatial QC; 但其输出 $\hat{C}_k$ 可作为细胞表型的 spatial reliability prior, 注入 foundation model 的 spatial tokenization 阶段。
- **弱连接/方法论连接**: perturbation prediction 在 SST 中常需 clean segmentation; MARC 提供的低共识细胞列表可作为 perturbation target 的 quality filter, 避免在模糊边界上建模虚假扰动效应。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name**: Consensus-Guided Active Learning for SST Annotation

originating limitation/observation: Authors note consensus is a surrogate and manual annotation is expensive [Paper] [Paper: PDF p. 1,7]; MARC identifies low-consensus cells (Fig 4) but doesn't leverage them for annotation efficiency. **core hypothesis**: Querying human annotators *only* on cells with MARC-predicted low consensus ($S_{k,c} < \tau$) yields higher annotation ROI than random or uncertainty-based sampling. **delta from paper**: MARC is passive QC; this integrates it into an active loop where low-consensus predictions directly drive annotation budget allocation. **initial method**: On Xenium data, simulate annotation budget B; compare: (a) random cell selection, (b) top-B cells by MARC's $S_{k,c}$, (c) top-B by model uncertainty (if available). Measure annotation time saved & downstream task (e.g., cell-type clustering) accuracy gain. **validation**: Annotation time per cell (expert timing), clustering ARI before/after adding B annotations. **failure modes**: If low-consensus cells are systematically un-annotatable (e.g., due to imaging artifacts), ROI drops; if consensus correlates poorly with true difficulty, sampling is inefficient. **innovation status**: unverified

- **name**: Cross-Platform Consensus Distillation

originating limitation/observation: Authors admit limited generalisability to other platforms [Paper] [Paper: PDF p. 7]; MARC trained on Xenium may fail on Visium/Slide-seq due to resolution/signal differences. **core hypothesis**: A small set of platform-aligned consensus targets (e.g., 100 tiles from Visium) can distill Xenium-trained MARC's consensus knowledge to new platforms via feature-level adaptation, avoiding full retraining. **delta from paper**: MARC is platform-specific; this proposes a lightweight transfer strategy leveraging its learned consensus representation. **initial method**: Freeze MARC encoder; add platform-specific adapter (e.g., small CNN) before decoder; train adapter + decoder head on Visium consensus targets using FUCL; compare to full Visium retraining. **validation**: Dice/p on Visium test set; parameter count/flops of adapter vs. full model. **failure modes**: If platform shifts break fundamental morphology-transcript relationships (e.g., Visium's spot-level vs Xenium's subcellular resolution), adapter fails; if no Visium consensus targets exist, distillation impossible. **innovation status**: unverified

- **name:** Graph-Augmented Consensus Refinement

originating limitation/observation: MARC treats each candidate cell in isolation (Eq. 8); but SST cell boundaries are relational—consensus for cell c depends on neighbors' morphology/transcript overlap [Paper] [Paper: PDF p. 1]. **core hypothesis:** Modeling candidate cells as nodes in a spatial graph (edges = proximity/overlap) and passing $\hat{C}_k$ messages enables contextual refinement of consensus scores, especially for touching cells. **delta from paper:** MARC is CNN-based and local; this injects explicit relational reasoning via GNN. **initial method:** Replace Eq. 8 aggregation with GNN readout: node features = $\{\text{mean}(\hat{C}_k \text{ on } c), \text{area}_c, \text{DAPI_intensity}_c\}$; edges = spatial distance $< r$; output refined $S'_{k,c}$. Train end-to-end with FUCL. **validation:** Dice/ ρ on test set; visual inspection of touching cell pairs in Fig 4—do refined scores better separate merged instances? **failure modes:** Graph construction sensitive to distance threshold r ; if cell instances are highly irregular, fixed-radius graphs misrepresent topology; adds inference latency. **innovation status:** unverified