

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	CellMSA: Context Modeling for Single-Cell Representation Learning	[Paper] [Paper: PDF p. 1]
Authors	Suyuan Zhao, Minghao Liu, Yizhen Luo, Zaiqing Nie	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (NeurIPS 2026 submission)	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Pretraining scale	~109 million human cell observations (65.6M primary)	[Paper] [Paper: PDF p. 1, 3, 6, 26]
Core analogy	Protein MSA → single-cell “MSA” context	[Paper] [Paper: PDF p. 2, Fig. 1]
Key innovation	Context-dependent gene-pair representation via CellMSA-Module + GenePairformer	[Paper] [Paper: PDF p. 4–5, Fig. 2]
Downstream tasks	Batch integration, cell type/state classification, perturbation prediction	[Paper] [Paper: PDF p. 7–9]
Code availability	https://github.com/PharMolix/CellMSA	[Paper] [Paper: PDF p. 1]

02 一句话总结

CellMSA 提出一种受蛋白质多序列比对（MSA）启发的单细胞上下文建模框架，通过跨批次、跨细胞类型的“类MSA”细胞集合，为每个目标细胞构建上下文感知的基因对（gene-pair）表示，并将其注入目标细胞编码器，从而提升细粒度细胞状态表征能力；该设计直击现有单细胞foundation model忽略跨样本关系、难以捕获基因共表达与疾病相关依赖的核心缺陷，但其预训练规模大（109M cells）、计算开销高，复现门槛显著；论文在Tabula Sapiens等标准基准上系统验证了其在batch integration、PT细胞状态分类和perturbation prediction上的SOTA性能，且可解释性分析证实其能捕获肾损伤相关的ECM重编程等生物学通路。

03 研究问题

现有单细胞foundation model普遍采用独立细胞编码范式（single-cell-as-token），或仅利用同一批次内细胞进行去噪，导致两大根本性局限：（1）无法区分技术噪声与真实生物变异，尤其在稀疏、低测序深度数据中；（2）丢失跨批次、跨细胞类型的基因共表达模式与状态特异性基因依赖关系，制约细胞状态表征的鲁棒性与分辨率。因此，核心问题是：**如何设计一种可扩展、基因级分辨率的上下文建模机制，使模型能从异质性细胞集合中稳定提取与细胞状态强相关的基因对依赖模式？** 论文假设：借鉴AlphaFold中MSA用于推断残基共进化与结构约束的逻辑，单细胞领域亦可通过聚合“相似但非相同”的细胞（same-batch/cross-batch/cross-type）的一致性与差异性表达模式，来识别marker基因与功能相关基因模块——这一假设驱动了CellMSA的整个架构设计。

04 研究背景与发展路径

单细胞foundation model演进呈现清晰的“独立→局部上下文→全局上下文”路径：早期模型（Geneformer, scGPT）将每个细胞视为独立token，仅学习基因共现统计；近期工作（CellPLM, STATE, Stack）开始引入多细胞上下文，但存在压缩损失（如gene-weighted averaging [15]）或上下文受限（仅同批同型细胞 [16]）；这些方法虽改善batch correction，却未能有效建模跨条件的基因协同变化。CellMSA定位为该路径的下一跃迁：它不满足于局部去噪，而是将上下文建模升维为“类MSA”结构——即显式保留基因维度对齐，使模型能在低维空间中高效计算跨细胞的基因对协方差（Outer-product Mean），再反哺高维目标细胞编码（GenePairformer）。这一路径选择直接回应了引言中指出的“现有方法未充分利用跨批次/跨类型关系”这一发展瓶颈 [Paper] [Paper: PDF p. 2]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
孤立建模导致噪声敏感	单细胞转录组高度稀疏、受测序深度/脱落/批次效应强烈干扰，独立建模难以区分生物变异与随机噪声	“when the model relies on only a single observation of a cell, it is often difficult to distinguish biological variation from stochastic noise” [Paper] [Paper: PDF p. 2]	[Paper] [Paper: PDF p. 2]
上下文信息利用不足且低效	现有上下文方法（如CellPLM, Stack）需压缩细胞表达（平均/编码/模块化），丢失基因级细节，限制细粒度基因依赖捕获	“such compression can discard gene-level information and therefore limit the model’s ability to capture fine-grained gene-gene dependencies” [Paper] [Paper: PDF p. 2]	[Paper] [Paper: PDF p. 2]
上下文构成缺乏生物多样性	多数方法仅组织同批同型细胞，上下文信号局限于局部实验条件，缺乏跨批次稳定性与跨类型对比性	“they do not explicitly exploit cross-batch signals or biologically related cell types… may be less effective at improving robustness across batches” [Paper] [Paper: PDF p. 2]	[Paper] [Paper: PDF p. 2]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
缺乏可解释的中间表征	模型输出为黑盒细胞嵌入，难以追溯其决策依据是否对应已知生物学机制（如疾病通路）	“existing approaches... provide limited additional information beyond denoising” [Paper] [Paper: PDF p. 2]; interpretability analysis is a key contribution [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 2–3, Fig. 4]

06 核心思想

CellMSA的核心思想是**将单细胞表征学习重构为一个“上下文驱动的对基因关系发现”过程**。其本质并非简单增加输入细胞数量，而是通过精心设计的三元上下文（same-batch/cross-batch/cross-type）与双阶段处理架构，实现两个关键跃迁：（1）**从细胞级到基因对级**：CellMSA-Module在低维空间中对齐所有上下文细胞的基因表达，通过Outer-product Mean操作直接聚合跨细胞的基因u-v共变模式，生成 $P \in \mathbb{R}^G \times \mathbb{G} \times \mathbb{D}^p$ 的基因对表示，而非传统方法的细胞级向量；（2）**从静态上下文到动态引导**：GenePairformer不将上下文作为额外输入序列，而是将基因对表示作为attention bias注入目标细胞自注意力，使目标细胞编码过程能主动参考“哪些基因对在相似细胞中稳定共表达”，从而实现细粒度、状态感知的编码。这一思想使模型既能利用丰富上下文，又避免了高维计算爆炸。

07 方法总览

CellMSA是一个两阶段上下文增强框架：第一阶段（CellMSA-Module）以目标细胞+其“类MSA”上下文（16 same-batch + 16 cross-batch + 8 cross-type cells）为输入，在低维空间（ $d'=128$ ）中迭代更新基因对表示 P^l 与上下文基因表示 m^l ，核心操作为Outer-product Mean（聚合跨细胞u-v共变）与Pair-weighted Averaging（用 P^l 调制 m^l 的信息聚合）；第二阶段（GenePairformer）将最终 PL^{MSA} 投影为head-specific pair bias R^0 ，并以此bias修正目标细胞（仅1行）的Transformer自注意力logits，实现pair-aware编码；预训练采用三目标联合优化：LMGM（掩码基因预测）、LRec（细胞表达重建）、LCCE（细胞对比学习），共同驱动模型学习鲁棒、判别性、信息丰富的表征 [Paper] [Paper: PDF p. 3–6, Fig. 2, Appendix A.1]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
CellMSA-Module	从MSA-like上下文中提取并压缩跨细胞一致性/差异性模式，生成context-dependent gene-pair representation PLMSA	解决“如何在压缩基因维度前提下高效利用多细胞上下文”问题；避免直接拼接高维细胞序列导致的计算爆炸	Input: Target cell + context cells ($S \text{ rows} \times G \text{ genes}$); Output: $PLMSA \in \mathbb{R}^G \times G \times dp$	Outer-product Mean & Pair-weighted Averaging modules detailed in [Paper] [Paper: PDF p. 5, Appendix A.1]; complexity analysis shows $O(SG^2dp^2)$ cost [Paper] [Paper: PDF p. 16]	Ablation shows >3% drop in PT state accuracy & >0.07 drop in Pearson Δ (Table 4); without it, GenePairformer degrades to standard Transformer [Paper] [Paper: PDF p. 10]
GenePairformer	将PLMSA作为 attention bias注入目标细胞编码，使目标细胞的基因表示能显式参考基因对依赖关系	解决“如何让目标细胞编码受益于上下文发现的基因对知识”问题；避免上下文信息被淹没在长序列中	Input: Target cell gene embeddings e^i ; Output: Final cell embedding $z^i \in \mathbb{R}^d$	Bias added as $RL+^1H_{uv} = RLH_{uv} + Q^LH_u(K^LH_v)^T/\sqrt{d^H}$ [Paper] [Paper: PDF p. 5]; enables iterative sequence-pair interaction	Ablation w/o CellMSA-Module implicitly removes this mechanism; full ablation confirms its necessity for SOTA performance [Paper] [Paper: PDF p. 10, Table 4]
Three-Source Context Retrieval	构建包含same-batch（本地去噪）、cross-batch（跨批次稳定性）、cross-type（功能对比）的异构上下文	解决“上下文应提供何种生物学信号”问题；单一来源上下文（如仅same-batch）无法同时满足鲁棒性与判别性需求	Input: Target cell c^i ; Output: $N^i = N^{samebatch^i} \cup N^{crossbatch^i} \cup N^{crosstype^i}$	Explicitly defined in [Paper] [Paper: PDF p. 4]; hierarchical clustering on cell-type expression used for cross-type sampling [Paper] [Paper: PDF p. 6, 26–27]	Ablation "Only Same-batch Context" drops PT accuracy by 2.9% vs full model (Table 4); label-free setting shows CellMSA still outperforms Stack without labels [Paper] [Paper: PDF p. 10, Appendix B.1.1]
Relation-type Embedding	为每个上下文细胞 $c_j \in N^i$ 添加relation-type label $rij \in \{same \text{ batch}, cross \text{ batch}, cross \text{ type}\}$ 的可学习嵌入	解决“模型如何区分不同来源上下文的语义”问题；确保same-batch信号用于去噪，cross-batch用于泛化，cross-type用于对比	Input: relation label rij ; Output: $E^{rel}(rij)$ added to neighbor cell input representation	Defined in [Paper] [Paper: PDF p. 4]; enables model to learn distinct roles for each context type	Not directly ablated, but critical for enabling the three-source design's intended functionality [Paper] [Paper: PDF p. 4]

09 关键公式与符号

论文未提供可核验的完整数学公式（如损失函数的显式求和形式），但明确定义了以下关键符号与操作：

- $\mathbf{X} \in \mathbb{R}^{N \times G}$: 单细胞表达矩阵， N 为细胞数， G 为基因数 [Paper] [Paper: PDF p. 3]
- $\mathbf{P}^0 \in \mathbb{R}^G \times G \times \mathbb{D}$: 初始基因对表示， $p^0_{uv} = f_{\text{pair}}(E^{\text{gene}}(u), E^{\text{gene}}(v))$ [Paper] [Paper: PDF p. 4]
- **Outer-product Mean**: $p^{l+1}_{uv} = p^l_{uv} + W_l p (1/S \sum_s a^l_{su} \otimes b^l_{sv})$ ，其中 a^l_{su}, b^l_{sv} 为 m^l_{su}, m^l_{sv} 的线性投影， $\otimes$ 为外积 [Paper] [Paper: PDF p. 5]
- **Pair-weighted Averaging**: $m^{l+1}_{su} = m^l_{su} + W_l o (\gamma^{lh}_{su} \odot \sum_v \text{softmax}_v(W^{lh}_b p^{l+1}_{uv}) v^{lh}_{sv})$ [Paper] [Paper: PDF p. 5]
- **GenePairformer attention bias**: $R^{L+1}_{uv} = R^L_{uv} + Q^{LH}_u (K^{LH}_v)^T / \sqrt{d^H}$ [Paper] [Paper: PDF p. 5]
- **Pretraining losses**: LMGM (masked gene CE), LRec (reconstruction CE), LCCE (InfoNCE contrastive) [Paper] [Paper: PDF p. 6]
- **Key metrics**: NMI, ARI, ASW, BRAS, iLISI, kBET, Conn, PCR (batch integration); Accuracy, Macro F1 (classification); Pearson Δ , PRAUC (perturbation) [Paper] [Paper: PDF p. 7–9, Appendix C.4–C.5]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Batch integration (Tabula Sapiens)	CellMSA achieves superior batch mixing while preserving biology	CellMSA vs PC-HVG/scVI/scGP T/Geneformer/STATE-SE/Stack; label-informed context retrieval for CellMSA & Stack; scib-metrics benchmark [Paper] [Paper: PDF p. 7]	CellMSA: Total score 0.736 (vs Stack 0.663, scVI 0.600); highest NMI (0.895), ARI (0.805), ASW (0.699), cLISI (1.000), and batch correction scores (BRAS 0.740, iLISI 0.242, kBET 0.627) [Table 1]	CellMSA provides more robust and biologically faithful integrated representations than all baselines under label-informed settings	That CellMSA is universally superior across <i>all</i> tissues without qualification; tissue-specific results show variance (e.g., lower gain in Lymph Node) [Appendix A.11]	[Paper] [Paper: PDF p. 7, Table 1, Appendix A.1–A.26]
PT cell state classification (Kidney Atlas)	CellMSA captures fine-grained disease-associated transcriptional states within same cell type	CellMSA vs scVI/scGPT/Geneformer/STATE-SE/Stack/CellPLM; 5-run avg; donor-split; HVG-PCA-KNN context for val/test [Paper] [Paper: PDF p. 8]	CellMSA: Accuracy 0.958 ± 0.004 , Macro F1 0.931 ± 0.006 (vs Stack 0.936 ± 0.008 , CellPLM 0.850 ± 0.010) [Table 2]	CellMSA excels at distinguishing subtle, disease-driven cell state transitions (aPT/dPT/dPT/D TL)	That this superiority generalizes to <i>all</i> kidney cell types or other organ injury models; only PT cells were tested	[Paper] [Paper: PDF p. 8, Table 2, Appendix C.2]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Perturbation prediction (Replogle)	CellMSA latent space enables more accurate modeling of perturbation-induced transcriptional shifts	CellMSA+STATE-ST vs Expression+STATE-ST/STATE-SE+STATE-ST/Stack+STATE-ST; Pearson Δ primary metric [Paper] [Paper: PDF p. 9]	CellMSA: Pearson Δ 0.433 (vs Stack 0.358, STATE-SE 0.353); +8.8% over strongest baseline [Table 3]	CellMSA representations encode richer regulatory information for predicting perturbation effects	That CellMSA alone (without STATE-ST) predicts perturbations; the method requires coupling with STATE-ST module	[Paper] [Paper: PDF p. 9, Table 3, Appendix C.2–C.3]
Interpretability (Fig. 4)	Gene-pair representations capture disease-associated network reconfiguration	Head-wise differential hub scores & GO enrichment on PT cells (healthy vs disease) [Paper] [Paper: PDF p. 9]	Head 7 shows significant enrichment for ECM reorganization, integrin signaling, cellular dedifferentiation (GO terms) [Fig. 4c]; top genes overlap known PT injury markers (CDH6, HAVCR1, etc.) [Paper] [Paper: PDF p. 9]	CellMSA's learned gene-pair modes are anchored in robust pathological signals and yield biologically interpretable latent programs	That these GO enrichments imply direct causal regulation; authors explicitly state patterns reflect "statistical associations rather than explicit causal regulatory relationships" [Paper] [Paper: PDF p. 10]	[Paper] [Paper: PDF p. 9, Fig. 4, Appendix B.2]
Ablation (Table 4)	Performance gains stem from effective MSA context utilization	Full Model vs w/o CellMSA-Module / w/o Context / Only Same-batch Context [Paper] [Paper: PDF p. 10]	Full model consistently best: PT accuracy 0.958 vs 0.854 (w/o Module), 0.878 (w/o Context), 0.929 (Only Same-batch); Pearson Δ 0.433 vs 0.355, 0.389, 0.400 [Table 4]	The CellMSA-Module and multi-source context are essential components; cross-batch/cross-type context provides measurable benefit beyond same-batch	That the specific architecture choices (e.g., Outer-product Mean) are optimal; no ablation tests alternative pair-representation mechanisms	[Paper] [Paper: PDF p. 10, Table 4, Fig. 5]

11 对结论的正确理解

CellMSA的核心结论是：通过引入受蛋白质MSA启发的、基因级对齐的多源细胞上下文建模机制，可以显著提升单细胞表征学习在多个下游任务上的性能，并产生可解释的基因对关系表征。这一结论得到充分支持：（1）在batch integration中，CellMSA在scib-metrics的全部12项指标上均领先或接近领先，且UMAP可视化（Fig. 3）直观显示其在Bladder数据上实现了细胞类型聚类紧密、供体ID混合均匀；（2）在PT细胞状态分类中，其

Macro F1 (0.931) 显著超越CellPLM (0.794)，证明其对同一谱系内疾病进展状态的分辨力；(3) 在 perturbation预测中，+8.8% Pearson Δ 表明其潜在空间更忠实地编码了扰动响应的基因级动力学；(4) Fig. 4 的GO富集与已知肾损伤通路一致，证实其表征具有生物学意义。需注意：所有结论均基于作者定义的特定实验设置（如label-informed context、特定数据集划分、STATE-ST耦合），并非绝对普适。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Statistical vs causal interpretation	Learned gene-pair patterns reflect statistical associations, not explicit causal regulatory relationships	Incorporate prior knowledge of gene regulation and causal machine learning methods to strengthen biological grounding	[Paper] [Paper: PDF p. 10]
Computational cost & scalability	Pretraining on 109M cells requires 20 days on 4×A800 GPUs; CellMSA-Module adds $O(SG^2d_p^2)$ complexity	Not explicitly stated, but implied by focus on efficiency in complexity analysis (Appendix A.2)	[Paper] [Paper: PDF p. 6, 16]
Dependence on high-quality annotations	Label-informed context retrieval (for CellMSA & Stack) uses cell-type labels, limiting applicability where labels are noisy or unavailable	Demonstrated viability of label-free (HVG-PCA-KNN) retrieval, though with lower performance (0.688 vs 0.748 total score) [Appendix B.1.1]	[Paper] [Paper: PDF p. 7, Appendix B.1.1]
Context construction bias	Pretraining corpus includes non-primary observations (e.g., atlas integrations), potentially overrepresenting certain cells or structures	Acknowledged in data audit: "This contextual distinction does not remove the possibility of overrepresenting particular cells or atlas-specific structures" [Paper] [Paper: PDF p. 26]	[Paper] [Paper: PDF p. 26]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Cross-type context relies on hierarchical clustering of mean expression	Using mean expression vectors (across batches) to define "biologically related" cell types may obscure condition-specific or rare-state relationships; e.g., injured macrophages may be closer to injured epithelial cells than to healthy macrophages in functional space	Undermines the biological validity of the "cross-type" signal, potentially reducing its utility for disease-state modeling	Replace mean expression with context-aware embeddings (e.g., from CellMSA itself) for clustering; compare downstream performance on PT state classification	[Paper] [Paper: PDF p. 6, 26–27] defines clustering on "mean expression vector over 61,982 vocabulary genes" after normalization
Gene-pair representation is computed per head, but interpretation focuses on single heads (e.g., head 7)	The 8-head structure may represent complementary or redundant information; selecting head 7 based on delta score could be cherry-picking, and the "disease program" might be distributed across heads	Overstates the specificity of head 7; risks missing collaborative or antagonistic interactions between heads	Perform ablation per head on PT classification; compute mutual information between head-wise hub scores and disease labels; test ensemble of top-N heads	[Paper] [Paper: PDF p. 9, Fig. 4a] shows differential hub scores across heads; [Appendix B.2.3] notes "different heads encode disease-associated pairwise activation modes" but doesn't quantify head interdependence
Label-free context retrieval uses HVG-PCA-KNN, which is standard but suboptimal for capturing functional similarity	HVG-PCA-KNN prioritizes technical variance (HVGs) and linear structure (PCA), potentially missing non-linear, pathway-level similarities crucial for cross-type context	Limits the effectiveness of CellMSA in real-world scenarios where cell-type labels are absent or unreliable	Compare label-free retrieval using CellMSA's own gene-pair representations (e.g., average P matrix) as similarity metric for KNN, against HVG-PCA baseline on Bladder integration	[Paper] [Paper: PDF p. 7] states label-free uses "HVG + PCA + KNN"; [Appendix B.1.1] reports CellMSA's label-free score (0.688) < label-informed (0.748), suggesting room for improvement
Perturbation context redefines "cross-type" as perturbation-defined states, breaking the original biological hierarchy	This ad-hoc redefinition ($N_{\text{crosstype}}$ = cells with different perturbations in same cell line) decouples the context logic from the pretraining paradigm, potentially causing domain shift	Questions the transferability of the pretraining objective; the model may not generalize well to novel perturbation contexts	Pretrain a separate CellMSA variant with perturbation-aware context hierarchy; compare its perturbation prediction performance against the main model	[Paper] [Paper: PDF p. 29] states: "Here, 'cross-type' refers to perturbation-defined cellular states rather than ontology-level cell types", confirming the deviation

14 学到的知识

- **MSA类比的迁移可行性**：蛋白质MSA的核心价值在于从同源序列中提取进化保守性与共变性，这一逻辑可成功迁移到单细胞领域——通过聚合“相似但非相同”的细胞（same/cross-batch/type），模型能稳健识别marker基因与共表达模块，这为跨模态基础模型设计提供了新范式。
- **基因对表示（gene-pair representation）是一种高效中间表征**：相比传统cell-level embedding, $P \in \mathbb{R}^G \times G \times \mathcal{D}$ 在低维空间中直接编码u-v基因关系，既保留基因级分辨率，又支持跨细胞统计聚合（Outer-product Mean），是平衡表达能力与计算效率的关键设计。
- **上下文来源的生物学意义必须显式建模**：CellMSA-Module为不同来源上下文（same/cross-batch/type）分配不同role（denoising/stability/contrast），并通过relation-type embedding实现，这比简单拼接更有效；实验证明cross-batch与cross-type上下文带来可测量增益（Table 4）。
- **可解释性需与下游任务对齐**：Fig. 4的解读不是泛泛而谈“网络重编程”，而是聚焦于PT细胞、使用已知肾损伤marker（CDH6, HAVCR1）和GO通路（ECM, integrin）进行验证，这种“任务驱动的可解释性”比单纯可视化更有说服力。
- **大规模预训练的收益与代价并存**：109M细胞规模带来SOTA性能，但也导致20天预训练周期和高GPU内存需求；其优势在batch integration和fine-grained state classification中尤为突出，但在某些任务（如simple cell type annotation）上与Stack差距缩小，提示需按任务需求权衡规模。

15 与既有知识的连接

- **候选连接/方法论连接**：CellMSA的“上下文细胞检索+低维pair表示+高维target编码”三段式架构，与graph neural networks（GNN）中的message passing有深层方法论共鸣：上下文细胞是邻居节点，Outer-product Mean是消息聚合函数，GenePairformer是节点更新函数；但CellMSA显式分离了“上下文处理”与“目标编码”，避免了GNN在超大图上的计算瓶颈。
- **候选连接/方法论连接**：其gene-pair representation与spatial transcriptomics中常建模的“基因共表达邻域”（如SPARK-X）概念相通，均关注基因对在空间/细胞邻域中的协同变化；但CellMSA将邻域从物理空间泛化到细胞表型空间，为跨模态对齐（如scRNA-seq + spatial）提供了新的pair-level对齐锚点。
- **候选连接/方法论连接**：预训练目标LMGM/LRec/LCCE的组合，体现了multi-omics foundation model的典型策略：LMGM（局部重构）对应DNA/RNA序列建模，LRec（全局重建）对应蛋白结构建模，LCCE（对比学习）对应跨模态对齐；这为构建统一的biomedical AI foundation model提供了模块化设计蓝图。
- **弱连接/方法论连接**：与perturbation prediction任务中STATE的耦合方式，揭示了foundation model与task-specific head的协作范式；但CellMSA本身不解决perturbation建模，其贡献在于提供更优的输入表征，这与用户研究方向中“perturbation prediction”形成互补而非直接覆盖。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Cross-modal Pair Alignment (CPA)

originating limitation/observation: CellMSA learns gene-pair representations from scRNA-seq context, but spatial transcriptomics (ST) also harbors spatially co-expressed gene pairs; current ST models lack a mechanism to align their spatial gene-pair patterns with scRNA-seq's cell-type-contextual pairs [Paper] [Paper: PDF p. 2, 9]. **core hypothesis**: Gene-pair representations from scRNA-seq (CellMSA) and ST (e.g.,

SpaGCN-derived spatial neighborhoods) share a common latent space that can be aligned via contrastive learning, enabling cross-modal imputation and spatial mapping of cell states. **delta from paper:** Extends CellMSA's gene-pair concept to spatial modality and introduces explicit cross-modal alignment loss, unlike CellMSA's unimodal focus. **initial method:** Pretrain CellMSA on scRNA-seq; extract $P^{sc} \in \mathbb{R}^G \times G$ from target cells; for ST spots, compute $P^{spat} \in \mathbb{R}^G \times G$ from spatial neighbors; train a lightweight projector to map both to shared space; apply InfoNCE loss between matched scRNA-seq cell types and ST spots. **validation:** (1) Impute missing genes in ST spots using aligned P^{sc} ; (2) Map scRNA-seq cell types to ST locations via nearest neighbor in aligned space; (3) Benchmark on mouse brain (MERFISH) and human breast cancer (Visium) datasets. **failure modes:** Poor alignment if spatial resolution is too low to resolve true co-expression; failure if scRNA-seq and ST use non-overlapping gene panels. **innovation status:** unverified

- **name:** Causal-Pair Refinement (CPR)

originating limitation/observation: Authors explicitly state CellMSA captures "statistical associations rather than explicit causal regulatory relationships" and propose future integration of causal ML [Paper] [Paper: PDF p. 10]. **core hypothesis:** Integrating causal discovery algorithms (e.g., PC algorithm on residualized expression) as a regularizer during CellMSA fine-tuning can prune spurious gene-pair edges and enhance the biological fidelity of $PLMSA$ for perturbation response prediction. **delta from paper:** Adds a causality-aware refinement layer on top of the pre-trained CellMSA-Module, moving beyond statistical correlation. **initial method:** For a fine-tuning dataset (e.g., Replogle), compute partial correlation residuals for each gene pair; use these residuals to weight the Outer-product Mean update ($p^{l+1}_{uv} \propto$ residual strength); jointly optimize with LMGM. **validation:** Compare CPR vs vanilla CellMSA on perturbation prediction (Pearson Δ , DE Overlap); perform knockdown simulation: mask top hub genes in $PLMSA$ and assess impact on predicted perturbation effect. **failure modes:** Causal discovery on sparse scRNA-seq data is notoriously unstable; residualization may remove biologically relevant non-linear dependencies. **innovation status:** unverified

- **name:** Lightweight Context Sampling (LCS)

originating limitation/observation: CellMSA's context size (40 cells) and pretraining cost (20 days) are prohibitive; Figure 5 shows saturation beyond 40 cells, suggesting redundancy [Paper] [Paper: PDF p. 10]. **core hypothesis:** A small, diverse subset of context cells (e.g., 8 cells selected via core-set sampling on gene-pair space) can retain >95% of the full-context performance while reducing CellMSA-Module computation by $5\times$. **delta from paper:** Replaces fixed-size random sampling with an active, representation-aware context selection strategy. **initial method:** During inference, compute initial P^0 for candidate context cells; select top-k cells that maximize determinant of the P^0 covariance matrix (diversity) and minimize reconstruction error of target cell's expression. **validation:** Measure PT state classification accuracy and Pearson Δ vs context size on held-out data; profile GPU memory/time reduction on A800. **failure modes:** Selection overhead may negate speedup; diversity metric may prioritize irrelevant outliers over biologically informative cells. **innovation status:** unverified