

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: discovery
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Rethinking Class Imbalance for Single-Cell Foundation Models: A Systematic Benchmark Across Architectures and Long-Tail Loss Functions	[Paper] [Paper: PDF p. 1]
Authors	Zeyu Dong, Jiahui Zhong	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
URL	http://arxiv.org/abs/2609.23325v1	[Paper meta]
PDF URL	https://arxiv.org/pdf/2609.23325v1	[Paper meta]
Publication date	2026-09-20	[Paper meta]
Code availability	https://github.com/jz890/sc-imbalance	[Paper] [Paper: PDF p. 7]
Core datasets	Multiple Sclerosis (MS), Zheng68K, human Pancreas	[Paper] [Paper: PDF p. 3]
Core backbones	scGPT, scBERT, Geneformer	[Paper] [Paper: PDF p. 3]
Evaluated losses	CE, weighted CE, class-balanced loss, focal loss, LDAM, logit-adjusted softmax	[Paper] [Paper: PDF p. 3]
Total runs	162 (3 × 3 × 6 × 3)	[Paper] [Paper: PDF p. 1]

02 一句话总结

该论文系统评测了六种长尾损失函数在三种单细胞基础模型（scGPT/scBERT/Geneformer）和三个真实数据集（MS/ Zheng68K/Pancreas）上的表现，发现整体准确率严重掩盖罕见细胞类别的系统性失效；这种失效可划分为两类：一类是“损失敏感型”（loss-sensitive），可通过重加权等损失设计显著改善；另一类是“严重纠缠型”（severely entangled），其失败根植于嵌入空间几何结构（如邻域吸收、高NC1值），无法被任何测试损失或架构缓解。论文由此提出首个可复现的scFM长尾基准，并给出基于嵌入几何先验（如NC1、最近邻混淆模式）的实操指南——例如优先选用class-balanced loss处理可恢复类，对严重纠缠类应转向数据增补或拒绝预测而非继续调损失。

03 研究问题

论文直面一个关键矛盾：单细胞基础模型（scFM）在细胞类型标注任务中报告高达97.5%的总体准确率，但这一指标是否可靠？尤其当罕见细胞类型（如疾病早期过渡态、病理亚群）恰恰是临床与机制研究的核心目标时，模型是否在“看不见的地方”持续失败？→ 作者假设：这种失败并非随机噪声，而是由数据内在不平衡结构驱动的、可诊断的系统性现象，且其可修复性取决于两个正交维度：一是训练样本的绝对稀缺程度（而非相对频率），二是嵌入空间中类间几何关系（如类中心距离、簇内紧致度）。→ 方法路径：通过控制变量实验（固定backbone fine-tuning protocol、固定基因panel、固定split策略），解耦损失函数选择的影响，再结合线性探针、UMAP可视化、NC1几何度量与跨架构混淆分析，将“为什么某些类永远失败”从经验观察升维为机制可解释的诊断框架。

04 研究背景与发展路径

单细胞基础模型（scGPT/scBERT/Geneformer）已成为细胞类型标注默认主干，但已有工作（Alsabbagh et al. 2023; Naziri et al. 2025）指出其在罕见子群上性能骤降，且该问题被聚合指标（如accuracy）系统性掩盖。现有缓解策略分三类：采样法（oversampling）、表示法（post-pretraining prototype shaping）、损失法（reweighting/margin adjustment）。其中，损失法因部署轻量、兼容预训练范式而具工程优势，但缺乏跨架构、跨数据集的系统性验证——Alsabbagh et al. (2023) 聚焦采样，Zhao et al. (2025) 提出专用损失+新预训练数据，均未在统一框架下横向比较通用长尾损失。本文填补此空白：以“损失函数”为单一干预轴，在保持所有其他条件（backbone config、data split、tokenization）不变前提下，构建162-run控制实验，将长尾问题从“是否有效”的粗粒度判断，推进到“何时有效、为何无效、如何预判”的细粒度机制理解。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Aggregate metrics mask rare-class failure	Accuracy > Macro-F1 > rare-class recall across all 9 (backbone, dataset) settings [Paper] [Paper: PDF p. 3]	Driven by dataset imbalance structure, not backbone pretraining [Paper] [Paper: PDF p. 1]	Figure 2 (left): consistent gap under plain CE; text states "this gap is present regardless of which foundation model is used" [Paper] [Paper: PDF p. 3]
Loss-level interventions are insufficient for some rare classes	Two MS classes (oligodendrocyte C, phagocyte) achieve near-zero F1 under <i>all</i> 6 losses & 3 backbones [Paper] [Paper: PDF p. 5]	Too few training examples (n=3 each) + transcriptional overlap causing neighborhood absorption in embedding space [Paper] [Paper: PDF p. 5–6]	Figure 3 (left): darkest rows across all three backbone columns; Figure 4: UMAP shows 116 test cells absorbed into unrelated classes; Section 5.1: "both have only 3 training examples" [Paper] [Paper: PDF p. 5]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Reweighting benefit is misattributed to relative frequency	Weighted CE performs best on MS but worst on Zheng68K despite similar imbalance ratios [Paper] [Paper: PDF p. 3]	Benefit depends on <i>absolute</i> training-set size of rare class, not its share of dataset or overall imbalance ratio [Paper] [Paper: PDF p. 1, 4]	Figure 3 (right): strong negative correlation ($r=-0.77$) between $\log(\text{training size})$ and $\Delta F1$; Section 4.3: "MS, whose rare classes have the fewest training examples in absolute terms [...] exhibits the greatest benefit" [Paper] [Paper: PDF p. 4]
Losses make hidden trade-offs obscured by Macro-F1	Logit adjustment boosts rare recall but incurs largest precision penalty among 6 losses [Paper] [Paper: PDF p. 4]	It shifts decision threshold rather than improving feature separability, increasing false positives [Paper] [Paper: PDF p. 4]	Figure 2 (right): logit-adjusted point lies far below $y=x$ line; Table 1: lowest rare-class precision (0.632 vs CE's 0.648); text: "achieves its recall gains primarily by shifting the decision threshold" [Paper] [Paper: PDF p. 4]

06 核心思想

论文核心思想是**将单细胞基础模型的长尾失效解构为两个正交可诊断的机制层**：第一层是**数据层瓶颈**（data scarcity），表现为极低训练样本数（如 $n=3$ ）导致嵌入空间中类中心无法形成可区分簇，进而引发“邻域吸收”（neighborhood absorption）——即少数样本被完全吞没进其他类的嵌入邻域；第二层是**优化层瓶颈**（optimization mismatch），指即使存在判别性信号（linear probe可验证），当前损失函数家族仍无法有效引导分类器头利用该信号，根源在于损失设计未适配单细胞嵌入的几何特性（如类间边界模糊、类内异质性高）。→ 这一思想直接颠覆了“重加权总能改善罕见类性能”的隐含假设，指出**损失选择的有效性必须以前置几何诊断为前提**：NC1值过高或跨架构一致混淆模式，即为“严重纠缠”信号，此时调损失是徒劳的；而 $\Delta F1$ 与 $\log(\text{absolute count})$ 的强负相关，则为“损失敏感”类提供了可量化的收益预测器。最终，论文将长尾问题从超参调优任务，重构为一个**基于嵌入几何先验的决策流程**（diagnostic → predict → select loss → validate）。

07 方法总览

方法采用严格的控制变量范式：在3个backbone（scGPT/scBERT/Geneformer）、3个dataset（MS/Zheng68K/Pancreas）、6个loss（CE/weighted CE/class-balanced/focal/LDAM/logit-adjusted）的全因子组合中，对每个单元执行3次随机种子训练（共162 run）；所有实验共享同一套预处理（scanpy HVG selection, $\ln(1+x)$ transform, gene panel fixed per dataset）与评估协议（validation checkpoint selected by Macro-F1, test evaluation by argmax）。关键创新在于**多尺度诊断闭环**：（1）宏观：用Macro-F1与rare-class recall/AUPRC量化损失效果；（2）中观：用per-class $\Delta F1$ 与 $\log(\text{training size})$ 回归定位可恢复类；（3）微观：用UMAP可视化（Figure 4）、NC1几何度量（Equation 4）、跨架构混淆矩阵（Section 5.2）和线性probe（Section 5.3）解析失败根源。整个流程不修改backbone结构或预训练，纯粹考察损失函数作为“接口层”的能力边界。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Controlled loss benchmark grid	Isolate loss-function effect by holding backbone, data split, preprocessing constant	To disentangle loss efficacy from architecture-specific biases or data leakage artifacts	Input: fixed train/test splits, frozen backbone encoder outputs; Output: per-(backbone,dataset,loss) Macro-F1/rare-recall	Section 3: "holding sample distribution and batch composition fixed throughout to isolate the effect of the loss-function axis" [Paper] [Paper: PDF p. 1]; Table 1 reports aggregated results [Paper] [Paper: PDF p. 5]	Would confound loss comparison with backbone variance (e.g., scBERT's frozen encoder vs scGPT's full FT) — see Section 3 protocol details [Paper] [Paper: PDF p. 2]
Per-class $\Delta F1$ analysis	Quantify gain from switching loss for each rare class c : $\Delta F1_{c} = \max_{\ell \in L} F_{\ell}^{(c)} - F_{\text{CE}}^{(c)}$	To test whether reweighting benefit is driven by absolute sample count, not relative frequency	Input: per-class F1 scores across all losses/seeds/backbones; Output: scalar $\Delta F1_c$ per rare class	Equation 3 [Paper] [Paper: PDF p. 4]; Figure 3 (right): scatter plot of $\Delta F1_c$ vs $\log(\text{training size})$ with $r=-0.77$ [Paper] [Paper: PDF p. 4]	Would obscure the key insight that "MS benefits most because its rare classes have smallest <i>absolute</i> counts", leading to incorrect generalization about imbalance ratio [Paper] [Paper: PDF p. 4]
Embedding geometry diagnostic (NC1 + nearest-neighbor)	Measure cluster tightness ($NC1 = \frac{\text{tr}(\Sigma_{W \times W})}{\text{tr}(\Sigma_{B \times B})}$) and confusion topology	To distinguish "severely entangled" classes (high NC1 or concentrated neighbor absorption) from "loss-sensitive" ones	Input: frozen test-set embeddings (scGPT/scBERT/Genformer under CE); Output: NC1 value per class, rank-1 neighbor class per entangled cell	Equation 4 [Paper] [Paper: PDF p. 6]; Section 5.2: "oligodendrocyte C shows substantially higher NC1 [...] quantitatively confirming it lacks tight clustering" [Paper] [Paper: PDF p. 6]; Figure 4 visualization [Paper] [Paper: PDF p. 7]	Would leave "why some classes never recover" as anecdotal; NC1 provides quantitative, backbone-invariant signature of geometric failure [Paper] [Paper: PDF p. 6]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Linear probe on frozen embeddings	Test whether discriminative signal exists <i>in the representation</i> independent of classifier head training	To localize bottleneck: is failure due to poor representation (pretrain issue) or poor classifier optimization (loss issue)?	Input: frozen CE-fine-tuned embeddings; Output: 5-fold CV F1 of class-balanced logistic regression	Section 5.3: probe achieves higher F1 than any trained head for oligodendrocyte C/phagocyte (e.g., scGPT probe 0.465 vs best trained 0.329) [Paper] [Paper: PDF p. 6]	Would falsely attribute failure to representation collapse; probe proves signal exists but is unused, implicating loss design [Paper] [Paper: PDF p. 6]

09 关键公式与符号

- **No verifiable closed-form equation is presented in the paper.** All listed equations are descriptive definitions or computational recipes, not derived models.
- **Equation 1:** $\text{Macro-F1} = 1/C \sum_{c=1}^C F1_{c,c}$ — Definition of unweighted mean F1 across C classes [Paper] [Paper: PDF p. 3]. Symbol $F1_{c,c}$ denotes F1 score of class c .
- **Equation 2:** $\text{Recall}_R = 1/|R| \sum_{c \in R} \text{Recall}_c$ — Definition of macro-averaged recall over rare-class set R [Paper] [Paper: PDF p. 3]. R is defined as classes with training frequency <5% [Paper] [Paper: PDF p. 3].
- **Equation 3:** $\Delta F1_{c,c} = \max_{\ell \in L} F^{\ell}_{c,c} - F^{(CE)}_{c,c}$ — Definition of per-class F1 gain from optimal loss over CE [Paper] [Paper: PDF p. 4]. L is the set of six losses.
- **Equation 4:** $\text{NC1} = \text{tr}(\Sigma_W) / \text{tr}(\Sigma_B)$ — Neural collapse trace ratio [Paper] [Paper: PDF p. 6]. Σ_W : average within-class scatter matrix; Σ_B : between-class scatter matrix of class centroids around global mean. Lower NC1 indicates better separation.
- **Key symbols:** R (rare-class set), $F1_{c,c}$ (class-wise F1), Recall_c (class-wise recall), NC1 (geometry metric), L (loss set), $\Delta F1_{c,c}$ (reweighting gain).

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Aggregate metric gap (Fig 2 left)	Plain CE yields consistent accuracy > Macro-F1 > rare-class recall across all architectures	Mean over 9 (backbone × seed) runs per dataset; same CE loss, fixed protocol	Gap present for all 3 datasets, regardless of backbone [Paper] [Paper: PDF p. 3]	Gap is inherent to data imbalance structure, not backbone-specific	That pretraining causes the gap — authors explicitly state "driven by dataset structure rather than pretraining" [Paper] [Paper: PDF p. 1]	[Paper] [Paper: PDF p. 3], Figure 2
Loss ranking (Table 1)	Class-balanced loss & LDAM are most consistent across datasets	Mean rank computed within each (backbone, dataset) cell before averaging	Class-balanced mean rank 2.4, LDAM 2.6 (out of 6) [Paper] [Paper: PDF p. 3]	These two losses generalize best to unseen dataset imbalances	That they are universally optimal — weighted CE tops MS Macro-F1 (0.721), LDAM tops Pancreas (0.819) [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 3], Table 1
$\Delta F1$ vs $\log(\text{size})$ regression (Fig 3 right)	Reweight benefit is predicted by absolute training-set size	Pearson correlation of $\Delta F1_c$ with $\log(\text{training size})$ across 19 recoverable rare classes	$r = -0.77$, $p < 0.001$ [Paper] [Paper: PDF p. 4]	Absolute count, not relative frequency, governs reweighting ROI	That this holds for <i>all</i> rare classes — 4 severely entangled classes excluded ($n=3$ samples) [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 3
Logit adjustment trade-off (Fig 2 right)	Logit adjustment trades rare-class precision for recall	Plot of rare-class precision vs recall for all 6 losses, averaged over 9 settings	Logit-adjusted point lies far below $y=x$ line; lowest precision (0.632) despite high recall (0.685) [Paper] [Paper: PDF p. 4]	Its recall gain stems from threshold shift, not improved separability	That it harms non-rare classes — non-rare precision spread is only 1.1 points vs 10.6 for rare [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 2

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Linear probe on frozen embeddings (Sec 5.3)	Discriminative signal exists for severely entangled classes	Class-balanced logistic regression on frozen CE embeddings, 5-fold CV	Probe F1 exceeds best trained head F1 for oligodendrocyte C (0.465 vs 0.329) and phagocyte (0.462 vs 0.329) [Paper] [Paper: PDF p. 6]	Bottleneck is in classifier training/loss design, not representation collapse	That a nonlinear probe would close the gap — authors note this as future work [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 6], Section 5.3

11 对结论的正确理解

- **"Class-balanced loss and LDAM are most consistent"** 意味着它们在9个(backbone, dataset)组合中平均排名最高 (2.4/2.6)，但不意味着它们在每个组合中都最优——例如weighted CE在MS上Macro-F1最高 (0.721)，LDAM在Pancreas上最高 (0.819) [Paper] [Paper: PDF p. 3]。一致性指鲁棒性，非绝对优越性。
- **"Reweighting benefit predicted by absolute count"** 是一个统计规律 ($r=-0.77$)，适用于"recoverable"类 (即排除 $n=3$ 样本的严重纠缠类后)，**不能外推至 $n<5$ 的极端稀缺场景**——论文明确将 $n=3$ 类标记为"severely entangled"并从回归中剔除[Paper] [Paper: PDF p. 4]。
- **"Logit adjustment trades precision for recall"** 是基于其在rare-class precision-recall图中位于 $y=x$ 线下方的观测，**不意味着它降低整体精度**——非罕见类的precision spread仅1.1点，表明其影响高度集中在罕见类[Paper] [Paper: PDF p. 4]。
- **"Failure rooted in embedding geometry"** 由多重证据支撑：UMAP显示116细胞被吸收 (Figure 4)、跨架构混淆模式一致 (Section 5.2)、NC1值异常 (oligodendrocyte C高，phagocyte低但邻域集中) [Paper] [Paper: PDF p. 6–7]，**但几何失败本身由数据稀缺 ($n=3$) 触发，非模型固有缺陷。**

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited backbone coverage	Only scGPT, scBERT, Geneformer evaluated; other models (scFoundation, CellPLM) remain untested	"Other existing single-cell foundation models [...] remain untested" [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]
Classifier head expressivity ceiling	Linear probe recovers signal unused by trained heads, suggesting current losses may not fully exploit representation	"A more expressive, nonlinear classifier head might extract additional signal beyond what the six losses we test currently achieve" [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Isolated imbalance axis	Study focuses solely on cell-type frequency imbalance; ignores compounding factors like demographic composition or batch effects	"Compounding variables such as demographic composition [...] or batch effects [...] require future investigation" [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
NC1's sensitivity to small-n classes	Phagocyte (n=3) has low NC1 (0.17–0.32) not because it's well-separated, but because tiny n makes ΣW artificially small — a known statistical artifact in scatter-matrix estimation	Misinterpreting low NC1 as "good geometry" could wrongly classify phagocyte as recoverable, delaying correct diagnosis of data scarcity	Compute NC1 with bootstrap resampling (n=100) on phagocyte's 3 samples to assess variance; compare to synthetic n=3 clusters from Gaussian mixture	Section 5.2: "its small cell count means a handful of tightly clustered cells embedded inside another class' s region can produce low within-class scatter despite total confusability" [Paper] [Paper: PDF p. 6]
Linear probe's CV setup	Probe uses 5-fold stratified CV <i>within test-set embeddings</i> , measuring internal separability, not train/test generalization — yet conclusions treat it as evidence of "unused signal"	If the probe overfits the test set (despite stratification), the "signal exists" claim weakens; true test requires held-out validation	Repeat probe on <i>held-out validation set</i> (10% of training data, as used for checkpoint selection) and compare F1 to trained head's validation F1	Section 5.3: "5-fold stratified cross-validation within the frozen test-set embeddings (measuring CV-internal separability, not train/test generalization)" [Paper] [Paper: PDF p. 6]
UMAP's role in Figure 4	UMAP is a stochastic, non-linear projection; visual "absorption" in Figure 4 may not reflect true high-dimensional geometry, especially for n=3 clusters	Over-reliance on UMAP could lead to false geometric conclusions; the core claim (neighborhood absorption) is better supported by centroid distances and NC1	Replace UMAP with t-SNE (different stochasticity) and PCA (linear) for same scGPT embeddings; verify if oligodendrocyte C/phagocyte still embed near confusion partners	Figure 4 caption: "UMAP (Healy and McInnes 2024) of MS test-set embeddings (scGPT)" — no robustness check reported [Paper] [Paper: PDF p. 7]

14 学到的知识

- **长尾失效不是单一级问题，而是数据层（n=3样本）与优化层（loss无法引导利用信号）的双重瓶颈：**前者需数据工程（如主动学习标注），后者需损失/分类器协同设计。
- **Macro-F1是危险的汇总指标：**它掩盖了logit adjustment这类"recall-for-precision"的隐性权衡，必须辅以precision-recall曲线或AUPRC分析。
- **嵌入几何可作为损失选择的前置诊断器：**NC1 > 1.0 或跨架构一致混淆（如phagocyte→oligodendrocyte A）是"放弃调损失、转向数据补全"的强信号；而 $\Delta F1$ 与log(absolute count)的负相关，则为"值得尝试class-balanced loss"提供量化依据。
- **线性probe是解耦瓶颈的黄金工具：**当probe F1 $\gg$ trained head F1，说明问题在分类器训练（loss/optimizer），而非表示学习（pretrain）——这对用户做perturbation prediction时诊断"是表征不对还是head不会用"极具价值。
- **计算开销几乎为零：**所有重加权损失增加的训练时间 < 3.2%，远小于backbone选择差异（scBERT比Geneformer慢18 $\times$ ）[Paper] [Paper: PDF p. 4]，故无理由不默认启用class-balanced loss。

15 与既有知识的连接

- **候选连接/方法论连接：**本文的"embedding geometry diagnostic"（NC1 + nearest-neighbor）与用户研究方向中的**cell state representation**和**perturbation prediction**高度契合——若扰动后细胞状态在嵌入空间中发生"邻域吸收"（如treated cell被吸收进control cluster），同样可用NC1突变或最近邻分布偏移来量化扰动效应的可检测性。
- **候选连接/方法论连接：**论文揭示的"绝对样本数决定重加权收益"规律，可迁移至用户**multi-omics**场景：当整合scRNA+scATAC时，若某稀有细胞类型的ATAC peak覆盖度极低（n=3 peaks），其跨模态对齐可能同样陷入"严重纠缠"，需优先提升该模态测序深度而非调alignment loss。
- **候选连接/方法论连接：**Figure 4的UMAP可视化策略（highlight rare cells against gray background）可直接复用于用户**spatial transcriptomics**研究——例如在Visium切片UMAP中高亮病灶区稀有细胞，观察其是否被吸收进邻近正常组织簇，从而判断空间微环境是否掩盖病理信号。
- **弱连接/方法论连接：**论文使用的scGPT/scBERT/Geneformer均为序列化建模（gene token order），与用户关注的**graph neural networks**无直接接口，但其"几何诊断"思想可启发GNN：用节点嵌入的类内/类间距离比（类似NC1）替代UMAP，诊断图结构对稀有细胞类型判别性的贡献。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** Geometry-Guided Reject Option for scFM

originating limitation/observation: Authors identify "severely entangled" classes via NC1 and nearest-neighbor patterns, and recommend "abstaining" rather than loss engineering [Paper] [Paper: PDF p. 7]. But no operational reject threshold is provided. **core hypothesis:** A joint threshold on $NC1 > \tau_1$ AND top-3 nearest neighbors belonging to the same non-self class with entropy $< \tau_2$ predicts unrecoverable classes with >95% precision. **delta from paper:** Paper diagnoses but doesn't automate rejection; this defines precise, geometry-based rejection criteria. **initial method:** On MS test embeddings, sweep τ_1 (NC1) and τ_2 (neighbor entropy) to maximize precision of "reject" label (true if F1 < 0.1 under all losses). Validate on

Zheng68K/Pancreas. **validation:** Reject rate vs. rare-class recall trade-off curve; compare to baseline rejection by training size <5 . **failure modes:** Over-rejection if τ thresholds too loose; under-rejection if NC1 estimation unstable for $n < 10$. **innovation status:** unverified

- **name:** Perturbation-Aware NC1 for Spatial Transcriptomics

originating limitation/observation: Paper uses NC1 on scRNA embeddings to diagnose rare-class failure; spatial data has inherent neighborhood structure (spots), but NC1 assumes i.i.d. samples. **core hypothesis:** Spatially constrained NC1 — where Σ_{W} includes only spots within 3-neighbor radius — better captures microenvironment-driven entanglement in spatial data. **delta from paper:** Adapts NC1 from i.i.d. scRNA to graph-structured spatial data by incorporating spatial adjacency. **initial method:** Build spot graph from Visium coordinates; compute spatial-NC1 = $\text{tr}(\Sigma_{W, \text{spatial}}) / \text{tr}(\Sigma_B)$ where $\Sigma_{W, \text{spatial}}$ averages scatter only over spatial neighbors. Correlate with perturbation prediction error. **validation:** On simulated perturbation (e.g., cytokine-treated spots), test if spatial-NC1 drop predicts successful recovery better than vanilla NC1. **failure modes:** Requires accurate spatial graph construction; sensitive to spot density variation. **innovation status:** unverified

- **name:** Multi-Omics Entanglement Transfer

originating limitation/observation: Paper finds $n=3$ training samples cause entanglement in scRNA; in multi-omics, one modality (e.g., scATAC) may have even lower coverage for rare cells. **core hypothesis:** Entanglement status (recoverable vs. severely entangled) transfers across modalities — if a rare cell type is severely entangled in scRNA, its scATAC embedding will show similarly high spatial-NC1. **delta from paper:** Extends entanglement diagnosis from single-modality to cross-modality consistency check. **initial method:** For rare classes in matched scRNA+scATAC, compute NC1 on both modalities' embeddings; measure correlation of NC1 values and confusion patterns. **validation:** Train modality-specific classifiers; test if "entangled in RNA" predicts "entangled in ATAC" for same class. **failure modes:** Modality-specific batch effects may dominate entanglement signal. **innovation status:** unverified