

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: discovery
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

- Title: Towards a knowledge-enhanced single-cell foundation model
- Authors: Hanqing Zhang, Jie Bao, Mei Ma, Shuai Liu, Jiaying Ma, Jiaguan Liu, Jiaxiao Li, Zhenbo Li, Wenwen Gong, Zhijun Cao
- Preprint: arXiv:2609.14970v1 [cs.AI], 2026-09-14
- Model name: scKITE (single-cell Knowledge-Integrated Transformer)
- Core innovation: Two-stage pretraining with lightweight auxiliary decoders for annotation and regulon prediction; decoders discarded post-pretraining [Paper: PDF p. 2–3].
- Pretraining corpus size: 179,067 pseudo-bulk transcriptomic profiles (≈0.18M), i.e., < 0.5% of Geneformer/scGPT/scFoundation [Paper: PDF p. 2, 3].
- Architecture: 12-layer Transformer encoder (hidden dim 512, 8 heads); two 2-layer autoregressive decoders (regulon & annotation) used only in Stage 2 [Paper: PDF p. 21–22].
- Input format: Gene tokens + binned expression values (51 levels) + mask embedding; max sequence length 2,049 [Paper: PDF p. 21].
- Output representations: Cell embedding = h_{cls} (Eq. 4); gene embedding = h_i for each expressed gene g_i (Eq. 5) [Paper: PDF p. 22].

02 一句话总结

scKITE

是一种知识增强型单细胞基础模型，通过在两阶段预训练中引入轻量级辅助解码器（分别监督细胞级自然语言注释和基因级调控程序），将生物学知识注入共享Transformer编码器；解码器在预训练后即被丢弃，仅保留知识增强的编码器，以极小数据量（<0.5% SOTA模型）在细胞类型标注、批次整合与扰动响应预测等下游任务上全面超越现有scFM [Paper: PDF p. 1–3].

03 研究问题

- 如何在显著扩大预训练数据规模的前提下，提升单细胞基础模型（scFM）的生物学可解释性与下游泛化能力？
 - 是否存在比单纯扩展转录组数据更高效的知识驱动缩放维度？
 - 细胞级文本注释与基因级调控程序能否作为互补监督信号，协同优化共享编码器的细胞状态与基因上下文表征？
- [Paper: PDF p. 1–2]

04 研究背景与发展路径

-

背景起点：scFMs（如Geneformer、scGPT、scFoundation）依赖大规模转录组预训练，但数据扩展已显现收益递减与计算成本剧增瓶颈；近期系统评估显示其缺乏类似大语言模型的清晰数据缩放律 [Paper: PDF p. 1–2, 14].

- 关键观察：作者的数据缩放分析发现，增加预训练数据带来的性能增益迅速饱和（scKITE w/o knowledge enhancement 在50%数据后达平台期），而知识增强预训练在所有数据尺度下均稳定提升性能（平均相对提升28.8%） [Paper: PDF p. 2–3, Fig. 1a, Supp. p. 23–24].

- 发展路径：从“数据驱动缩放”转向“知识驱动缩放”——利用CELLxGENE衍生的CellWhisperer语料库中配对的自然语言细胞注释（cell-level text annotation）与pySCENIC推断的激活调控子（regulon）序列（gene-level regulatory program），构建双轨监督信号 [Paper: PDF p. 2–3, Fig. 1b, Supp. p. 18–19].

- 方法演进：继承Transformer架构与掩码表达重建（masked-expression reconstruction），但创新性地引入Stage 2知识增强阶段，通过跨注意力连接的轻量解码器联合优化，避免参数膨胀 [Paper: PDF p. 3–4, Supp. p. 22–23].

05 论文识别的核心痛点

Pain point / Manifestation / Cause or author explanation / Evidence from the paper

Pain point: Diminishing returns from data scaling

Manifestation: Performance plateaus rapidly (e.g., scKITE w/o knowledge enhancement saturates after 50% corpus); marginal gains require massive computational cost

Cause or author explanation: Transcriptomic data alone lacks explicit biological semantics; scaling without structural guidance yields redundant representation capacity

Evidence from the paper: “Our data scaling analyses showed that incorporating biological knowledge [...] provided additional scaling dimension than simply increasing data size” [Paper: PDF p. 1]; “scKITE (w/o knowledge enhancement) reached a performance plateau after scaling to 50% of the pretraining data” [Paper: PDF p. 3]; Fig. 1a shows flat curve beyond 50% for ablation model [Paper: PDF p. 5].

Pain point: Lack of biologically grounded supervision

Manifestation: Existing scFMs learn statistical patterns but fail to explicitly encode cell identity logic or gene regulatory grammar, limiting zero-shot generalization and interpretability

Cause or author explanation: Standard masked autoencoding reconstructs expression values but does not enforce alignment with known biological hierarchies or mechanisms

Evidence from the paper: “Cellular systems are inherently complex, arising from coordinated interactions [...] Incorporating these complementary sources [...] may therefore help scFMs learn representations that better capture both cellular context and underlying regulatory structure” [Paper: PDF p. 2]; cross-attention analysis confirms annotation decoder attends to marker genes, regulon decoder to TF targets [Paper: PDF p. 10–13, Fig. 5].

Pain point: Architectural inefficiency in knowledge integration

Manifestation: Prior attempts to inject knowledge often require task-specific heads at inference time or full multi-modal architectures, compromising generality and transferability

Cause or author explanation: Directly fusing heterogeneous modalities (text + expression) risks representation entanglement or inference-time dependency on unavailable annotations

Evidence from the paper: “These decoders are used only during pretraining and subsequently discarded, yielding a general-purpose encoder [...] without requiring annotation or regulon information at inference time” [Paper: PDF p. 4]; “downstream inference requires only transcriptomic input” [Supp. p. 23].

06 核心思想

scKITE 的核心思想是“知识蒸馏式预训练”（knowledge distillation via auxiliary

supervision)：不改变下游使用范式（纯转录组输入），而是在预训练阶段，通过两个轻量、任务专用的解码器（annotation decoder & regulon decoder），将细胞级文本注释与基因级调控程序作为“教师信号”，经由跨注意力机制（cross-attention）反向引导共享编码器学习更具生物学意义的隐藏状态；解码器本身不参与下游推理，其唯一作用是将结构化生物学知识“蒸馏”进编码器权重中，实现知识增强与模型简洁性的统一 [Paper: PDF p. 3–4, Fig. 1c–d].

07 方法总览

scKITE 采用两阶段预训练框架：

- Stage 1（转录组自监督）：标准掩码表达重建（masked-expression reconstruction），使用30%掩码率，仅优化编码器 [Paper: PDF p. 3, Supp. p. 22].
- Stage 2（知识增强）：在Stage 1检查点上初始化，保留10%掩码率的表达重建目标，并并行引入两个轻量自回归解码器：
 - Annotation decoder：以<cls>及基因序列为Key/Value，生成配对的自然语言细胞注释序列（e.g., “Neuron cell type from the thalamic complex...”） [Paper: PDF p. 3, 5, Supp. p. 22–23].
 - Regulon decoder：同上，生成TF-target调控子序列（e.g., “ALX3 <arrow> Z1C2 SNAP25 ... <regulonsep> ATF1 <arrow> NFATC1 USP32 ...”） [Paper: PDF p. 3, 5, Supp. p. 18–19].
- 损失函数：Stage 2联合优化三目标加权和： $L_{\text{Stage2}} = \lambda_{\text{expr}} L_{\text{expr}} + \lambda_{\text{reg}} L_{\text{reg}} + \lambda_{\text{ann}} L_{\text{ann}}$ ，其中 L_{expr} 为均方误差（Eq. 6）， $L_{\text{reg}}/L_{\text{ann}}$ 为token级交叉熵（Eq. 7–8），所有 $\lambda=1$ [Paper: PDF p. 23, Eq. 9].
- 下游使用：仅加载训练完成的编码器； h_{cls} 为cell embedding， h_i 为gene embedding [Paper: PDF p. 22, Eq. 4–5].

08 核心模块拆解

Module / Function / Why needed / Input and output / Supporting evidence / Known or expected effect of removal

Module: Shared Transformer Encoder

Function: Produces contextualized hidden states $H = [h_{\text{cls}}, h_1, \dots, h_n]$ for input transcriptomic sequence X

Why needed: Core representation backbone; must absorb both expression statistics and biological knowledge

Input and output: Input: Gene-token IDs + binned expression + mask embeddings (max len 2049) [Supp. p. 21]; Output: H (Eq. 3) [Paper: PDF p. 22]

Supporting evidence: “the encoder produces contextualized hidden states $H = [h_{\text{cls}}, h_1, \dots, h_n]$ = Encoder(X)” [Paper: PDF p. 22, Eq. 3]; used for all downstream tasks [Paper: PDF p. 4, Fig. 1d]

Known or expected effect of removal: Complete failure of all downstream tasks; reverts to unenhanced baseline performance (as in scKITE w/o knowledge enhancement) [Paper: PDF p. 3, 7].

Module: Annotation Decoder

Function: Autoregressively generates natural-language cell annotation sequence conditioned on encoder states H

Why needed: Provides cell-level semantic supervision, guiding encoder to prioritize marker genes and hierarchical identity signals

Input and output: Input: H , causal self-attention; Output: token logits over text vocabulary [Supp. p. 22]; loss L_{ann} (Eq. 7) [Paper: PDF p. 23]

Supporting evidence: “Annotation supervision was assessed by examining whether decoder attention preferentially focused on cell-type marker genes” [Paper: PDF p. 10]; Fig. 5b–d show strong enrichment of canonical markers [Paper: PDF p. 13]

Known or expected effect of removal: Loss of zero-shot cell annotation gain (64.0% macro-F1 drop) and impaired hierarchical immune organization (ARI/NMI drop) [Paper: PDF p. 2, 6].

Module: Regulon Decoder

Function: Autoregressively generates TF-target regulon sequence conditioned on H

Why needed: Provides gene-level regulatory supervision, guiding encoder to encode TF-target relationships and context-dependent regulation

Input and output: Input: H, causal self-attention; Output: token logits over gene/regulon vocabulary [Supp. p. 22]; loss L_{reg} (Eq. 8) [Paper: PDF p. 23]

Supporting evidence: “Regulatory supervision was assessed by examining whether decoder attention preferentially accessed genes within externally supported TF regulatory programs” [Paper: PDF p. 10]; Fig. 5e–h show CollecTRI target enrichment and cell-context specificity [Paper: PDF p. 13]

Known or expected effect of removal: Loss of perturbation-response prediction gain (19.8% Top-20 DE MSE increase) and reduced recovery of direction-correct DE genes [Paper: PDF p. 2, 8].

Module: Cross-Attention Mechanism

Function: Enables decoders to attend to full sequence of encoder hidden states H, forming query-key-value mapping

Why needed: Critical interface for knowledge injection; allows decoders to “read out” relevant biological features from encoder context

Input and output: Query: decoder hidden states; Key/Value: H [Supp. p. 22]; enables attention percentile analysis [Supp. p. 28–30]

Supporting evidence: “Decoder cross-attention between the annotation/regulon decoders and the shared encoder representations enables identification of genes associated with cell identity and transcription factor regulatory programs” [Paper: PDF p. 13, Fig. 5a]

Known or expected effect of removal: Without cross-attention, decoders cannot guide encoder learning; knowledge signals become disconnected, collapsing to Stage 1 performance.

09 关键公式与符号

ID / Formula / Meaning / Page / Notes

ID: Eq. 3

Formula: $H = [h_{\text{cls}}, h_1, \dots, h_n] = \text{Encoder}(X)$

Meaning: Encoder outputs contextualized hidden states for input sequence X

Page: p. 22

Notes: Foundation for all representations; h_{cls} and h_i are direct outputs.

ID: Eq. 4

Formula: $z_{\text{cell}} = h_{\text{cls}}$

Meaning: Cell-level representation is the <cls> token's final hidden state

Page: p. 22

Notes: Used for cell type annotation, batch integration, UMAP [Paper: PDF p. 4, 7, 9].

ID: Eq. 5

Formula: $z_{\text{gi}} = h_i$

Meaning: Gene-level representation is the hidden state of the i-th expressed gene

Page: p. 22

Notes: Contextual: same gene has different z_{gi} across cells; used for perturbation prediction [Paper: PDF p. 4, 8].

ID: Eq. 6

Formula: $\sum_{i \in M} (x_{\text{mask}, i} - x_i)^2$

Meaning: Masked-expression reconstruction loss (L_{expr})

Page: p. 22

Notes: Regression head predicts binned expression values at masked positions M.

ID: Eq. 9

Formula: $L_{\text{Stage2}} = \lambda_{\text{expr}} L_{\text{expr}} + \lambda_{\text{reg}} L_{\text{reg}} + \lambda_{\text{ann}} L_{\text{ann}}$

Meaning: Joint optimization objective for Stage 2

Page: p. 23

Notes: Balances transcriptomic fidelity (L_{expr}) with biological knowledge (L_{reg} , L_{ann}).

ID: Eq. 10

Formula: $\text{AvgBIO} = (\text{NMI} + \text{clip}(\text{ARI}, 0, 1) + \text{ASW}_{\text{cell}}) / 3$

Meaning: Composite score for biological conservation in batch integration

Page: p. 26

Notes: Higher = better cell-type preservation; used in Fig. 3a.

ID: Eq. 11

Formula: $\text{ASW}_{\text{batch}} = 1 - \text{Silhouette}_{\text{batch}}$

Meaning: Silhouette_{batch}

Page: `

Notes: Batch average silhouette width within each cell type

Field 6: p. 26

Field 7: Measures batch mixing quality per cell type; used in AvgBATCH (Eq. 12).

ID: Eq. 12

Formula: $\text{AvgBATCH} = (\text{ASW}_{\text{batch}} + \text{GraphConn}) / 2$

Meaning: Composite score for batch mixing

Page: p. 27

Notes: Higher = better batch-effect removal; used in Fig. 3a.

ID: Eq. 13

Formula: $\text{OverallScore} = 0.6 \times \text{AvgBIO} + 0.4 \times \text{AvgBATCH}$

Meaning: Weighted summary metric for batch integration

Page: p. 27

Notes: Emphasizes biological conservation (60%) over batch mixing (40%).

10 实验设计与证据链

Experiment / Claim tested / Comparison and conditions / Result / Supported conclusion / Unsupported stronger conclusion / Source

Experiment: Data scaling (Fig. 1a)

Claim tested: Knowledge enhancement provides scalable performance gain beyond data size

Comparison and conditions: scKITE vs. scKITE (w/o knowledge enhancement) trained on 10%/25%/50%/100% of corpus (35,813–358,134 profiles); fixed architecture, evaluation tasks

Result: scKITE consistently outperformed ablation across all fractions; avg 28.8% relative improvement; ablation plateaued at 50%

Supported conclusion: Biological knowledge acts as an orthogonal, non-saturating scaling dimension

Unsupported stronger conclusion: That knowledge enhancement universally dominates data scaling across all scFM architectures and corpora

Source: [Paper: PDF p. 3, Fig. 1a, p. 5]

Experiment: Zero-shot cell annotation (Fig. 2a)

Claim tested: scKITE enables accurate label-free cell typing

Comparison and conditions: scKITE vs. scGPT vs. Geneformer vs. ablation on 5 benchmarks (Human Pancreas, MS, etc.); frozen encoder + k-NN classifier

Result: scKITE mean macro-F1=0.500 (zero-shot), outperforming scGPT (0.430) and Geneformer (0.399); retained advantage after fine-tuning (0.668 vs. 0.561/0.543)

Supported conclusion: Knowledge-enhanced pretraining improves zero-shot capability and fine-tuning efficiency

Unsupported stronger conclusion: That scKITE generalizes to all uncured clinical datasets without domain adaptation

Source: [Paper: PDF p. 4, Fig. 2a, p. 7]

Experiment: Batch integration (Fig. 3a)

Claim tested: scKITE balances biological conservation and batch mixing

Comparison and conditions: scKITE vs. ablation vs. scGPT vs. Geneformer on 4 datasets (Perirhinal cortex, COVID-19, etc.); frozen encoder, no fine-tuning
 Result: scKITE mean AvgBIO=0.474 (+0.136 vs. ablation), mean AvgBATCH=0.938 (+0.102); exceeded Geneformer by 6.5% (AvgBIO) and 4.2% (AvgBATCH)
 Supported conclusion: Knowledge enhancement improves integration robustness across diverse technical/biological batch sources
 Unsupported stronger conclusion: That scKITE eliminates all batch effects without sacrificing rare cell type resolution
 Source: [Paper: PDF p. 6, Fig. 3a, p. 9]

Experiment: Perturbation prediction (Fig. 4b–c)
 Claim tested: scKITE gene embeddings improve GEARS-based response forecasting
 Comparison and conditions: scKITE vs. scGPT vs. scFoundation vs. GEARS vs. ablation in GEARS framework on Norman/Replogle; gene embeddings replaced, rest unchanged
 Result: scKITE achieved lowest Top-20 DE MSE in both datasets; highest Pearson correlation in Seen1/Seen2/unseen-single (Norman); improved direction-correct DE recovery ($P=0.010$)
 Supported conclusion: Contextual gene representations enriched with regulatory knowledge enhance perturbation generalization
 Unsupported stronger conclusion: That scKITE predicts absolute expression levels (not just DE rank/direction) with high fidelity
 Source: [Paper: PDF p. 8, Fig. 4b–e, p. 11]

Experiment: Cross-attention interpretation (Fig. 5b–e)
 Claim tested: Annotation/regulon decoders guide encoder attention to biologically relevant genes
 Comparison and conditions: Annotation decoder attention percentiles vs. marker genes; Regulon decoder vs. CollecTRI TF targets
 Result: Marker genes enriched in 196/198 cell types ($P=3.7e-34$); CollecTRI targets enriched for 32/45 TFs ($P=5.9e-2$); context-specific patterns (e.g., TBX21 in NK cells)
 Supported conclusion: Knowledge supervision is mechanistically implemented via attention routing to validated biological entities
 Unsupported stronger conclusion: That attention percentiles quantitatively predict causal regulatory impact (beyond correlation)
 Source: [Paper: PDF p. 10–13, Fig. 5, p. 13]

11 对结论的正确理解

- scKITE

的优势源于知识增强预训练范式本身，而非单纯模型容量或数据工程技巧：其179k样本量远小于SOTA (30M+)，且架构 (12-layer, 512-dim) 小于Geneformer/scGPT，证明知识是更高效的数据“压缩”形式 [Paper: PDF p. 2–3].

-

“知识增强”特指细胞级文本注释与基因级调控程序的双轨监督，二者互补：前者锚定细胞身份 (e.g., “Neuron from thalamus”)，后者建模基因调控逻辑 (e.g., “TBX21 → IFNG”)，共同塑造层次化表征 [Paper: PDF p. 2, 10–13].

- 性能提升是可解释、可验证的：通过decoder-to-encoder cross-attention分析，证实annotation decoder聚焦marker genes (Fig. 5b–d)，regulon decoder retrieves external TF targets (Fig. 5e–h)，排除了黑箱性能幻觉 [Paper: PDF p. 10–13].

- scKITE 是通用编码器：下游任务 (cell annotation, batch integration, perturbation prediction) 均只用 h_cls 或 h_i ，无需修改或附加模块，符合foundation model定义 [Paper: PDF p. 4, Fig. 1d].

- 结论不声称取代多组学或空间转录组：论文未涉及spatial transcriptomics、multi-omics或cross-modal alignment实验，其“weak connection/methodological connection”判断准确 [User context note].

12 作者明确承认的限制

Limitation / Specific manifestation / Future direction proposed by authors / Source

Limitation: Dependence on supervision quality

Specific manifestation: Cell annotations vary in completeness/specificity across datasets; pySCENIC-inferred regulons are predictive, not experimentally causal

Future direction proposed by authors: Incorporate richer cell identity knowledge (curated literature, expert annotations); use experimentally grounded regulatory resources (e.g., ChIP-seq, perturbation data)

Source: [Paper: PDF p. 12]

Limitation: Corpus/architecture/benchmark specificity

Specific manifestation: Data-efficiency pattern observed within specific CELLxGENE corpus, Transformer architecture, and benchmark suite; not a universal scaling threshold

Future direction proposed by authors: Systematic exploration of other knowledge sources (perturbation-derived causality, chromatin accessibility, TF-binding) and integration strategies

Source: [Paper: PDF p. 14]

Limitation: Regulon inference limitations

Specific manifestation: pySCENIC provides predicted TF-target relationships, not experimentally established causal networks

Future direction proposed by authors: Integrate more standardized, experimentally grounded descriptions of cellular states and regulatory interactions

Source: [Paper: PDF p. 12, 14]

13 批判性分析

[Analysis] Observation / Potential issue or alternative explanation / Why it matters / How to test it / Basis

[Analysis] Observation: Geometric sketching for nested subsets may bias diversity

Potential issue or alternative explanation: Using geometric sketching [42] to select nested subsets could over-represent dominant cell types or expression manifolds, under-sampling rare states; this might inflate apparent gains of knowledge enhancement on minority classes

Why it matters: If knowledge enhancement mainly benefits well-sampled classes, its real-world utility for rare disease or developmental biology applications is overstated

How to test it: Re-run scaling analysis using stratified random sampling by cell type or tissue origin, and compare performance delta on rare vs. common classes

Basis: [Supp. p. 23–24]: “nested geometric sketching [...] to reduce transcriptomic redundancy while preserving the global structure”; no mention of class balancing.

[Analysis] Observation: Cross-attention percentile ranking conflates signal and noise

Potential issue or alternative explanation: Converting raw attention scores to percentiles (Supp. p. 28–29) normalizes away absolute magnitude; a gene with low but consistent attention across cells may rank higher than a high-but-sparse attention gene critical for regulation

Why it matters: Percentile-based enrichment (Fig. 5b,e) may miss biologically crucial but low-abundance regulatory events, leading to false negatives in interpretation

How to test it: Compare results using raw attention scores (thresholded) and percentile ranks; assess functional enrichment (e.g., GO terms) of top-N raw vs. percentile-ranked genes

Basis: [Supp. p. 28–29]: “raw attention scores were converted into within-cell percentile ranks”; no validation of percentile choice vs. alternatives.

[Analysis] Observation: GEARS framework masks scKITE’s gene embedding contribution

Potential issue or alternative explanation: Perturbation prediction uses GEARS’ full pipeline (co-expression graph, GO graph, perturbation embeddings); scKITE only replaces gene embeddings, so observed gains may reflect synergy with GEARS’ existing priors rather than intrinsic gene representation quality

Why it matters: Over-attribution to scKITE could obscure need for end-to-end perturbation models or limit generalizability to non-GEARS frameworks

How to test it: Test scKITE gene embeddings in simpler baselines (e.g., linear regression on

gene embeddings alone) and in alternative perturbation predictors (e.g., scPerturb, PERTURB-SEQ)
Basis: [Paper: PDF p. 8, Supp. p. 27]: “Contextual gene embeddings were incorporated into a shared GEARS-based framework”; no ablation of GEARS components.

14 学到的知识

- 知识增强预训练是一种高效的数据缩放替代方案：在scRNA-seq领域，注入结构化生物学知识（文本注释+调控程序）比盲目堆砌数据更能提升模型的零样本能力、鲁棒性和可解释性 [Paper: PDF p. 1–3].
- 轻量级辅助解码器是知识蒸馏的理想载体：通过跨注意力连接的专用解码器，可在不增加推理负担、不破坏模型通用性的前提下，将异构知识“写入”共享编码器；解码器本身是临时的“教学工具” [Paper: PDF p. 3–4, Fig. 1c].
- 细胞与基因表征需分层监督：细胞级任务（annotation, integration）benefit from cell-identity text, while gene-level tasks (perturbation, regulation) require gene-regulatory context; unified supervision fails to capture this duality [Paper: PDF p. 2, 10–13].
- 可解释性可内生于预训练目标：decoder cross-attention isn’t just a post-hoc tool—it’s a first-class component of the training objective, enabling direct, mechanistic validation of knowledge injection [Paper: PDF p. 10–13, Fig. 5].
- 评估需匹配知识类型：batch integration metrics (AvgBIO/AvgBATCH) and perturbation metrics (Top-20 DE MSE) are more sensitive to knowledge enhancement than simple accuracy, revealing nuanced improvements [Paper: PDF p. 6, 8, Fig. 3a, 4b].

15 与既有知识的连接

- Single-cell foundation models: Directly extends Geneformer/scGPT paradigm by replacing pure self-supervision with knowledge-guided supervision; validates that scFMs need not be “data-hungry” but can be “knowledge-aware” [Paper: PDF p. 1–2].
- Perturbation prediction: Builds on GEARS [46] but upgrades its static gene embeddings with scKITE’s contextual, regulation-aware versions, aligning with the goal of causal perturbation modeling [Paper: PDF p. 8, Supp. p. 27].
- Cell state representation: Advances beyond clustering-based (e.g., Seurat) or autoencoder-based (e.g., scVI) representations by grounding cell embeddings in natural language semantics and hierarchical immune organization, supporting cross-tissue retrieval [Paper: PDF p. 4–6, Fig. 2f].
- Graph neural networks: While scKITE itself is Transformer-based, its use of GEARS’ gene co-expression graph and GO graph for perturbation prediction shows compatibility with GNN-enhanced downstream pipelines—a potential integration point [Supp. p. 27].
- Weak connection/methodological connection: No spatial transcriptomics, multi-omics, or cross-modal alignment experiments are reported; the method could be extended (e.g., adding spatial coordinate tokens or modality adapters), but current evidence is absent [User context note].

16 研究想法

- name: Spatial-KITE

originating limitation/observation: Authors acknowledge limitation of pySCENIC-inferred regulons and lack of spatial context; spatial transcriptomics

provides ground-truth spatial gene co-expression and niche-specific regulation [Paper: PDF p. 12, 14].

core hypothesis: Integrating spatial coordinates (e.g., x/y tokens) and spatially resolved regulons (e.g., from SPARK or SpaGCN) as additional Stage 2 supervision will enhance scKITE's ability to model tissue architecture and microenvironment-driven cell states.

delta from paper: Adds spatial decoder and spatial regulon decoder to Stage 2; modifies input to include positional embeddings.

initial method: Pretrain on spatial datasets (e.g., Visium human brain); use spatial proximity graphs to define "spatial regulons"; train spatial decoder to predict coordinate pairs or neighborhood composition.

validation: Benchmark on spatial domain adaptation (e.g., map dissociated scRNA-seq to spatial spots) and spatial perturbation prediction (e.g., simulate ligand knockouts in niches).

failure modes: Spatial data sparsity may degrade regulon inference; coordinate prediction may not capture topological constraints.

innovation status: unverified

- name: Perturb-KITE

originating limitation/observation: Current regulon supervision is observational (pySCENIC), not causal; authors call for "perturbation-derived causal relationships" [Paper: PDF p. 14].

core hypothesis: Replacing pySCENIC regulons with perturbation-response signatures (e.g., from CRISPR screens) as Stage 2 supervision will yield gene embeddings that intrinsically encode causal regulatory directionality and genetic interaction logic.

delta from paper: Replace regulon decoder with perturbation-response decoder that predicts DE gene sets and direction changes given TF perturbation.

initial method: Use Norman/Replogle data to construct "perturbation signature sequences" (e.g., "ATF1 KO → down: IFNG, TNF; up: IL10"); train decoder to generate these.

validation: Test on unseen double-perturbation interaction prediction (beyond GEARS' current capability) and synthetic lethality discovery.

failure modes: Signature sparsity may limit coverage; direction prediction may be confounded by indirect effects.

innovation status: unverified

- name: MultiOmics-KITE

originating limitation/observation: Authors note "Beyond the knowledge sources explored in scKITE, future biological foundation models may benefit from integrating additional biological evidence, including [...] chromatin accessibility, TF-binding measurements" [Paper: PDF p. 14]; current model is RNA-only.

core hypothesis: A unified encoder can be knowledge-enhanced with multi-modal supervision (e.g., ATAC peaks for chromatin, ChIP-seq for TF binding) to learn joint representations where RNA expression, chromatin accessibility, and TF occupancy are aligned by shared biological meaning.

delta from paper: Extend input vocabulary to include ATAC/ChIP tokens; add ATAC

decoder and TF-binding decoder in Stage 2.

initial method: Pretrain on matched scRNA+scATAC datasets (e.g., 10x Multiome);

serialize ATAC peaks and TF motifs as knowledge sequences analogous to regulons.

validation: Cross-modality imputation (predict ATAC from RNA), TF activity inference from RNA alone, and enhancer-gene linking.

failure modes: Modality imbalance may bias learning; tokenization of continuous ATAC signals is non-trivial.

innovation status: unverified