

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods/discovery
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Rethinking Class Imbalance for Single-Cell Foundation Models: A Systematic Benchmark Across Architectures and Long-Tail Loss Functions	[Paper] [Paper: PDF p. 1]
Authors	Zeyu Dong, Jiahui Zhong	[Paper] [Paper: PDF p. 1]
Venue	arXiv	[Paper] [Paper: PDF p. 1]
URL	http://arxiv.org/abs/2609.23325v1	[Paper meta]
PDF URL	https://arxiv.org/pdf/2609.23325v1	[Paper meta]
Publication date	2026-09-20	[Paper meta]
Code URL	https://github.com/jz890/sc-imbalance	[Paper] [Paper: PDF p. 7]
Backbones	scGPT, scBERT, Geneformer	[Paper] [Paper: PDF p. 2]
Datasets	Multiple Sclerosis (MS), Zheng68K, human Pancreas	[Paper] [Paper: PDF p. 2]
Losses evaluated	Cross-entropy (CE), weighted CE, class-balanced loss, focal loss, LDAM, logit-adjusted softmax	[Paper] [Paper: PDF p. 3]
Total runs	162 (3 backbones × 3 datasets × 6 losses × 3 seeds)	[Paper] [Paper: PDF p. 1]
Key metrics	Macro-F1, rare-class recall (Recall _R), rare-class precision, rare-class macro-AUPRC, Δ F1 _c , NC1	[Paper] [Paper: PDF p. 3–6]

02 一句话总结

该论文系统评测了六种长尾损失函数（CE、weighted CE、class-balanced loss、focal loss、LDAM、logit-adjusted softmax）在三种单细胞基础模型（scGPT/scBERT/Geneformer）和三个真实数据集（MS/ Zheng68K/ Pancreas）上的表现，共162次受控训练；发现整体准确率严重掩盖罕见细胞类别的系统性失败，且该失败可划分为两类机制：一类是“loss-sensitive”（可通过损失函数优化恢复），另一类是“severely entangled”（所有损失与架构均失效，根植于嵌入几何结构）；作者进一步揭示：对可恢复类，重加权收益由

绝对训练样本数而非相对频率决定；class-balanced loss 和 LDAM 是最稳健的选择，而 logit adjustment 实质上是**以精度为代价换取召回**。该工作不扩展至 spatial 或 multi-omics，但其 benchmark 设计可直接复用于用户 perturbation prediction 场景。

03 研究问题

论文直面一个被广泛忽视却临床关键的矛盾：单细胞基础模型（如 scGPT）在 cell-type annotation 上报告高达 97.5% 的 aggregate accuracy，但这一指标是否真实反映其对疾病相关罕见细胞亚群（如 MS 中的 oligodendrocyte C）的判别能力？[Paper] [Paper: PDF p. 1] 作者质疑：当前主流假设——即“长尾损失函数能系统性缓解罕见类失败”——是否成立？该假设是否依赖特定 backbone 架构或数据集结构？[Paper] [Paper: PDF p. 1] 更深层的问题是：当损失函数优化失效时，瓶颈究竟在数据稀缺性、表示坍缩（neural collapse）、还是分类器设计？能否通过嵌入几何特征（如 NC1、最近邻分布）在训练前预判某类是否“不可救”？[Paper] [Paper: PDF p. 5–6]

04 研究背景与发展路径

单细胞基础模型（scGPT/scBERT/Geneformer）已成为 cell-type annotation 默认 backbone，但其高 aggregate accuracy 被证实由常见类主导，罕见类（尤其疾病相关过渡态/病理态）持续被低估 [Paper] [Paper: PDF p. 1]；Alsabbagh et al. (2023) 已在采样策略层面验证此现象，但未系统考察损失函数轴 [Paper] [Paper: PDF p. 1–2]。既有长尾学习方法分三类：(1) 采样法（如 SMOTE、随机过采样），但会改变训练分布；(2) 表示解耦法（如 decoupled representation + classifier calibration），需额外训练阶段；(3) 损失重加权法（如 class-balanced loss、LDAM），可即插即用，但其在单细胞基础模型上的跨架构鲁棒性未知 [Paper] [Paper: PDF p. 2]。本文选择第三条路径，因其与用户研究方向（perturbation prediction、cell state representation）高度兼容：损失函数是轻量级、可迁移的干预模块，无需修改 backbone 或引入新架构，便于嵌入到用户现有 pipeline 中 [Paper] [Paper: PDF p. 2]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Aggregate metrics mask rare-class failure	Accuracy > Macro-F1 > rare-class recall across all 9 (backbone, dataset) settings	Driven by dataset imbalance structure, not pretraining bias	[Paper] [Paper: PDF p. 3], Figure 2 (left), [Paper] [Paper: PDF p. 4]
Loss-level interventions are insufficient for some rare classes	Two MS classes (oligodendrocyte C, phagocyte) achieve near-zero F1 under <i>all</i> six losses and <i>all</i> three backbones	Too few training examples (n=3) + transcriptional overlap → embedding geometry failure, not classifier limitation	[Paper] [Paper: PDF p. 5], Figure 3 (left), Figure 4, [Paper] [Paper: PDF p. 6]
Reweighting benefit is misattributed to relative frequency	Weighted CE performs best on MS but worst on Zheng68K despite similar imbalance ratio	Benefit is predicted by <i>absolute</i> training-set size of rare class, not its share of dataset	[Paper] [Paper: PDF p. 4], Figure 3 (right), Equation 3, $r = -0.77$ ($p < 0.001$)

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Loss functions make hidden trade-offs obscured by Macro-F1	Logit adjustment boosts rare-class recall but <i>lowers</i> precision vs. CE	It shifts decision threshold rather than improving feature separability → more false positives	[Paper] [Paper: PDF p. 4], Figure 2 (right), Table 1 (precision column)

06 核心思想

论文核心洞察是：**罕见类失败不是单一现象，而是具有可诊断的双重机制**——这直接挑战了“换一个更好的损失函数就能解决所有长尾问题”的简化假设。第一重机制（loss-sensitive regime）源于训练信号不足但尚可补救：此类别在嵌入空间中仍保有线性可分性（linear probing 可恢复非零 F1），其性能提升与绝对样本数强负相关（Figure 3 right），故重加权有效；这支持用户在 perturbation prediction 中对低丰度 perturbation 响应细胞采用 class-balanced loss。第二重机制（severely entangled regime）是结构性失败：极少数样本（n=3）导致嵌入点被完全吸收进无关类邻域（Figure 4），NC1 几何指标与最近邻熵可提前预警；此时损失函数优化无效，瓶颈在数据本身或表示学习阶段，提示用户对极稀有 perturbation 状态应优先考虑数据增广或 abstention 策略，而非调参。该二分法将“是否值得投入损失工程”转化为一个可量化、可预测的决策问题，而非经验试错。

07 方法总览

论文采用**控制变量+多维诊断**范式：固定 backbone 微调协议、数据预处理、split 划分，仅系统性遍历 loss 函数轴（6 losses × 3 backbones × 3 datasets × 3 seeds = 162 runs）；评估指标覆盖 aggregate（accuracy）、平衡（Macro-F1）、长尾专用（Recall_R, AUPRC）三层；诊断层则引入：(1) per-class ΔF1 分析（Equation 3）定位可恢复类；(2) UMAP + nearest-neighbor + NC1（Equation 4）刻画嵌入几何；(3) linear probe 在 frozen embeddings 上测试 discriminative signal 是否残留。整个流程不引入新模型或数据，纯粹通过严谨 benchmark 揭示现有工具链的边界与机制。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Loss-function grid	Systematically compare 6 long-tail losses under identical conditions	Isolate loss-axis effect from architecture/data confounders; test off-the-shelf robustness	Input: logits + labels; Output: scalar loss	[Paper] [Paper: PDF p. 3], Table 1, Figure 2	Without this grid, no cross-loss ranking (e.g., class-balanced loss rank 2.4) or trade-off quantification (e.g., logit adjustment’ s precision penalty) possible

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Per-class $\Delta F1$ analysis (Eq. 3)	Quantify gain of best loss over CE for each rare class c	Test hypothesis that reweighting benefit depends on absolute sample count, not relative frequency	Input: $F1_c$ under each loss; Output: $\Delta F1_c$ scalar	[Paper] [Paper: PDF p. 4], Figure 3 (right), $r = -0.77$ correlation	Without per-class $\Delta F1$, the key insight “absolute count predicts benefit” would be invisible; dataset-level averages (Table 1) hide this trend
Embedding geometry diagnostics (NC1, nearest-neighbor entropy)	Detect “severely entangled” classes before training	Distinguish data-scarcity failure (fixable by more data) from classifier failure (fixable by loss)	Input: frozen test-set embeddings; Output: NC1 ratio (Eq. 4), neighbor entropy	[Paper] [Paper: PDF p. 6], Figure 4, NC1 values for oligodendrocyte C (1.19–1.79) vs. phagocyte (0.17–0.32)	Without NC1/neighbor analysis, Figure 4’s visual absorption would remain anecdotal; no quantitative signature to trigger “abstain” recommendation in Section 6
Linear probe on frozen embeddings	Test whether discriminative signal exists <i>in representation</i> despite classifier failure	Localize bottleneck: if probe outperforms trained head, issue is classifier training, not representation collapse	Input: frozen embeddings + labels; Output: CV-F1 score	[Paper] [Paper: PDF p. 6], probe $F1 >$ trained $F1$ for oligodendrocyte C (0.465 vs. 0.329) and phagocyte (0.462 vs. 0.000)	Without linear probe, conclusion “loss design leaves signal unused” [Paper] [Paper: PDF p. 6] would lack direct evidence; could wrongly blame pretraining

09 关键公式与符号

- **No verifiable closed-form equations** are presented in the paper beyond definitions. All listed equations are metric definitions or geometric ratios, not learned models or algorithmic formulas.
- **Equation 1:** $\text{Macro-F1} = \frac{1}{|C|} \sum_{c=1}^{|C|} F1_c$ — unweighted mean of per-class F1 scores across $|C|$ classes [Paper] [Paper: PDF p. 3].
- **Equation 2:** $\text{Rare-class recall} = \frac{1}{|R|} \sum_{c \in R} \text{Recall}_c$ — macro-average restricted to rare class set R [Paper] [Paper: PDF p. 3].
- **Equation 3:** $\text{Per-class gain} = \Delta F1_c = \max_{\ell \in L} F1_c^{\ell} - F1_c^{\text{CE}}$ — best-loss improvement over CE for class c , used for correlation with sample count [Paper] [Paper: PDF p. 4].
- **Equation 4:** $\text{Neural collapse trace ratio} = \text{NC1} = \frac{\text{tr}(\Sigma_W)}{\text{tr}(\Sigma_B)}$ — ratio of within-class to between-class scatter; lower = tighter clusters [Paper] [Paper: PDF p. 6].
- **Key symbols:** R = set of rare classes (training frequency $< 5\%$) [Paper] [Paper: PDF p. 3]; L = set of six losses [Paper] [Paper: PDF p. 4]; Σ_W , Σ_B = within-class and between-class

scatter matrices [Paper] [Paper: PDF p. 6].

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Aggregate metrics gap	CE' s accuracy > Macro-F1 > rare-class recall holds across architectures	Mean over 9 (backbone×seed) runs per dataset; same train/test split, preprocessing	Gap consistent for all three datasets (Figure 2 left)	Dataset imbalance structure, not backbone choice, drives the gap	That pretraining has <i>no</i> role — authors note variance in scBERT' s CE Macro-F1 vs. Alsabbagh et al. due to config differences [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 3], Figure 2 (left)
Loss ranking by Macro-F1	Class-balanced loss & LDAM are most consistent	Rank each loss within each (backbone, dataset) cell, then average rank across 9 cells	Class-balanced loss mean rank 2.4, LDAM 2.6 (Table 1)	These two are top generalists; weighted CE wins on MS but fails on Zheng68K	That they are universally optimal — weighted CE beats them on MS Macro-F1 (0.721 vs. 0.716)	[Paper] [Paper: PDF p. 3], Table 1
Logit adjustment trade-off	Logit adjustment trades rare-class precision for recall	Plot rare-class precision vs. recall for all losses (Figure 2 right)	Logit adjustment has highest recall gain (+0.055) but lowest precision (−0.031 vs. CE)	Its gain comes from threshold shift, not improved separability	That it harms non-rare classes — non-rare precision spread is only 1.1 points [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 2 (right), Table 1
ΔF1 vs. absolute sample count	Absolute training-set size predicts reweighting gain	Pearson correlation of log(sample count) vs. ΔF1_c for rare classes (excluding severely entangled)	$r = -0.77$, $p < 0.001$ ($n = 19$) [Paper] [Paper: PDF p. 4]	Gain is driven by absolute scarcity, not relative imbalance	That the relationship is causal — authors state correlation, not causation	[Paper] [Paper: PDF p. 4], Figure 3 (right)

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Linear probe on frozen embeddings	Discriminative signal exists for severely entangled classes	Fit class-balanced logistic regression on CE-frozen test embeddings, 5-fold CV	Probe F1 > best trained F1 for oligodendrocyte C (0.465 vs. 0.329) and phagocyte (0.462 vs. 0.000)	Bottleneck is classifier training, not representation collapse	That a nonlinear probe would close the gap — not tested	[Paper] [Paper: PDF p. 6]

11 对结论的正确理解

- “Class-balanced loss is most consistent” 意味着它在 9 个 (backbone, dataset) 组合中平均排名最高 (2.4)，并非在每个组合中都排名第一 (weighted CE beats it on MS Macro-F1)；其优势在于稳定性，适合用户在未知数据上快速部署。
- “Logit adjustment trades precision for recall” 是一个**定量结论**：它在 Table 1 中 rare-class precision 列数值最低 (0.650 for MS)，同时 recall 列较高 (0.632)，图 2 右侧点位于 y=x 线下方，表明其设计本质是校准阈值而非增强特征。
- “Severely entangled classes are unrecoverable” 是指在当前实验设置下 (6 losses, 3 backbones, fixed fine-tuning protocol)，它们的 F1 始终接近零；但 linear probe 证明信号存在，因此“unrecoverable” 特指**所测试的损失函数族无法利用该信号**，而非绝对不可分。
- “Absolute sample count predicts gain” 是一个**empirical regularity** ($r = -0.77$)，适用于该 benchmark 的三个数据集，但未声称是普适物理定律；用户在自己的 perturbation 数据上需重新验证该相关性。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited backbone coverage	Only scGPT, scBERT, Geneformer tested; scFoundation and CellPLM untested	Extend benchmark to other foundation models (scFoundation, CellPLM)	[Paper] [Paper: PDF p. 7]
Classifier head expressivity	Linear probe recovers signal missed by trained heads, suggesting current heads may be insufficiently expressive	Test more expressive classifier heads (e.g., MLPs) beyond linear probes	[Paper] [Paper: PDF p. 7]
Isolated imbalance axis	Study focuses solely on cell-type class imbalance; ignores compounding factors like demographic composition or batch effects	Investigate interactions between class imbalance and demographic/batch variables	[Paper] [Paper: PDF p. 7]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The “severely entangled” regime is defined by near-zero F1 under all losses, but the linear probe shows non-trivial F1 (0.175–0.465). This suggests the failure is not in the <i>representation</i> , but in the <i>training dynamics</i> of the classifier head (e.g., gradient starvation, poor initialization).	The linear probe uses class-balanced logistic regression with CV, while the trained heads use standard CE-based optimization. The gap may reflect optimization pathology (e.g., vanishing gradients for rare classes) rather than an inherent limitation of loss functions.	If true, the bottleneck is engineering (optimizer, learning rate schedule) not algorithmic (loss design), shifting focus to training stability.	Replace the linear probe with a <i>retrained</i> classifier head using the same loss but with modified optimization (e.g., rare-class-specific learning rates, gradient clipping) and compare F1.	[Paper] [Paper: PDF p. 6]: “Discriminative signal therefore survives... placing the bottleneck partly in loss design rather than solely in data scarcity.” — authors acknowledge loss design as <i>part</i> of bottleneck, leaving room for optimization factors.
NC1 is computed on <i>frozen test-set embeddings</i> , but the paper claims it “predicts which rare classes will fail regardless of loss choice” [Paper] [Paper: PDF p. 7]. However, NC1 is a static geometric measure; it cannot capture how different losses reshape the embedding manifold during training (e.g., LDAM’s margin may alter $\Sigma_{W_W}/\Sigma_{B_B}$).	NC1 on CE embeddings may not generalize to LDAM or logit-adjusted embeddings. A class with high NC1 under CE might have low NC1 under LDAM, making the “prediction” invalid for losses that actively modify geometry.	Over-reliance on CE-only NC1 could mislead users into abandoning loss engineering for classes that <i>are</i> recoverable under geometry-aware losses.	Compute NC1 separately for each (backbone, loss) combination (e.g., scGPT/CE, scGPT/LDAM) and correlate with $\Delta F1$; test if CE-NC1 remains predictive across losses.	[Paper] [Paper: PDF p. 6]: NC1 values reported only for CE embeddings (“under plain CE” , “restricted to MS’ s 11 rare classes under plain CE”). No NC1 values shown for other losses.
The study uses fixed, globally precomputed training-set statistics for all losses (e.g., class frequencies for weighting). In real-world perturbation prediction, class distributions may shift dynamically (e.g., time-series perturbations), making static statistics suboptimal.	Static weighting assumes stationary class priors, violating the non-stationary nature of many biological perturbations (e.g., drug response kinetics). This could explain why gains are modest on Zheng68K (less imbalanced but more dynamic?).	For user’ s perturbation prediction work, static loss functions may need adaptation to temporal or conditional priors.	Implement online estimation of class frequencies during training (e.g., exponential moving average) and benchmark against static version on a simulated time-series perturbation dataset.	[Paper] [Paper: PDF p. 2]: “Every loss under test computes its class-level term from fixed, globally precomputed training-set statistics” . No discussion of non-stationary extensions.

14 学到的知识

- **Loss selection is not one-size-fits-all:** class-balanced loss is the safest default for rare-class recovery, but logit adjustment is a precision-recall dial — useful when false negatives are catastrophic (e.g., missing a pathogenic perturbation state), even if it increases false positives.
- **Per-class diagnosis beats aggregate metrics:** Reporting a single “rare-class recall” number (e.g., 0.632) obscures whether it’s driven by one recoverable class gaining +0.2 or ten entangled classes stuck at 0.0 — Figure 3’s heatmap and $\Delta F1$ plot are essential for debugging.
- **Geometry-first debugging works:** Before tuning any hyperparameter, compute NC1 and nearest-neighbor entropy on frozen embeddings — if $NC1 > 1.0$ and neighbor entropy > 0.85 for a rare class, prioritize data collection or abstention over loss engineering.
- **Absolute count > relative frequency:** When designing experiments for low-abundance perturbation responses (e.g., < 10 cells), expect diminishing returns from reweighting; invest instead in deeper sequencing or targeted enrichment.
- **Linear probing is a powerful sanity check:** If a simple logistic regression on frozen embeddings outperforms your fancy fine-tuned head, your bottleneck is likely training instability or head architecture, not the backbone or loss.

15 与既有知识的连接

- **Candidate connection / methodological connection:** 该工作与用户研究方向中 **perturbation prediction** 的连接是方法论级的：它提供了一套可即插即用的 loss-function benchmark protocol (162-run grid) and diagnostic toolkit (NC1, $\Delta F1$, linear probe) that can be directly applied to evaluate how well scGPT/scBERT handle rare perturbation states (e.g., “early apoptosis” or “drug-resistant subclone”) without modifying the backbone.
- **Candidate connection / methodological connection:** 对 **cell state representation** 的启示在于：论文证明 “severely entangled” 类的失败源于嵌入几何 (Figure 4)，而非表示能力缺失 (linear probe recovers signal)，这支持用户采用 post-hoc representation refinement (e.g., prototype-guided alignment [Weerasekara et al. 2026]) rather than discarding the foundation model.
- **Candidate connection / methodological connection:** 与 **graph neural networks** 的潜在接口在于：论文中 nearest-neighbor absorption (e.g., phagocyte $\rightarrow$ oligodendrocyte A) resembles graph neighborhood mixing; future work could replace k-NN with GNN-based neighborhood aggregation to mitigate absorption.
- **Weak connection / methodological connection:** 与 **spatial transcriptomics** 和 **multi-omics** 的连接目前为弱连接——论文未涉及空间坐标或多组学模态，但其核心诊断框架 (geometry-first, per-class $\Delta F1$) 可迁移；例如，在 spatial data 中，可定义 “spatially rare” 类 (e.g., niche-specific cells) 并计算 spatial-NC1。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** Dynamic Loss Scheduler for Perturbation Time Series

originating limitation/observation: Static, globally precomputed class weights fail under non-stationary perturbation dynamics [Paper] [Paper: PDF p. 2] **core hypothesis:** Online estimation of class frequencies (e.g., exponential moving average over time bins) will improve rare-perturbation recall in time-series scRNA-seq. **delta from paper:** Replaces fixed statistics with adaptive, temporal statistics; integrates with existing loss families (e.g., class-balanced loss with EMA weights). **initial method:** On simulated perturbation time series (e.g., 0h/6h/24h drug treatment), compute class frequency per time bin, apply EMA ($\alpha=0.9$), use smoothed frequencies for loss weighting. **validation:** Compare rare-class recall of dynamic vs. static weighting on time-series benchmarks (e.g., Perturb-seq datasets); ablate α . **failure modes:** Over-smoothing (α too high) masks rapid transitions; under-smoothing (α too low) adds noise. **innovation status:** unverified

- **name:** Geometry-Guided Loss Selection

originating limitation/observation: NC1 computed only on CE embeddings may not predict performance under geometry-modifying losses like LDAM [Analysis] **core hypothesis:** A lightweight geometric predictor (e.g., NC1 + neighbor entropy) trained on CE embeddings can forecast which loss will maximize $\Delta F1$ for a given rare class. **delta from paper:** Moves from descriptive diagnosis (NC1 tells you *if* a class is hard) to prescriptive recommendation (NC1 + entropy tells you *which loss* to pick). **initial method:** Extract NC1 and normalized neighbor entropy for all rare classes in MS/ Zheng68K/ Pancreas under CE; train a small MLP to predict best-loss rank (1–6) from these two features. **validation:** Test predictor on held-out rare classes; measure accuracy of top-2 loss recommendation. **failure modes:** Poor generalization to new datasets with different geometric distributions; fails if NC1/entropy are collinear. **innovation status:** unverified

- **name:** Entanglement-Aware Abstention

originating limitation/observation: Severely entangled classes (e.g., oligodendrocyte C) have near-zero F1 but non-zero linear probe F1, indicating signal exists but is hard to extract [Paper] [Paper: PDF p. 6] **core hypothesis:** An ensemble of linear probes (one per rare class) on frozen embeddings can serve as a low-cost, high-recall “abstention gate” : if probe F1 < threshold, defer prediction to expert review or data augmentation. **delta from paper:** Turns linear probe from a diagnostic tool into an operational safety mechanism. **initial method:** For each rare class c , train class-balanced logistic probe on frozen CE embeddings; at inference, compute probe confidence; if confidence < 0.3, output “ABSTAIN” . **validation:** Measure abstention rate vs. rare-class recall gain on test set; compare F1 of “abstain + human review” pipeline vs. full automation. **failure modes:** High abstention rate on borderline cases; probe confidence poorly calibrated for out-of-distribution samples. **innovation status:** unverified