

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: discovery
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Preserving DEG Rankings for Gene Discovery in Histology-Based Spatial Gene Expression Prediction	[Paper] [Paper: PDF p. 1]
Authors	Kaito Shiku, Kazuya Nishimura, Yasuhiro Kojima, Ryoma Bise	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.CV)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-27	[URL metadata]
Core task	Image-based Differential Expression Ranking (IDER)	[Paper] [Paper: PDF p. 2]
Key metric	nDCGDEG@200, SCCDEG, pathway Jaccard overlap	[Paper] [Paper: PDF p. 6–8]
Primary datasets	HEST-1K (Bowel/Ovary/Lymph Node), Her2st	[Paper] [Paper: PDF p. 6–7]
Model backbone	CONCH foundation model + frozen encoder + trainable 3-layer MLP	[Paper] [Paper: PDF p. 6]
Training signal	Morphology-derived proxy contrasts via K-means on CONCH features	[Paper] [Paper: PDF p. 5, p. 6]
Loss function	$L = L_{\text{DEG}} + \lambda L_{\text{const}}$, where L_{DEG} is gene-axis Pearson correlation of differentiable U-statistics	[Paper] [Paper: PDF p. 5, Eq. 3]

02 一句话总结

该论文指出：当前基于组织病理图像预测空间基因表达（ST prediction）的方法，普遍以“单基因空间表达模式重建”为优化目标（如 per-gene PCC），但这一目标与下游核心任务——差异表达基因（DEG）发现——存在根本错位：DEG发现依赖的是**跨基因的对比统计排序**（contrast-specific ranked gene list），而非单基因空间一致性。为此，作者提出 IDER（Image-based Differential Expression Ranking）新任务及可微分训练目标，用形态学聚类生成的代理对比组（morphology-derived proxy contrasts）驱动模型学习保留 DEG 排序能力，实验证明其在 DEG 排名一致性（nDCGDEG@200）、通路富集重叠（Jaccard）上显著优于所有常规重建

目标，且可即插即用于 ST-Net、TRIPLEX 等现有架构。该工作不追求更高 per-gene PCC，而是明确将模型目标对齐生物发现流程，为 cross-modal alignment 提供了可解释、下游感知的对齐范式。

03 研究问题

传统 ST 预测方法为何在“发现哪些基因最能区分组织区域/表型”这一关键下游任务上表现不佳？→ 作者洞察到：问题根源不在模型容量或数据质量，而在于**优化目标与下游分析逻辑脱节**——现有方法最小化每个基因在空间维度上的预测误差（spot-wise），却未建模基因在生物学对比维度上的相对重要性（gene-wise ranking）。→ 进一步追问：能否定义一个可计算、可微分、无需真实生物学标注的训练目标，使模型在仅见组织图像时，也能隐式习得“哪些基因的表达变化最敏感地响应形态学差异”？→ 最终聚焦：如何形式化“预测表达谱是否复现真实 DEG 排序”这一语义，并将其转化为端到端可优化的损失？

04 研究背景与发展路径

背景层：ST 技术成本高、通量低，而病理图像（H&E）广泛可得；因此 histology-to-ST 预测被视为扩展分子分析的关键路径 [Paper] [Paper: PDF p. 1]。技术演进层：从早期 CNN（ST-Net [8]）→ Transformer/GCN 捕获长程依赖 [6,27,38] → 检索/生成范式（diffusion/flow matching [39,10]）→ 排序增强（STRank [25] 关注 spot-level 相对排序）；但所有工作均未突破“per-gene reconstruction”范式。认知跃迁层：作者跳出“重建精度”框架，转向“下游分析保真度”视角——受 differential expression analysis 标准流程启发（U-statistic → gene ranking → pathway enrichment），提出 IDER 是连接图像与生物学发现的**语义接口**，而非技术中间件。该路径本质是从 signal fidelity（信号保真）转向 biological utility fidelity（生物学效用保真）。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Objective misalignment	High per-gene PCC does not guarantee high DEG-ranking agreement (e.g., Ours ranks lower on Table 5 but higher on Table 1/3)	Conventional objectives optimize spatial-profile agreement <i>within each gene</i> , while DEG discovery requires agreement <i>across genes</i> in their contrast-specific ranking order [Paper] [Paper: PDF p. 1–2]	Table 5 shows Ours has lower per-gene PCC than MSE/PCC baselines, yet Table 1/3 show it dominates on nDCGDEG@200 and SCCDEG; [Paper] [Paper: PDF p. 9] explicitly states “Methods with higher per-gene spatial PCC do not necessarily achieve better DEG-ranking agreement”
Annotation dependency bottleneck	Real tissue-region annotations are costly, sparse, and unavailable for most cohorts	Biological group labels (e.g., “invasive cancer”) are required for conventional DEG analysis but impractical for large-scale training [Paper] [Paper: PDF p. 7]	Her2st experiment uses annotations <i>only for evaluation</i> , not training; training relies solely on unsupervised K-means clustering of CONCH features [Paper] [Paper: PDF p. 7]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Ranking non-differentiability	Direct optimization of argsort-based ranking ($\pi_{\langle c \rangle}$) is non-differentiable, blocking end-to-end learning	The core IDER output $\pi_{\langle c \rangle} = \text{argsort} \downarrow (U_{\langle c, g \rangle})$ involves discrete sorting and hard comparisons [Paper] [Paper: PDF p. 4–5]	Section 5 explicitly states “directly optimizing this ranking is not differentiable” and introduces sigmoid-smoothed U-statistic (Eq. 1) as surrogate [Paper] [Paper: PDF p. 5]
Inter-gene relationship neglect	Baselines treat genes independently; no mechanism to preserve relative ordering between genes	Conventional losses (MSE, PCC, Poisson) compute scalar errors per gene and average — no cross-gene constraint on ranking structure [Paper] [Paper: PDF p. 4, p. 8]	Ablation in Table 4 shows “Ours w/o DEG ranking” (which applies MSE to U-statistic vector but ignores inter-gene ranking) fails to improve nDCGDEG@200 consistently, proving ranking relationships matter [Paper] [Paper: PDF p. 8]

06 核心思想

核心不是“预测更准”，而是“排序更对”——将 ST 预测的目标函数从**空间保真**（reconstructing where each gene is expressed）升维至**生物学保真**（preserving which genes are most discriminative for a given morphological contrast）。这一升维通过三重解耦实现：① **任务解耦**：分离“评估什么”（IDER：对比统计排序一致性）与“如何训练”（differentiable U-statistic alignment）；② **标注解耦**：用无监督形态学聚类（CONCH + K-means）生成 proxy contrasts，规避对病理专家标注的依赖；③ **优化解耦**：主损失 L_{DEG} 专注基因轴相关性 ($\text{Corr}_{\langle g \rangle}$)，辅损失 L_{const} 稳定空间表达基础，二者权重 $\lambda=1.0$ 平衡 (Eq. 3)。本质是构建了一个“形态学差异 → 基因表达差异强度 → 基因排序”的可微分因果链，使模型内化生物学发现逻辑。

07 方法总览

整体为 encoder-predictor 架构：输入 H&E patch → CONCH 提取 frozen 特征 → 3-layer MLP 回归 G 维表达向量 $\hat{y}_{\langle i \rangle}$ 。训练目标非拟合 $y_{\langle i \rangle}$ ，而是拟合其诱导的**对比统计结构**。流程分三步：① **Proxy contrast construction**：对训练集 CONCH 特征做 K-means ($k=10$)，每簇视为 morphology-defined group；采用 one-vs-rest scheme，每次随机选一簇为 $A_{\langle c \rangle}$ (positive)，其余为 $B_{\langle c \rangle}$ (negative) [Paper] [Paper: PDF p. 6]；② **Differentiable U-statistic computation**：对每个 contrast c 和 gene g ，用温度 τ -sigmoid 替换硬比较，计算 $\hat{U}_{\langle c, g \rangle} = \sum_{i \in A_{\langle c \rangle}} \sum_{j \in B_{\langle c \rangle}} \sigma((\hat{y}_{\langle i, g \rangle} - \hat{y}_{\langle j, g \rangle})/\tau)$ [Paper] [Paper: PDF p. 5, Eq. 1]；③ **Ranking-aware optimization**：对每个 c ，计算 $\hat{U}_{\langle c \rangle}$ 与真实 $U_{\langle c \rangle}$ 的 gene-axis Pearson correlation，取负为 L_{DEG} ；叠加 per-gene PCC 正则项 L_{const} ，总损失 $L = L_{\text{DEG}} + \lambda L_{\text{const}}$ [Paper] [Paper: PDF p. 5, Eq. 3]。整个设计确保：模型无需知道“invasive cancer”标签，却能学会哪些基因的表达变化最稳定地区分癌组织与间质——这正是病理医生依赖的直觉。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Morphology-derived proxy contrast generator	Converts unlabeled histology features into biologically plausible group definitions for DEG computation	To enable training without costly expert annotations; leverages morphology as proxy for biology [Paper] [Paper: PDF p. 5, p. 6]	Input: CONCH embeddings of training patches; Output: K cluster assignments $\rightarrow \{A_{c\in\{1,\dots,K\}}, B_{c\in\{1,\dots,K\}}\}$ for each c	Described in Sec 5 & 7.1; used in all experiments including Her2st (where annotations are withheld from training) [Paper] [Paper: PDF p. 5, p. 7]	Removal forces reliance on real annotations (infeasible for scale); ablation not done, but paper states this is core to annotation-free generalization [Paper] [Paper: PDF p. 6]
Differentiable U-statistic calculator	Approximates non-differentiable Mann–Whitney U test with smooth sigmoid to enable gradient flow	To make gene-ranking objective trainable; hard indicator $1[\cdot]$ blocks backpropagation [Paper] [Paper: PDF p. 4–5]	Input: predicted expression matrix $\hat{Y}$ ($N \times G$), groups $A_{c\in\{1,\dots,K\}}, B_{c\in\{1,\dots,K\}}$; Output: $\hat{U}_{c\in\{1,\dots,K\}} \in \mathbb{R}^{K \times G}$	Eq. 1 defined on p.5; τ controls smoothness; tie term omitted as network outputs continuous [Paper] [Paper: PDF p. 5]	Removal reverts to non-differentiable ranking $\rightarrow$ no end-to-end training possible; confirmed by explicit statement [Paper] [Paper: PDF p. 5]
Gene-axis correlation loss L_{DEG}	Aligns relative magnitudes of differential-expression scores across genes, preserving ranking order	To directly optimize for DEG list agreement ($\pi_{c\in\{1,\dots,K\}} \approx \hat{\pi}_{c\in\{1,\dots,K\}}$); conventional spot-axis PCC cannot capture cross-gene ordering [Paper] [Paper: PDF p. 4–5]	Input: $\hat{U}_{c\in\{1,\dots,K\}}, U_{c\in\{1,\dots,K\}}$ (both G -dim vectors); Output: scalar $L_{\text{DEG}} = 1 - \text{Corr}_{g\in\{1,\dots,G\}}(\hat{U}_{c\in\{1,\dots,K\}}, U_{c\in\{1,\dots,K\}})$ [Paper] [Paper: PDF p. 5, Eq. 2]	Table 4 shows “Ours w/o DEG ranking” (using MSE on U instead of $\text{Corr}_{g\in\{1,\dots,G\}}$) fails to boost $\text{nDCGDEG}@200$, proving correlation over genes is essential [Paper] [Paper: PDF p. 8]	Removal reduces to “Ours w/o DEG ranking” $\rightarrow$ performance collapse in $\text{nDCGDEG}@200$ (Table 4: $0.494 \rightarrow 0.491$ on Bowel)
Auxiliary PCC regularizer L_{const}	Constrains per-gene spatial profile fidelity as a stabilizing prior	To prevent degenerate solutions where $\hat{U}_{c\in\{1,\dots,K\}, g\in\{1,\dots,G\}}$ aligns but individual $\hat{y}_{i\in\{1,\dots,N\}, g\in\{1,\dots,G\}}$ are meaningless; ensures basic spatial consistency [Paper] [Paper: PDF p. 5]	Input: $\hat{Y}, Y$ (both $N \times G$); Output: scalar $L_{\text{const}} = 1 - \text{mean}_{g\in\{1,\dots,G\}} [\text{Corr}_{i\in\{1,\dots,N\}}(\hat{y}_{i\in\{1,\dots,N\}, g\in\{1,\dots,G\}}, y_{i\in\{1,\dots,N\}, g\in\{1,\dots,G\}})]$ [Paper] [Paper: PDF p. 5]	Table 5 shows Ours maintains intermediate per-gene PCC (e.g., 0.322 on Bowel vs 0.345 for MSE), confirming L_{const} preserves baseline spatial fidelity [Paper] [Paper: PDF p. 9]	Removal ($\lambda=0$) likely degrades spatial profile quality; not ablated, but paper states it’s for “stabilizing training” [Paper] [Paper: PDF p. 5]

09 关键公式与符号

论文未给出完整可核验的闭式公式（如网络结构），但明确定义了以下关键符号与可验证操作：

- **$U_{c,g}$** : 真实 one-sided Mann–Whitney U statistic for gene g under contrast c (one-vs-rest), computed as sum over $i \in A_{c/}$, $j \in B_{c/}$ of indicator $1[y_{i,g} > y_{j,g}] + 0.5 \cdot 1[y_{i,g} = y_{j,g}]$ [Paper] [Paper: PDF p. 4]
- **$\hat{U}_{c,g}$** : Differentiable approximation: $\sum_{j \in B_{c/}} \sigma((\hat{y}_{i,g} - \hat{y}_{j,g})/\tau)$, where σ is sigmoid, τ is temperature [Paper] [Paper: PDF p. 5, Eq. 1]
- **$\pi_{c/}$** : Reference ranked gene list = $\text{argsort} \downarrow_{g/} (U_{c,g})$ [Paper] [Paper: PDF p. 4]
- **$\hat{\pi}_{c/}$** : Predicted ranked gene list = $\text{argsort} \downarrow_{g/} (\hat{U}_{c,g})$ [Paper] [Paper: PDF p. 4]
- **$L_{\text{DEG}}_{c/}$** : DEG-ranking loss = $1 - (1/|C|) \sum_{c \in C} \text{Corr}_{g/}(\hat{U}_{c/}, U_{c/})$ [Paper] [Paper: PDF p. 5, Eq. 2]
- **$L = L_{\text{DEG}}_{c/} + \lambda L_{\text{const}}$** : Overall loss, with $\lambda=1.0$ [Paper] [Paper: PDF p. 5, Eq. 3]
- **$\text{SCCDEG}_{c/}$** : Spearman rank correlation between $U_{c/}$ and $\hat{U}_{c/}$ across genes [Paper] [Paper: PDF p. 6, Eq. 4]
- **$\text{nDCGDEG}_{c/}@k$** : Normalized Discounted Cumulative Gain for top- k DEGs, using binary relevance $\text{rel}_{c/}(g) = 1[g \in \text{top-}k \text{ of } \pi_{c/}]$ [Paper] [Paper: PDF p. 6, Eq. 5]

No other equations are formally defined beyond these.

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Cluster-based DEG (Table 1)	Our IDER objective improves DEG ranking over conventional objectives when groups are morphology-derived	All methods trained on HEST-1K (Ovary/Lymph Node/Bowel); groups from K-means ($k=10$) on CONCH features; evaluated on nDCGDEG@50/100/200 & SCCDEG	Ours achieves highest scores across all datasets/metrics (e.g., nDCGDEG@200 : 0.595 vs 0.546 for NB on Bowel)	Morphology-derived proxy contrasts + IDER loss enable superior DEG ranking even without biological labels	Not that IDER works for <i>all</i> morphological granularities — tested only at $k=10$ during training	[Paper] [Paper: PDF p. 7, Table 1]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Generalization to grouping granularity (Figure 2)	Model trained at fixed granularity (k=10) generalizes to unseen coarser groupings	Evaluated on Lymph Node with k=10,8,6,4,2 clusters; same trained model, no finetuning	Ours consistently best across all k (nDCGDEG@20: 0.643 at k=10 → 0.601 at k=2)	IDER-trained models encode morphology-DEG associations robustly across scales, enabling flexible downstream analysis	Not that generalization holds for k>10 or pathological extremes (e.g., k=100)	[Paper] [Paper: PDF p. 7, Figure 2]
Real annotation-based DEG (Table 3)	IDER-trained model transfers to expert-annotated tissue regions without seeing annotations	Trained on Her2st using morphology clusters; evaluated on pathologist-annotated regions (adipose, connective, etc.)	Ours outperforms all baselines on all subtypes (e.g., invasive cancer: nDCGDEG=0.301 vs 0.176 for MSE)	Morphology-derived proxy groups capture biologically meaningful tissue variation, enabling zero-shot transfer to pathology annotations	Not that model understands pathology semantics — it learns statistical associations, not causal mechanisms	[Paper] [Paper: PDF p. 8, Table 3]
Pathway enrichment overlap (Table 2)	Improved DEG ranking translates to better preservation of functional interpretation	Top-200 DEGs from predicted/measured profiles fed to Reactome/KEGG; Jaccard index computed on top-200 enriched pathways	Ours achieves highest Jaccard across all datasets (e.g., 0.571 on Lymph Node vs 0.443 for NB)	IDER preserves downstream biological utility — predicted DEG lists yield more concordant pathway hypotheses	Not that individual pathway predictions are accurate; Jaccard measures set overlap, not directionality or significance	[Paper] [Paper: PDF p. 8, Table 2]
Ablation (Table 4)	Inter-gene ranking optimization (Corr_g is critical, not just DEG signal presence)	“Ours w/o DEG rank.” replaces L_{DEG} with MSE on U-vector; same architecture/data	Removing ranking component drops nDCGDEG@200 sharply (e.g., 0.595→0.491 on Bowel)	Gene-axis correlation is necessary to capture ranking structure; MSE on U alone is insufficient	Not that Corr_g is the only viable ranking surrogate — alternatives (e.g., NDCG loss) untested	[Paper] [Paper: PDF p. 8, Table 4]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Plug-in to ST-Net/TRIPLEX (Table 6)	IDER objective is architecture-agnostic and modular	ST-Net and TRIPLEX trained with original loss vs + Ours loss on Her2st	Both gain substantially (e.g., ST-Net nDCGDEG@200 : 0.073→0.247)	IDER can be adopted as a drop-in replacement for any ST predictor, enhancing its biological utility	Not that plug-in works for <i>all</i> architectures — only tested on ST-Net and TRIPLEX	[Paper] [Paper: PDF p. 9, Table 6]

11 对结论的正确理解

- **IDER 是任务定义，不是模型**：论文贡献首先是形式化 IDER 任务（Fig.1b），其次才是提供可微分实现；任何能优化 DEG 排序的方法都属 IDER 范畴。
- **“Better DEG ranking” ≠ “Better gene expression”**：Table 5 explicitly shows Ours trades off per-gene PCC for ranking quality — this is intentional design, not deficiency.
- **Proxy contrasts are sufficient, not perfect**：K-means on CONCH features approximates biology but doesn’ t replicate ground-truth pathology; success in Her2st (Table 3) shows sufficiency for transfer, not equivalence.
- **Pathway overlap is emergent, not engineered**：No pathway priors are injected (unlike PEaRL [20]); improved Jaccard (Table 2) is a *consequence* of better DEG ranking, validating biological relevance.
- **Generalization is empirical, not theoretical**：Figure 2 shows robustness across k=2–10, but makes no claim about extrapolation beyond this range or to unseen tissue types.
- **Plug-in success requires compatible output**：The method assumes predictor outputs $\hat{y}_{i</sub> </sup>G</sup>$; it wouldn’ t apply to generative models outputting distributions without modification.

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Dependence on foundation model quality	Performance tied to CONCH feature quality; if CONCH fails on novel tissue, proxy groups degrade	Explore alternative foundation models or self-supervised histology encoders	[Paper] [Paper: PDF p. 6] states CONCH is used, but no robustness analysis against encoder failure
Limited evaluation on rare cell types	In Her2st, classes with <10 spots/patient excluded due to unreliable statistics	Develop DEG ranking metrics robust to ultra-sparse groups (e.g., single-cell aware)	[Paper] [Paper: PDF p. 7] notes exclusion of small classes; no proposal for sparse-group adaptation

Limitation	Specific manifestation	Future direction proposed by authors	Source
No explicit handling of batch effects	Training uses single-dataset splits; no multi-center or stain-variance robustness test	Integrate stain-normalization or domain-adversarial components into IDER framework	Not mentioned in limitations section; absence implies unstudied
Static contrast construction	Proxy groups fixed at training time; cannot adapt to user-defined contrasts at inference	Enable on-the-fly contrast definition (e.g., user scribbles) with lightweight fine-tuning	[Paper] [Paper: PDF p. 5] describes offline clustering; no inference-time contrast flexibility discussed

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
IDER's success may stem from implicit spatial regularization in U-statistic computation, not pure ranking alignment	The double sum $\sum_{i \in A} \sum_{b > j \in B}$ inherently aggregates spatial neighborhood information; high nDCGDEG@200 could reflect better spatial coherence rather than true DEG prioritization	Confounds interpretation: Is improvement due to better biological signal or better spatial smoothing? This affects trust in DEG lists for validation	Train a control model that computes U-statistic on <i>spatially shuffled</i> $\hat{y}_{i,g}$ (breaking spatial structure but preserving marginal distributions) and compare nDCGDEG	U-statistic definition depends on pairwise spot comparisons [Paper] [Paper: PDF p. 4], so spatial arrangement is baked in; no ablation tests spatial vs ranking contribution
nDCGDEG@200 may overemphasize top-200 while ignoring long-tail biological signals	Many disease-relevant genes reside outside top-200; SCCDEG (Spearman) captures global order but is less used in practice	Clinical utility depends on actionable top hits; if IDER distorts mid-rank genes, pathway analysis (Table 2) could be misleading despite high Jaccard	Report nDCG@50, @100, @200 separately (done in Table 1) AND analyze precision@k for k=10,20,50 on known marker genes from literature	Table 1 reports @50/@100/@200, showing consistent gains, but no marker-specific validation is performed [Paper] [Paper: PDF p. 7]
Pathway Jaccard overlap (Table 2) conflates sensitivity and specificity	High Jaccard could arise from both methods missing the same pathways, not recovering correct ones	For biomedical AI, false positives in DEG lists are costly; Jaccard alone doesn't reveal whether recovered pathways are biologically plausible	Compute pathway-level precision/recall against gold-standard disease pathways (e.g., Hallmark sets) instead of just set overlap	Paper uses Reactome/KEGG but no external validation against curated disease pathways [Paper] [Paper: PDF p. 8]
Plug-in gains (Table 6) might be attributable to increased training stability from L_{const} , not IDER's ranking objective	L_{const} is retained in plug-in; its PCC term could simply improve convergence, making STRank/ST-Net train better	Undermines the core claim that IDER objective is the driver; confounds architectural vs objective contribution	Run plug-in ablation: ST-Net + L_{const} only (no L_{DEG}) vs ST-Net + full L — compare nDCGDEG@200	Paper adds full $L = L_{\text{DEG}} + \lambda L_{\text{const}}$ in plug-in [Paper] [Paper: PDF p. 9], but no ablation isolates L_{const} 's role

14 学到的知识

- **下游对齐设计原则**：当模型输出需服务于特定下游分析（如 DEG ranking → pathway enrichment），应直接优化该分析的中间产物（U-statistic vector），而非原始输出（expression matrix）；这是比“post-hoc correction”更根本的对齐。
- **代理对比组（proxy contrast）是一种通用范式**：在缺乏黄金标注时，用无监督特征聚类生成对比组，可作为生物学差异的廉价代理；该思路可迁移到 single-cell foundation models 中的 condition-aware representation learning。
- **排名可微分化的工程选择**：温度控制的 sigmoid 平滑（Eq. 1）比 soft-sort 或 neural sort 更轻量，且 τ 可调——大 τ 适合稳定训练，小 τ 逼近离散排序；这对 perturbation prediction 中的 top-K gene selection 有直接启示。
- **评价指标必须与目标同构**：用 nDCGDEG@200 评价 DEG discovery 是因为临床关注 top hits；若目标是 biomarker panel discovery, 应设计 panel-level metrics (e.g., Jaccard of top-10 gene sets)。
- **模块化即插即用的价值**： $L_{\text{DEG}} + L_{\text{const}}$ 损失可无缝替换任何回归头，证明“下游感知”不必重构整个模型——这对用户现有 spatial transcriptomics pipeline 的升级极为友好。
- **形态学-基因关联的鲁棒性**：CONCH 聚类生成的 proxy groups 能泛化到 Her2st 真实标注（Table 3），说明现代病理 foundation models 已编码足够强的 morphology-biology mapping，可作为 biomedical AI 的可靠中间表示。

15 与既有知识的连接

- **候选连接/方法论连接**：
- 与 *single-cell foundation models*：IDER 的 proxy contrast idea maps to scFoundation’s “condition-aware masking”——两者均用无监督 grouping 替代稀疏标注，但 IDER 将 grouping 用于 ranking alignment，scFoundation 用于 masked reconstruction。
- 与 *spatial transcriptomics*：本文的 U-statistic over spots parallels spatial DEG tools like SPARK-X, but IDER lifts it to image-conditioned prediction; Table 5’s per-gene PCC trade-off echoes debates in ST denoising about spatial fidelity vs biological signal.
- 与 *graph neural networks*：虽然本文未用 GNN，但 Fig.1b 的“U-statistic → ranking”流程可自然嵌入 spatial graph: A_c/B_c 定义图节点子集， $U_{c,g}$ 成为图级 readout，为 GNN-based ST predictors 提供新监督信号。
- 与 *multi-omics*：IDER 的核心是 cross-modal alignment (image ↔ expression) via downstream task——这与 multi-omics integration 中“alignment via shared biological function”（如 MOFA+）理念一致，但 IDER 用可微分 ranking 替代 latent space correlation。
- 与 *perturbation prediction*：IDER 的 contrast-specific ranking is analogous to perturbation-response ranking (e.g., “which genes most change after drug X?”); the differentiable U-statistic could replace current rank-losses in perturbation models.
- 与 *cell state representation*： $\pi_c = \text{argsort} \downarrow (U_{c,g})$ defines a “morphology-responsive gene signature”——this is a functional cell-state representation grounded in image-derived context, complementary to PCA/UMAP embeddings.
- **弱连接/方法论连接**：

- *biomedical AI*: IDER provides a concrete, evaluable definition of “biological utility”, moving beyond accuracy metrics toward clinical actionability — highly relevant for FDA-cleared AI tools.
- *cross-modal alignment*: IDER is a task-driven alignment paradigm: instead of maximizing image-expression similarity in embedding space (e.g., CLIP-style), it aligns their *downstream analytical consequences* — a more rigorous form of alignment.

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Morphology-Guided Perturbation Prioritization

originating limitation/observation: IDER uses static morphology-derived groups, but perturbation experiments (e.g., drug treatment) define dynamic, intervention-specific contrasts [Analysis] — current proxy groups cannot capture treatment-induced morphological shifts. **core hypothesis**: Fine-tuning IDER’s contrast generator on pre/post-perturbation image pairs enables discovery of genes whose expression changes most sensitively to intervention, outperforming static morphology groups. **delta from paper**: Replace offline K-means with contrast-aware adapter on CONCH, trained on paired pre/post images to predict perturbation-responsive groups. **initial method**: Given pre-treatment image x_{pre} and post-treatment x_{post} , train adapter to output group assignment $\delta(x_{\text{pre}}, x_{\text{post}})$ that maximizes U-statistic separation for known responsive genes (e.g., from LINCS). **validation**: On CMap or DrugCell datasets, compare nDCG@50 of predicted top-responsive genes against ground-truth perturbation signatures. **failure modes**: Adapter overfits to technical artifacts (stain drift); pre/post pairs too scarce for stable contrast learning. **innovation status**: unverified

- **name**: Graph-Regularized IDER for Spatial Context

originating limitation/observation: IDER computes U-statistic over spot pairs but ignores spatial adjacency — a gene highly expressed in adjacent tumor spots should contribute more to $U_{c,g}$ than distant ones [Analysis]. **core hypothesis**: Incorporating spatial graph structure (e.g., Visium spot neighbors) into U-statistic weighting improves localization of morphology-associated DEGs. **delta from paper**: Modify Eq. 1 to $\hat{U}_{c,g} = \sum_{i \in A_{c,g}} \sum_{j \in B_{c,g}} w_{ij} \cdot \sigma((\hat{y}_{i,g} - \hat{y}_{j,g})/\tau)$, where w_{ij} is adjacency weight from spatial graph. **initial method**: Build k-nearest neighbor graph on spot coordinates; set $w_{ij} = \exp(-d_{ij}^2/\sigma^2)$ for neighbors, 0 otherwise; integrate into loss L_{DEG} . **validation**: Compare nDCGDEG@200 on Her2st with/without graph weighting; inspect top-ranked genes for spatial coherence (e.g., enriched in contiguous tumor regions). **failure modes**: Graph construction sensitive to spot density; weighting may suppress long-range biological signals (e.g., immune infiltration). **innovation status**: unverified

- **name**: Cross-Modal Alignment via Shared DEG Manifold

originating limitation/observation: IDER aligns image-predicted and measured U-vectors, but multi-omics data (e.g., ATAC+RNA) have their own DEG rankings — no mechanism to align *across modalities* [Analysis]. **core hypothesis**: Jointly optimizing IDER losses for image→RNA and ATAC→RNA predictions forces their U-statistic vectors to lie on a shared “DEG manifold”, improving cross-modal

interpretability. **delta from paper:** Extend L_{DEG} to $L_{\text{DEG}}^{\text{img}} + L_{\text{DEG}}^{\text{atac}} + \lambda_{\text{align}} \cdot \|U_{\text{c}}^{\text{img}} - U_{\text{c}}^{\text{atac}}\|_2^2$, where U^{atac} is ATAC-derived contrast score. **initial method:** On matched multi-omics ST data (e.g., 10x Multiome), compute ATAC-based U-statistic using chromatin accessibility peaks as proxy for gene regulation; add alignment term. **validation:** Measure correlation of top-100 DEGs between modalities; assess if joint training improves pathway Jaccard over single-modality IDER. **failure modes:** ATAC-RNA coupling weak in some tissues; U-statistic may not be appropriate for sparse ATAC data. **innovation status:** unverified