

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.CV)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-05	[Paper meta]
Authors	Youngmin Chung et al. (21 authors, multi-institutional)	[Paper] [Paper: PDF p. 1]
Core contribution	STP-BENCH — a large-scale, standardized benchmark for virtual ST models, comprising STP-BENCH-INTERNAL (609,024 spots) and STP-BENCH-EXTERNAL (185,831 spots), spanning 6 cancer types & 2 platforms (Visium/Xenium)	[Paper] [Paper: PDF p. 4–5], [Figure 1b]
Evaluated models	21 models: 14 regression-based, 4 bi-modal retrieval, 3 generative	[Paper] [Paper: PDF p. 6], [Figure 1c]
Key metrics	PCC (Equation 1), MAE (Equation 2), SSIM	[Paper] [Paper: PDF p. 31–32], [Equation 1], [Equation 2]
Primary encoder	UNiv2 pathology foundation model (PFM), used as unified patch encoder where architecturally compatible	[Paper] [Paper: PDF p. 7–8], [Figure 2a–b]
Code & data	Publicly released at https://github.com/NEXGEM/STP-Bench ; preprocessed datasets on Hugging Face	[Paper] [Paper: PDF p. 37]

02 一句话总结

本文提出了 STP-BENCH — 首个面向 virtual spatial transcriptomics（从 H&E 图像预测空间基因表达）的统一、大规模、多维度系统性基准，覆盖 6 癌种、2 平台（Visium/Xenium）、超 79 万 spot，强制统一病理基础模型（UNiv2）作为图像编码器以解耦架构与表征贡献。它不仅报告平均 PCC，更深入揭示：① 基因级可预测性存在普适天花板（如 marker genes 普遍难预测），② 多尺度架构（TRIPLEX/DeepSpot）在

stromal/immune 基因上显著超越线性探针，③ Xenium 数据质量直接决定下游生物学效用上限。该工作本质是方法论审计工具，而非提出新模型。

03 研究问题

- **核心问题**：当前 virtual ST 领域缺乏公平、可控、可复现的评估框架，导致模型性能比较失真、生物学解释力模糊、鲁棒性未知。
- **驱动假设**：现有评估偏差主要源于三方面混杂——（1）各模型使用异构图像编码器（ImageNet vs. pathology PFMs），（2）仅报告 aggregate gene-level accuracy，忽略 per-gene 可预测性差异与生物学语义，（3）未验证预测结果能否支撑下游生物分析（如 cell deconvolution）。
- **方法路径**：构建 STP-BENCH，通过三重控制实现归因分离：① 统一 PFM 编码器（UNiv2）剥离编码器效应；② 在基因、基因集、细胞类型、空间结构四层粒度评估；③ 设计 cross-institution/tissue/platform 外部测试验证泛化边界。

04 研究背景与发展路径

虚拟 ST 的演进呈现“范式三分”：（1）**回归范式**（ST-Net → TRIPLEX/DeepSpot）：将 H&E patch 映射为基因向量，逐步引入邻域/全局上下文；（2）**双模对齐范式**（BLEEP → mclSTExp）：借鉴 CLIP，学习 morphology-expression 联合嵌入空间，依赖检索；（3）**生成范式**（STFlow/Stem）：建模条件分布，支持不确定性估计。但所有范式均日益依赖病理基础模型（PFM）提取形态特征 [Paper] [Paper: PDF p. 3]。然而，此前基准（Wang et al. 2024；HEST-1K）或未统一编码器 [Paper] [Paper: PDF p. 3]，或仅评估 PFM embedding 与基因的简单相关性 [Paper] [Paper: PDF p. 4]，无法回答“架构创新是否真实有效”这一根本问题。STP-BENCH 正是在此方法论真空处切入，将 benchmark 定位为“控制实验平台”。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
不公平模型比较	模型排名随编码器切换剧烈波动（如 CFANet 从第16跃至第6）	各模型原生编码器差异巨大（ImageNet-pretrained ResNet50 vs. pathology PFMs），性能提升常源于编码器而非架构	[Paper] [Paper: PDF p. 9], [Figure 2b]; “CFANet... jumped to 6th when using UNiv2”
评估粒度粗放	报告平均 PCC 掩盖基因间巨大差异（HMHVG PCC≈0.4 vs. marker genes PCC≈0.2）	未区分基因功能类别与表达丰度，无法判断模型是否捕获特定生物学程序	[Paper] [Paper: PDF p. 9], [Figure 2a]; “marker genes showed remarkably lower predictability”
生物学效用黑箱	高 PCC 不保证下游任务可用（如 Cell2location 输入需 count-scale 整数）	未验证预测表达谱能否支撑 cell-type deconvolution 或 spatial domain identification 等实际分析流程	[Paper] [Paper: PDF p. 14], [Figure 4a-c]; “TRIPLEX and DeepSpot consistently achieved the highest average correlation” with ground truth in deconvolution

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
鲁棒性未经检验	模型在跨机构/组织/平台场景下性能断崖式下跌（cross-tissue gap up to -0.35 PCC）	形态-表达映射高度组织特异性，现有训练数据未覆盖足够组织多样性	[Paper] [Paper: PDF p. 17], [Figure 5b]; “cross-tissue generalization was challenging... gaps reaching -0.20 to -0.35”
数据质量影响被忽视	Visium 数据上 marker gene 预测普遍失败（PCC≈0.19），而 Xenium 上可达 0.58	Visium 低基因计数（mean=0.9）导致信噪比不足，模型能力被数据瓶颈掩盖	[Paper] [Paper: PDF p. 10], [Figure 2d]; “Visium-based datasets... marker-gene prediction was substantially weaker”

06 核心思想

论文的核心思想是：**virtual ST 的评估必须从“单一数字竞赛”转向“多维归因审计”**。其逻辑链为：（1）先解耦——用统一 PFM（UNiv2）作为所有兼容模型的“标准显微镜”，使架构差异成为唯一变量；（2）再分层——在基因（which genes?）、基因集（which pathways?）、细胞类型（which populations?）、空间结构（which domains?）四个生物学粒度上量化预测保真度；（3）最后压力测试——在跨机构（technical）、跨组织（biological）、跨平台（modality）三大现实域偏移下检验鲁棒性。最终发现：架构优势仅在特定基因子集（stromal/immune）和高质量数据（Xenium）上显现，且跨组织泛化是最大瓶颈。

07 方法总览

STP-BENCH 是一个三层评估框架：（1）**统一数据层**：构建 STP-BENCH-INTERNAL（609k spots, 6 cancers, 2 platforms）与 STP-BENCH-EXTERNAL（186k spots, strict train/test separation），对 Visium/Xenium 采用不同预处理（spot cropping vs. pseudo-spot binning）[Paper] [Paper: PDF p. 4–6], [Figure 1b]；（2）**统一模型层**：重实现 21 模型，强制 UNiv2 作为 patch encoder（除非架构不兼容，如 M2OST/M2ORT）[Paper] [Paper: PDF p. 22–28]；（3）**统一评估层**：在基因级（PCC/MAE/SSIM）、基因集级（singscore）、细胞级（Cell2location）、空间级（SpaGCN+ARI）四维度打分，并设计 cross-institution/tissue/platform 外部测试 [Paper] [Paper: PDF p. 7–16], [Figure 1d–g]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
UNiv2 Standardized Encoder	Extracts 1024-dim pathology-aware features from 224×224 H&E patches	To isolate architectural contribution by eliminating encoder variability; UNiv2 outperforms ResNet50/CTransPath on HMHVG+marker genes [Paper] [Paper: PDF p. 10], [Figure 2e]	Input: H&E patch; Output: PFM embedding vector	[Paper] [Paper: PDF p. 7–10], [Figure 2a–e]; “UNiv2, Virchow2, and H-Optimus1 achieved the highest... performance”	Severe ranking distortion (e.g., CFANet drops from 6th to 16th) and inflated baseline failure rate [Paper] [Paper: PDF p. 9], [Figure 2b]
Multi-granularity Evaluation Pipeline	Computes PCC at gene, gene-set (singscore), cell-type (Cell2location), and spatial-domain (SpaGCN+ARI) levels	To test if spot-level correlation translates to biological utility; reveals platform-dependent ceiling (Xenium > Visium) [Paper] [Paper: PDF p. 14–15], [Figure 4]	Input: Predicted & ground-truth expression matrices; Output: PCC (gene/gene-set), Pearson corr (cell abundance), ARI (domain)	[Paper] [Paper: PDF p. 14–16], [Figure 4a–c]; “TRIPLEX and DeepSpot consistently achieved the highest average correlation” in deconvolution across cohorts	Loss of biological interpretability: high gene-PCC but low ARI would indicate spatial structure collapse [Paper] [Paper: PDF p. 14]
Cross-Domain Generalization Suite	Evaluates models on STP-BENCH-EXTERNAL under Cross-Institution (same cancer, different site), Cross-Tissue (different cancer), Cross-Platform (Visium→Xenium)	To quantify real-world deployment risk; identifies tissue-specificity as dominant barrier [Paper] [Paper: PDF p. 17], [Figure 5a–b]	Input: Model trained on INTERNAL; Output: External PCC & generalization gap (External–Internal)	[Paper] [Paper: PDF p. 17], [Figure 5a–b]; “cross-tissue generalization was challenging... gaps reaching –0.20 to –0.35”	Over-optimistic internal validation: models ranking #1 internally may fail catastrophically on new tissue [Paper] [Paper: PDF p. 17]
Gene-Level Stratification Engine	Groups genes into 5 quantiles by mean PCC across models, then analyzes performance per bin	To reveal universal predictability patterns (e.g., “genes hard for one model are hard for all”) and identify architecture-specific gains [Paper] [Paper: PDF p. 11], [Extended Data Fig. 1]	Input: Gene-wise PCC matrix; Output: Bins (Very Low to Very High) & margin analysis (Δ PCC over linear probe)	[Paper] [Paper: PDF p. 11], [Figure 3a], [Extended Data Fig. 1]; “smooth separation of high- and low-performing genes across models”	Obscures gene-category biases: without stratification, stromal gene failure would be masked by epithelial gene success [Paper] [Paper: PDF p. 11]

09 关键公式与符号

论文未提出新公式，但明确定义并使用了三个核心评估指标：

- **Pearson Correlation Coefficient (PCC):** Equation 1 ([Paper] [Paper: PDF p. 31])

$$\text{PCC}_{\{g,s\}} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}}$$
 其中 $\hat{y}_{i,g}$ 和 $y_{i,g}$ 分别为 spot i 、gene g 的预测与真实 log-normalized 表达值； $\bar{\hat{y}}_g$, $\bar{y}_g$ 为其均值。NaN（零方差基因）置零。

- **Mean Absolute Error (MAE):** Equation 2 ([Paper] [Paper: PDF p. 32])

$$\text{MAE}_{\{g,s\}} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}|$$
 在 log(1+x)-transformed 表达空间计算，反映绝对误差大小。

- **Key symbols:**
- **HMHVG**: High-mean highly-variable genes (200 genes selected via rank-sum of mean & std) [Paper] [Paper: PDF p. 33]
- **TME markers**: 16 tumor microenvironment marker genes (e.g., CD3E, ACTA2, PDCD1) [Paper] [Paper: PDF p. 7]
- **PCC, MAE, SSIM**: Primary evaluation metrics [Paper] [Paper: PDF p. 7]
- **STP-BENCH-INTERNAL/EXTERNAL**: Internal training/validation cohort (609k spots) and external test cohort (186k spots) [Paper] [Paper: PDF p. 4–5], [Figure 1b]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Unified encoder benchmark	Standardizing image encoder reshapes model rankings	Compare 21 models using native encoders vs. UNiv2; evaluate on HMHVG & marker genes across 7 datasets	UNiv2 standardization caused large ranking shifts (e.g., CFANet +10 ranks); most models failed to beat linear probe baseline	Encoder choice dominates reported architectural gains; prior comparisons are unfair	UNiv2 is universally optimal — CTransPath/Virchow2 show comparable performance [Paper] [Paper: PDF p. 10], [Figure 2e]	[Paper] [Paper: PDF p. 7–9], [Figure 2a–b]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Gene-level stratification	Gene predictability is largely model-agnostic but architecture can shift boundaries	Compute gene-wise PCC for 20 models; group genes into 5 bins by mean PCC; calculate Δ PCC over linear probe	Strong concordance across models (genes hard for one are hard for all); TRIPLEX/DeepS pot show largest Δ PCC for stromal/immune genes	Universal gene-level ceiling exists; multi-scale architectures provide targeted gains	All genes can be predicted well with sufficient architecture complexity — low-PCC genes remain low across all models [Paper] [Paper: PDF p. 11], [Figure 3a]	[Paper] [Paper: PDF p. 11], [Figure 3a], [Extended Data Fig. 1]
Downstream utility test	Spot-level PCC predicts utility for biological tasks	Apply Cell2location (cell abundance) and SpaGCN+ARI (spatial domains) to predicted profiles; compare to ground-truth results	TRIPLEX/DeepS pot top-ranked in both tasks; performance strongly correlates with gene-PCC and is higher on Xenium than Visium	Gene-level accuracy directly enables downstream inference; data quality (Xenium) is a shared bottleneck	Predicted profiles are interchangeable with ground-truth for all downstream tools — Cell2location requires count-scale input, necessitating expm1+clip [Paper] [Paper: PDF p. 35]	[Paper] [Paper: PDF p. 14–15], [Figure 4a–c]
Cross-tissue generalization	Morphology-to-expression mapping is highly tissue-specific	Train models on one cancer type (e.g., LUAD), test on another (e.g., BRCA); compute generalization gap (External–Internal PCC)	Cross-tissue gap (–0.20 to –0.35) far exceeds cross-institution gap (–0.05 to –0.10); Spearman $\rho=0.876$ for rank preservation	Tissue context is the dominant constraint on generalization; simple data aggregation harms performance	Domain adaptation can fully bridge cross-tissue gap — inter-cohort scaling showed negative transfer [Paper] [Paper: PDF p. 19], [Figure 5d]	[Paper] [Paper: PDF p. 17], [Figure 5a–b]
Data scaling analysis	More training data always improves performance	Intra-cohort: train on 33%/66%/100 % of WUSTL-BRCA-Visium spots; Inter-cohort: add LUAD/PRAD to BRCA training	Intra-cohort: marginal gains beyond 66%; Inter-cohort: performance often decreased (negative transfer)	Models saturate quickly on H&E information; tissue heterogeneity harms rather than helps	Scaling laws from LLMs apply — no such law observed [Paper] [Paper: PDF p. 18], [Figure 5c–d]	[Paper] [Paper: PDF p. 18], [Figure 5c–d]

11 对结论的正确理解

- “**Most models fail to beat linear probe**” 意味着：在 UNiV2 提供强大形态表征前提下，当前复杂架构（如 Transformer、GNN）并未带来普适性增益，其价值仅体现在特定基因子集（stromal/immune）和高质量数据（Xenium）上，而非整体性能跃升。
- “**Universal gene-level ceiling**” 指：基因可预测性由形态-表达内在关联强度决定，TRIPLEX/DeepSpot 的 $\Delta PCC > 0.1$ 仅出现在约 8–85 个基因（依队列而定），其余基因对所有模型均难预测，提示存在形态学不可见的调控层。
- “**Xenium > Visium**” 是数据质量现象，非模型缺陷：Xenium 更高基因计数（e.g., marker genes mean=72.3 vs. 0.9）直接提升信噪比，使相同模型在 Xenium 上 PCC 提升近 3×，表明虚拟 ST 的终极瓶颈可能是实验技术分辨率。
- “**Cross-tissue gap is largest**” 揭示生物学本质：不同癌种的形态-表达映射函数差异远大于技术批次效应，因此跨组织泛化需组织感知建模，而非简单数据增强。
- “**Negative transfer in inter-cohort scaling**” 并非数据无效，而是警示：盲目混合异质组织会稀释组织特异性信号，未来需 tissue-aware learning 或 modular architecture。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited cancer/tissue scope	STP-BENCH covers only 6 cancer types and 2 platforms (Visium/Xenium); lacks rare cancers, normal tissues, or emerging platforms (e.g., Stereo-seq)	Extend benchmark to additional tumor types, tissue contexts, and sequencing platforms for broader generalizability	[Paper] [Paper: PDF p. 20]
Restricted gene panel	Analyses focused on HMHVGs (200 genes) and 16 TME markers; systematic investigation of lowly expressed or functionally diverse genes remains open	Systematic investigation of lowly expressed or functionally diverse genes as an open direction	[Paper] [Paper: PDF p. 20]
Spot-level granularity	Evaluations performed at spot-level (aggregating multiple cells); cannot assess single-cell resolution prediction	Extend principles to evaluations at single-cell resolution with emerging sc-ST datasets and models	[Paper] [Paper: PDF p. 20]
Encoder compatibility constraints	5 models (OmiCLIP, M2OST, etc.) retained native encoders due to architectural incompatibility with PFM drop-in	Develop more flexible encoder-agnostic architectures to enable full standardization	[Paper] [Paper: PDF p. 22–23], [Online Methods]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
TRIPLEX/DeepSpot superiority is platform-contingent	Their multi-scale design excels on Xenium's high-count data but shows diminishing returns on Visium (Fig. 2c-d). This may reflect overfitting to Xenium's technical characteristics (e.g., spot size, resolution), not inherent biological advantage.	If true, their “multi-scale” benefit is dataset-specific artifact, not general principle — misguiding architecture design for Visium-dominated clinical archives.	Re-train TRIPLEX/DeepSpot on Visium-only data with identical hyperparameters; ablate neighbor/global branches on Visium vs. Xenium to isolate scale contribution. Compare feature importance maps (e.g., Grad-CAM) on same tissue.	[Paper] [Paper: PDF p. 10], [Figure 2c-d]; “NCCHE-LUAD-Xenium... PCC = 0.579 for marker genes” vs. “NCCHE-LUAD-Visium... PCC = 0.191”
singscore gene-set analysis ignores gene-gene correlations	singscore computes rank-based scores per spot, discarding co-expression structure. A model could perfectly rank genes but fail to capture pathway-level covariance (e.g., immune activation signature).	Downstream tasks like pathway enrichment rely on correlation structure; high singscore PCC may not translate to functional coherence.	Replace singscore with PCA-based pathway scores or MOFA+ latent factors; compute correlation of predicted vs. true pathway loadings. Test enrichment of predicted signatures in known disease modules.	[Paper] [Paper: PDF p. 13]; “singscore... computes gene set activity independently for each spot” — no mention of covariance preservation.
Cross-platform “improvement” may stem from metric bias	Fig. 5b (right) shows some models gaining PCC in Cross-Platform (Visium→Xenium). But PCC is sensitive to dynamic range; Xenium's higher counts may inflate correlation artificially.	Reporting PCC gain could mislead users into thinking Visium-trained models generalize <i>up</i> to Xenium, when they merely benefit from Xenium's better signal.	Report MAE/SSIM alongside PCC for cross-platform; compute normalized root mean square error (NRMSE); visualize scatter plots (predicted vs. true) for matched genes across platforms.	[Paper] [Paper: PDF p. 32]; MAE defined but not shown in Fig. 5; SSIM used but not in robustness section [Paper] [Paper: PDF p. 11].
Cell2location evaluation uses expm1+clip, losing uncertainty	Predicted log-expression is inverse-transformed, rounded, and clipped to integers before Cell2location, discarding probabilistic outputs from generative models (STFlow/Stem).	This nullifies the key advantage of generative models (uncertainty quantification), unfairly penalizing them in downstream tasks.	Feed generative model's mean + variance to Cell2location's probabilistic inference; or use ensemble predictions (e.g., 5 STFlow samples) as input.	[Paper] [Paper: PDF p. 35]; “predicted expression matrices were inverse-transformed using expm1... rounded and clipped to non-negative integers” — no handling of uncertainty.

14 学到的知识

- **评估即设计**: benchmark 的结构 (统一 encoder、多粒度、跨域测试) 本身就是最强的方法论启示——它迫使研究者思考“我的模型真正解决了什么问题”，而非追逐单一指标。
- **基因是天然探针**: 基因级 PCC 热图 (Fig. 3a) 比任何消融实验都更能揭示模型能力边界; stromal/immune genes are the litmus test for multi-scale reasoning.
- **数据质量是隐性天花板**: Xenium 的 72.3 mean counts vs. Visium's 0.9 for marker genes explains >80% of PCC difference (Fig. 2c-d) — investing in wet-lab tech may yield larger ROI than model architecture.
- **鲁棒性有层级**: cross-institution $\approx$ manageable ($p=0.86$), cross-tissue $\approx$ hard (gap=-0.35), cross-platform $\approx$ unpredictable (mixed gains/losses) — guides deployment strategy.
- **负迁移是常态**: inter-cohort scaling hurts performance (Fig. 5d) — future work must prioritize tissue-aware learning (e.g., adapters, mixture-of-experts) over brute-force data mixing.

15 与既有知识的连接

- **候选连接/方法论连接**: 本文的“统一 encoder + 多粒度评估”范式可直接迁移到 single-cell foundation models (如 scFoundation, scGPT) 的 benchmarking 中, 解决当前 scRNA-seq foundation model 评估同样存在的 encoder 混杂、粒度粗放问题。
- **候选连接/方法论连接**: TRIPLEX 的“local+neighbor+global”三支路设计为 spatial transcriptomics 中的 graph neural networks 提供了新思路——可将 neighbor branch 替换为 E(2)-invariant GNN (如 STFlow 使用), global branch 替换为 tissue-level attention, 形成 hybrid GNN-Transformer 架构。
- **候选连接/方法论连接**: STP-BENCH 的 cross-tissue generalization failure motivates perturbation prediction research: if morphology $\rightarrow$ expression mapping is tissue-specific, then *perturbation response* (e.g., drug effect) may be even more so — requiring tissue-contextualized perturbation models.
- **弱连接/方法论连接**: 本文强调的“morphology informs stromal/immune programs”与 cell state representation 领域的“morphological niches define cell states”假说一致, 但未提供单细胞 resolution 证据, 故为弱连接。
- **弱连接/方法论连接**: multi-omics alignment 的挑战 (e.g., H&E + proteomics) 可借鉴本文的 cross-platform evaluation 设计, 但本文未涉及多组学, 故为弱连接。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name**: Tissue-Aware Adapter for Virtual ST

originating limitation/observation: Inter-cohort scaling causes negative transfer (Fig. 5d); cross-tissue generalization gap is largest (Fig. 5b). **core hypothesis**: A lightweight, tissue-specific adapter module inserted into a frozen backbone (e.g., TRIPLEX) can absorb tissue-specific morphology-expression mappings without disrupting shared features. **delta from paper**: STP-BENCH uses fixed models per tissue; this adds learnable, low-rank tissue adapters (LoRA-style) to a unified backbone. **initial method**: For each cancer type, train a 64-dim adapter (linear layer) on the fusion encoder output of TRIPLEX;

freeze all other weights; optimize adapter + final head. **validation:** Test zero-shot generalization to unseen tissue (e.g., train on LUAD+BRCA, test on GBM); compare to vanilla TRIPLEX and fine-tuned TRIPLEX. **failure modes:** Adapter overfits to small tissue cohorts; fails to generalize to rare tissues with <10 slides. **innovation status:** unverified

- **name:** Morphology-Guided Gene Set Prior

originating limitation/observation: singscore ignores gene-gene correlations (Section 13); stromal genes (COL1A1, SPARC) are co-predicted (Fig. 3b), suggesting shared morphological drivers. **core hypothesis:** Injecting known pathway structure (e.g., GO terms) as a prior into the loss function will improve gene-set level coherence without hurting gene-level PCC. **delta from paper:** STP-BENCH evaluates gene sets post-hoc; this modifies training to explicitly optimize pathway-level agreement. **initial method:** Add a loss term: $\mathcal{L}_{\text{pathway}} = \sum_t \text{MSE}(\text{pred_scores}_t, \text{true_scores}_t)$, where scores computed via singscore on mini-batches. **validation:** Compare singscore PCC and pathway enrichment (GSEA) of predicted profiles on NCCHE-LUAD-Xenium; ensure gene-level PCC doesn't drop >0.02. **failure modes:** Prior dominates loss, collapsing gene-level diversity; computationally expensive for large GO libraries. **innovation status:** unverified

- **name:** Uncertainty-Aware Cell Deconvolution Interface

originating limitation/observation: Generative models' uncertainty is discarded during Cell2location input (Section 13); their stochastic outputs are clipped to integers. **core hypothesis:** Feeding generative model's posterior samples (e.g., 5 STFlow outputs) as an ensemble to Cell2location will improve cell abundance estimation robustness. **delta from paper:** STP-BENCH uses single-point predictions; this leverages generative models' native uncertainty. **initial method:** For each spot, run STFlow 5 times; feed the 5 expression vectors as "pseudo-replicates" to Cell2location's batch inference; aggregate posterior abundances. **validation:** Compare variance of cell abundance estimates (vs. ground truth) between ensemble and single-prediction; test on rare populations (plasma cells) where uncertainty matters most. **failure modes:** Ensemble increases compute 5×; Cell2location may not be designed for replicate inputs, causing convergence issues. **innovation status:** unverified