

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	OmicSync: Reliability-Aware Spatial Multi-Omics Clustering with Evidence-Constrained LLM Reasoning	[Paper] [Paper: PDF p. 1]
Authors	Rabeya Tus Sadia, Qiang Ye, Qiang Cheng	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (v2)	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Core task	Spatial domain clustering + per-spot reliability auditing via evidence-constrained LLM reasoning	[Paper] [Paper: PDF p. 1–2]
Key model	KAN-GCN backbone + CrossModalTransformer + UncertaintyMoE + ClusteringHead + CellTypeHead + ImputationHeads	[Paper] [Paper: PDF p. 4–7]
LLM component	Llama-3.3-70B (via Groq API), used <i>post-hoc</i> for reasoning; no fine-tuning or gradient flow	[Paper] [Paper: PDF p. 9]
Datasets	Four 10x CytAssist FFPE spatial proteomics datasets: Human Tonsil, Breast Cancer, Glioblastoma, Tonsil Add-on	[Paper] [Paper: PDF p. 11]
Evaluation metrics	ARI, NMI, FMI, SiLC, AMI, Jaccard, CHI, Purity, DBI (Task A); GR, CA, SC (Task C); epistemic routing uncertainty u , modality-routing vector $\vec{g}$; assignment confidence c	[Paper] [Paper: PDF p. 11–13, Table 1–5]

02 一句话总结

OmicSync 是一个将空间多组学聚类与模型衍生证据驱动的 LLM 推理耦合的框架，它不只输出斑点（spot）所属结构域（domain），还同步输出三个可解释信号：软分配置信度 c 、路由不确定性 u 和模态权重向量 $\vec{g}$ ；这些信号被结构化为证据字典，输入 Llama-3.3-70B 生成五种策略

(Stepwise/Counterfactual/Contrastive/Uncertainty/Standard) 的自然语言可靠性报告；其扩展版 OmicSync-R 进一步用自动计算的推理质量分数 (GR+CA+SC) 作为 REINFORCE 奖励，反向调节聚类头，实现“推理引导聚类”的闭环优化。该工作直击当前空间多组学方法普遍存在的“黑箱分区”缺陷——缺乏对单个斑点分配可靠性的量化、对模态贡献的归因、以及对决策依据的可追溯解释。

03 研究问题

现有空间多组学域发现方法（如 GROVER、SpatialGlue）仅返回斑点到结构域的硬划分或软概率矩阵，但无法回答三个关键临床/分析级问题：（1）该斑点的分配是否可靠？（2）是 RNA、ADT 还是组织学图像主导了该决策？（3）为什么应信任这一分配？[Paper] [Paper: PDF p. 1] 作者洞察到，这种“不可审计性”会将聚类错误传播至下游分析（如配体-受体推断、细胞状态映射），尤其在组织边界或数据质量退化区域风险极高 [Paper] [Paper: PDF p. 1]。因此，研究问题被明确定义为：如何构建一个端到端框架，在完成无监督空间域聚类的同时，为每个斑点生成**可验证、可归因、可信赖**的解释性输出，并进一步探索该解释性是否能反哺并提升聚类本身的几何质量？

04 研究背景与发展路径

空间多组学分析已从单模态（RNA-only）[9] 发展为多模态融合（RNA+ADT+H&E）[5-8]，技术演进路径清晰：STAGATE/GraphST 引入图神经网络建模空间邻近性 → SpatialGlue/MISO/GROVER/COSMOS 探索跨模态对齐与表示学习。但所有现有方法均止步于“聚类输出”，未将**可靠性建模**（reliability estimation）和**可解释性生成**（explanation generation）纳入统一架构。OmicSync 的发展路径是：以 GROVER 的 KAN-GCN 图编码器为基座 [Paper] [Paper: PDF p. 3, 6]，叠加五大新组件——空间位置编码（解决同分子异位置混淆）、跨模态 Transformer（增强模态间上下文交互）、不确定性 MoE 路由（同时输出 $\bar{g}$ 和 u_i ）、ClusteringHead（Student’ s t-kernel 软聚类）、CellTypeHead（伪标签正则化）。这一路径不是替代已有方法，而是通过模块化扩展，在不破坏原有表示能力的前提下，注入可解释性基因。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Opaque partitioning	Methods return only flat cluster labels, no indication of per-spot reliability or modality contribution	Downstream analyses treat all assignments as equally reliable, propagating errors into biological conclusions [Paper] [Paper: PDF p. 1]	“most spatial domain discovery methods return only a flat partition... without indicating which assignments are reliable, why a spot was assigned... or which molecular modality primarily drove each assignment” [Paper] [Paper: PDF p. 1]
Unauditable explanations	Existing explainability (e.g., attention maps, SHAP) reveals influential features but not spot-specific, multi-signal grounded justifications	No prior work couples LLMs with structured, model-derived evidence (confidence, uncertainty, routing weights) for per-spot reliability reports [Paper] [Paper: PDF p. 3]	“To our knowledge, however, existing work has not coupled an LLM with a trained spatial clustering model through structured, model-derived evidence” [Paper] [Paper: PDF p. 3]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Static clustering-reasoning decoupling	Reasoning is purely post-hoc; explanations cannot influence the latent structure that generated them	Base OmicSync’ s Task C operates after training and does not backpropagate into the clustering objective [Paper] [Paper: PDF p. 18]	“Base OmicSync’ s Task C operates after model training and does not back-propagate into the clustering objective; it explains rather than optimises the partition” [Paper] [Paper: PDF p. 18]
Dataset-agnostic contrastive learning	Fixed spatial exclusion radius (n_{hops}) in InfoNCE loss harms performance on heterogeneous tissues (e.g., tumor-stroma boundaries)	Homogeneous tissue (e.g., tonsil germinal centers) needs broader exclusion ($n_{hops}=2$), while heterogeneous tissue needs finer resolution ($n_{hops}=1$) [Paper] [Paper: PDF p. 7]	“Homogeneous tissue... uses $n_{hops}=2$... Heterogeneous tissue... uses $n_{hops}=1$ ” [Paper] [Paper: PDF p. 7]

06 核心思想

论文的核心思想是建立一条**从数学信号到自然语言的可审计链路**（auditable chain）：聚类模型内部产生的三个核心可靠性信号（ c_i, u_i, g_i ）并非仅供可视化，而是被严格结构化为 LLM 的唯一输入证据字典；LLM 的生成过程被系统性约束（禁止引入未提供基因名、蛋白名、文献引用），确保每句解释均可回溯至模型自身输出；进而，该解释的质量（GR/CA/SC）又被设计为非可微奖励，通过 REINFORCE 反向调节聚类头的软分配分布 q_i ，形成“解释质量→聚类质量”的闭环反馈。这超越了传统可解释性（XAI）的被动解释范式，将解释本身升格为一种**主动的、可量化的、可优化的模型内在属性**。

07 方法总览

OmicSync 是一个端到端训练的多任务框架，其方法路径遵循“**信号提取 → 结构化 → 解释生成 → （可选）闭环优化**”逻辑：首先，通过 KAN-GCN 编码器和 CrossModalTransformer 提取斑点的多模态特征；其次，UncertaintyMoE 模块在 MC-Dropout 下运行，同步输出 g_i （模态路由均值）和 u_i （路由方差），ClusteringHead 输出 q_i 和 c_i ；第三，将 q_i, c_i, u_i, g_i 邻域组成、顶部标记等组装为证据字典，输入 Llama-3.3-70B 生成五种策略的解释；最后，OmicSync-R 将 GR/CA/SC 加权和 R_i 作为 REINFORCE 奖励，更新 q_i 的采样策略，使高分解释对应的分配概率增大。整个流程中，LLM 始终是冻结的黑盒，梯度仅流经聚类头，保证了训练可行性。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
SpatialPositionEncoder	Adds sinusoidal 2D positional bias to each modality's feature vector before GCN	To distinguish spots with identical molecular profiles but different locations (e.g., germinal center edge vs. center), which molecular data alone cannot capture	Input: spot coordinate q ; Output: $PE_m(q) \in \mathbb{R}^{d_m}$ [Paper] [Paper: PDF p. 5]	“This design allows the model to incorporate spatial context and tissue architecture that are not captured by molecular composition alone” [Paper] [Paper: PDF p. 5]	Without it, spatially adjacent but molecularly similar spots (e.g., same cell type across region) would have indistinguishable representations, degrading spatial coherence of clusters [Analysis]
UncertaintyMoE	Routes cross-modal tokens e'_1, e'_2, e'_3 via MC-Dropout gating network to produce fused z , while estimating $\bar{g}$ and u_i	To jointly provide interpretable modality attribution ($\bar{g}$) and quantifiable epistemic uncertainty (u_i)—two signals essential for evidence-constrained reasoning	Input: averaged token $\bar{e}$; Output: $\bar{g} \in [0,1]^3, u_i \in \mathbb{R}_{\geq 0}, z \in \mathbb{R}^{d_c}$ [Paper] [Paper: PDF p. 6]	“The mean gate values $\bar{g}_i$... are used as an interpretable proxy for the relative contribution... The scalar u_i ... is defined as the epistemic routing uncertainty” [Paper] [Paper: PDF p. 7]	Removal eliminates both $\bar{g}$ and u_i , breaking the core evidence chain for Task C; reasoning would lack modality grounding and uncertainty calibration [Paper] [Paper: PDF p. 3]
ClusteringHead	Performs soft assignment to K learnable centroids using Student's t -kernel, outputs $q_i, \hat{c}_i, c_i$	To generate probabilistic, differentiable cluster assignments required for both evaluation (ARI) and REINFORCE reward weighting	Input: L^2 -normalized z ; Output: $q_i \in [0,1]^{K \times K}, c_i = \max_k q_{ik}$ [Paper] [Paper: PDF p. 7]	“The predicted domain for spot i is $\hat{c}_i = \arg \max_k q_{ik}$, and the assignment confidence is defined as $c_i = \max_k q_{ik}$ ” [Paper] [Paper: PDF p. 7]	Removal collapses Task A to unsupervised representation learning only; no q_i means no c_i , no R reward, and no basis for domain-level reasoning [Paper] [Paper: PDF p. 3]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Evidence-Constrained Reasoning Module	Converts model-derived signals into five types of natural-language reports using fixed Llama-3.3-70B prompts	To translate quantitative, model-internal signals into human-auditable, faithfulness-constrained explanations, enabling spot-level trust assessment	Input: evidence dictionary (including $\hat{c}_i$, q , $\bar{g}$, u , top markers, neighborhood); Output: $J^{\theta}_i \in \text{text}$ [Paper] [Paper: PDF p. 8–9]	“The language model is instructed not to introduce gene names, protein names, spot identifiers, citations, or biological claims that are absent from the supplied evidence” [Paper] [Paper: PDF p. 8]	Removal reduces OmicSync to a standard clustering method with no interpretability layer; all Task C results (Table 3–5, Fig. 3) vanish [Paper] [Paper: PDF p. 8]
OmicSync-R REINFORCE Loop	Uses $R_t = w_1 GR_t + w_2 CA_t + w_3 SC_t$ as reward to update q_t via policy gradient, without backpropagating through LLM	To close the reasoning-clustering loop, allowing explanation quality to shape latent geometry, addressing the static decoupling limitation	Input: q_t , sampled a_t, J^{θ}_t, R_t ; Output: $L_{\text{reinforce}}$ for gradient update [Paper] [Paper: PDF p. 9–10]	“OmicSync-R... feeds automatically computed reasoning-quality scores back into model training, allowing evidence-grounded reasoning coherence to influence the learned latent structure” [Paper] [Paper: PDF p. 2]	Removal reverts to base OmicSync; the ARI improvement (+0.99) and 8/9 metric gains on Breast Cancer (Table 7) would not occur [Paper] [Paper: PDF p. 17]

09 关键公式与符号

论文未给出单一主导性公式，但定义了多个关键符号与可核验公式，全部源自原文：

- **Assignment confidence:** $q = \max_{1 \leq k \leq K} q_{jk}$ [Equation 3, PDF p. 4]
- **Modality-routing constraint:** $\sum_{m=1}^3 G_{im} = 1, i = 1, \dots, N$ [Equation 4, PDF p. 4]
- **Spatial encoding:** $PE_m(G_i) = W \begin{bmatrix} \sin(G_{i,x} f) \\ \cos(G_{i,x} f) \\ \sin(G_{i,y} f) \\ \cos(G_{i,y} f) \end{bmatrix}^T \in \mathbb{R}^{d_m}$ [Equation 7, PDF p. 5]
- **MC-Dropout routing variance (epistemic uncertainty):** $u_i = \sum_{m=1}^3 \text{Var}_{t=1, \dots, T} [g_{m,t}]$ [Equation 13, PDF p. 6]
- **Soft assignment (Student’ s t-kernel):** $q_{jk} = (1 + \| \hat{z}_i - \mu_k \|^2_2)^{-1} / \sum_{k'} (1 + \| \hat{z}_i - \mu_{k'} \|^2_2)^{-1}$ [Equation 15, PDF p. 7]
- **Grounding Rate (GR):** $GR_t = |M_t \cap J_t| / |M_t|$, where M_t = supplied marker set, J_t = markers mentioned in justification [Equation 18, PDF p. 9]
- **REINFORCE reward:** $R_t = w_1 GR_t + w_2 CA_t + w_3 SC_t$, with $w_1=0.5, w_2=0.3, w_3=0.2$ [Equation 20, PDF p. 9]

- **REINFORCE loss:** $L_{\text{reinforce}} = -(1/|S_{\text{R}}|) \sum_{i \in S_{\text{R}}} \text{sg}(R_i - b_t) \log q_{i, a_i}$ [Equation 23, PDF p. 10]
- **Extended objective:** $L_{\text{OmicSync-R}} = L_{\text{OmicSync}} + \lambda L_{\text{R}} L_{\text{reinforce}}$ [Equation 24, PDF p. 10]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Task A clustering (Table 1)	OmicSync achieves superior clustering quality across diverse spatial proteomics datasets	Compared against GROVER, MISO, SpatialGlue, COSMOS on 4 datasets; k-means applied to Z for $K \in \{6-10\}$; best K reported	Best average rank on Tonsil (1.44), Glioblastoma (1.78), Tonsil Add-on (1.22); 2nd on Breast Cancer (2.33); best ARI on all 4	OmicSync learns a more discriminative latent space Z , better aligned with curated reference partitions and exhibiting superior intrinsic cluster separation (high CHI, low DBI)	That OmicSync is universally superior—its Purity on Tonsil (57.71) < GROVER (69.4), indicating a trade-off	[Paper] [Paper: PDF p. 12, Table 1]
Task C reasoning quality (Table 3, Fig. 3A)	Stepwise strategy yields highest joint faithfulness	All 5 strategies evaluated on identical 40 spots (10/dataset); same evidence dictionary, different prompt templates	Stepwise: GR=1.00, CA=1.00, SC=0.975; Uncertainty: GR=0.074, CA=1.00	Structured, step-by-step prompting maximizes grounding in supplied evidence and alignment with uncertainty tiers	That Stepwise is optimal for all downstream tasks—it sacrifices flexibility for strict faithfulness, potentially limiting counterfactual insight depth	[Paper] [Paper: PDF p. 13, Table 3; Figure 3A]
Reliability audit (Table 5, Fig. 3F)	High-confidence spots exhibit lower uncertainty and higher spatial homogeneity	Stratified 40 explained spots into High ($q \geq 0.35$, $n=9$), Medium, Low ($q < 0.20$, $n=8$); computed u_i , neighborhood homogeneity %	High group: $\bar{u}=0.034$, homogeneity=75.6%; Low group: $\bar{u}=0.111$ ($\sim 3.3\times$), homogeneity=60.0%	The three reliability signals (q , u_i , neighborhood) co-vary meaningfully, validating their use as proxies for assignment stability	That this correlation implies causation—e.g., high q causes low u_i —the paper only reports correlation ($r=-0.42$) [Figure 3D]	[Paper] [Paper: PDF p. 15, Table 5; Figure 3F]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
OmicSync-R ablation (Table 7)	Reasoning-quality reward improves clustering metrics on challenging dataset	OmicSync-R vs. base OmicSync on Human Breast Cancer at $k=10$; same Z , only q_i updated via REINFORCE	ARI $\uparrow +0.99$, FMI $\uparrow +1.79$, Jaccard $\uparrow +3.08$, DBI $\downarrow -13.46$; NMI $\downarrow -1.90$	Evidence-grounded reasoning coherence can partially align with and improve geometric clustering quality, even without LLM gradients	That OmicSync-R generalizes to all datasets—the paper explicitly restricts evaluation to Breast Cancer due to resource cost [Paper] [Paper: PDF p. 10, 17]	[Paper] [Paper: PDF p. 17, Table 7]
k-sensitivity test (Section 9.6)	OmicSync-R benefit is k -dependent	Reported ARI of OmicSync-R for $k=6-9$ vs. $k=10$ on Breast Cancer	$k=6-9$: ARI=23.68–27.77; $k=10$: ARI=46.72	The REINFORCE signal interacts strongly with centroid count; optimization is sensitive to K choice	That $k=10$ is globally optimal—the paper does not test other k for baselines, so comparison is incomplete	[Paper] [Paper: PDF p. 17]

11 对结论的正确理解

OmicSync 的核心贡献是**方法论范式创新**，而非单纯性能突破：它首次将空间多组学聚类、可靠性量化 (q_i, u_i, g_i)、证据结构化、LLM 约束推理、以及推理-聚类闭环 (OmicSync-R) 整合为一个连贯、可复现、可审计的框架。其结论必须被限定在以下范围内：(1) 性能优势体现在特定指标 (ARI/CHI/DBI) 和特定数据集 (Tonsil Add-on 最显著)，并非全指标碾压；(2) Task C 的“解释”本质是模型信号的**重述与结构化**，而非生物学发现，其价值在于可验证性 (GR/CA/SC) 而非 novelty；(3) OmicSync-R 的 +0.99 ARI 是 proof-of-concept，其资源开销 (220 LLM calls) 和 k -敏感性表明它尚不适合常规部署；(4) 所有“模态主导”结论 (如 RNA-dominant in Glioblastoma) 均为 g_i 的统计观察，作者明确强调 g_i 是 “proxy”，非因果归因 [Paper] [Paper: PDF p. 13]。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Post-hoc nature of base Task C	Explanations do not backpropagate into clustering objective; they explain but do not optimize the partition	Introduce OmicSync-R to close the reasoning-clustering loop via REINFORCE [Paper] [Paper: PDF p. 18]	[Paper] [Paper: PDF p. 18]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Resource intensity of OmicSync-R	Requires repeated LLM queries (220 total) and reward computation during training, making it computationally expensive	Explore amortised reward models, cached reasoning evaluations, and smaller verifier models to reduce cost [Paper] [Paper: PDF p. 18]	[Paper] [Paper: PDF p. 18]
k-sensitivity of OmicSync-R	Benefit concentrated at $k=10$; ARI drops sharply for $k=6-9$, suggesting poor generalization across cluster numbers	Investigate reward annealing or multi- k training to reduce k -sensitivity [Paper] [Paper: PDF p. 18]	[Paper] [Paper: PDF p. 18]
Pseudo-label dependency of Task B	CellTypeHead uses Leiden-derived pseudo-labels from RNA only, not external ground-truth annotations	Extend framework to additional modalities (ATAC-seq, spatial metabolomics) and higher-resolution platforms (Xenium, MERFISH) [Paper] [Paper: PDF p. 18]	[Paper] [Paper: PDF p. 18]
Limited scope of evidence types	Reasoning is constrained to only 5 evidence types (q , u_i , $\bar{g}$, markers, neighborhood); explanations inherit upstream uncertainty in these signals	Investigate graph-level or neighbourhood-aware reward formulations to improve spatial consistency [Paper] [Paper: PDF p. 18]	[Paper] [Paper: PDF p. 18]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis				
GR metric conflates marker presence with biological relevance	GR counts exact string matches (e.g., "CD19") but ignores synonyms ("CD19 antigen"), functional equivalence ("B-cell marker"), or contextual omission (justification says "B-cell surface protein" but omits "CD19" name). This may underestimate true grounding.	Over-reliance on GR could mislead optimization—e.g., OmicSync-R might learn to force literal name repetition rather than conceptual fidelity.	Replace GR with a semantic similarity metric (e.g., Sentence-BERT cosine between M_i and J_i) or conduct human expert evaluation of justification quality beyond keyword matching.	GR definition is purely lexical: $GR = \setminus$	$M_i \cap J_i \setminus$	$/ \setminus$	$M_i \setminus$	[Equation 18, PDF p. 9]; no semantic handling is described.

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
* <i>Uncertainty MoE's u_i measures routing instability, not clustering uncertainty</i> *	u_i is variance of $g_{m,t}$ across MC-Dropout samples, reflecting confidence in <i>which modality to trust</i> , not confidence in <i>which cluster to assign</i> . A spot could have low u_i (stable routing) but high q_{ik} entropy (ambiguous cluster assignment).	Conflating these two distinct uncertainties (<i>routing</i> vs. <i>assignment</i>) risks misinterpreting u_i as a global reliability score. The paper's own negative correlation $r = -0.42$ confirms they are related but non-identical [Figure 3D].	Compute and report clustering entropy $H(q_i) = -\sum_k q_{ik} \log q_{ik}$ alongside u_i , and analyze their joint distribution (e.g., scatter plot) to validate if low u_i truly predicts low $H(q_i)$.	The paper defines u_i solely as "epistemic routing uncertainty" [Equation 13, PDF p. 6] and q as "assignment confidence" [Equation 3, PDF p. 4], treating them as separate signals.

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Stepwise strategy's high CA/GR may stem from prompt verbosity, not deeper reasoning	The 5-step template forces explicit mention of all evidence types, artificially inflating CA (by mandating hedging language when u_i is high) and GR (by requiring marker naming in step 1). Simpler strategies may be more concise but less "faithful" by this metric.	Optimizing for GR/CA/SC may prioritize prompt compliance over explanatory utility—e.g., a clinician might prefer a concise Contrastive explanation over a verbose Stepwise one.	Conduct a user study with domain experts (pathologists, computational biologists) rating explanations for <i>clinical utility</i> , <i>conciseness</i> , and <i>actionability</i> , independent of GR/CA/SC scores.	The paper states Stepwise "encourages the language model to explicitly reference..." [Paper] [Paper: PDF p. 13], implying the structure drives the metric gains, not inherent superiority.

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis				
OmicSync-R's reward is sparse and noisy	Only 10 spots ($S_{sub>R</sub>}$) are sampled every 25 epochs for reward computation, making the REINFORCE signal highly stochastic and potentially unrepresentative of the full dataset.	Sparse sampling could lead to unstable updates or overfitting to the sampled subset, explaining the transient CA degradation at epoch 425 [Table 6].	Increase *	$S_{sub>R</sub>}$	and/or sample stratified by confidence tier (c_i^*) and dataset to ensure balanced representation of reliability regimes during training.	The paper specifies *	$S_{sub>R</sub>}$	$= 10$ and $N_{sub>R</sub>}$ = 25 [Paper] [Paper: PDF p. 9, 11], yielding only 220 total LLM queries for 600 epochs.

14 学到的知识

- **可靠性信号工程**：一个鲁棒的空间多组学模型需同时输出三类正交信号：*assignment confidence* (a_i , from clustering head softmax/t-kernel)、*epistemic uncertainty* (u_i , from MC-Dropout variance in routing)、*modality attribution* (g_i , from MoE gate mean)；三者共同构成可审计的“证据三角”。
- **LLM as constrained decoder, not oracle**：将 LLM 用作后处理模块时，必须通过**结构化证据字典 + 严格系统提示 + 自动化 faithfulness metrics** (GR/CA/SC) 将其锚定在模型自身输出上，避免幻觉，使其成为信号翻译器而非知识生成器。
- **REINFORCE for non-differentiable feedback**：当需要将不可微信号（如文本质量分数）反馈至神经网络时，REINFORCE 是可行方案；关键是设计**轻量级、可计算的 reward** (GR/CA/SC 加权) 和**稳定 baseline** (EMA b_t)，并接受其高方差特性。
- **Adaptive spatial contrastive learning**：在 InfoNCE 损失中， $n_{sub>hops</sub>}$ 不应是超参，而应基于数据自适应——用 RNA 空间邻域相似度预估组织同质性，动态设置排除半径，可缓解 ARI/SiIC 权衡。
- **k-sensitivity is a critical failure mode**：任何依赖聚类头 (ClusteringHead) 的闭环优化都必须验证其对 K 的鲁棒性；OmicSync-R 在 $k=10$ 外性能骤降，警示我们不能默认最优 K 对所有任务一致。

15 与既有知识的连接

- **候选连接/方法论连接**：OmicSync 的 KAN-GCN backbone 直接继承自 GROVER [5]，其图卷积设计（空间 + 特征邻接矩阵）与用户关注的 *graph neural networks* 高度契合；UncertaintyMoE 的 MC-Dropout + MoE 架构，与用户研究中的 *uncertainty-aware GNNs* 方法论同源。

- **候选连接/方法论连接**: Task B 的伪标签 (Leiden on RNA) 与用户 *single-cell foundation models* 中常用的 self-supervised pretext tasks (如 masked autoencoding) 逻辑一致, 均利用数据内在结构生成监督信号。
- **候选连接/方法论连接**: OmicSync-R 的 REINFORCE loop 为用户 *perturbation prediction* 任务提供了新思路: 若将 perturbation effect (如 gene knockout) 视为 “reward”, 可训练模型预测哪些 latent dimensions are most sensitive, bypassing differentiable simulation.
- **候选连接/方法论连接**: 五策略推理 (尤其是 Counterfactual/Contrastive) 与用户 *cell state representation* 研究中所需的 “what-if” 分析高度匹配, 其结构化 prompt 模板可直接迁移至细胞状态扰动解释。
- **弱连接/方法论连接**: 虽然论文未涉及 *multi-omics beyond RNA/ADT/H&E*, 但其模态路由 (g) 和缺失模态插补 (ImputationHeads) 模块的设计原则 (如 UncertaintyMoE、per-modality GCN) 可平滑扩展至 ATAC/代谢组等新模态, 符合用户 *multi-omics* 方向。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name**: SpatialNeighbourhoodVerifier

originating limitation/observation: Spatial consistency (SC) is the most unstable component of the REINFORCE reward (Table 6), and OmicSync-R shows declining SC in late training, suggesting neighborhood composition becomes less predictive as soft assignments sharpen [Paper] [Paper: PDF p. 16–17]. **core hypothesis**: Neighborhood-level coherence is better optimized by a graph-aware reward that aggregates evidence across the k -nearest neighbors, rather than scoring individual spots in isolation. **delta from paper**: Replaces spot-level SC with a graph-level $SC_{\text{graph}} = \text{mean}(SC_i)$ over a local subgraph, and incorporates neighborhood homogeneity directly into the reward weight. **initial method**: For each sampled spot i , construct its 5-neighbor subgraph G_i . Compute SC_{graph} as the fraction of neighbors in G_i assigned to the same domain as i . Use $SC_{\text{graph}} \times c_i$ as the reward weight for i 's R . **validation**: Train OmicSync-R with this new reward on Breast Cancer; compare SC trajectory (Table 6) and final clustering metrics (Table 7) against original. **failure modes**: Increased computational cost per reward step; potential over-smoothing if k is too large. **innovation status**: unverified

- **name**: CrossModalAlignmentAdapter

originating limitation/observation: The CrossModalTransformer fuses modalities *before* routing (Fig. 1, Sec 4.4), but UncertaintyMoE routes *after* fusion, potentially diluting modality-specific signals needed for precise attribution [Paper] [Paper: PDF p. 6]. **core hypothesis**: Performing cross-modal attention *within* each modality's graph encoder (i.e., letting RNA nodes attend to ADT neighbors) will create richer, more aligned cross-modal features, leading to more stable and biologically meaningful $\bar{g}$. **delta from paper**: Modifies KAN-GCN encoders (Sec 4.3) to include cross-modal adjacency matrices (e.g., $A_{s \rightarrow RNA \rightarrow ADT}$) and intra-modality attention layers that attend across modalities. **initial method**: For RNA modality, compute $e_{s \rightarrow RNA} = \text{KAN}(A_{s \rightarrow RNA} X_1 W_{GCN}^{1 \rightarrow 1})$ and $e_{s \rightarrow RNA \rightarrow ADT} = \text{KAN}(A_{s \rightarrow RNA \rightarrow ADT} X_2 W_{GCN}^{2 \rightarrow 2})$; merge via attention. Repeat for other modality pairs. **validation**: Compare $\bar{g}$ stability (variance across MC-Dropout) and GR

scores on Task C against base OmicSync. **failure modes:** Risk of over-fusion blurring modality distinctions; increased parameter count. **innovation status:** unverified

- **name:** PerturbativeReasoningReward

originating limitation/observation: OmicSync-R uses static, model-derived evidence, but user research focuses on *perturbation prediction*; a reasoning module that explains *why a perturbation changes a domain assignment* would be more actionable. **core hypothesis:** Training a reasoning module to generate counterfactual explanations for *in silico* perturbations (e.g., "if CD19 expression were zeroed, assignment shifts to Stroma") can yield a more robust and causal latent space. **delta from paper:** Extends Task C to include *perturbed evidence dictionaries* (e.g., $\bar{g}$ recalculated after masking ADT features) and trains OmicSync-R with a reward $R_{\text{pert}} = w_1 GR_{\text{pert}} + w_2 CA_{\text{pert}} + w_3 SC_{\text{pert}}$. **initial method:** For each i in S_R , apply random ADT/RNA masking (10% prob), recompute $\bar{g}$, u_i , q_i , and neighborhood; feed perturbed dictionary to Llama; compute R_{pert} . **validation:** On a simulated perturbation dataset (e.g., scRNA-seq + CRISPR screen), measure if R_{pert} -guided model better predicts true perturbation outcomes than base OmicSync. **failure modes:** Requires high-fidelity perturbation simulation; LLM may hallucinate unsupported mechanisms. **innovation status:** unverified