

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

- Title: STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images
- Authors: Youngmin Chung, Ji Hun Ha, Andrew H. Song, Cristina Almagro-Pérez, Chaeyoung Seo, Won Jun Suh, Jeong Won Beom, Kyoung Bin Oh, Eytan Ruppin, Faisal Mahmood, Joo Sang Lee
- Source: arXiv preprint (2026-09-05), arXiv:2609.05956v1
- URL: <https://arxiv.org/abs/2609.05956v1>
- PDF URL: <https://arxiv.org/pdf/2609.05956v1>
- Code & data: Publicly released at <https://github.com/NEXGEM/STP-Bench> and Hugging Face (<https://huggingface.co/datasets/nexgem/STP-Bench>) [Paper: PDF p. 37]
- Key datasets: STP-BENCH-INTERNAL (609,024 spots, 6 cancer types, Visium/Xenium), STP-BENCH-EXTERNAL (185,831 spots, 6 cancer types) [Paper: PDF p. 4-5, Fig. 1b]
- Evaluated models: 21 virtual ST models across three families - regression-based (n=14), bi-modal retrieval-based (n=4), generative-based (n=3) [Paper: PDF p. 6, Fig. 1c]
- Core encoder: UNiv2 pathology foundation model (PFM) used as standardized patch encoder where architecturally compatible [Paper: PDF p. 7-8]
- Metrics: Pearson Correlation Coefficient (PCC) [Eq. 1, p. 31], Mean Absolute Error (MAE) [Eq. 2, p. 32], Structural Similarity Index Measure (SSIM) [Paper: PDF p. 7, 32]

02 一句话总结

STP-BENCH 是首个大规模、跨平台、标准化的 virtual spatial transcriptomics (virtual ST) 基准，通过统一使用 pathology foundation model (UNiv2) 作为图像编码器，在 609,024 个 spot 的内部数据集 (STP-BENCH-INTERNAL) 和 185,831 个 spot 的外部数据集 (STP-BENCH-EXTERNAL) 上系统评估了 21 种模型；结果表明：多数模型未超越 UNiv2 线性探针基线，模型排名因统一编码器而显著重排，基因级可预测性具有跨模型一致性，且 multi-scale 架构 (TRIPLEX/DeepSpot) 在 stromal/immune 基因和下游生物学任务中表现最优 [Paper: PDF p. 8-19].

03 研究问题

- 如何在公平、可控、可复现条件下系统评估 virtual ST 模型的真实架构贡献？[Paper: PDF p. 3-4]
- 哪些基因或基因集能被可靠地从组织形态学 (H&E) 中恢复？其可预测性是否由模型架构主导，还是受形态-转录耦合本质限制？[Paper: PDF p. 11-13, Fig. 3a-e]
- virtual ST 预测结果是否保留下游生物学分析所需的结构--包括细胞类型丰度估计 (Cell2location) 和空间结构域识别 (SpaGCN)？[Paper: PDF p. 14-15, Fig. 4]

- virtual ST

模型在跨机构、跨组织、跨平台等真实域偏移场景下的泛化鲁棒性如何？数据规模与多样性是否带来性能提升？[Paper: PDF p. 16-18, Fig. 5]

04 研究背景与发展路径

- 技术动因：Spatial transcriptomics (ST) 实验成本高，催生 virtual ST（从 H&E 预测空间基因表达）计算范式 [Paper: PDF p. 2]。

- 方法演进：三大建模范式并行发展：(1) 回归式（如 ST-Net -> TRIPLEX/DeepSpot），直接映射 patch->expression；(2) 双模态对齐式（如 BLEEP/STco/mclSTExp），借鉴 CLIP 范式学习 joint embedding space；(3) 生成式（如 STFlow/Stem），建模 conditional distribution via diffusion/flow matching [Paper: PDF p. 3-6]。

- 瓶颈识别：既有评估存在三重缺陷：(i) 数据小、异质、不统一（如 Wang et al. 2024 仅用 2 个 Visium 数据集；HEST-1K 仅评估 PFM embedding + 简单回归）；(ii) 图像编码器未标准化（native encoders 混淆 architecture vs. encoder 贡献）；(iii) 评估止步于 aggregate gene-level PCC，忽略 per-gene reliability、gene-set activity、下游 utility 和鲁棒性 [Paper: PDF p. 3-4]。

- 解决方案路径：构建 STP-BENCH -- 大规模 (>30k spots/dataset)、多平台 (Visium+Xenium)、多癌种 (6)、统一 PFM 编码、全栈重实现、多粒度评估 (gene -> gene set -> cell type -> domain -> robustness) [Paper: PDF p. 4-5]。

05 论文识别的核心痛点

Pain point / Manifestation / Cause or author explanation / Evidence from the paper

Pain point: Unfair architectural comparison

Manifestation: Model rankings inconsistent when native vs. unified (UNiv2) encoders used (e.g., CFANet jumps from 16th to 6th) [Paper: PDF p. 9]

Cause or author explanation: Prior works inherit original image encoders differing in pretraining domain/scale/paradigm; performance gains may reflect feature extraction, not model design [Paper: PDF p. 3-4]

Evidence from the paper: Fig. 2b shows rank reversal; “CFANet ... jumped to 6th when using UNiv2” [Paper: PDF p. 9]; “evaluations in previous works ... are likely unfair comparisons” [Paper: PDF p. 9]

Pain point: Aggregate evaluation obscures biological utility

Manifestation: High average PCC on HMHVGs masks poor recovery of TME marker genes (PCC约0.2 vs. 0.4) and fails to reveal which biological programs are recoverable [Paper: PDF p. 9]

Cause or author explanation: Evaluation confined to “average predictive accuracy on highly variable genes”, neglecting per-gene reliability, gene-set coherence, and downstream task fidelity [Paper: PDF p. 2-4]

Evidence from the paper: Fig. 2a shows HMHVG vs. marker gene gap; Fig. 3a heatmap shows gene-wise concordance; “genes that are difficult ... remain similarly challenging across diverse models” [Paper: PDF p. 11]

Pain point: Lack of robustness assessment under real-world shifts

Manifestation: No systematic evaluation of cross-institution, cross-tissue, or cross-platform generalization [Paper: PDF p. 4]

Cause or author explanation: Prior benchmarks do not assess model reliability under domain shifts or data scaling - critical for clinical deployment [Paper: PDF p. 2-4]

Evidence from the paper: Fig. 5a-b quantifies generalization gaps; “cross-tissue generalization was challenging ... gaps reaching -0.20 to -0.35” [Paper: PDF p. 17]; “cross-platform transfer ... showed negligible performance loss” [Paper: PDF p. 17]

Pain point: Unclear data quality dependence

Manifestation: Performance varies drastically between Visium (low counts) and Xenium (high counts) datasets, but cause is unexamined [Paper: PDF p. 10]

Cause or author explanation: Gene expression prediction quality is confounded by underlying transcript detection sensitivity and signal-to-noise ratio, not just morphology [Paper: PDF p. 10, 19]

Evidence from the paper: Fig. 2c-d: NCCHE-LUAD-Xenium (mean counts=52.1/72.3) achieves PCC约0.58 vs. NCCHE-LUAD-Visium (mean counts=9.2/0.9) at PCC约0.20; “gap is largely driven by data sparsity rather than morphological uncoupling alone” [Paper: PDF p. 10]

06 核心思想

- 核心主张：virtual ST

领域的进展被不严谨的基准评估所掩盖；真正的架构创新必须在统一图像编码器（PFM）下被隔离评估，否则报告的增益可能完全源于 encoder 差异而非模型设计 [Paper: PDF p. 3-4, 9, 18].

- 关键洞见 1（Encoder Dominance）：patch encoder 的选择是性能的主导因素；UNiv2 等大规模 PFM

使多数复杂模型无法超越其线性探针基线，挑战了“架构复杂性驱动性能”的默认假设 [Paper: PDF p. 8-9].

- 关键洞见 2（Gene-level Universality）：基因可预测性具有跨模型强一致性（Fig. 3a），表明 morphology-expression coupling 是数据固有属性，而非模型可塑性；architecture 的作用在于将预测边界向更难基因（如 stromal/immune markers）轻微右移 [Paper: PDF p. 11, 19].

- 关键洞见 3（Multi-scale Advantage）：能整合局部、邻域、全局形态上下文的架构（TRIPLEX, DeepSpot）在 stromal/ECM、immune/inflammation、specialized epithelial 基因上取得最大 margin，因其依赖 meso-to-macro scale tissue patterns invisible to local patches alone [Paper: PDF p. 11-13, 19].

- 关键洞见 4（Platform-dependence）：virtual ST 的生物学效用上限由底层 ST 平台的数据质量（transcript counts, SNR）决定；Xenium 的高灵敏度使 downstream tasks (Cell2location, SpaGCN) perform substantially better than Visium, confirming a shared data-quality bottleneck [Paper: PDF p. 14-15, 19].

07 方法总览

STP-BENCH 是一个端到端 benchmarking framework，包含三大支柱：

1. Comprehensive performance evaluation：在 STP-BENCH-INTERNAL 上，以 UNiv2 为统一 patch encoder，评估 21 模型在 HMHVGs（200 genes）和 TME marker genes（16 genes）上的 PCC/MAE/SSIM；对比 native vs. unified encoder；进行 gene-wise 和 gene-set (singscore) 分析 [Paper: PDF p. 7-13, Fig. 2-3].

2. Multi-granularity biological utility evaluation：在三个 cohort (NCCHE-LUAD-Xenium/Visium, WUSTL-BRCA-Visium) 上，使用 Cell2location 评估 predicted profiles 对 cell type abundance 的重建能力（PCC per cell type），使用 SpaGCN + ARI 评估 spatial domain identification fidelity [Paper: PDF p. 14-15, Fig. 4].

3. Robustness & scalability assessment：在 STP-BENCH-EXTERNAL 上，测试 cross-institution/cross-tissue/cross-platform generalization (Spearman ρ of internal vs. external PCC)；进行 intra-cohort (data volume) 和 inter-cohort (tissue diversity) scaling 实验 [Paper: PDF p. 16-18, Fig. 5].

所有模型均 re-implemented in PyTorch with patient-level 5-fold CV (except HEST-bench), fixed seed (2021), and standardized preprocessing (224x224 patches, log1p

normalization, ImageNet norm) [Paper: PDF p. 30-31, 34].

08 核心模块拆解

Module / Function / Why needed / Input and output / Supporting evidence / Known or expected effect of removal

Module: UNlv2 PFM Encoder

Function: Extracts 1024-dim histology embeddings from 224x224 H&E patches

Why needed: To disentangle encoder contribution from architectural innovation; enables fair comparison across models [Paper: PDF p. 7-9]

Input and output: Input: H&E patch (224x224); Output: 1024-dim vector [Paper: PDF p. 25-26]

Supporting evidence: Fig. 2b shows rank reversal when swapping native $\leftrightarrow$ UNlv2; “unified morphological encoding substantially re-orders model rankings” [Paper: PDF p. 2]

Known or expected effect of removal: Removal (i.e., reverting to native encoders) would reintroduce unfair comparisons and obscure true architectural effects, as shown in Fig. 2b [Paper: PDF p. 9]

Module: HMMVG + Marker Gene Panel

Function: Defines evaluation gene set: 200 high-mean highly-variable genes + 16 TME markers (e.g., CD3E, ACTA2, PDCD1) [Paper: PDF p. 7, 33]

Why needed: To move beyond arbitrary gene sets and focus on biologically interpretable, clinically relevant targets spanning epithelial/stromal/immune lineages [Paper: PDF p. 7, 33]

Input and output: Input: Raw ST count matrices; Output: Subsetted gene expression matrix [Paper: PDF p. 33]

Supporting evidence: Fig. 2a shows performance gap between HMMVGs (PCC $\approx$ 0.4) and markers (PCC $\approx$ 0.2); Fig. 3e shows immune gene sets (T Cell Activation) recovered by top models [Paper: PDF p. 13]

Known or expected effect of removal: Removal would eliminate biological interpretability anchor; using only HMMVGs would miss the critical challenge of predicting low-abundance, functionally important markers [Paper: PDF p. 9]

Module: singscore-based Gene Set Scoring

Function: Computes per-spot gene set activity score by ranking genes within spot and averaging ranks of member genes [Paper: PDF p. 13, 35]

Why needed: To evaluate whether virtual ST preserves functional pathway activity, not just individual gene levels; enables efficient computation across thousands of spots [Paper: PDF p. 13]

Input and output: Input: Predicted/ground-truth expression matrix (spots x genes); Output: Spot x gene_set matrix of scores [Paper: PDF p. 13]

Supporting evidence: Fig. 3c-e show TRIPLEX/DeepSpot top-performing on immune/stromal gene sets; “gene set scoring performance was substantially higher on NCCHE-LUAD-Xenium” mirroring gene-level gap [Paper: PDF p. 13]

Known or expected effect of removal: Removal would reduce evaluation to spot-level only, missing functional coherence; using simple mean expression instead of rank-based singscore would be sensitive to batch effects and violate assumptions of ST data sparsity [Paper: PDF p. 13]

Module: Cell2location Deconvolution

Function: Estimates spatial cell type abundance from ST expression using scRNA-seq reference (e.g., LuCA for LUAD) [Paper: PDF p. 35]

Why needed: To test if virtual ST profiles retain sufficient biological structure for clinically relevant downstream analysis (cell composition mapping) [Paper: PDF p. 14]

Input and output: Input: Predicted/ground-truth ST matrix (spots x genes); Output: Spots x cell_types abundance matrix [Paper: PDF p. 35]

Supporting evidence: Fig. 4a shows TRIPLEX/DeepSpot achieve highest PCC with ground-truth abundances; “major cell populations ... were generally well-recovered, whereas rare ... populations ... exhibited lower correlations” [Paper: PDF p. 14]

Known or expected effect of removal: Removal would leave evaluation at molecular level only; using a simpler deconvolution method (e.g., CIBERSORTx) without spatial priors would underestimate the value of spatially coherent predictions [Paper: PDF p. 35]

Module: SpaGCN Spatial Clustering

Function: Identifies spatial domains from ST expression + coordinates using graph neural network (no histology input) [Paper: PDF p. 36]

Why needed: To test if virtual ST preserves spatially organized tissue architecture, independent of morphology priors [Paper: PDF p. 14]

Input and output: Input: Predicted/ground-truth ST matrix + spot coordinates; Output: Domain labels per spot [Paper: PDF p. 36]

Supporting evidence: Fig. 4b-c show TRIPLEX/DeepSpot top-performing on ARI; “both downstream tasks yielded substantially higher performance for Xenium-based than Visium-based cohorts” [Paper: PDF p. 14]

Known or expected effect of removal: Removal would omit validation of spatial coherence; using k-means instead of SpaGCN would ignore spatial graph structure and fail to capture domain boundaries [Paper: PDF p. 36]

09 关键公式与符号

- Equation 1 (PCC):

$$\text{PCC}_{\{g,s\}} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2} \sqrt{\sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}} \quad \text{[Paper: PDF p. 31]}$$

- $(\hat{y}_{i,g}, y_{i,g})$: predicted and ground-truth log-normalized expression of gene g at spot i

- $(\bar{\hat{y}}_g, \bar{y}_g)$: means over all spots in section s

- Used as primary metric for spot-level gene prediction accuracy; NaN for zero-variance genes set to 0 [Paper: PDF p. 31].

- Equation 2 (MAE):

$$\text{MAE}_{\{g,s\}} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}| \quad \text{[Paper: PDF p. 32]}$$

- Measures absolute deviation in $\log(1+x)$ -transformed expression space.

- Aggregated same as PCC: gene-wise $\rightarrow$ section-wise $\rightarrow$ dataset-wise mean $\pm$ std [Paper: PDF p. 32].

- Other key symbols:

- HMMVG: High-mean highly-variable genes (200 selected via rank-sum of mean expression and variability) [Paper: PDF p. 33].

- TME markers: 16 curated genes (e.g., CD3E, ACTA2, PDCD1) representing epithelial/stromal/immune lineages [Paper: PDF p. 7, 33].

- ARI: Adjusted Rand Index for spatial domain agreement between predicted and ground-truth labels [Paper: PDF p. 15, 36].

- SSIM: Structural Similarity Index Measure for spatial expression map coherence [Paper: PDF p. 32].

10 实验设计与证据链

Experiment / Claim tested / Comparison and conditions / Result / Supported conclusion / Unsupported stronger conclusion / Source

Experiment: Fig. 2a (Internal PCC)

Claim tested: Unified PFM standardization reveals true architectural ranking

Comparison and conditions: 21 models evaluated on STP-BENCH-INTERNAL with UNlv2 (w/ PFM) vs. native encoders (w/o PFM); HMMVGs and 16 markers

Result: Most w/ PFM models < linear probing baseline (UNlv2 LP); TRIPLEX/DeepSpot > baseline; w/o PFM models mostly < baseline

Supported conclusion: UNlv2 linear probing is a strong baseline; multi-scale regression models (TRIPLEX/DeepSpot) have genuine architectural advantage

Unsupported stronger conclusion: "All other models are useless" - false, as some (e.g., Path2Space, EGN) marginally surpass baseline [Paper: PDF p. 9]

Source: [Paper: PDF p. 8-9, Fig. 2a]

Experiment: Fig. 2c-d (Expression level stratification)

Claim tested: Prediction accuracy is driven by transcript abundance, not inherent unpredictability

Comparison and conditions: PCC computed per gene quantile (Very Low to Very High) on NCCHE-LUAD-Xenium (high counts) vs. NCCHE-LUAD-Visium (low counts)

Result: Strong correlation between expression level and PCC ($p < 1e-12$); Xenium achieves PCC ≈ 0.58 for markers, Visium only ≈ 0.19

Supported conclusion: Data sparsity (low transcript counts) is a major bottleneck for marker gene prediction, not morphology uncoupling

Unsupported stronger conclusion: "Morphology contains no signal for immune genes" - false, as Xenium shows high predictability [Paper: PDF p. 10]

Source: [Paper: PDF p. 10, Fig. 2c-d]

Experiment: Fig. 3a (Gene-wise heatmap)

Claim tested: Gene predictability is universal across models

Comparison and conditions: PCC computed per gene across 20 models (excluding zero-shot OmiCLIP/STPath) on union of HMMVGs+markers

Result: Smooth separation of high/low-performing genes; consistent ordering across models; curved boundary indicates architecture shifts predictability threshold

Supported conclusion: Gene-level predictability is governed by morphology-expression coupling, not model choice; architectures shift the boundary, not the fundamental ceiling

Unsupported stronger conclusion: "Architecture determines which genes are predictable" - overstates; it shifts margin, but core easy/hard genes are shared [Paper: PDF p. 11]

Source: [Paper: PDF p. 11, Fig. 3a]

Experiment: Fig. 4a (Cell2location)

Claim tested: Virtual ST preserves cell-type spatial organization

Comparison and conditions: Cell2location applied to ground-truth vs. predicted ST; PCC computed per cell type (e.g., malignant epithelial, T cells)

Result: TRIPLEX/DeepSpot achieve highest PCC; major populations well-recovered, rare populations (plasma/mast cells) poorly recovered

Supported conclusion: Top-performing gene-level models translate to superior cell deconvolution; platform quality (Xenium > Visium) limits upper bound

Unsupported stronger conclusion: "Virtual ST enables clinical-grade cell typing" - unsupported, as rare populations fail [Paper: PDF p. 14]

Source: [Paper: PDF p. 14-15, Fig. 4a]

Experiment: Fig. 5a (Cross-tissue generalization)

Claim tested: Internal rankings predict external performance under biological shift

Comparison and conditions: Spearman ρ between internal PCC and external PCC averaged across all cross-tissue dataset pairs (e.g., train on LUAD, test on BRCA)

Result: $\rho = 0.876$ ($p = 1.87e-6$), strong rank preservation despite large absolute drop (gap ≈ -0.2 to -0.35)

Supported conclusion: Architectural superiority is generalizable across tissues; cross-tissue shift is harder than cross-institution

Unsupported stronger conclusion: "Models trained on one cancer generalize to all cancers" - false, as absolute performance drops severely [Paper: PDF p. 17]

Source: [Paper: PDF p. 16-17, Fig. 5a]

11 对结论的正确理解

- "Most models fail to beat linear probing" means that, under unified UNiv2 encoding, the incremental gain of complex architectures (e.g., Transformers, GNNs, contrastive alignment) over a simple linear map from PFM features is often marginal or negative - not that these models are useless, but that their reported gains in prior work were likely inflated by superior native encoders [Paper: PDF p. 8-9].
- "Gene predictability is universal" means that the ranking of genes by ease-of-prediction (e.g., COL1A1 easy, PDCD1 hard) is consistent across all 20+ models - not that all models achieve identical PCC for each gene, but that the relative difficulty landscape is data-intrinsic [Paper: PDF p. 11, Fig. 3a].
- "TRIPLEX/DeepSpot are best" is context-dependent: they lead on HMMVGs, markers, gene sets, Cell2location, and SpaGCN within this benchmark, but their advantage is most pronounced for stromal/immune genes requiring multi-scale reasoning; they do not dominate on all metrics (e.g., SSIM trends are similar but not shown as top) [Paper: PDF p. 11-15].
- "Xenium > Visium" reflects platform-specific technical advantages (higher sensitivity, more transcripts), not a fundamental limitation of virtual ST - it means the ceiling of what morphology can predict is raised by better ground-truth data quality [Paper: PDF p. 10, 14, 19].
- "Negative transfer in inter-cohort scaling" means adding BRCA+LUAD+PRAD training data harms BRCA test performance - not that multi-cancer training is always bad, but that naive aggregation without tissue-aware adaptation is detrimental due to morphological specificity [Paper: PDF p. 18, Fig. 5d].

12 作者明确承认的限制

Limitation / Specific manifestation / Future direction proposed by authors / Source

Limitation: Limited cancer/tissue scope

Specific manifestation: STP-BENCH covers only 6 cancer types and 2 platforms (Visium/Xenium); lacks rare tumors, normal tissues, and emerging platforms (e.g., Stereo-seq) [Paper: PDF p. 20]

Future direction proposed by authors: Extend benchmark to additional tumor types, tissue contexts, and sequencing platforms for broader generalizability [Paper: PDF p. 20]

Source: [Paper: PDF p. 20]

Limitation: Restricted gene panel

Specific manifestation: Analyses focused on HMMVGs (200) and 16 TME markers; systematic investigation of lowly expressed, housekeeping, or functionally diverse genes is absent [Paper: PDF p. 20]

Future direction proposed by authors: Systematic investigation of lowly expressed or functionally diverse genes remains an open direction [Paper: PDF p. 20]

Source: [Paper: PDF p. 20]

Limitation: Spot-level resolution only

Specific manifestation: Evaluations performed at spot-level (aggregates multiple cells); single-cell ST and virtual ST models are emerging but not benchmarked [Paper: PDF p. 20]

Future direction proposed by authors: Future benchmarking efforts may extend principles to single-cell resolution as data and models mature [Paper: PDF p. 20]

Source: [Paper: PDF p. 20]

13 批判性分析

[Analysis] Observation / Potential issue or alternative explanation / Why it matters / How to test it / Basis

[Analysis] Observation: Linear probing baseline uses UNiv2, but its architecture is not "zero-parameter" - it includes Softplus output activation and log1p normalization, while some models (e.g., retrieval-based) have no such constraints [Paper: PDF p. 23, 31].

Potential issue or alternative explanation: The baseline may be artificially advantaged by domain-appropriate output constraints (non-negativity) and preprocessing, making it harder for other models to beat. A truly minimal baseline (e.g., linear + identity) might yield different rankings.

Why it matters: Overstating the strength of the baseline could misattribute architectural weakness; fairness requires matching all components, not just the encoder.

How to test it: Re-run Fig. 2a with a stripped-down linear probe: no Softplus, raw counts (no log1p), and compare. If rankings shift (e.g., more models beat it), the current baseline is inflated.

Basis: [Paper: PDF p. 23 (Softplus), p. 31 (log1p), p. 8 (baseline definition)]

[Analysis] Observation: Gene set analysis (Fig. 3e) uses singscore on HMMVG+marker union, but many GO terms have poor overlap with this limited panel - filtering retained only gene sets with ≥ 5 overlapping genes covering $\geq 10\%$ of original set [Paper: PDF p. 35].

Potential issue or alternative explanation: This stringent filtering may exclude biologically relevant pathways (e.g., metabolism, DNA repair) simply because their genes weren't in the HMMVG/marker panel, creating a biased view of "recoverable biology".

Why it matters: Conclusions about "which biological programs are recoverable" are constrained by the evaluation gene set, not morphology. It risks conflating panel incompleteness with biological irrecoverability.

How to test it: Expand gene panel to include broad functional categories (e.g., Hallmark gene sets) and recompute singscore. If new pathways (e.g., OxPhos) show high PCC, current conclusions are panel-limited.

Basis: [Paper: PDF p. 35 (filtering criteria), p. 13 (singscore rationale)]

[Analysis] Observation: Cross-platform transfer (Visium->Xenium) shows "negligible loss" (Fig. 5b right), but Xenium has higher transcript counts - the gain may reflect easier prediction on higher-SNR data, not true cross-platform robustness [Paper: PDF p. 17].

Potential issue or alternative explanation: The apparent success masks a confound: models aren't generalizing across platforms, but benefiting from Xenium's superior data quality. A true test would be Xenium->Visium, which likely shows larger degradation.

Why it matters: Misinterpreting this as "platform-agnostic" could mislead developers into ignoring platform-specific calibration needs for clinical deployment.

How to test it: Conduct reverse transfer (Xenium-trained -> Visium-test) and report gap. If gap is large (e.g., > 0.2), the current "robustness" claim is asymmetric and context-dependent.

Basis: [Paper: PDF p. 17 ("Visium -> Xenium"), p. 10 (Xenium counts > Visium)]

[Analysis] Observation: Inter-cohort scaling shows negative transfer (Fig. 5d), but the experiment adds LUAD then PRAD - the order may matter. Adding a more morphologically similar cancer first (e.g., BRCA->other breast subtypes) might avoid negative transfer.

Potential issue or alternative explanation: The conclusion "simple aggregation is detrimental" is overly broad; it depends on the pairwise morphological distance between cancers, not just count. A tissue-aware curriculum (similar->dissimilar) might help.

Why it matters: Overgeneralizing could discourage multi-cancer training; a nuanced view would guide better data curation strategies (e.g., cluster cancers by morphology before merging).

How to test it: Cluster cancers by histological similarity (e.g., using PFM embeddings), then test scaling order: similar->dissimilar vs. random. If similar-first improves BRCA performance, negative transfer is order-dependent.

Basis: [Paper: PDF p. 18 (scaling order: BRCA->LUAD->PRAD), p. 19 ("tissue-specific nature")]

14 学到的知识

- Benchmarking hygiene is non-negotiable: Standardizing the image encoder (PFM) is essential to isolate architectural contributions; prior field progress was likely overestimated due to encoder heterogeneity [Paper: PDF p. 3-4, 9, 18].
- virtual ST has a "morphology ceiling": Gene predictability is largely universal

across models, implying that the limit is set by how much transcriptional information morphology actually contains, not by current model capacity [Paper: PDF p. 11, 19].

- Multi-scale context is irreplaceable for microenvironment biology: Stromal (COL1A1), immune (LAG3), and specialized epithelial (SFTPC) genes require integration beyond local patches - architectures like TRIPLEX (target+neighbor+global branches) or DeepSpot (spot+sub-spot+neighbor) are uniquely suited [Paper: PDF p. 11-13, 19].
- Data quality is the master variable: Xenium's higher transcript counts lift performance across all levels (gene PCC, gene-set scores, Cell2location, SpaGCN), proving that virtual ST's ultimate utility is gated by experimental ST platform quality, not just algorithmic ingenuity [Paper: PDF p. 10, 14, 19].
- Robustness is hierarchical: Cross-institution shifts (technical) preserve rankings well ($\rho > 0.86$); cross-tissue shifts (biological) preserve rankings but with large absolute drops (gap ≈ 0.3); cross-platform shifts are unstable and model-specific - guiding deployment: prioritize tissue-matched models [Paper: PDF p. 16-17, Fig. 5].

15 与既有知识的连接

- single-cell foundation models: STP-BENCH operates at spot-level, not single-cell; however, its finding that morphology-to-expression coupling is intrinsic (not model-dependent) [Paper: PDF p. 11] suggests single-cell virtual ST may face even stricter ceilings due to greater cellular heterogeneity within spots - motivating future single-cell extension [Paper: PDF p. 20].
- spatial transcriptomics: Directly addresses ST's cost barrier; validates that Xenium's technical superiority translates to virtual ST utility [Paper: PDF p. 10, 14], reinforcing ST platform choice as a key experimental design factor.
- graph neural networks: Models like EGGN and SEPAL use GNNs for spatial refinement [Paper: PDF p. 24-25], but STP-BENCH shows their spot-level PCC (Fig. 2a) lags behind TRIPLEX/DeepSpot - suggesting that pure spatial graph reasoning without explicit multi-scale morphology integration is insufficient.
- multi-omics: STP-BENCH is inherently multi-omics (histology + transcriptomics); its conclusion that encoder choice dominates architecture [Paper: PDF p. 9] implies that for other multi-omics pairs (e.g., genomics+transcriptomics), representation learning quality may similarly eclipse fusion architecture.
- biomedical AI: Provides a template for rigorous benchmarking in biomedical AI: large-scale, standardized, multi-metric, and biologically grounded - moving beyond "SOTA chasing" to understanding fundamental limits [Paper: PDF p. 2-4].
- perturbation prediction / cell state representation / cross-modal alignment: Weak connection/methodological connection. STP-BENCH does not address perturbations (e.g., drug treatment), latent cell states, or explicit cross-modal alignment beyond CLIP-style contrastive learning (BLEEP/STco) - those are distinct problem formulations not evaluated here [Paper: PDF p. 3-6].

16 研究想法

- name: Morphology-Informed Gene Set Prioritization (MIGSP)

originating limitation/observation: Gene set analysis (Fig. 3e) is constrained by the HMHVG+marker panel; many biologically relevant pathways are excluded due to poor overlap [Paper: PDF p. 35].

core hypothesis: Morphology-informed gene set selection - prioritizing gene sets whose member genes are individually predictable from H&E (high gene-wise PCC) - will yield more robust and biologically coherent virtual ST predictions than fixed panels.

delta from paper: Instead of predefining panels, dynamically select gene sets based on empirical predictability (e.g., top 10% of genes by median PCC across models), then compute singscore only on those.

initial method: On STP-BENCH-INTERNAL, compute gene-wise PCC for all models; for each GO term, calculate mean PCC of its members; retain top-k terms by mean PCC; re-run gene-set scoring (Fig. 3e) on this morphology-prioritized set.

validation: Compare ARI (Fig. 4c) and Cell2location PCC (Fig. 4a) using morphology-prioritized vs. fixed (GO BP 2023) gene sets; expect higher downstream fidelity for prioritized sets.

failure modes: If morphology-prioritized sets are too narrow (e.g., only ECM genes), they may lack functional diversity; if predictability is noisy, selection may overfit.

innovation status: unverified

- name: Tissue-Aware Multi-Cancer Training (TAMCT)

originating limitation/observation: Inter-cohort scaling shows negative transfer (Fig. 5d) because naive aggregation of BRCA+LUAD+PRAD harms BRCA performance [Paper: PDF p. 18].

core hypothesis: Learning tissue-specific adapter modules (e.g., LoRA layers) on top of a shared backbone, conditioned on tissue-type embeddings, will enable positive transfer across cancers without sacrificing tissue-specific fidelity.

delta from paper: Replace uniform training on merged data (Fig. 5d) with a modular architecture: shared encoder + tissue-specific adapters + tissue-type token input.

initial method: Modify TRIPLEX/DeepSpot to accept tissue-type ID; add trainable LoRA adapters to key layers; train on BRCA+LUAD+PRAD with tissue ID; evaluate BRCA test performance vs. baseline (Fig. 5d).

validation: If TAMCT achieves BRCA PCC > baseline (Fig. 5d) and maintains LUAD/PRAD performance, negative transfer is mitigated.

failure modes: Adapter overfitting to small tissue cohorts; increased inference latency; need for tissue-ID at test time.

innovation status: unverified

- name: Cross-Platform Calibration via Latent Alignment (CPLA)

originating limitation/observation: Cross-platform transfer (Visium->Xenium) shows model-specific gains/losses (Fig. 5b right), suggesting platform mismatch is not handled uniformly [Paper: PDF p. 17].

core hypothesis: Aligning the latent spaces of Visium and Xenium expression profiles (e.g., via adversarial domain adaptation on PFM-conditioned embeddings) will stabilize cross-platform generalization.

delta from paper: Add a domain alignment module between the PFM encoder and the ST predictor, trained to minimize Visium-Xenium distribution divergence in the prediction head's input space.

initial method: For TRIPLEX trained on Visium, add a gradient reversal layer before the fusion encoder; train with Visium (source) and Xenium (target) pseudo-spot

embeddings to confuse a domain classifier.

validation: Test calibrated model on STP-BENCH-EXTERNAL cross-platform pairs; expect reduced variance in Fig. 5b right and higher mean PCC than uncalibrated.

failure modes: Alignment may erase biologically meaningful platform differences; requires paired Visium/Xenium data for stable training.

innovation status: unverified