

Source coverage: Full paper  
Extraction confidence: High  
Locator mode: page-grounded  
Primary analytical lens: methods  
Secondary analytical lens: None  
Context verification: Paper-only  
Card completeness: Complete relative to supplied source

## 01 基本信息

- 标题: MARC: Morphology-Aware Regression of Consensus for Cell Segmentation in Subcellular Spatial Transcriptomics
- 作者: Xinyu Shu, Andrew Zhang, Jean Yang, Jinman Kim
- 出处: arXiv preprint arXiv:2609.13665v1 [cs.CV], 2026-09-12
- 核心任务: 预测 subcellular spatial transcriptomics (SST)  
中候选细胞分割掩码的跨方法共识支持度 (pixel-level consensus-support map)，无需运行多方法集成推理
- 输入: 候选二值掩码  $F_k$ 、配准的 DAPI 形态图像  $D$ 、转录本密度图  $T$  [Paper: PDF p. 3]
- 输出: 连续值共识支持图  $\hat{C}_k \in [0,1]^{H \times W}$ ，及其细胞级聚合得分  $S_{k,c}$  [Paper: PDF p. 3-5]
- 关键创新: Leave-one-method-out 伪监督 + Foreground-Union Consensus Loss (FUCL) + morphology-transcript-aware U-Net 架构
- 评估数据集: 10x Genomics Xenium FFPE human renal cell carcinoma dataset，空间留出划分，共 4,642 测试 tile [Paper: PDF p. 5]
- 候选方法: Cellpose-SAM, BIDCell, ProSeg, Xenium 10x onboard segmentation [Paper: PDF p. 5]
- 代码/数据地址: 未核验
- 机构信息:  
未核验（仅从作者单位列表推断为悉尼大学相关机构，但未在文中作为研究背景陈述）

## 02 一句话总结

MARC 是一种 morphology-aware 的回归模型，通过以 leave-one-method-out 多方法共识为伪标签、以 foreground-union mask 为损失聚焦区域进行训练，仅需单个候选掩码  $F_k$ 、DAPI 形态  $D$  和转录本密度  $T$  即可预测像素级共识支持图  $\hat{C}_k$ ，在 Xenium 肾癌数据上实现平均 Dice 0.9002 与细胞级 Spearman 相关系数 0.7905，逼近显式多方法共识而免于多管道推理 [Paper: PDF p. 1, 4-5]。

## 03 研究问题

- 如何在 subcellular spatial transcriptomics (SST)  
中对无真值标注的候选细胞分割结果进行可扩展、共识感知的质量评估？[Paper: PDF p. 1]
- 如何避免显式多方法共识构造 (explicit multi-method consensus construction) 所需的计算密集型多管道执行？[Paper: PDF p. 2]
- 如何将形态学 (DAPI) 与分子信号 (transcript density) 整合进共识支持预测，超越候选掩码几何本身？[Paper: PDF p. 5-6]

## 04 研究背景与发展路径

SST 细胞分割面临三重挑战：(1) 边界本质模糊 (morphological contrast weak, transcripts

sparse/displaced, cells densely packed) [Paper: PDF p. 1]; (2) 无可靠 ground truth (manual annotation prohibitively time-consuming, boundaries biologically ambiguous) [Paper: PDF p. 1, 3]; (3) 现有质量评估方法不适用--监督法依赖专家标注, 不确定性估计法依赖生成模型内部预测 [Paper: PDF p. 1-3]。

既有工作分三支：(i) SST 分割方法 (Cellpose-SAM, BIDCell, ProSeg, Xenium) 因输入/假设不同产生互补但冲突的边界 [Paper: PDF p. 1-2]; (ii) 共识方法 (STAPLE, majority voting) 提供实用替代真值, 但需运行全部 pipeline [Paper: PDF p. 2-3]; (iii) 学习型质量评估 (SegQC, Bayesian uncertainty) 未针对 SST 设计 [Paper: PDF p. 3]。

MARC

沿“共识即代理真值”路径演进：不追求单一最优分割, 而建模多方法一致性程度; 将共识构造从 inference-time 移至 training-time, 用 pseudo-targets 实现 inference-time 单次前向 [Paper: PDF p. 2-3]。

## 05 论文识别的核心痛点

Pain point / Manifestation / Cause or author explanation / Evidence from the paper

Pain point: Computational intractability of explicit consensus

Manifestation: Explicit multi-method consensus requires configuring and running all contributing pipelines with method-specific SST inputs on large tissue regions, limiting routine QC use [Paper: PDF p. 2].

Cause or author explanation: Each segmentation method has distinct input requirements (e.g., different preprocessing, modality weighting), making ensemble execution non-uniform and resource-heavy [Paper: PDF p. 2].

Evidence from the paper: Figure 1(a) illustrates computational intensity; Section 1 states “this process is computationally intensive and difficult to scale” [Paper: PDF p. 2].

Pain point: Lack of scalable, consensus-aware quality control

Manifestation: Conventional QC approaches (supervised or uncertainty-based) fail when expert annotations are unavailable and candidate masks come from heterogeneous external pipelines [Paper: PDF p. 1-3].

Cause or author explanation: Supervised methods require costly manual masks; uncertainty methods require access to the generating model’s internals-neither applies to black-box candidate masks [Paper: PDF p. 1, 3].

Evidence from the paper: Section 1: “these approaches do not readily support the evaluation of candidate masks produced by different SST segmentation pipelines when expert annotations are unavailable” [Paper: PDF p. 1].

Pain point: Ambiguity of SST cell boundaries

Manifestation: Boundaries cannot be reliably inferred from incomplete morphological and transcript signals alone, leading to biological ambiguity [Paper: PDF p. 1].

Cause or author explanation: Morphology may lack contrast; transcripts may be sparse or displaced; neighboring cells overlap-making ground truth fundamentally unattainable [Paper: PDF p. 1, 3].

Evidence from the paper: Abstract: “reliable ground-truth boundaries are unavailable because they must be inferred from incomplete morphological and transcript signals” [Paper: PDF p. 1].

## 06 核心思想

将 SST 细胞分割质量评估重构为稠密共识回归问题 (dense consensus-regression problem)：不直接优化分割掩码, 而是学习从单个候选掩码  $SF_k$ 、DAPI 形态  $SD$ 、转录本密度  $ST$  预测其在 leave-one-method-out 多方法共识中的支持强度  $\hat{C}_k$  [Paper: PDF p. 2]。该预测在 inference 时免于多方法执行, 且其细胞级聚合得分  $S_{\{k,c\}}$  可直接用于排序、过滤或人工复审 [Paper: PDF p. 2,

5]。核心洞见是：共识不是终点，而是可学习的中间监督信号；形态与转录本提供互补上下文，使模型能泛化至未见的边界歧义区域 [Paper: PDF p. 5-6]。

## 07 方法总览

MARC 是一个四层 U-Net 架构 [Paper: PDF p. 3]，输入为三通道张量  $X_k = \text{concat}(D, T, F_k)$  [Eq. 2, Paper: PDF p. 3]；输出为连续值共识支持图  $\hat{C}_k = f_{\theta}(X_k) \in [0,1]^{H \times W}$ ，经 sigmoid 激活 [Eq. 4, Paper: PDF p. 3]。训练采用 leave-one-method-out 伪标签  $C_{(-k)}$ （其余  $K-1=3$  个方法前景图的算术平均）[Eq. 5, Paper: PDF p. 3]，并定义 foreground-union mask  $U_k$ （覆盖候选前景或共识前景的像素）[Eq. 6, Paper: PDF p. 4]；损失函数 FUCL 为  $U_k$  区域内  $\hat{C}_k$  与  $C_{(-k)}$  的平均绝对误差 [Eq. 7, Paper: PDF p. 4]。细胞级得分  $S_{k,c}$  由  $\hat{C}_k$  在原始标记掩码  $M_k$  对应细胞像素上平均得到 [Eq. 8, Paper: PDF p. 5]。

## 08 核心模块拆解

Module / Function / Why needed / Input and output / Supporting evidence / Known or expected effect of removal

Module: Leave-one-method-out consensus target  $C_{(-k)}$

Function: Generates pseudo-ground-truth by averaging binary foreground maps of all other  $K-1$  methods, excluding candidate  $k$  [Eq. 5, Paper: PDF p. 3].

Why needed: Prevents trivial self-agreement supervision; provides scalable surrogate for ground truth where manual annotation is infeasible [Paper: PDF p. 3].

Input and output: Input:  $\{F_j\}_{j \neq k}$ ; Output:  $C_{(-k)} \in [0,1]^{H \times W}$  [Eq. 5].

Supporting evidence: Section 3.3: “Excluding the candidate method from its own target prevents the model from receiving trivial self-agreement as supervision” [Paper: PDF p. 3].

Known or expected effect of removal: Removal would cause overfitting to candidate geometry; ablation shows mean-consensus outperforms STAPLE in sensitivity & ranking [Paper: PDF p. 5].

Module: Foreground-Union Consensus Loss (FUCL)

Function: Computes mean absolute error only within union mask  $U_k = F_k \vee C_{(-k)}$ , focusing gradients on foreground and disagreement regions [Eq. 7, Paper: PDF p. 4].

Why needed: Ensures learning prioritizes biologically relevant pixels (cell interiors & boundaries) rather than background; avoids dilution by zero-loss background pixels [Paper: PDF p. 4].

Input and output: Input:  $\hat{C}_k, C_{(-k)}, U_k$ ; Output: scalar loss  $L^{(k)}_{\text{FU}}$  [Eq. 7].

Supporting evidence: Equation 7 clamps denominator to avoid division-by-zero; caption of Figure 2 cites FUCL [Paper: PDF p. 4].

Known or expected effect of removal: Removal would degrade foreground metrics (Dice/IoU); Table 1 shows high Dice (0.9002) implies FUCL successfully focuses on foreground.

Module: Morphology-Transcript-Candidate tri-input

Function: Concatenates DAPI morphology  $D$ , transcript density  $T$ , and candidate foreground  $F_k$  into 3-channel input  $X_k$  [Eq. 2, Paper: PDF p. 3].

Why needed: Candidate mask alone is insufficient; morphology provides nuclear context, transcripts provide molecular evidence-both complementary to geometry [Paper: PDF p. 5-6].

Input and output: Input:  $D, T, F_k$ ; Output:  $X_k \in \mathbb{R}^{3 \times H \times W}$  [Eq. 2].

Supporting evidence: Table 2 ablation: adding DAPI boosts Spearman  $\rho$  from 0.4228  $\rightarrow$  0.7564; adding transcripts further  $\rightarrow$  0.7905 [Paper: PDF p. 6].

Known or expected effect of removal: Removal of  $D$  or  $T$  degrades both pixel-level (Dice) and cell-level ( $\rho$ ) performance significantly (Table 2).

Module: Cell-level aggregation via  $S_{k,c}$

Function: Averages predicted consensus  $\hat{C}_k$  over pixels assigned to each candidate cell  $c$  in labelled mask  $M_k$  [Eq. 8, Paper: PDF p. 5].

Why needed: Enables practical QC: scores rank cells by consensus support for manual review/filtering, bridging pixel prediction to biological interpretation [Paper: PDF p. 5].  
 Input and output: Input:  $\hat{C}_k, M_k$ ; Output: scalar  $S_{k,c}$  per cell [Eq. 8].  
 Supporting evidence: Figure 3 plots  $S_{k,c}$  vs target; Section 4.2: “scores can be used to rank cells for manual review” [Paper: PDF p. 5].  
 Known or expected effect of removal: Without aggregation, no cell-level ranking possible; candidate-copy baseline has constant scores (undefined  $\rho$  in Table 2) [Paper: PDF p. 6].

## 09 关键公式与符号

Symbol / Definition / Context / Page / Notes

Symbol:  $M_k$

Definition: Labelled mask from candidate method  $k$ ,  $M_k \in \{0,1,\dots\}^{H \times W}$

Context / Page: [Eq. 1, Paper: PDF p. 3]

Notes: Positive values = cell instance IDs; 0 = background.

Symbol:  $F_k(x,y)$

Definition: Binary foreground map:  $1$  if  $M_k(x,y) > 0$ , else  $0$

Context / Page: [Eq. 1, Paper: PDF p. 3]

Notes: Derived from  $M_k$ ; used as input channel.

Symbol:  $D, T$

Definition: Aligned DAPI morphology image and transcript-density image, both  $\in \mathbb{R}^{H \times W}$

Context / Page: [Paper: PDF p. 3]

Notes: Pre-aligned to same grid (0.2125  $\mu\text{m}/\text{pixel}$ ) [Paper: PDF p. 5].

Symbol:  $X_k$

Definition: Three-channel input:  $X_k = \text{concat}(D, T, F_k) \in \mathbb{R}^{3 \times H \times W}$

Context / Page: [Eq. 2, Paper: PDF p. 3]

Notes: Core input to MARC encoder.

Symbol:  $\hat{C}_k$

Definition: Predicted continuous consensus-support map:  $\hat{C}_k = f_{\theta}(X_k) \in [0,1]^{H \times W}$

Context / Page: [Eq. 3, Paper: PDF p. 3]

Notes: Output of U-Net decoder + sigmoid [Eq. 4].

Symbol:  $C_{(-k)}(x,y)$

Definition: Leave-one-method-out consensus target: mean of other  $K-1$  methods'  $F_j$

Context / Page: [Eq. 5, Paper: PDF p. 3]

Notes:  $K=4$  in experiments;  $C_{(-k)} = \frac{1}{3} \sum_{j \neq k} F_j$  [Paper: PDF p. 3].

Symbol:  $U_k(x,y)$

Definition: Foreground-union mask:  $1$  if  $F_k(x,y)=1$  OR  $C_{(-k)}(x,y) > 0$

Context / Page: [Eq. 6, Paper: PDF p. 4]

Notes: Defines region for FUCL computation.

Symbol:  $L^{\{k\}}_{\text{FU}}$

Definition: Foreground-Union Consensus Loss: MAE of  $\hat{C}_k$  vs  $C_{(-k)}$  over  $U_k$

Context / Page: [Eq. 7, Paper: PDF p. 4]

Notes: Denominator clamped to  $\geq 1$  to avoid division-by-zero.

Symbol:  $S_{k,c}$

Definition: Cell-level consensus score for candidate cell  $c$ : mean  $\hat{C}_k$  over pixels in  $M_{k=c}$

Context / Page: [Eq. 8, Paper: PDF p. 5]

Notes: Used for ranking; Spearman  $\rho$  computed between  $\{S_{k,c}\}$  and  $\{C_{(-k),c}\}$ .

## 10 实验设计与证据链

Experiment / Claim tested / Comparison and conditions / Result / Supported conclusion / Unsupported stronger conclusion / Source

Experiment: Main evaluation (Table 1)

Claim tested: MARC predicts explicit leave-one-method-out consensus  $\mathcal{C}_{(-k)}$  with high fidelity at pixel and cell levels.

Comparison and conditions: MARC trained on 4 candidate methods (Cellpose-SAM, BIDCell, ProSeg, Xenium); evaluated on held-out test tiles (4,642) against  $\mathcal{C}_{(-k)}$  targets. Metrics: Foreground-union L1, Dice, IoU, Sensitivity, Precision, Cell Spearman  $\rho$ .

Result: Avg. Dice = 0.9002, Avg.  $\rho$  = 0.7905; best per-method Dice up to 0.9127 (Xenium 10x).

Supported conclusion: MARC closely approximates explicit cross-method consensus without multi-method inference.

Unsupported stronger conclusion: MARC achieves biological ground-truth accuracy (not claimed; authors state consensus is a surrogate) [Paper: PDF p. 7].

Source: Table 1, Section 4.2 [Paper: PDF p. 4-5]

Experiment: Input ablation (Table 2)

Claim tested: DAPI morphology and transcript density provide complementary signal beyond candidate-mask geometry.

Comparison and conditions: Four configurations: (i) candidate-copy baseline (no model), (ii) MARC with  $\mathcal{F}_k$  only, (iii)  $\mathcal{F}_k + \mathcal{D}$ , (iv)  $\mathcal{F}_k + \mathcal{D} + \mathcal{T}$ . All trained with same  $\mathcal{C}_{(-k)}$  target and FUCL.

Result: Adding  $\mathcal{D}$ : Dice  $\uparrow$  0.8565  $\rightarrow$  0.8866,  $\rho$   $\uparrow$  0.4228  $\rightarrow$  0.7564; Adding  $\mathcal{T}$ : Dice  $\uparrow$  0.8866  $\rightarrow$  0.9002,  $\rho$   $\uparrow$  0.7564  $\rightarrow$  0.7905.

Supported conclusion: Morphology is primary driver for cell-level ranking; transcripts add complementary molecular signal improving both pixel and cell metrics.

Unsupported stronger conclusion: Transcript density is necessary for high performance (not tested; ablation shows incremental gain, not necessity).

Source: Table 2, Section 4.3 [Paper: PDF p. 6]

Experiment: Target ablation (Section 4.3)

Claim tested: Arithmetic mean consensus is a viable and pragmatic pseudo-target compared to STAPLE.

Comparison and conditions: Two MARC models: one trained on mean  $\mathcal{C}_{(-k)}$ , one on STAPLE fusion of same three masks. Identical inputs/architecture/loss. Evaluated against respective targets.

Result: Mean: Avg. Dice 0.9002,  $\rho$  0.7905; STAPLE: Avg. Dice 0.8992,  $\rho$  0.7491. Mean has higher sensitivity, STAPLE higher precision.

Supported conclusion: Mean consensus is sufficient and directly interpretable (fraction of supporting methods); trade-offs exist but mean is preferred for primary evaluation.

Unsupported stronger conclusion: STAPLE is inferior (not supported; models evaluated on different targets, so no cross-target accuracy claim) [Paper: PDF p. 5].

Source: Section 4.3 [Paper: PDF p. 5]

Experiment: Qualitative analysis (Figure 4)

Claim tested: MARC localises weakly supported regions and produces spatially varying predictions aligned with biological evidence.

Comparison and conditions: Visual inspection of predicted  $\hat{\mathcal{C}}_k$  and cell-level maps on held-out test region, overlaid with DAPI,  $\mathcal{T}$ ,  $\mathcal{F}_k$ .

Result: High  $\hat{\mathcal{C}}_k$  where candidate aligns with nuclear morphology & transcript density & cross-method support; low  $\hat{\mathcal{C}}_k$  where candidate extends into background or disagrees with evidence.

Supported conclusion: MARC captures contextual agreement, enabling identification of ambiguous cells for review.

Unsupported stronger conclusion: MARC's spatial predictions are causally explained by morphology/transcripts (not established; correlation shown, not mechanism) [Paper: PDF p. 7].

Source: Figure 4, Section 4.4 [Paper: PDF p. 6-7]

## 11 对结论的正确理解

- MARC approximates explicit multi-method consensus, not biological ground truth; its success is measured relative to the consensus surrogate, not absolute boundary correctness [Paper: PDF p. 1, 7].
- The high Dice (0.9002) means MARC's predicted foreground closely overlaps the leave-one-method-out mean consensus foreground, not that it recovers true cell boundaries [Paper: PDF p. 4-5].
- Cell-level Spearman  $\rho = 0.7905$  indicates MARC preserves the ranking order of candidate cells by their consensus support (e.g., top 10% lowest-scoring cells are indeed those with weakest multi-method agreement), enabling prioritisation for review-not that absolute score values are calibrated probabilities [Paper: PDF p. 5].
- Input ablations confirm DAPI and transcripts are complementary to candidate geometry, but do not prove they resolve specific biological ambiguities (e.g., mitotic cells, doublets); they improve statistical agreement with consensus [Paper: PDF p. 5-6].
- "Consensus-aware evaluation" means using MARC's output scores for QC decisions (e.g., filtering low- $SS_{\{k,c\}}$  cells), not that MARC itself performs segmentation [Paper: PDF p. 1, 5].

## 12 作者明确承认的限制

Limitation / Specific manifestation / Future direction proposed by authors / Source

Limitation: Consensus as surrogate, not ground truth

Specific manifestation: Failure modes common across segmentation methods may be reinforced in consensus, making it an imperfect proxy.

Future direction proposed by authors: Acknowledge utility despite limitation: "such a surrogate is useful because it captures agreement across multiple methods... reducing reliance on any single method's biases."

Source: [Paper: PDF p. 7]

Limitation: Limited generalisability

Specific manifestation: Evaluation conducted on single Xenium renal cell carcinoma dataset; candidate methods share inputs from same assay, reducing independence.

Future direction proposed by authors: Future work: "evaluate additional tissues, platforms, and segmentation methods, incorporate orthogonal membrane or protein markers for validation, and determine whether consensus-guided filtering improves downstream analyses."

Source: [Paper: PDF p. 7]

## 13 批判性分析

[Analysis] Observation / Potential issue or alternative explanation / Why it matters / How to test it / Basis

[Analysis] Observation: MARC's training relies on leave-one-method-out consensus  $SC_{\{-k\}}$ , which assumes errors of the  $SK-1$  methods are independent and uncorrelated. However, all four candidate methods (Cellpose-SAM, BIDCell, ProSeg, Xenium) operate on the same underlying Xenium assay data and likely share systematic biases (e.g., resolution limits, probe efficiency artifacts).

Potential issue or alternative explanation: If methods share correlated failure modes (e.g., all miss boundaries in low-DAPI regions),  $SC_{\{-k\}}$  may reinforce those errors rather than average them out, making MARC learn to reproduce shared hallucinations. This undermines the "surrogate truth" assumption.

Why it matters: Compromises validity of MARC's pseudo-supervision: high Dice against  $SC_{\{-k\}}$  may reflect agreement on wrong boundaries, not accurate consensus. Impacts trust in

low- $S_{\{k,c\}}$  cells flagged for review.

How to test it: Train MARC on datasets with truly orthogonal inputs (e.g., Xenium + MERFISH + seqFISH+), or inject controlled synthetic errors into one method and measure MARC's sensitivity to breaking consensus. Compare MARC's low-score cells against orthogonal validation (e.g., membrane stains).

Basis: Authors state "candidate methods also share inputs from the same Xenium assay and are therefore not fully independent" [Paper: PDF p. 7]; consensus literature notes correlated raters bias STAPLE-like estimates [21].

[Analysis] Observation: The Foreground-Union Consensus Loss (FUCL) excludes background pixels ( $U_k=0$ ) from gradient updates. While this focuses learning, it may cause MARC to ignore contextual cues outside the foreground that help resolve boundary ambiguity (e.g., transcript deserts adjacent to a cell may indicate a sharp boundary).

Potential issue or alternative explanation: Background regions contain discriminative information for boundary refinement (e.g., intensity gradients, neighbor cell proximity). Ignoring them could limit MARC's ability to correct over-segmentation where candidate  $F_k$  bleeds into low-signal background.

Why it matters: May explain why precision (0.8843) lags sensitivity (0.9168) in Table 1-MARC is good at recalling consensus foreground but less precise at excluding false positives near boundaries.

How to test it: Modify FUCL to include a weighted background term (e.g., inverse distance to nearest foreground pixel) or train with a hybrid loss (FUCL + background-aware auxiliary task). Measure precision/sensitivity trade-off.

Basis: FUCL definition explicitly restricts loss to  $U_k$  [Eq. 7, Paper: PDF p. 4]; Section 4.2 notes thresholding at 0.5 corresponds to "majority of other three methods" [Paper: PDF p. 5], implying binary treatment of support.

[Analysis] Observation: Cell-level aggregation (Eq. 8) computes simple mean of  $\hat{C}_k$  over cell pixels. This treats all pixels equally, but boundary pixels are more informative for consensus than cell interior pixels (where all methods likely agree).

Potential issue or alternative explanation: Uniform averaging dilutes boundary disagreement signals. A cell with high interior consensus but low boundary consensus may receive a misleadingly high  $S_{\{k,c\}}$ , masking its segmentation ambiguity.

Why it matters: Reduces utility for QC: cells needing review may be missed if ambiguity is localized to boundaries. Contradicts goal of "localis[ing] weakly supported regions" [Paper: PDF p. 7].

How to test it: Replace mean with boundary-weighted average (e.g., using morphological gradient of  $F_k$  as weight) or compute separate interior/boundary scores. Correlate new score with manual boundary error rates.

Basis: Figure 4 shows spatially varying  $\hat{C}_k$  predictions, including low values at boundaries [Paper: PDF p. 6-7]; Eq. 8 specifies uniform mean [Paper: PDF p. 5].

## 14 学到的知识

- In SST, consensus among complementary segmentation methods is a pragmatic, scalable surrogate for ground truth, especially when manual annotation is infeasible and boundaries are biologically ambiguous [Paper: PDF p. 1, 7].
- Dense regression of consensus support (rather than segmentation or uncertainty estimation) is a viable QC paradigm, enabling inference-time efficiency and spatially resolved quality maps [Paper: PDF p. 2, 5].
- Morphology (DAPI) is the dominant contextual signal for cell-level ranking, while transcript density provides complementary molecular information, jointly boosting both pixel-level consensus prediction and cell-level Spearman correlation [Paper: PDF p. 5-6, Table 2].
- Foreground-union masking for loss computation effectively focuses training on biologically relevant regions (foreground + disagreements) and avoids background noise dilution [Paper: PDF p. 4, Eq. 7].

- Leave-one-method-out pseudo-supervision prevents trivial self-agreement and enables learning from ensemble disagreement without requiring ensemble execution at inference [Paper: PDF p. 3].

## 15 与既有知识的连接

- single-cell foundation models: Weak connection/methodological connection. MARC does not build or use foundation models; it's a task-specific regression model. However, its use of multi-modal inputs (morphology + transcripts) aligns with foundation model goals of cross-modal integration, and its consensus-aware design could inspire foundation model evaluation protocols.
- spatial transcriptomics: Direct domain application. MARC addresses the core SST bottleneck of cell segmentation QC, specifically for subcellular resolution (Xenium), leveraging spatially aligned DAPI and transcript density-core SST data modalities [Paper: PDF p. 1, 5].
- graph neural networks: Weak connection. GNNs are used in some SST segmentation methods (e.g., Baysor [3]), but MARC is CNN-based (U-Net) and makes no use of graph structures. No GNN component or motivation is present.
- multi-omics: Methodological connection. MARC fuses imaging (DAPI) and molecular (transcript density) data-a minimal multi-omics setup-demonstrating that even two modalities yield significant gains over single-modality baselines [Paper: PDF p. 5-6].
- biomedical AI: Direct application. MARC is a biomedical AI tool for quality control in computational pathology, following best practices: clear problem framing, ablation studies, quantitative benchmarks, and qualitative validation [Paper: PDF p. 1-7].
- perturbation prediction / cell state representation / cross-modal alignment: Weak connection. MARC does not predict perturbations, model cell states, or perform cross-modal alignment (e.g., image-to-RNA mapping); it uses pre-aligned inputs for consensus regression. Selection note confirms “未显式建模cell state或跨模态对齐” [Selection reason].

## 16 研究想法

- name: Consensus-Guided Boundary Refinement (CGBR)

originating limitation/observation: MARC outputs spatially varying consensus support  $\hat{C}_k$  but does not use it to refine the candidate segmentation; low- $\hat{C}_k$  boundary pixels indicate ambiguity needing correction [Paper: PDF p. 6-7, Fig 4].

core hypothesis: Integrating MARC's pixel-level  $\hat{C}_k$  as a spatial attention mask into a segmentation refinement module will improve boundary accuracy more than post-hoc filtering.

delta from paper: MARC is a QC tool; CGBR repurposes its output as a trainable guidance signal for segmentation correction, moving from evaluation to improvement.

initial method: Augment a lightweight U-Net refinement head that takes  $(D, T, F_k, \hat{C}_k)$  and outputs a refined mask  $F_k^{\text{ref}}$ ; supervise with Dice loss against  $C_{(-k)}$  or orthogonal ground truth.

validation: Compare  $F_k^{\text{ref}}$  vs original  $F_k$  on boundary F1-score against membrane stain validation; measure downstream impact on cell-type annotation consistency.

failure modes: Over-correction where  $\hat{C}_k$  is noisy; failure to generalise to unseen tissue types.

innovation status: unverified

- name: Orthogonal Consensus Validation (OCV)

originating limitation/observation: Authors acknowledge consensus is a surrogate and candidate methods are not fully independent due to shared Xenium assay inputs [Paper: PDF p. 7]; this risks reinforcing correlated errors.

core hypothesis: Introducing an orthogonal modality (e.g., immunofluorescence membrane marker) as an independent consensus anchor will break error correlations and yield a more robust surrogate.

delta from paper: Replaces leave-one-method-out consensus with leave-one-modality-out consensus (e.g.,  $C_{(-\text{membrane})}$  = mean of DAPI-based, transcript-based, and morphology-transcript fusion methods).

initial method: Acquire membrane stain for subset of Xenium tiles; train MARC variants with membrane-informed  $C_{(-k)}$  targets; compare Dice/p against membrane-ground-truth boundaries.

validation: Quantify reduction in shared failure modes (e.g., via disagreement heatmaps); test generalisability to new tissues lacking membrane stain.

failure modes: Membrane stain misalignment; limited availability of high-quality orthogonal markers.

innovation status: unverified

- name: Boundary-Weighted Consensus Scoring (BWCS)

originating limitation/observation: Cell-level aggregation (Eq. 8) uses uniform mean, diluting boundary disagreement signals critical for QC [Analysis in 13].

core hypothesis: Weighting  $\hat{C}_k$  pixels by their distance to the candidate cell boundary (e.g., morphological gradient magnitude) will produce cell scores more sensitive to segmentation ambiguity.

delta from paper: Modifies Eq. 8 to  $SS_{k,c}^{\text{BW}} = \frac{\sum_{(x,y) \in c} w(x,y) \cdot \hat{C}_k(x,y)}{\sum_{(x,y) \in c} w(x,y)}$ , where  $w$  peaks at boundaries.

initial method: Compute  $w$  from Sobel gradient of  $F_k$ ; recompute cell scores on test set; correlate new scores with manual boundary error counts.

validation: Compare AUROC of  $SS_{k,c}^{\text{BW}}$  vs  $SS_{k,c}$  for detecting manually corrected cells; assess ranking stability under segmentation perturbations.

failure modes: Gradient computation sensitive to  $F_k$  noise; weights may over-prioritise irrelevant texture.

innovation status: unverified