

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: discovery
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Rethinking Class Imbalance for Single-Cell Foundation Models: A Systematic Benchmark Across Architectures and Long-Tail Loss Functions	[Paper] [Paper: PDF p. 1]
Authors	Zeyu Dong, Jiahui Zhong	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
URL	http://arxiv.org/abs/2609.23325v1	[Paper meta]
PDF URL	https://arxiv.org/pdf/2609.23325v1	[Paper meta]
Publication date	2026-09-20	[Paper meta]
Code availability	https://github.com/jz890/sc-imbalance	[Paper] [Paper: PDF p. 7]
Backbones evaluated	scGPT, scBERT, Geneformer	[Paper] [Paper: PDF p. 3]
Datasets	Multiple Sclerosis (MS), Zheng68K, human Pancreas	[Paper] [Paper: PDF p. 3]
Loss functions benchmarked	Cross-entropy (CE), weighted CE, class-balanced loss, focal loss, LDAM, logit-adjusted softmax	[Paper] [Paper: PDF p. 3]
Total runs	162 (3 backbones × 3 datasets × 6 losses × 3 seeds)	[Paper] [Paper: PDF p. 1]
Key metrics	Macro-F1, rare-class recall (Recall _R), rare-class precision, rare-class macro-AUPRC, Δ F1 _c , NC1	[Paper] [Paper: PDF p. 3–6]

02 一句话总结

该论文系统评测了六种长尾损失函数在三种单细胞基础模型（scGPT/scBERT/Geneformer）和三个真实数据集（MS/Zheng68K/Pancreas）上的表现，发现整体准确率严重掩盖罕见细胞类别的系统性失败；这种失败可划分为两类机制：一类是“损失敏感型”（loss-sensitive），其性能可通过重加权类损失显著提升，且提升幅度由绝对训练样本数而非相对频率决定；另一类是“严重纠缠型”（severely entangled），即使更换所有损失函数

与架构，仍因嵌入几何结构缺陷（如邻域吸收、高NC1）而无法恢复，需通过线性探针验证信号是否尚存。该工作作为scFM在疾病相关稀有细胞建模中提供了首个机制驱动的损失选择指南。

03 研究问题

论文直面一个被广泛忽视但临床关键的矛盾：单细胞基础模型（scFM）在细胞类型分类任务中报告高达97.5%的总体准确率，却对罕见、常具疾病意义的细胞亚群（如MS中的oligodendrocyte C、phagocyte）持续失效——而这些失效恰恰是长尾损失函数本应解决的核心问题。作者追问：（1）这种失效是模型预训练固有缺陷，还是数据结构或损失设计导致？（2）不同长尾损失函数在跨架构、跨数据集场景下的鲁棒性是否存在可预测的排序？（3）失效是否具有可诊断的几何表征？能否据此提前识别哪些罕见类“可救”、哪些“不可救”？（4）若可救，什么因素决定某类从重加权中获益的程度？这些问题共同指向一个更深层目标：将scFM长尾问题从经验调参层面，推进至机制可解释、证据可追溯、决策可指导的科学评估范式。

04 研究背景与发展路径

单细胞基础模型（scGPT/scBERT/Geneformer等）已成为细胞注释默认主干，但其高聚合准确率被证实由常见细胞主导，罕见细胞（如病理过渡态、早期病变亚群）常被系统性忽略 [Paper] [Paper: PDF p. 1]。此前工作已识别该现象：Alsabbagh et al. (2023) 在采样策略层面尝试缓解，Naziri et al. (2025) 揭示疾病亚组性能断崖式下降，Al Amin et al. (2025) 指出人口统计学不平衡亦有影响 [Paper] [Paper: PDF p. 1–2]。然而，损失函数这一核心干预轴尚未被系统检验——现有研究或聚焦特定新损失（Zhao et al. 2025）、或耦合采样与模型修改（Cheng et al. 2023）、或采用非标准协议（如冻结编码器+多专家头）[Paper] [Paper: PDF p. 2]。本文承接此空白，将长尾学习经典方法（Cui et al. 2019; Cao et al. 2019; Menon et al. 2021）首次完整迁移到scFM场景，严格控制变量（固定数据划分、批大小、优化器、微调协议），仅改变损失函数，从而隔离其独立效应。路径上，它从“是否有效”（Section 4）跃迁至“为何有效/无效”（Section 5），引入神经坍塌（neural collapse）理论与嵌入几何分析，将性能差异锚定到可计算的几何量（NC1、最近邻熵、UMAP空间吸收模式），完成从现象描述到机制诊断的闭环。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Aggregate metrics mask rare-class failure	Overall accuracy > Macro-F1 > rare-class recall across all 9 (backbone, dataset) settings [Paper] [Paper: PDF p. 3]	Driven by dataset imbalance structure, not pretraining artifacts [Paper] [Paper: PDF p. 1, 3]	Figure 2 (left): consistent gap under plain CE; text states “this gap is present regardless of which foundation model is used” [Paper] [Paper: PDF p. 3]
Loss-level interventions are insufficient for some rare classes	Two MS classes (oligodendrocyte C, phagocyte) achieve near-zero F1 under <i>all</i> six losses and <i>all</i> three backbones [Paper] [Paper: PDF p. 5]	Too few training examples (n=3 each) to learn distinguishable representation; failure persists even in non-foundation baselines (5-NN, RF) [Paper] [Paper: PDF p. 5]	Figure 3 (left): darkest rows across all columns; Section 5.1: “both have only 3 training examples” ; Table 1: CE F1 for these classes ≈ 0 [Paper] [Paper: PDF p. 5]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Reweighting benefit is misattributed to relative frequency	Weighted CE performs best on MS but worst on Zheng68K despite similar imbalance ratios [Paper] [Paper: PDF p. 4]	Benefit is predicted by <i>absolute</i> training-set size of rare class, not its share of dataset or global imbalance ratio [Paper] [Paper: PDF p. 1, 4]	Figure 3 (right): strong negative correlation ($r=-0.77$) between $\log(\text{training size})$ and $\Delta F1_{_c}$; MS rare classes have smallest absolute counts [Paper] [Paper: PDF p. 4]
Loss functions make hidden trade-offs obscured by Macro-F1	Logit adjustment boosts rare recall but incurs largest precision penalty among all six losses [Paper] [Paper: PDF p. 4]	It shifts decision thresholds rather than improving feature separability, leading to more false positives [Paper] [Paper: PDF p. 4]	Figure 2 (right): logit-adjusted point lies far below $y=x$ line; text: “lowest rare-class precision of all six losses” [Paper] [Paper: PDF p. 4]

06 核心思想

论文的核心思想是：**单细胞基础模型的长尾失效并非单一问题，而是由两种根本不同的机制驱动的双轨现象，必须用不同工具诊断与应对**。第一轨是“损失敏感型”失效：其根源在于标准交叉熵损失对小样本类的梯度压制，可通过重加权类损失（如class-balanced loss）有效缓解；关键洞见是，此类缓解效果不取决于“该类占多少比例”，而取决于“该类有多少个细胞”——绝对样本数越少，重加权增益越大（Figure 3右）。第二轨是“严重纠缠型”失效：其根源是极低样本数（ $n=3$ ）导致嵌入空间中该类无法形成可分离簇，反而被吸收进邻近类的几何邻域（Figure 4），此时更换任何损失函数均无效；但线性探针证明判别信号仍存在于冻结嵌入中（Section 5.3），说明瓶颈在分类器训练而非表示坍塌，提示需转向解耦式校准（如Kang et al. 2020）或拒绝选项（reject-option）。这一双轨框架将经验性“试错调参”升维为基于几何证据（NC1、最近邻熵）和统计证据（ $\Delta F1$ vs. $\log(\text{size})$ ）的理性决策流程。

07 方法总览

论文采用“控制变量+多维诊断”方法论：在162次受控训练中，固定所有超参数（学习率、批大小、优化器、微调协议、基因面板），仅系统替换损失函数，以纯净地量化损失效应。评估维度分三层：（1）**聚合层**：报告Macro-F1与Rare-class Recall（Eq. 1-2），揭示指标失真；（2）**细粒度层**：计算每类 $\Delta F1_{_c}$ （Eq. 3）并关联其训练样本数，定位可修复类；（3）**机制层**：对失效类进行嵌入几何分析——用NC1（Eq. 4）量化类内/类间散度，用UMAP可视化（Figure 4）与最近邻熵刻画吸收模式，并用线性探针（Section 5.3）区分“信号缺失”与“信号未利用”。整个方法链路清晰：从宏观性能差异（Fig 2）→ 到中观类级响应（Fig 3）→ 再到微观几何归因（Fig 4, Eq. 4），最终导向实践指南（Section 6）。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Loss-function grid	Systematically evaluates 6 long-tail losses (CE, weighted CE, class-balanced, focal, LDAM, logit-adjusted) across all backbone-dataset combinations	Isolates loss effect from architecture/data confounders; tests off-the-shelf robustness of general-purpose losses	Input: logits + true labels; Output: scalar loss value per sample	Table 1 reports full results; Section 4.2 ranks losses by mean position across 9 cells [Paper] [Paper: PDF p. 3–4]	Without this grid, no cross-architecture comparison possible; conclusions about "most consistent" losses (class-balanced/LDAM) vanish [Analysis]
Rare-class definition & metric suite	Defines rare class as training frequency <5%; computes $\text{Recall}_{R>0.5}(\ell)$ (Eq. 2), rare-precision, rare-macro-AUPRC	Exposes aggregate metric blindness; AUPRC avoids threshold-commitment bias inherent in F1	Input: test predictions & labels; Output: scalar per metric	Figure 2 (right) plots precision vs. recall; Table 1 includes AUPRC; text notes logit adjustment's AUPRC weakness despite F1 strength [Paper] [Paper: PDF p. 3–4]	Using only accuracy/Macro-F1 would hide logit adjustment's precision-recall trade-off [Paper] [Paper: PDF p. 4]
Per-class $\Delta F1_{c \in L}$ analysis	Computes $\max_{\ell \in L} F1_{\ell, c} - F1_{\ell, c}(\text{CE})$ (Eq. 3) for each rare class c	Tests hypothesis that reweighting benefit depends on absolute sample count, not relative frequency	Input: per-class F1 scores across all losses/seeds/backbones; Output: $\Delta F1_{c \in L}$ vector	Figure 3 (right) shows strong negative correlation ($r=-0.77$) with $\log(\text{training size})$; text states "reintroducing severely entangled classes yields weaker but still significant correlation" [Paper] [Paper: PDF p. 4]	Removing this analysis would leave the key insight ("absolute count predicts gain") unsupported; MS vs. Zheng68K performance difference remains unexplained [Analysis]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Embedding geometry diagnostics	Computes NC1 (Eq. 4), nearest-neighbor confusion entropy, UMAP visualization (Figure 4), linear probe on frozen embeddings	Distinguishes two failure regimes: “loss-sensitive” (fixable) vs. “severely entangled” (geometrically rooted)	Input: frozen test-set embeddings + labels; Output: NC1 scalar, entropy, probe F1	Figure 4 shows absorption in UMAP; Section 5.2 reports NC1 values (e.g., oligodendrocyte C: 1.19–1.79); Section 5.3 shows probe F1 > trained F1 for entangled classes [Paper] [Paper: PDF p. 5–7]	Without geometry analysis, the “severely entangled” regime would be misattributed to loss choice; no basis for recommending data collection over loss engineering [Paper] [Paper: PDF p. 6]

09 关键公式与符号

- **No verifiable closed-form equations** are presented in the paper. All listed equations are definitions or computational summaries:
- Equation 1: $\text{Macro-F1} = \frac{1}{|C|} \sum_{c=1}^{|C|} F1_c$ — definition of unweighted mean F1 across $|C|$ classes [Paper] [Paper: PDF p. 3]
- Equation 2: $\text{Rare-class recall} = \frac{1}{|R|} \sum_{c \in R} \text{Recall}_c$ — definition of macro-averaged recall over rare class set R [Paper] [Paper: PDF p. 3]
- Equation 3: $\Delta F1_c = \max_{\ell \in L} F1^{\ell}_c - F1^{(CE)}_c$ — definition of per-class F1 gain from best loss over CE [Paper] [Paper: PDF p. 4]
- Equation 4: $NC1 = \frac{\text{tr}(\Sigma_W)}{\text{tr}(\Sigma_B)}$ — neural collapse trace ratio, where Σ_W is average within-class scatter, Σ_B is between-class scatter of centroids [Paper] [Paper: PDF p. 6]
- **Key symbols/variables:**
 - R : set of rare classes (training frequency <5%) [Paper] [Paper: PDF p. 3]
 - $F1_c$: F1 score of class c [Paper] [Paper: PDF p. 3]
 - ℓ : loss function from set L (6 total) [Paper] [Paper: PDF p. 4]
 - Σ_W , Σ_B : within-class and between-class scatter matrices for NC1 computation [Paper] [Paper: PDF p. 6]
 - $NC1$: neural collapse indicator (lower = better separation) [Paper] [Paper: PDF p. 6]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Aggregate metric gap (Fig 2 left)	Plain CE produces consistent gap: Accuracy > Macro-F1 > Rare-recall across all architectures/datasets	Mean of 9 backbone × seed runs per dataset bar; same train/test splits, hyperparameters	Gap present in all 3 datasets, regardless of backbone (e.g., scBERT MS CE Macro-F1=0.639) [Paper] [Paper: PDF p. 3]	Gap is inherent to data imbalance structure, not backbone-specific artifact	That pretraining has <i>no</i> role — authors note variance vs. Alsabbagh et al. arises from config differences [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 3], Figure 2 (left)
Loss ranking (Table 1)	Class-balanced loss and LDAM are most consistent across 9 (backbone, dataset) cells	Rankings computed within each (backbone, dataset) cell before averaging; mean rank over 9 cells	Class-balanced: mean rank 2.4; LDAM: 2.6; both outperform others in consistency [Paper] [Paper: PDF p. 3]	These two losses offer best general-purpose robustness for scFM long-tail tasks	That they are universally optimal — e.g., weighted CE beats them on MS Macro-F1 [Paper] [Paper: PDF p. 3]	[Paper] [Paper: PDF p. 3], Table 1
$\Delta F1$ vs. training size (Fig 3 right)	Reweight benefit ($\Delta F1_{\text{sub}} < \Delta F1_{\text{sup}}$) is predicted by absolute training-set size, not relative frequency	Pearson correlation of $\log(\text{training size})$ with $\Delta F1_{\text{sub}} < \Delta F1_{\text{sup}}$ across 19 recoverable rare classes	Strong negative correlation ($r = -0.77$, $p < 0.001$); robust to exclusion thresholds [Paper] [Paper: PDF p. 4]	Absolute sample count is the primary predictor of reweighting efficacy in scFM	That relative frequency is irrelevant — authors test multiple cutoffs and find trend holds [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 3 (right)
Logit adjustment trade-off (Fig 2 right)	Logit adjustment trades rare-class precision for recall	Plot of rare-precision vs. rare-recall for all 6 losses, averaged over 9 settings	Logit-adjusted point lies far below $y=x$ line; lowest precision, highest recall gain among losses [Paper] [Paper: PDF p. 4]	Its recall gains stem from threshold shift, not improved separability	That it harms non-rare classes — text notes their precision/recall spreads are small (1.1/2.1 pts) [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 4], Figure 2 (right)

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Linear probe on frozen embeddings (Sec 5.3)	Severely entangled classes retain discriminative signal unused by trained classifiers	Logistic regression probe on CE-fine-tuned frozen embeddings, 5-fold CV	Probe F1 exceeds best trained F1 for oligodendrocyte C/phagocyte (e.g., scGPT: 0.465 vs. 0.329); smaller margin for microglial cell [Paper] [Paper: PDF p. 6]	Bottleneck is classifier training, not representation collapse	That a nonlinear probe would close the gap — authors explicitly state this as future work [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 6], Section 5.3

11 对结论的正确理解

论文结论必须置于其严格控制的实验边界内理解：（1）“Class-balanced loss and LDAM are most consistent”指在**所测试的6种损失、3种架构、3个数据集、3个随机种子**条件下，其平均排名最高，**不意味着它们在所有可能损失或新数据集上最优**；（2）“Reweighting benefit predicted by absolute size”是针对**可修复的罕见类**（即排除4个严重纠缠类后n=19的回归），**不否定相对频率在其他场景（如采样策略）的作用**；（3）“Severely entangled classes are unrecoverable by loss choice”特指**本文评估的6种损失及3种架构**，**不排除未来设计的新损失（如结合几何约束的损失）能缓解**；（4）“Signal exists in frozen embeddings”由线性探针证实，**但该信号是否足够支持高精度临床决策，未被验证**；（5）所有结论基于**细胞类型分类任务**，**不直接推广至cell state representation、perturbation prediction或cross-modal alignment等用户研究方向**，属弱连接/方法论连接。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited backbone coverage	Only scGPT, scBERT, Geneformer evaluated; other models (scFoundation, CellPLM) remain untested	“Other existing single-cell foundation models, such as scFoundation and CellPLM [...] remain untested” [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]
Classifier head expressivity	Linear probe recovers signal unused by trained heads, suggesting current losses may not fully exploit discriminative capacity	“A more expressive, nonlinear classifier head might extract additional signal beyond what the six losses we test currently achieve” [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]

Limitation	Specific manifestation	Future direction proposed by authors	Source
Isolated imbalance axis	Study focuses solely on cell-type class imbalance; ignores compounding variables like demographic composition or batch effects	“Compounding variables such as demographic composition [...] or batch effects [...] require future investigation” [Paper] [Paper: PDF p. 7]	[Paper] [Paper: PDF p. 7]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
NC1 interpretation conflates scarcity and geometry	Phagocyte’ s low NC1 (0.17–0.32) is attributed to tight clustering inside another class, but could also reflect high intra-class homogeneity due to biological uniformity (e.g., all phagocytes ingest identical myelin fragments) rather than data scarcity	Misattribution could lead to wrong intervention (e.g., collecting more phagocyte samples when biology dictates uniformity)	Compute NC1 on synthetic phagocyte-like clusters with controlled homogeneity vs. scarcity; compare to real data	[Paper] [Paper: PDF p. 6]: “its small cell count means a handful of tightly clustered cells embedded inside another class’ s region can produce low within-class scatter” — this is an <i>assumption</i> , not proven
Linear probe uses same embeddings as trained head, but different optimization	Probe uses stratified CV on frozen embeddings, while trained head uses end-to-end fine-tuning with gradient updates — the gap may reflect optimization difficulty (e.g., vanishing gradients for rare classes) rather than loss design flaw	If true, focus should shift to optimizer modifications (e.g., rare-class-specific learning rates) rather than new loss functions	Replace linear probe with a shallow MLP head trained <i>only on frozen embeddings</i> (same loss, same optimizer) and compare F1 to full fine-tuning	[Paper] [Paper: PDF p. 6]: “Since the probe and the model’ s classifier head are fit on the same fine-tuned embeddings, this localizes the bottleneck to classifier training” — but training dynamics differ
Rare-class definition (<5%) is arbitrary and dataset-dependent	Using fixed 5% threshold ignores dataset-specific distributions (e.g., Zheng68K’ s smallest class has ~70 cells vs. MS’ s single digits); may misclassify “moderately rare” classes as common	Could dilute $\Delta F1$ correlations or mask finer-grained regimes (e.g., ultra-rare vs. moderately rare)	Repeat $\Delta F1$ analysis with adaptive thresholds (e.g., top-k rarest classes per dataset) and test correlation stability	[Paper] [Paper: PDF p. 3]: “A class is considered rare if its training-split frequency is below 5% per domain experience” — no justification for 5% or validation of its universality

14 学到的知识

- **指标陷阱警示**：Macro-F1和accuracy在长尾场景下具有欺骗性；必须强制报告**per-class metrics**（F1, recall, precision）和**threshold-free metrics**（AUPRC）才能暴露真实失效模式。
- **绝对数量优先**：在scFM微调中，罕见类的可修复性由其**绝对训练样本数**（而非占比或全局不平衡比）主导，这颠覆了传统长尾学习中“相对频率决定权重”的直觉，提示数据收集应聚焦于填补绝对空缺。
- **几何先于损失**：嵌入空间的几何属性（NC1、最近邻熵、UMAP吸收）可在训练前或训练初期诊断失效类型，是比盲目尝试损失函数更高效的调试路径。
- **损失即权衡**：长尾损失不是“增强器”，而是“调节器”——logit adjustment提升recall以牺牲precision为代价，class-balanced loss则平衡提升两者，选择需匹配下游任务成本（如漏诊vs误诊代价）。
- **信号存在 ≠ 可用**：线性探针证明，即使在严重纠缠类中，判别信号仍线性可分，说明当前损失函数家族未能充分激发该信号，为设计新损失（如几何感知损失）提供明确靶点。

15 与既有知识的连接

- **候选连接/方法论连接**：本文的“双轨失效”框架（loss-sensitive vs. severely entangled）与计算机视觉中“minority collapse”理论（Fang et al. 2021）形成呼应，但将其首次实证落地于单细胞领域，并赋予生物学解释（如phagocyte的myelin ingestion导致转录重叠）。
- **候选连接/方法论连接**：使用NC1量化嵌入几何，直接继承Papyan et al. (2020) 的神经坍塌理论，但创新性地将其应用于scFM长尾诊断，而非仅作为训练动态观察。
- **候选连接/方法论连接**：线性探针验证信号存在，延续Alain & Bengio (2017) 的probe范式，但将其用于区分“数据稀缺”与“损失设计不足”，拓展了probe在生物AI中的诊断价值。
- **候选连接/方法论连接**：强调绝对样本数而非相对频率，与Buda et al. (2018) 在CV中发现的“effective number of samples”框架一致，证实该规律跨模态稳健，但在scFM中首次量化验证。
- **弱连接/方法论连接**：虽未涉及spatial transcriptomics、graph neural networks或multi-omics，但其几何诊断方法（UMAP/NC1/nearest-neighbor）可直接迁移至空间转录组嵌入分析；其损失比较框架可扩展至多组学融合模型的模态不平衡处理。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Geometric-aware loss reweighting

originating limitation/observation: NC1 and nearest-neighbor entropy diagnose entanglement but current losses ignore geometry [Paper] [Paper: PDF p. 6]; linear probe shows signal exists but is unused [Paper] [Paper: PDF p. 6] **core hypothesis**: Incorporating NC1 and neighbor entropy into loss weighting (e.g., down-weighting classes with high NC1 or high absorption entropy) will improve recovery of severely entangled classes without harming others **delta from paper**: Replaces static class-frequency weights with dynamic geometry-aware weights computed from frozen embeddings **initial method**: For each class c , compute weight $w_c = \alpha \times \exp(-\beta \times \text{NC1}_c) + \gamma \times \exp(-\delta \times \text{entropy}_c)$; use w_c in class-balanced loss formulation **validation**: Train scGPT on MS with new loss; compare F1 for oligodendrocyte C/phagocyte vs. baseline class-balanced loss;

ablate α , β , γ , δ **failure modes**: Over-smoothing ($w_{c \rightarrow c} \rightarrow 0$ for all c) if β/δ too large; instability if NC1/entropy noisy on small n **innovation status**: unverified

- **name**: Entanglement-aware data augmentation

originating limitation/observation: Severely entangled classes have $n=3$ samples, causing geometric absorption [Paper] [Paper: PDF p. 5]; synthetic oversampling (Bej et al. 2021) is generic, not geometry-informed **core hypothesis**: Augmenting rare classes by interpolating toward their dominant confusion partners (e.g., phagocyte $\rightarrow$ oligodendrocyte A) will create geometrically plausible synthetic samples that break absorption **delta from paper**: Moves beyond random/synthetic oversampling to biologically grounded, geometry-targeted augmentation **initial method**: For phagocyte ($n=3$), generate 10 synthetic cells via convex combination with oligodendrocyte A centroid (weight 0.7) and phagocyte centroid (weight 0.3); add to training set **validation**: Compare F1 for phagocyte under augmented vs. non-augmented training with class-balanced loss; verify reduced absorption in UMAP (Figure 4) **failure modes**: Overfitting to interpolation direction; creating samples that reinforce wrong biology (e.g., if oligodendrocyte A is not true biological parent) **innovation status**: unverified

- **name**: Multi-loss ensemble for rare-class calibration

originating limitation/observation: Different losses trade precision/recall differently (Fig 2 right) [Paper] [Paper: PDF p. 4]; no single loss dominates all rare classes (Table 1) **core hypothesis**: Ensembling predictions from multiple losses (e.g., class-balanced for precision, logit-adjusted for recall) with class-specific gating will outperform any single loss on rare-class AUPRC **delta from paper**: Shifts from selecting one best loss to dynamically combining complementary losses per class **initial method**: Train 6 models (one per loss); for each rare class c , learn gating weights via logistic regression on validation set to maximize c 's F1; apply gated average at test time **validation**: Measure rare-class macro-AUPRC on MS test set; compare to best single loss (class-balanced: 0.734) **failure modes**: Gating overfits to validation set; increased inference latency; no guarantee of monotonic AUPRC improvement **innovation status**: unverified