

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper] [Paper: PDF p. 1]
Authors	Youngmin Chung, Ji Hun Ha, Andrew H. Song, et al.	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Code URL	https://github.com/NEXGEM/STP-Bench	[Paper] [Paper: PDF p. 2]
Data URL	Hugging Face: https://huggingface.co/datasets/nexgem/STP-Bench	[Paper] [Paper: PDF p. 37]
Core contribution	First large-scale, multi-platform, standardized benchmark for virtual ST models with unified PFM encoding, gene-level interpretability, and downstream biological utility evaluation	[Paper] [Paper: PDF p. 2–4]
Key datasets	STP-BENCH-INTERNAL (609,024 spots, 6 cancer types, Visium/Xenium); STP-BENCH-EXTERNAL (185,831 spots, 6 cancer types)	[Paper] [Paper: PDF p. 4–5], [Figure 1b]
Evaluated models	21 models across regression (n=14), bi-modal retrieval (n=4), generative (n=3) families	[Paper] [Paper: PDF p. 6], [Figure 1c]
Primary metric	Pearson Correlation Coefficient (PCC) per gene, averaged across spots → sections → folds	[Paper] [Paper: PDF p. 31], [Equation 1]

02 一句话总结

该论文构建了STP-BENCH——首个面向虚拟空间转录组学（virtual ST）的统一、大规模、多平台系统性基准，覆盖Visium与Xenium两种主流ST技术平台及六种癌症类型；其核心创新在于强制统一病理基础模型

（PFM）作为图像编码器，从而解耦模型架构与图像表征能力，揭示多数现有模型未超越线性探针基线的本质问题；同时首次系统评估基因级可预测性、通路级恢复能力、细胞类型去卷积与空间结构识别等下游生物学效用，并量化跨机构/组织/平台泛化鲁棒性。该工作不提出新模型，而是为single-cell foundation models、spatial transcriptomics和multi-omics建模提供可复现、可归因、可迁移的评估基础设施。

03 研究问题

虚拟ST领域缺乏公平、可控、可复现的基准：既有评估依赖小规模异质数据集、不一致训练/推理流程、未标准化图像编码器，导致模型性能差异无法归因于架构本身；更关键的是，评估长期局限于整体基因相关性，忽视哪些基因/通路真正可从形态学推断、预测结果能否支撑下游生物学分析（如细胞组成、空间域识别）、以及模型在真实分布偏移下的可靠性。因此，研究问题聚焦于：**如何构建一个能分离“图像编码能力”与“模型架构能力”的标准化基准，并系统刻画虚拟ST在分子、细胞、组织多尺度上的可解释性边界与泛化极限？**

04 研究背景与发展路径

虚拟ST起源于ST实验成本高昂的现实约束，早期以ST-Net为代表采用CNN回归框架；随后演进为三类范式：(1) 回归式（引入邻域上下文、多尺度、示例集、文本先验）；(2) 双模态对齐式（CLIP范式，学习形态-表达联合嵌入空间）；(3) 生成式（扩散/流匹配建模联合分布）。所有范式均日益依赖病理基础模型（PFM）提取形态特征，但此前评估中各模型沿用原生编码器（ResNet/ImageNet预训练/自建CNN），造成架构贡献与编码器贡献严重混淆。Wang et al. 2024仅用原生编码器评估两套Visium数据，而HEST-1K虽规模大却仅用PFM嵌入+简单回归器测试，未覆盖完整模型谱系。STP-BENCH正是在此断裂处切入：它不延续单点改进，而是重构评估范式——将PFM作为“公共接口”，使21种模型在相同形态语义输入下竞争，从而暴露架构的真实增量价值。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
评估不公平性	模型排名随编码器切换剧烈变动（如CFANet从第16跃至第6）；多数模型未超UNiv2线性探针基线	原有评估混杂了图像编码器差异（预训练域/规模/范式）与模型架构差异，导致性能提升归属错误	[Paper] [Paper: PDF p. 9], [Figure 2b], [Paper] [Paper: PDF p. 18]
生物学效用黑箱	预测结果是否保留细胞类型丰度、空间结构等高阶生物信号未知	仅报告基因级PCC无法验证下游任务可行性；既往工作未在统一框架下测试Cell2location/SpaGCN等工具	[Paper] [Paper: PDF p. 14], [Figure 4a-c], [Paper] [Paper: PDF p. 19]
基因级可预测性模糊	HMHVG与TME标记基因预测性能差距达2×（PCC≈0.4 vs ≈0.2），但成因不明	数据稀疏性主导（Xenium高计数时两者PCC均≈0.58）而非形态学不可解；低表达基因信噪比低，放大预测误差	[Paper] [Paper: PDF p. 9-10], [Figure 2c-d], [Paper] [Paper: PDF p. 19]
泛化机制不透明	跨组织泛化性能下降远超跨机构（gap -0.35 vs -0.1），但原因未解析	组织特异性形态-表达映射强于技术批次效应；简单多癌种数据融合反而引发负迁移	[Paper] [Paper: PDF p. 17], [Figure 5b], [Paper] [Paper: PDF p. 19]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
平台依赖性未量化	Xenium与Visium数据质量差异对预测上限的影响无定量证据	Xenium更高灵敏度与转录本计数直接提升所有模型PCC，且下游任务性能同步提升，证明数据质量是共享瓶颈	[Paper] [Paper: PDF p. 10], [Figure 2c–d], [Paper] [Paper: PDF p. 14], [Paper] [Paper: PDF p. 19]

06 核心思想

论文的核心思想是：**虚拟ST的性能天花板由“形态学信息含量”与“数据质量”共同决定，而非单纯由模型复杂度驱动**；因此，评估必须解耦编码器与架构、穿透基因级可预测性、贯通下游生物学效用、并锚定真实世界分布偏移场景。这一思想体现为三大设计原则：(1) **强制统一PFM接口**——将UNIV2作为所有兼容模型的默认编码器，使架构比较在同一起跑线上；(2) **多粒度可解释性评估**——从单基因PCC热图→通路singscore→Cell2location丰度→SpaGCN空间域，形成证据链；(3) **鲁棒性压力测试**——定义Cross-Institution/Cross-Tissue/Cross-Platform三类泛化场景，量化gap并检验rank preservation。最终结论是：TRIPLEX/DeepSpot等多尺度架构的价值不在“绝对精度”，而在对stromal/immune等长程依赖基因的边际增益，这恰是single-cell foundation models需建模的关键跨尺度关联。

07 方法总览

STP-BENCH方法论是“评估即实验设计”：首先构建STP-BENCH-INTERNAL（609k spots, 6 cancers, 2 platforms）与STP-BENCH-EXTERNAL（186k spots, 6 cancers）双轨数据集，确保统计效力与泛化检验分离；其次对21个模型实施统一重实现，强制UNIV2编码（除架构不兼容者如M2OST/M2ORT）；接着执行三级评估：(1) **基础性能层**——HMHVG与16个TME标记基因的PCC/MAE/SSIM；(2) **生物学效用层**——Cell2location细胞丰度相关性、SpaGCN空间域ARI；(3) **鲁棒性层**——三类跨域泛化gap与data scaling（intra-/inter-cohort）分析。所有评估均基于spot-level配对（H&E patch ↔ ST spot），使用log1p归一化表达与标准增强流水线，确保可复现性。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Unified PFM Encoder (UNIV2)	Standardize morphological feature extraction across all compatible models	To isolate architectural contribution by eliminating encoder variability as confounder	Input: 224×224 H&E patch; Output: d-dim embedding vector	[Paper] [Paper: PDF p. 7–9], [Figure 2a,b,e], [Paper] [Paper: PDF p. 18]	Model rankings collapse (e.g., CFANet drops from 6th to 16th); most models fall below linear probe baseline [Paper] [Paper: PDF p. 9]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Gene-level Stratification Pipeline	Partition genes into predictability bins (Very Low to Very High) based on mean PCC across models	To test whether gene-level predictability is intrinsic (morphology-driven) rather than model-specific	Input: Gene-wise PCC matrix (genes $\times$ models); Output: 5 quantile bins	[Paper] [Paper: PDF p. 9], [Extended Data Fig. 1], [Figure 3a]	Loss of insight into universal predictability ceiling; inability to identify architecture-specific gains (e.g., TRIPLEX' s stromal gene advantage) [Paper] [Paper: PDF p. 11]
Downstream Biological Utility Layer	Apply Cell2location (cell abundance) and SpaGCN (spatial domains) to predicted expression matrices	To validate whether virtual ST preserves biologically meaningful structure beyond spot-level correlation	Input: Predicted spot $\times$ gene matrix; Output: Per-cell-type PCC (Cell2location), ARI (SpaGCN)	[Paper] [Paper: PDF p. 14–15], [Figure 4a–c], [Paper] [Paper: PDF p. 19]	Downstream performance decouples from gene-level PCC (e.g., STFlow low PCC but usable for deconvolution? Not assessed); no validation of clinical utility [Paper] [Paper: PDF p. 14]
Cross-Domain Generalization Framework	Define Cross-Institution (same cancer, different sites), Cross-Tissue (different cancers), Cross-Platform (Visium $\rightarrow$ Xenium) transfer tasks	To quantify real-world deployment reliability under technical/biological/platform shifts	Input: Model trained on INTERNAL; Output: PCC gap (EXTERNAL – INTERNAL) & Spearman ρ of rank preservation	[Paper] [Paper: PDF p. 17], [Figure 5a–b], [Paper] [Paper: PDF p. 19]	Inability to guide model selection for specific clinical settings (e.g., “use TRIPLEX for cross-tissue”); no mechanistic insight into why tissue shift hurts more than institution shift [Paper] [Paper: PDF p. 17]
Multi-Scale Morphological Reasoning (TRIPLEX/DeepSpot)	Integrate local patch + neighboring spots + whole-slide context (TRIPLEX) or spot/sub-spot/neighbor features (DeepSpot)	To capture long-range morphological dependencies (e.g., fibrosis gradients, immune fronts) invisible to local patches alone	Input: Local image embedding + neighbor embeddings + global slide embedding (TRIPLEX); Output: Gene expression vector	[Paper] [Paper: PDF p. 11, 19], [Figure 3b], [Paper: Online Methods p. 25–26]	Loss of marginal gain on stromal/immune genes (e.g., COL1A1, LAG3); gene set scores for T Cell Activation drop significantly [Paper] [Paper: PDF p. 11, 13]

09 关键公式与符号

论文未提出新公式，但明确定义并使用三个核心评估指标：

- **Pearson Correlation Coefficient (PCC):** $\text{PCC}_{g,s} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}}$ [Equation 1, Paper: PDF p. 31] —— 主要指标，计算每个基因 g 在切片 s 上预测 $\hat{y}$ 与真值 y 的线性相关性。
- **Mean Absolute Error (MAE):** $\text{MAE}_{g,s} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}|$ [Equation 2, Paper: PDF p. 32] —— 衡量预测误差绝对值，在log1p归一化空间计算。
- **Structural Similarity Index Measure (SSIM):** 使用 `skimage.metrics.structural_similarity` 计算，输入为二维空间网格上的预测/真值表达矩阵，考虑局部亮度、对比度与结构 [Paper] [Paper: PDF p. 32]。

关键符号：

- $\hat{y}_{i,g}, y_{i,g}$ $\$$: spot i 上 gene g 的预测/真值表达（log1p归一化）
- $\bar{\hat{y}}_g, \bar{y}_g$ $\$$: gene g 在所有spots上的预测/真值均值
- HMHVG: High-Mean Highly-Variable Genes (200 genes)
- TME markers: 16 tumor microenvironment marker genes (e.g., CD3E, ACTA2, PDCD1)
- PFM: Pathology Foundation Model (e.g., UNiv2, Virchow2)

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
UNiv2 vs native encoders	Unified PFM eliminates encoder confounding	Compare CFANet/HisToGene using native encoder vs UNiv2; same training protocol	CFANet jumps from 16th to 6th; HisToGene improves markedly	Encoder choice dominates reported architectural gains; prior comparisons are unfair	UNiv2 is universally optimal (not tested against all PFMs in all scenarios)	[Paper] [Paper: PDF p. 9], [Figure 2b]
HMHVG vs TME marker prediction	Performance gap stems from data sparsity, not morphology uncoupling	Evaluate both gene sets on NCCHE-LUAD-Xenium (high counts) vs NCCHE-LUAD-Visium (low counts)	Xenium: HMHVG PCC=0.586, Marker PCC=0.579; Visium: HMHVG PCC=0.191, Marker PCC=0.191	Gap is driven by low transcript counts in Visium, not inherent unpredictability of immune genes	All TME markers are equally predictable if counts are sufficient (not gene-specific analysis)	[Paper] [Paper: PDF p. 10], [Figure 2c–d]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Gene-wise predictability concordance	Some genes are intrinsically hard/easy across all models	Compute PCC per gene across 20 models; cluster genes by mean PCC	Smooth separation in heatmap; high Spearman correlation of gene ranks across models	Gene-level predictability is governed by morphology-expression coupling strength, not model architecture	This coupling is deterministic (no stochastic modeling of uncertainty assessed)	[Paper] [Paper: PDF p. 11], [Figure 3a], [Extended Data Fig. 1]
Multi-scale models on stromal genes	TRIPLEX/DeepSpot gain stems from long-range context integration	Identify genes with $\Delta PCC \geq 0.1$ over linear probe; manually annotate functional categories	Top gains: COL1A1, SPARC, LAG3 (stromal/immune); all require meso-macro scale patterns	Multi-scale reasoning captures tissue-level organization beyond local patches	This mechanism generalizes to single-cell resolution (not tested)	[Paper] [Paper: PDF p. 11, 13], [Figure 3b], [Paper] [Paper: PDF p. 19]
Cross-tissue generalization	Biological heterogeneity harms more than technical variation	Train on LUAD, test on BRCA/PRAD; compare gap to cross-institution (same cancer, different sites)	Cross-tissue gap: -0.20 to -0.35 ; Cross-institution gap: -0.05 to -0.10	Morphology-to-expression mapping is highly tissue-specific; simple data fusion causes negative transfer	Domain adaptation strategies (e.g., tissue-aware fine-tuning) would resolve this (not implemented/tested)	[Paper] [Paper: PDF p. 17], [Figure 5b], [Paper] [Paper: PDF p. 19]

11 对结论的正确理解

论文结论必须严格限定于其证据范围：(1) “多数模型未超线性探针” 仅指在UNiv2编码下对HMHVG/TME基因的PCC评估，不否定其 在其他任务（如分割、分类）或特定基因子集上的优势；(2) “基因可预测性具有一致性” 指200个HMHVG+16个marker基因在20个模型间的相对排序稳定，但未涵盖全转录组（尤其低表达/ubiquitous基因）；(3) “TRIPLEX/DeepSpot优势在多尺度” 证据仅来自其对stromal/immune基因的 ΔPCC 增益及下游任务表现，未证明其内部机制（如cross-attention）是唯一有效路径；(4) “Xenium数据质量提升上限” 基于其更高平均计数与同步提升的PCC/Cell2location/SpaGCN性能，但未控制其他变量（如RNA integrity、library prep）；(5) “跨组织泛化难” 结论基于Visium→Visium转移，未测试Xenium→Xenium或跨平台→跨组织复合场景。所有结论均指向**评估范式革新**，而非否定模型架构价值。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Cancer type & platform scope	Limited to 6 cancer types and 2 ST platforms (Visium/Xenium)	Extend to additional tumor types, tissue contexts, and emerging sequencing platforms	[Paper] [Paper: PDF p. 20]
Gene panel restriction	Analyses restricted to HMHVGs (200 genes) and 16 TME markers	Systematic investigation of lowly expressed or functionally diverse genes remains open	[Paper] [Paper: PDF p. 20]
Spot-level granularity	Evaluation performed at spot-level (aggregated multi-cell signals)	Future benchmarking should extend to single-cell ST datasets and virtual ST models	[Paper] [Paper: PDF p. 20]
Downstream task coverage	Only Cell2location (deconvolution) and SpaGCN (spatial domains) evaluated	Broader assessment of other tools (e.g., spatial DE, trajectory inference) needed	[Paper] [Paper: PDF p. 14–15]
Zero-shot model comparability	OmiCLIP/STPath evaluated without fine-tuning, unlike others	Develop unified protocols for fair zero-shot vs fine-tuned comparison	[Paper] [Paper: PDF p. 22], [Online Methods p. 29–30]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Linear probe baseline uses UNlv2, but its "simplicity" is misleading	UNlv2 itself is a massive ViT trained on >1M slides; linear probing leverages immense pre-trained knowledge, not just "simplicity". A true null model might be random projection or shallow CNN.	Overstates the "failure" of complex models; conflates architectural complexity with computational cost/interpretability trade-offs.	Replace UNlv2 linear probe with: (a) ResNet50 linear probe, (b) Random Gaussian projection, (c) Shallow 2-layer MLP on raw pixels. Compare ranking shifts.	[Paper] [Paper: PDF p. 9], [Figure 2a], [Paper] [Paper: PDF p. 10]
Gene set analysis uses singscore on union of HMHVG+markers	This gene set is biased toward high-expression/high-variability genes; singscore may perform poorly on sparse or low-variance genes common in scRNA-seq.	Underestimates ability of virtual ST to recover subtle regulatory programs; limits relevance to single-cell foundation models targeting rare cell states.	Re-run singscore on full gene universe (where available) or use AUCell; compare with scRNA-seq-derived gene sets (e.g., from PanglaoDB).	[Paper] [Paper: PDF p. 13], [Online Methods p. 35]

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Cross-platform transfer (Visium→Xenium) shows "negligible loss"	This is likely because Xenium's higher sensitivity compensates for domain shift, not because models are platform-agnostic. The reverse (Xenium→Visium) may fail catastrophically.	Misleads about true platform interoperability; critical for users planning multi-platform studies.	Explicitly test Xenium→Visium transfer on same cohorts; measure gap asymmetry and whether fine-tuning on small Xenium→Visium adapter bridges it.	[Paper] [Paper: PDF p. 17], [Figure 5b right], [Paper] [Paper: PDF p. 18]
"Negative transfer" in inter-cohort scaling attributed to tissue heterogeneity	Could also stem from batch effects (e.g., HEST-PRAD vs WUSTL-BRCA staining protocols) or annotation inconsistencies, not pure biology.	Obscures whether the problem is biological (tissue-specificity) or technical (batch correction failure); impacts design of multi-omics alignment strategies.	Apply ComBat/Harmony to harmonize expression matrices before training; re-run scaling experiments. If negative transfer persists, tissue-specificity is confirmed.	[Paper] [Paper: PDF p. 18], [Figure 5d], [Online Methods p. 21]
Robustness analysis uses Spearman ρ of rank preservation	High ρ means top models stay top, but says nothing about absolute performance degradation magnitude or which models fail hardest.	Insufficient for clinical deployment where even small PCC drop in key markers (e.g., PD-L1) matters.	Report model-specific gap distributions (Fig. 5b) alongside clinical impact metrics (e.g., % samples with PCC < 0.3 for CD274).	[Paper] [Paper: PDF p. 17], [Figure 5b], [Paper] [Paper: PDF p. 19]

14 学到的知识

- **评估基础设施优先级高于模型创新**：在数据/标注/协议不统一的领域（如spatial transcriptomics），构建 STP-BENCH这类基准比提出单个SOTA模型更具杠杆效应；其代码/数据开源直接加速整个社区进展。
- **PFM是虚拟ST的“操作系统”**：UNiv2/Virchow2等PFM已将形态表征能力推至瓶颈，后续架构创新必须聚焦于如何**有效利用**这些高质量特征（如TRIPLEX的跨尺度融合），而非重复优化底层编码。
- **基因级可预测性是硬边界**：200个HMHVG+16个marker的PCC热图显示，约30%基因在所有模型上 PCC<0.1，构成形态学信息天花板；这为single-cell foundation models的预训练目标（如masking策略）提供实证约束——应优先学习可预测基因的调控逻辑。
- **下游效用是终极验证**：Cell2location/SpaGCN性能与基因PCC高度一致（Spearman=0.902），证明spot-level精度是必要条件；但若某模型PCC中等却显著提升特定细胞类型丰度（如Tregs），则提示其捕捉了独特生物学信号。
- **泛化需分层诊断**：Cross-Institution（技术）gap小，说明模型对染色/scan变异鲁棒；Cross-Tissue（生物）gap大，揭示形态-表达映射的组织特异性本质；这对multi-omics对齐中“跨组织先验”的设计具有直接指导意义。

- **数据质量是隐性瓶颈：**Xenium与Visium的性能鸿沟贯穿所有层级（基因→通路→细胞→空间），表明提升测序深度/灵敏度可能比模型改进带来更大收益；这为perturbation prediction等任务的数据采集标准提供依据。

15 与既有知识的连接

- **候选连接/方法论连接：**STP-BENCH的“统一编码器+多粒度评估”范式可直接迁移到single-cell foundation models评估——例如，将scFoundation或scGPT的细胞嵌入作为“PFM”，在统一嵌入空间内评估不同下游任务（cell type annotation, trajectory inference, perturbation response）的性能，解耦表征质量与任务头设计。
- **候选连接/方法论连接：**其gene-wise PCC热图与singscore通路分析，为multi-omics中cross-modal alignment提供了可量化的目标函数——例如，在graph neural networks对齐scRNA-seq与spatial proteomics时，可最大化对齐后嵌入在STP-BENCH基因集上的PCC一致性。
- **候选连接/方法论连接：**TRIPLEX的“local+neighbor+global”三支路设计，启发了spatial transcriptomics中GNN架构的升级——例如，在cell state representation中，可构建三级图：节点=cell，边=spatial proximity (local)、kNN in expression space (neighbor)、tissue-level region membership (global)。
- **弱连接/方法论连接：**其跨平台（Visium↔Xenium）泛化分析，与biomedical AI中domain adaptation研究弱连接——但STP-BENCH发现简单数据融合有害，暗示需要更精细的adapter（如LoRA）或tissue-aware contrastive learning，而非传统DA方法。
- **弱连接/方法论连接：**对低表达基因预测失败的归因（数据稀疏性），与perturbation prediction中“rare cell state response”建模困难形成呼应——二者均指向需提升底层数据质量或开发对稀疏性鲁棒的损失函数（如zero-inflated objectives）。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** Morphology-Guided Gene Prioritization for scFoundation Pretraining

originating limitation/observation: STP-BENCH reveals ~30% of HMMVG+marker genes are intrinsically unpredictable ($PCC < 0.1$) across all models, suggesting their expression is weakly coupled to morphology; conversely, top-predictable genes (e.g., COL1A1, LAG3) reflect strong morphology-program coupling [Paper] [Paper: PDF p. 11, 13], [Figure 3b]. **core hypothesis:** Pretraining single-cell foundation models on gene subsets prioritized by STP-BENCH predictability will yield representations more transferable to spatial tasks than uniform masking. **delta from paper:** STP-BENCH identifies *which* genes are morphology-informative; this idea leverages that list to *curate pretraining objectives*, moving from evaluation to generative modeling. **initial method:** Use STP-BENCH gene-wise PCC (averaged across models/datasets) as weights for gene masking probability in scGPT pretraining; compare against uniform masking and expression-variance-based masking. **validation:** Fine-tune on STP-BENCH tasks (virtual ST prediction, Cell2location) and benchmark on independent spatial datasets (e.g., SRT-Atlas); measure gain on low-PCC genes. **failure modes:** If morphology-predictable genes are highly co-expressed, masking them may not improve generalization; if they are technical artifacts (e.g., ribosomal), benefit vanishes. **innovation status:** unverified

- **name:** Cross-Tissue Adapter for Spatial Multi-Omics Alignment

originating limitation/observation: STP-BENCH shows cross-tissue generalization gap is severe (-0.35) and negative transfer occurs when naively merging cancer types [Paper] [Paper: PDF p. 17, 19], [Figure 5b,d], implying tissue-specific morphology-expression manifolds. **core hypothesis:** A lightweight, tissue-conditioned adapter module inserted between PFM encoder and ST predictor can align tissue-specific manifolds without full retraining. **delta from paper:** STP-BENCH diagnoses the problem (tissue specificity); this idea proposes a *modular solution* compatible with existing STP-BENCH models (e.g., TRIPLEX), enabling plug-and-play cross-tissue deployment. **initial method:** For each tissue type, learn a tissue-specific adapter (2-layer MLP) that transforms UNiv2 embeddings; train adapters end-to-end with frozen backbone on multi-tissue data, using contrastive loss to pull same-tissue embeddings closer. **validation:** Test adapter on STP-BENCH cross-tissue tasks (e.g., LUAD $\rightarrow$ BRCA); compare gap reduction vs full fine-tuning; ablate adapter to confirm necessity. **failure modes:** Adapter may overfit to small tissue cohorts; if tissue manifolds are non-linearly separable, MLP fails; requires tissue label at inference. **innovation status:** unverified

- **name:** SSIM-Guided Diffusion for Spatial Structure Preservation

originating limitation/observation: STP-BENCH uses SSIM as secondary metric but finds it trends consistently with PCC [Paper] [Paper: PDF p. 10, 11]; however, generative models (STFlow/Stem) are evaluated only on PCC/MAE, ignoring their structural advantage [Paper] [Paper: PDF p. 6, 28–29]. **core hypothesis:** Incorporating SSIM as an explicit loss term during diffusion training will improve spatial coherence of generated expression maps, particularly for long-range patterns (e.g., tumor-stroma boundaries). **delta from paper:** STP-BENCH *measures* spatial structure via SSIM; this idea *optimizes for it* in generative modeling, bridging the gap between evaluation metric and training objective for spatial transcriptomics. **initial method:** Modify STFlow's denoising objective to include weighted SSIM loss between predicted and ground-truth spatial grids, alongside MSE; tune weight to balance fidelity and structure. **validation:** Compare SSIM scores of STFlow variants on STP-BENCH; test downstream impact on SpaGCN ARI and visual inspection of boundary sharpness. **failure modes:** SSIM optimization may degrade spot-level PCC; grid rescaling (p.32) introduces interpolation artifacts; SSIM is sensitive to normalization choices. **innovation status:** unverified