

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Correlation-Guided Flow Matching with Annealed Masking for Spatial Transcriptomics Generation	[Paper] [Paper: PDF p. 1]
Authors	Yupei Zhang, Hao Chen, Li Pan, Chao Li, Xiaohan Xing	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (cs.LG)	[Paper] [Paper: PDF p. 1]
Publication date	2026-09-01	[Paper] [Paper: PDF p. 1]
Core task	Histology-to-ST prediction (conditional generation of spatial gene expression from H&E images)	[Paper] [Paper: PDF p. 1–2]
Key method	CorrFlow: annealed masked flow matching + gene graph-regularized optimization	[Paper] [Paper: PDF p. 1, Fig. 2, Sec. 3]
Primary benchmark	HEST-1K (10 patient-stratified cancer datasets), HMHVG-50 gene panel	[Paper] [Paper: PDF p. 7, Table 1]
Main metric	PCC (Pearson correlation coefficient), HPCC (Hallmark-Gene PCC), GGC-Pearson	[Paper] [Paper: PDF p. 7, 14–15, Table 1, 7]
Baseline anchor	STFlow (conditional flow matching baseline)	[Paper] [Paper: PDF p. 1, 7, Table 1]
Code/data availability	Not stated in text; no URL, GitHub, or repository link provided	Not verifiable from supplied material

02 一句话总结

本文提出 CorrFlow，一种面向空间转录组（ST）生成的、**基因相关性引导的条件流匹配框架**，通过退火掩码策略与基因图正则化双路径建模基因-基因依赖关系，解决现有生成模型将基因视为独立预测目标、无法保留生物学共表达结构的根本缺陷；该方法在10个 HEST-1K 癌症数据集上系统性超越 STFlow 等基线，在 PCC 和 HPCC 上取得最优平均性能，且提升在高度相关基因子集和通路层面尤为显著；其设计直指用户研究中 perturbation prediction 与 cross-modal alignment 的核心需求——即如何在跨模态生成中注入并保持分子层级的结构化先验。

03 研究问题

论文聚焦于：如何在 histology-to-ST 的条件生成任务中，显式建模并利用基因间的生物学依赖关系（如共表达、通路协同、调控网络），以突破当前生成模型因“每基因独立优化”导致的生物失真瓶颈？该问题源于对现有范式的理论诊断：标准流匹配（CFM）与扩散目标函数在数学上天然分解为 per-gene 损失（Proposition 1 [Paper] [Paper: PDF p. 4]），导致模型无激励去学习跨基因联合分布，即使共享网络骨干也无法被目标函数识别或奖励。因此，问题本质不是模型容量不足，而是**训练信号缺失**——需要重构损失函数与优化约束，使基因依赖成为可学习、可奖励、可正则化的显式变量。

04 研究背景与发展路径

早期工作（ST-Net [8]）采用确定性回归，忽略表达不确定性；检索法（BLEEP [35]）依赖参考集覆盖度；近期生成范式（Stem [40], STFlow [11]）虽建模条件分布并提升采样效率，但仍未解决“基因独立性假设”这一底层建模缺陷。作者指出，该缺陷与生物学事实严重冲突：基因表达受调控网络、共表达模块与通路活动协同支配 [21, 31, 36]；而现有方法仅在特征编码器中偶有引入图结构 [25]，却从未将其嵌入生成动力学（dynamics）本身。CorrFlow 的发展路径是**从理论缺陷出发→提出可证明改变最优解性质的机制（annealed masking）→辅以结构化正则（gene graph）→形成闭环验证**，而非经验式堆叠模块。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper		
Per-gene decomposition of training objective	Uneven gene-level performance; highly correlated genes (e.g., x_{31} in Fig. 1) predicted poorly despite accurate prediction of others (x_{11}, x_{21})	Standard CFM/diffusion loss decomposes over gene dimensions → optimal predictor for gene g depends only on marginal $p(x_{g1} \setminus$	$x^t, t, c)$, <i>not joint</i> $p(x^{(M)}_1 \setminus$	$x^{(O)}_1, c)^*$ [Paper] [Paper: PDF p. 4–5, Prop. 1 & Rem. 1]	[Paper] [Paper: PDF p. 2, Fig. 1 caption]; [Paper] [Paper: PDF p. 4, Eq. 3]; [Paper] [Paper: PDF p. 5, "Remark 1"]
Shortcut reconstruction near $t=1$	Network copies near-target values from x^t instead of learning meaningful transport dynamics	As $t \rightarrow 1$, $x^t \rightarrow x^1$, making endpoint prediction trivial without explicit pressure to use cross-gene context	[Paper] [Paper: PDF p. 5, "Conditional flow matching suffers from a practical shortcut issue..."]; [Paper] [Paper: PDF p. 5, Eq. 8 context]		

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Violation of known co-expression structure	Predictions may satisfy per-gene accuracy but violate biological priors (e.g., STRING) or data-driven modules (e.g., WGCNA)	Finite capacity and noisy gradients cause drift from structured ground truth, even if joint modeling is incentivized	[Paper] [Paper: PDF p. 6, "However, finite model capacity and noisy gradients can still lead to predictions that violate known co-expression structures."]

06 核心思想

论文的核心思想是：将基因依赖从“隐式统计现象”升格为“显式可优化变量”，通过双重干预——在训练动态中强制联合建模（annealed masking），在输出空间中施加结构化约束（gene graph regularization）——实现生成结果的数值准确性与生物学一致性的协同提升。这一思想拒绝“后处理校准”或“特征级图卷积”的浅层整合，而是深入生成过程的两个关键环节：1) 输入扰动设计（masking schedule coupled to t ）使模型必须在缺失部分基因时推理其余基因；2) 输出空间正则（Huber + Laplacian on fused gene graph）将外部功能知识（STRING）与数据驱动共表达（WGCNA）编码为软约束，引导预测落在生物合理流形上。

07 方法总览

CorrFlow 是一个端到端的 conditional flow matching 框架，以 histology features z , spatial coordinates q , timestep t , and masked interpolant $\hat{x}^t$ 为输入，预测终点表达 x^1 。其方法总览遵循“问题→机制→保障”逻辑链：针对 per-gene decomposition 问题，引入 Annealed Masked Flow Matching (Annealed-MFM)——通过 t -dependent masking ratio $p(t)=p_{max} \cdot t$ 动态移除输入中的基因维度，迫使模型学习 $p(x^{(M)1}_1 \mid x^{(O)1}_1, c)$ 而非 $p(x^{g_1}_1 \mid x^t, t, c)$ ；针对 shortcut reconstruction 问题，该掩码在 t 接近1时最重，直接切断复制路径；针对 biological violation 问题，引入 Gene Graph-Regularized Optimization——融合 STRING（先验功能关联）与 WGCNA（数据驱动共表达）构建基因亲和图 S ，并定义 Huber-based local smoothness ($L_{lo}C_{al}$) 与 Laplacian global smoothness ($L_{glo}b_{al}$) 双重正则项，共同约束预测 $\hat{x}^1$ 的结构合理性。最终目标为 $L = L_{mf_m} + \rho L_{lo}C_{al} + \lambda L_{glo}b_{al}$ [Paper] [Paper: PDF p. 14, Eq. 16]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Annealed Masking Schedule	Progressively masks gene dimensions during interpolation, with ratio $p(t) = p_{\max} \cdot t$; uses learnable mask tokens m to avoid train-inference norm mismatch	To break per-gene input-output correspondence and provably shift optimal solution from marginal to joint conditional estimation (Prop. 2); suppresses shortcut reconstruction near $t=1$	Input: x^t, t ; Output: masked $\tilde{x}^t$ (Eq. 5)	[Paper] [Paper: PDF p. 5, Prop. 2 & proof in App. A.1]; [Paper] [Paper: PDF p. 5, "suppress this by coupling..."]; [Paper] [Paper: PDF p. 5, learnable token rationale]	Ablation shows -0.004 avg PCC drop (Table 2: 0.613→0.609); Fig. 3(c) shows gains concentrated on high-correlation genes, confirming joint modeling benefit
Gene Affinity Graph Construction	Fuses external functional prior (STRING $S^{(s)}$) and data-driven co-expression (WGCNA $S^{(w)}$) via weighted average $S = \alpha S^{(s)} + (1-\alpha)S^{(w)}$, then computes normalized adjacency A and Laplacian L (Eq. 10)	To encode biologically grounded structural constraints that cannot be learned solely from limited ST data; complementary sources mitigate dataset-specific noise and generalization gaps	Input: STRING DB, training x^t ; Output: graph $G=(V,E,S), A, L$	[Paper] [Paper: PDF p. 6, Eq. 9 & 10]; [Paper] [Paper: PDF p. 6, "captures functional associations... co-expression landscape specific to current dataset"]	Ablation shows larger drop: -0.008 avg PCC (Table 2: 0.613→0.605); removing either STRING (-0.009) or WGCNA (-0.006) hurts performance (Table 5)
Local Graph Constraint ($L_{lo}C_{al}$)	Applies Huber penalty on z-scored prediction discrepancies $\Delta_{n,ij}$ across graph edges $(i,j) \in E$, weighted by affinity $w_{ij} \propto S_{ij}$	To enforce pairwise consistency among functionally related genes, robust to outliers on weak edges	Input: $\tilde{x}^t, S, \mu_i, \sigma_i$; Output: scalar $L_{lo}C_{al}$ (Eq. 11)	[Paper] [Paper: PDF p. 6, Eq. 11]; [Paper] [Paper: PDF p. 6, "penalize the discrepancy... promoting smoothness among co-regulated genes"]	Ablation shows -0.008 avg PCC drop (Table 2: 0.613→0.605); hyperparameter study confirms sensitivity to ρ (Table 6)
Global Graph Constraint ($L_{glo}b_{al}$)	Applies spectral penalty $\tilde{x}^{t,nT}L\tilde{x}^{t,n}$ using normalized graph Laplacian L , encouraging alignment with low-frequency eigenmodes	To capture large-scale co-expression modules beyond pairwise edges, suppressing graph-wide oscillations	Input: $\tilde{x}^t, L$; Output: scalar $L_{glo}b_{al}$ (Eq. 12)	[Paper] [Paper: PDF p. 6–7, Eq. 12]; [Paper] [Paper: PDF p. 7, "penalizes predictions that oscillate rapidly between neighboring genes"]	Ablation shows -0.004 avg PCC drop (Table 2: 0.613→0.609); hyperparameter study shows $\lambda=10^{-3}$ optimal (Table 6)

09 关键公式与符号

论文未提供单一主导性“新公式”，但明确定义了以下关键公式与符号，全部可核验：

- **Linear interpolant:** $x^t = (1-t)x^o + t x^1$, $t \in [0,1]$ [Paper] [Paper: PDF p. 4, Eq. 1]
- **Standard CFM loss decomposition:** $L_CFM(\theta) = \sum_g L^{(g)}_CFM(\theta)$ [Paper] [Paper: PDF p. 4, Eq. 3]
- **Annealed masking ratio:** $p(t) = p_{max} \cdot t$ [Paper] [Paper: PDF p. 5, Eq. 8]
- **Masked input:** $\tilde{x}^{t,g} = m^g$ if $g \in M$, else $x^{t,g}$ [Paper] [Paper: PDF p. 5, Eq. 5]
- **Fused gene affinity:** $S = \alpha S^{(s)} + (1-\alpha) S^{(w)}$ [Paper] [Paper: PDF p. 6, Eq. 9]
- **Normalized adjacency & Laplacian:** $A = D^{-1/2} S D^{-1/2}$, $L = I - A$ [Paper] [Paper: PDF p. 6, Eq. 10]
- **Local graph constraint:** $L_{local} = (1/N) \sum_n \sum_{(i,j) \in e} w_{ij} \text{Huber}_\beta(\Delta_{n,ij})$ [Paper] [Paper: PDF p. 6, Eq. 11]
- **Global graph constraint:** $L_{global} = (1/N) \sum_n \tilde{x}^{1,nT} L \tilde{x}^{1,n}$ [Paper] [Paper: PDF p. 7, Eq. 12]
- **Overall objective:** $L = L_MFM + L_graph$ [Paper] [Paper: PDF p. 14, Eq. 16]
- **PCC definition:** $r^g = \text{cov}(\hat{y}^{:,g}, y^{:,g}) / (\sigma(\hat{y}^{:,g}) \sigma(y^{:,g}))$ [Paper] [Paper: PDF p. 14, Eq. 17]
- **HPCC definition:** $HPCC = (1/|K|) \sum_k (1/|P_k \cap G|) \sum_{\{g \in P_k \cap G\}} r^g$ [Paper] [Paper: PDF p. 7, Eq. 13]
- **GGC-Pearson definition:** $\text{corr}(\text{vec}(\Delta(\hat{C})), \text{vec}(\Delta(C)))$ [Paper] [Paper: PDF p. 15, Eq. 20]

关键符号： x^o (ZINB prior sample), x^1 (ground-truth ST), x^t (interpolant), $\tilde{x}^t$ (masked input), M/O (masked/observed gene sets), $S^{(s)}/S^{(w)}$ (STRING/WGCNA affinity), L (graph Laplacian), r^g (gene-wise PCC), $HPCC$ (pathway-averaged PCC), $GGC\text{-}Pearson$ (gene-gene correlation preservation).

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Main benchmark (HEST-1K, HMMVG-50)	CorrFlow > STFlow & other baselines on PCC/HPCC	10 datasets, patient-stratified CV, same backbone, 100 epochs	Avg PCC: STFlow 0.600 $\rightarrow$ CorrFlow 0.613 (+2.2%); Avg HPCC: 0.613 $\rightarrow$ 0.628 (+2.4%)	Annealed-MFM + gene graph improves both numerical accuracy and pathway-level coherence	Not that CorrFlow is universally superior on all downstream tasks (e.g., survival prediction)	[Paper] [Paper: PDF p. 8, Table 1]; [Paper] [Paper: PDF p. 8, "Quantitative Comparison"]
Ablation study (HMMVG-50)	Each component contributes positively and complementarily	Remove masking, L_graph , L_global , L_local , STRING, or WGCNA	Full model (0.613) > w/o masking (0.609) > w/o L_graph (0.605); w/o STRING (0.604) < w/o WGCNA (0.607)	Annealed masking and graph regularization are both necessary; STRING and WGCNA provide complementary priors	Not that masking alone suffices without graph constraint (gap is larger for L_graph removal)	[Paper] [Paper: PDF p. 8, Table 2]; [Paper] [Paper: PDF p. 15, Table 5]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Hyperparameter study (masking)	t -proportional masking schedule is optimal	Compare $f(t)=t$, $f(t)=1-t$, $f(t)=learnable$; vary p_{max}	$f(t)=t$ & $p_{max}=0.75$ yield best avg PCC (0.613)	Motivation validated: stronger masking near $t=1$ most effective against shortcuts	Not that other schedules are ineffective— $f(t)=learnable$ also achieves 0.613 (Table 3)	[Paper] [Paper: PDF p. 8–9, Table 3]
Gene-level PCC significance (HEST-1K)	CorrFlow outperforms baselines at gene level, not just dataset average	Paired Wilcoxon on 500 gene-dataset pairs, Holm correction	vs STFlow: Mean Diff=+0.0129, Wins=330, Losses=170, $p=1.49 \times 10^{-16}$	Improvement is robust across diverse genes, not driven by few outliers	Not that improvement is uniform across all genes—some show no gain (Fig. 3b shows points below diagonal)	[Paper] [Paper: PDF p. 19, Table 12]; [Paper] [Paper: PDF p. 18, C.5]
GGC-Pearson evaluation (HEST-1K)	CorrFlow better preserves gene-gene correlation structure	Compare predicted vs ground-truth C matrices (Eq. 19)	Avg GGC-Pearson: CorrFlow 0.648 > STFlow 0.633 > BLEEP-UNI 0.628	Dependency-aware design directly improves dependency-structure fidelity, validating core motivation	Not that GGC-Pearson correlates perfectly with PCC—some datasets show tradeoffs (e.g., PAAD STFlow 0.685 > CorrFlow 0.624, Table 7)	[Paper] [Paper: PDF p. 17, Table 7]; [Paper] [Paper: PDF p. 15, "GGC" section]

11 对结论的正确理解

CorrFlow 的核心结论是：在 histology-to-ST 生成中，显式建模基因依赖（通过 annealed masking 强制联合建模 + gene graph 施加结构约束）能系统性提升预测的数值精度（PCC）与生物学一致性（HPCC, GGC-Pearson），且这种提升源于对现有方法底层优化缺陷的针对性修正，而非单纯模型容量增加。正确理解需注意三点：1) 提升是稳健但适度的：PCC 平均提升 2.2%，HPCC 提升 2.4%，反映的是基础建模范式的改进，而非颠覆性性能飞跃；2) 收益具有结构性：提升在通路层面（HPCC）和高相关基因子集（Fig. 3c）更显著，证实其“生物一致性”定位；3) 有效性依赖于双组件协同：ablation 显示 masking 与 graph 各自贡献，但完整方案效果最佳，表明二者解决不同层面问题（动态建模 vs. 空间约束）。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Lack of external validation	Evaluation uses HEST-1K and STImage-1K4M, but no fully independent external cohort with different tissue prep, platform, or scanner	Incorporate independently collected ST cohorts to assess clinical robustness and out-of-distribution generalization	[Paper] [Paper: PDF p. 19, "D Limitations and Future Work", first paragraph]
Insufficient clinical translation readiness	Current prediction quality remains inadequate for direct clinical use due to intrinsic challenge of inferring molecular states from morphology alone	Improve robustness via stronger dependency-aware modeling and higher-quality ST training data	[Paper] [Paper: PDF p. 19, second paragraph]
Untested downstream utility	Evaluation focuses on reconstruction fidelity (PCC, GGC), not impact on biological/clinical analysis	Assess whether generated ST profiles benefit downstream tasks: tissue-domain identification, pathway activity estimation, biomarker discovery, patient stratification, prognosis modeling	[Paper] [Paper: PDF p. 19–20, third paragraph]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The "annealed masking" is applied uniformly across all genes, yet biological dependencies are highly heterogeneous (e.g., housekeeping vs. pathway-specific genes). Uniform $p(t)$ may under-mask critical modules or over-mask noisy ones.	Uniform masking ignores gene-specific functional roles and variance, potentially diluting signal for tightly co-regulated modules while adding noise to unstable genes. This could explain why graph-structured masking (App. A.3) underperforms random annealed masking (Table 10: $0.608 < 0.613$).	If masking strategy is suboptimal, the joint modeling incentive is weakened, limiting gains. Understanding gene-specific masking could unlock larger improvements.	Implement gene-group-aware masking (e.g., mask by Hallmark pathway or WGCNA module) and compare PCC/HPCC on those groups; analyze per-module PCC gain vs. masking frequency.	[Paper] [Paper: PDF p. 13, App. A.3]; [Paper] [Paper: PDF p. 7, Eq. 13 defines HPCC by Hallmark pathways]; [Paper] [Paper: PDF p. 6, WGCNA used for graph]

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
The gene graph S is constructed once per dataset and frozen during training, but the model's internal representation of gene relationships likely evolves. A static graph may become misaligned with the model's learned manifold.	Static graph regularization could act as a brittle prior, especially if WGCNA $S^{(w)}$ is noisy or STRING $S^{(s)}$ is incomplete for context-specific interactions, leading to over-smoothing or suppression of valid biological variation.	This risks trading off biological fidelity for artificial smoothness, particularly in heterogeneous tissues like tumors. It questions the optimality of the "fused graph" design.	Train with adaptive graph (e.g., predict S from z and q), or ablate graph update frequency; measure correlation between S and learned $\hat{x}'$ covariance on held-out spots.	[Paper] [Paper: PDF p. 6, "We fuse them via weighted averaging..."]; [Paper] [Paper: PDF p. 7, "Lglobal penalizes predictions that oscillate rapidly..."]
The primary metric PCC measures linear correlation but is insensitive to distributional shifts (e.g., correct gradient but wrong absolute scale). CorrFlow's lower MSE-Mean (Table 8) suggests improved calibration, but PCC alone cannot confirm if biological patterns (e.g., bimodal expression) are preserved.	Relying on PCC/HPCC may overstate biological coherence if the model learns to match means/variances well but fails on higher-order statistics (skew, multimodality) crucial for cell state inference.	For user's <i>cell state representation</i> goal, preserving distribution shape is as vital as correlation. A high PCC does not guarantee faithful state reconstruction.	Compute Wasserstein distance or KL divergence between predicted and ground-truth per-gene expression histograms; evaluate on single-cell deconvolution accuracy using CorrFlow output.	[Paper] [Paper: PDF p. 17, Table 8 reports MSE-Mean]; [Paper] [Paper: PDF p. 15, "MSE-Mean measures the absolute deviation..."]; User research direction: <i>cell state representation</i>

14 学到的知识

- **流匹配的可塑性**：标准 CFM 目标 (Eq. 3) 虽数学上分解，但通过输入扰动 (masking) 可严格诱导联合建模 (Prop. 2)，证明生成目标函数可被“重定向”而非仅靠模型架构。
- **退火调度的双重角色**： $p(t)=p_{max} \cdot t$ 不仅是超参，更是连接训练动态 (t) 与生物学约束 (依赖强度) 的桥梁，其有效性 (Table 3) 验证了“越接近目标越需强依赖引导”的直觉。
- **图正则的尺度分离智慧**： $L_{l_{CaI}}$ (Huber on edges) 与 $L_{glo}b_{aI}$ (Laplacian spectrum) 分别捕获局部配对一致性与全局模块平滑性，这种多尺度约束比单一图卷积或全连接更契合基因网络的层次结构。
- **先验融合的实证权重**： $\alpha=0.6$ (Table 3) 表明在 ST 生成中，外部功能知识 (STRING) 略优于数据驱动共表达 (WGCNA)，提示跨-dataset generalizability of functional priors matters more than dataset-specific noise.
- **评估需分层**：PCC (per-gene)、HPCC (per-pathway)、GGC-Pearson (per-gene-pair) 构成三层验证，缺一不可——CorrFlow 在 HPCC/GGC 上提升更大，恰恰印证其设计目标达成。

15 与既有知识的连接

- **候选连接/方法论连接：**与用户 *single-cell foundation models* 的连接在于：CorrFlow 的 gene graph construction (STRING+WGCNA) mirrors how scFoundation models integrate prior networks (e.g., CellxGene) with learned embeddings; 其 annealed masking parallels masked autoencoding in scBERT, but adapted to continuous flow dynamics.
- **候选连接/方法论连接：**与用户 *graph neural networks* 的连接在于： $L_{\text{lo}} C_{\text{AI}}$ 和 $L_{\text{glo}} b_{\text{AI}}$ 构成一种“图正则化生成”范式，区别于标准 GNN 的消息传递，它将图结构作为输出空间的几何约束，可迁移至 spatial omics 的图生成任务。
- **候选连接/方法论连接：**与用户 *perturbation prediction* 的连接在于：annealed masking simulates gene knockdown (masking g forces inference from others), making CorrFlow's architecture inherently interpretable for *in silico* perturbation—predicting $\hat{x}'$ under M directly yields counterfactual expression.
- **弱连接/方法论连接：**与 *multi-omics* 和 *cross-modal alignment* 的连接较弱——CorrFlow 是单模态生成 (histology $\rightarrow$ ST)，未涉及 multi-omics integration 或跨模态对齐损失；但其“条件生成+结构正则”框架可扩展为 multi-conditional (e.g., histology + methylation $\rightarrow$ ST)。
- **弱连接/方法论连接：**与 *spatial transcriptomics* 和 *biomedical AI* 是直接领域应用，但未涉及 spatial graph construction (e.g., spot neighborhoods) or clinical endpoint prediction.

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** Gene-Group Adaptive Annealing

originating limitation/observation: Uniform $p(t)$ masking ignores functional heterogeneity; Table 10 shows graph-structured masking underperforms, suggesting naive grouping isn't enough. **core hypothesis:** Masking ratio should adapt per gene group (e.g., Hallmark pathway) based on its average correlation strength and functional importance, not globally. **delta from paper:** Replace scalar $p_{\max}$ with pathway-specific $p_{\max}^k$; compute $p^k(t) = p_{\max}^k \cdot t$ for genes in pathway k . **initial method:** Use HMMVG-50 genes' average absolute correlation (Fig. 3c) and MSigDB pathway enrichment score to rank pathways; assign higher $p_{\max}^k$ to top k pathways. **validation:** Compare PCC/HPCC gain on high-correlation pathways (e.g., E2F targets) vs. low-correlation ones; ablate per-pathway masking. **failure modes:** Over-masking fragile pathways; poor generalization if pathway scores are dataset-biased. **innovation status:** unverified

- **name:** Dynamic Gene Graph Refinement

originating limitation/observation: Frozen S (Eq. 9) may misalign with evolving model representations; Section 13 notes static graph could over-smooth. **core hypothesis:** The gene affinity graph S should be dynamically updated during training to reflect the model's current understanding of dependencies. **delta from paper:** Replace fixed S with a lightweight adapter that predicts S from histology features z and spatial coords q , trained jointly with main loss. **initial method:** Add a small MLP $S_{\text{pred}}(z, q)$ outputting $G \times G$ matrix; initialize close to fused S ; optimize L_{graph} using predicted S . **validation:** Monitor cosine similarity between predicted S and ground-truth C (Eq. 19) during training; compare final S sparsity vs. fixed S . **failure modes:** Increased training instability; adapter overfitting to noise. **innovation status:** unverified

- **name:** Perturbation-Aware Contrastive Alignment

originating limitation/observation: CorrFlow generates ST from histology, but user needs *perturbation prediction*; current setup lacks explicit contrastive signal for counterfactuals. **core hypothesis:** Jointly train CorrFlow with a contrastive loss that pulls together histology + perturbed-ST pairs (e.g., $z + \hat{x}^1$ under M) and pushes apart $z +$ unperturbed x^1 . **delta from paper:** Add contrastive loss $L_{contrast} = -\log[\exp(\text{sim}(z, \hat{x}^1_M)/\tau) / \sum \exp(\text{sim}(z, \hat{x}^1_{M'})/\tau)]$ over sampled masks M' . **initial method:** Sample M and M' (e.g., disjoint pathways) per batch; use $\hat{x}^1$ from CorrFlow denoiser as embedding. **validation:** Test zero-shot perturbation prediction: mask gene g in test histology, predict $\hat{x}^1$; measure ΔPCC vs. baseline on g and its partners. **failure modes:** Contrastive loss dominating L_{MFM} , degrading base generation quality. **innovation status:** unverified