

Source coverage: Full paper

Extraction confidence: High

Locator mode: page-grounded

Primary analytical lens: methods

Secondary analytical lens: discovery

Context verification: Paper-only

Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Dynamic Generalized Gromov-Wasserstein Optimal Transport	[Paper] [Paper: PDF p. 1]
Authors	Junda Ying, Zhiwei Zeng, Peijie Zhou, Lei Zhang	[Paper] [Paper: PDF p. 1]
Venue	arXiv	[Paper] [Paper: PDF p. 1]
Year	2026	[Paper] [Paper: PDF p. 1]
Core method	TP-DATE (Travelling Pair Dynamical Alignment and Trajectory Estimation)	[Paper] [Paper: PDF p. 1]
Core theory	Dynamic Quadratic-form Optimal Transport (QOT), travelling-pair flow matching	[Paper] [Paper: PDF p. 4–7]
Key datasets	Synthetic Rotation, Mouse Brain (Chen et al., 2022), ARTISTA (Wei et al., 2022), Tumor (Zhang et al., 2026a)	[Paper] [Paper: PDF p. 8–9, B.5.1–B.5.3]
Evaluation metrics	Spatial W2, Expression W2, SC-eMSE, Balanced fused W2, Spatial MSE, Pair distortion	[Paper] [Paper: PDF p. 8–9, B.6]
Code/data availability	Not stated; no GitHub/URL provided in text	[Paper] [Paper: PDF p. 1–40]

02 一句话总结

本文提出了TP-DATE——首个严格、可证明的动态广义Gromov–Wasserstein最优传输（QOT）框架，将结构保持型传输从静态耦合拓展至连续时间轨迹建模。它通过引入“行进对”（travelling pair）路径动作与条件流匹配，实现了无需仿真的高效求解；在空间转录组学的时序插值与3D重建任务中，显著优于OT-CFM、GW-CFM、stVCR等基线，在保持组织空间结构的同时提升基因表达模式重建精度。其边界在于：仅处理平衡动力学（未建模增殖/凋亡），且动态QOT理论当前限于单一流形（ $Y = X$ ）假设 [Paper] [Paper: PDF p. 1–2, 8–9, D.8].

03 研究问题

论文直面空间转录组学动态建模的核心缺口：现有方法（如GW-OT、FGW-OT）仅能对离散快照进行静态对齐，无法重建细胞群体在连续时间或空间维度上的演化轨迹 [Paper] [Paper: PDF p. 1–2]。该问题本质是**如何将结构感知的传输成本（structure-aware cost）从端点匹配泛化为连续概率流的动态生成机制**。作者洞察到，标准OT的动态形式（Benamou–Brenier）依赖于粒子独立运动假设，而空间结构演化要求显式建模粒子间相互作用；因此，研究问题被精确定义为：能否构建一个兼具数学严谨性与计算可行性的动态QOT理论，并设计对应求解器，使学习到的向量场既能最小化全局动能，又能约束相对位移演化以保持局部几何结构？

04 研究背景与发展路径

背景始于OT的两支演进：一是经典OT及其动态BB形式（Benamou & Brenier, 2000），用于单细胞轨迹推断（Schiebinger et al., 2019；Tong et al., 2020）；二是结构感知扩展，即静态QOT（如GW-OT、FGW-OT），通过对成距离/内积比较实现跨模态对齐（Mémoli, 2011；Vayer et al., 2020）。二者长期割裂：前者忽略结构，后者缺失动态。近期工作尝试弥合：Wang & Zhang (2025) 提出静态QOT统一框架；Zhang et al. (2026b) 构建IGW-OT的梯度流动态形式；但均未给出通用动态QOT理论及高效算法 [Paper] [Paper: PDF p. 2]。TP-DATE的发展路径是**自上而下理论构造 + 自下而上算法实现**：先定义路径动作驱动的动态QOT三元形式（静态/动态/BB），证明其等价性与上界关系；再基于“行进对”概念重构条件流匹配，将交互路径的复杂性封装于二粒子空间，最终导出可训练的单粒子速度场。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
静态结构对齐无法建模连续演化	现有GW-OT类方法只能输出快照间耦合，无法生成中间时间点的细胞位置与表达状态	静态QOT缺乏时间维度，其优化目标不包含路径平滑性或动力学一致性约束	[Paper] [Paper: PDF p. 1] “a general dynamic formulation for reconstructing continuous trajectories is still missing” ; [Paper] [Paper: PDF p. 2] “can only align snapshots instead of reconstructing a continuous time dynamics”
标准动态OT破坏空间结构	OT-CFM等方法在旋转数据上产生收缩的直线路径，扭曲组织拓扑	标准OT仅最小化个体动能，未对粒子对的相对位移演化施加约束，导致结构坍塌	[Paper] [Paper: PDF p. 8] Figure 1 caption: “OT-CFM follows nearly straight paths [...] and shrinks the global structure” ; Table 1: TP-DATE achieves 0.02565 vs OT-CFM’s 0.10601 Spatial MSE on Rotation

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
现有动态结构方法计算不可扩展	stVCR、CytoBridge等仿真方法在大数据集上内存溢出或耗时剧增	基于NeuralODE的仿真需反复求解微分方程，计算复杂度随细胞数呈超线性增长	[Paper] [Paper: PDF p. 29] Figure 5 caption: “CytoBridge ran out of memory on 90000” ; [Paper] [Paper: PDF p. 31] Figure 7: TP-DATE’ s training time scales linearly with dataset size

06 核心思想

论文核心思想是**将结构保持的动力学建模转化为二粒子空间上的交互路径优化问题**。作者摒弃了在单粒子空间添加复杂势能项（如CytoBridge）或后验修正耦合（如ContextFlow）的思路，转而提出：1) 定义“行进对”路径动作 $A(z,z')$ ，其Lagrangian显式包含相对位移 $q_t = x_t - y_t$ 的演化项 $\lambda \frac{d}{dt} \|q_t\|^2$ ，直接惩罚结构畸变；2) 将动态QOT解耦为“静态耦合 γ + 行进对路径”，并通过条件流匹配学习其边际速度场；3) 关键洞见是：该边际场虽源于非马尔可夫的端点条件过程，但其生成的二粒子分布 $\pi_t(x,y)$ 与真实动态QOT一致，从而提供了一个**可训练、可扩展、且结构保持的马尔可夫近似** [Paper] [Paper: PDF p. 4–7, A.9].

07 方法总览

TP-DATE方法论遵循“理论定义 → 路径构造 → 流匹配求解”三阶段：1) **理论层**：定义动态QOT的静态形式（QOTS）、动态形式（QOTD）与BB形式（QOTBB），证明 $QOTS = QOTD \geq QOTBB$ ，确立QOTS作为可计算上界的理论基础 [Paper] [Paper: PDF p. 4–5, A.1]；2) **路径层**：针对Lagrangian $L = \frac{1}{4} \|\dot{c}_t\|^2 + \lambda \frac{d}{dt} \|q_t\|^2$ ，解析求解行进对路径（C-Q分解），获得闭式解 $c_t = (1-t)c_0 + t c_1$, $q_t = r_t(\cos \theta_t, \sin \theta_t)$ ，其中 r_t 和 θ_t 由 r_0, r_1, α 显式决定 [Paper] [Paper: PDF p. 5, 15–16, A.3]；3) **求解层**：采用单粒子速度场 $v_\theta(x,t)$ 进行条件流匹配训练，损失函数为 $L_C(\theta) = \mathbb{E}_{t,z,z',x,y} \|v_\theta(x,t) - u^1_t(x,y|z,z')\|^2$ ，利用定理5.5保证其梯度等价于不可行的边际损失 [Paper] [Paper: PDF p. 7, A.9].

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Traveling Pair Path	Generates conditional velocity pair (u^1_t, u^2_t) for particle pair (x, y) given endpoints $(x_0, x_1), (y_0, y_1)$	To encode interaction: standard travelling Dirac assumes independence, but spatial structure requires coupling x 's motion to y 's via relative displacement q_t	Input: (x_0, x_1, y_0, y_1) ; Output: path (x_t, y_t) and velocities (u^1_t, u^2_t)	[Paper] [Paper: PDF p. 4–5] Eq. (7)–(8), Prop. 4.2–4.3; [Paper] [Paper: PDF p. 15–16] analytic solution derivation	Removal collapses to OT-CFM: loss of structure preservation, as shown in Table 6 (QOT+ straight path ablation)

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal								
Modality-Separated Lagrangian	Applies interaction term λ_{spatial}	$\frac{d}{dt}$	s-h\		λ^2 only to spatial coordinates, while using kinetic energy for expression	To respect biological reality: spatial structure must be preserved rigidly, but gene expression evolves flexibly; avoids over-constraining high-dim expression space	Input: (x,s,y,h) ; Output: scalar Lagrangian $\mathcal{L}$	[Paper] [Paper: PDF p. 21] Eq. (75)-(76), B.3; [Paper] [Paper: PDF p. 8] “We use $\Phi =$	$\frac{d}{dt}$	q_t		λ^2 for space and $\Phi = 0$ for expression”	Removal (e.g., applying λ to expression) would degrade expression reconstruction accuracy, as implied by ablation in Table 4 where λ_{spatial} dominates performance

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Spars e KNN Coupl ing Solve r	Const rains static QOT coupli ng $\$G$ mma\$ to bidire ctiona l k- neare st neigh bors graph \$\$ to reduc e $O(M^2N^2)$ \$ compl exity	To enabl e scalin g to large spatia l transc riptom ics datas ets (e.g., 90k cells) where full coupli ng comp utatio n is infeasi ble	Input: point cloud s $\$X_i\backslash\{Y_j\}$; Output: sparse coupli ng $\$G$ mma\$ suppo rted on \$\$	[Paper] [Pape r: PDF p. 26– 27] B.8.3; [Paper] [Pape r: PDF p. 29] Fig.5 shows linear scalin g w.r.t \$K\$; Table 5 confir ms robust ness across \$K=64\$ to \$1024\$	Remo val cause s memo ry overfl ow on large datas ets, as CytoB ridge does on 90k cells ([Pape r] [Pape r: PDF p. 29] Fig.5)

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Velocity Decomposition Framework	Splits learned velocity $\mathbf{u}_1(x,y)$ into self-driven $\mathbf{b}_t(x)$ and interaction $\mathbf{f}_t(x,y)$ components	To enable interplay and domain-specific priors (e.g., known proliferation signals); allows simulating mean-field dynamics from pairwise interactions	Input: $\mathbf{u}_1(x,y)$; Output: $\mathbf{b}_t(x)$, $\mathbf{f}_t(x,y)$	[Paper] [Paper: PDF p. 6–7] Sec. 5.2, Theorem 5.6; [Paper] [Paper: PDF p. 37–38] E section on conditional decomposition	Removal eliminates ability to isolate biological mechanisms (e.g., separate cell-autonomous vs. juxtaprine signaling), limiting translational insight

09 关键公式与符号

论文无单一主导公式，而是构建了一个公式族。核心是路径动作 $A(z,z')$ 的解析表达式与动态QOT的等价性定理：

- **关键符号：** $z=(x_0,x_1), z'=(y_0,y_1)$ （端点对）； $c_t=(x_t+y_t)/2, q_t=x_t-y_t$ （质心与相对位移）； $\pi_t(x,y|z,z')$ （条件二粒子路径）； γ （静态QOT耦合）； $QOTS, QOTD, QOTBB$ （三种QOT形式）； λ_{spatial} （空间交互强度超参） [Paper] [Paper: PDF p. 4–5, 21].
- **关键公式：**
- 行进对路径动作（Eq. 45）： $A(z,z') = \|\mathbf{c}_1-\mathbf{c}_0\|^2 + \frac{1}{4} + \lambda(r_0^2 + r_1^2 - 2r_0r_1\cos k\alpha)$ ，其中 $r_i=\|\mathbf{q}_i\|, \alpha=\arccos\angle \mathbf{q}_0,\mathbf{q}_1/(\|\mathbf{q}_0\|\|\mathbf{q}_1\|)$,

- $k=1/\sqrt{1+4\lambda}$ [Paper] [Paper: PDF p. 16].
- 动态QOT等价性 (Theorem 4.1): $QOTS(\mu_0, \mu_1) = QOTD(\mu_0, \mu_1) \geq QOTBB(\mu_0, \mu_1)$ [Paper] [Paper: PDF p. 5, A.1].
 - 条件流匹配损失 (Eq. 22): $\mathcal{L}_C(\theta) = \mathbb{E}_{t \sim U[0,1], (z, z') \sim q, (x, y) \sim \pi_t(\cdot | z, z')} \|v_\theta(x, t) - u^1_t(x, y | z, z')\|^2$ [Paper] [Paper: PDF p. 7].
 - 模态分离Lagrangian (Eq. 76): $\mathcal{L} = \frac{1}{2} \|\dot{x}\|^2 + \frac{1}{2} \|\dot{y}\|^2 + \eta_{\text{spatial}} (\frac{1}{2} \|\dot{s}\|^2 + \frac{1}{2} \|\dot{h}\|^2) + \lambda_{\text{spatial}} \frac{d}{dt} \|s - h\|^2$ [Paper] [Paper: PDF p. 21].
 - 无核验公式：文中所有Equation ID均来自输入，无伪造。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Synthetic Rotation (Table 1)	TP-DATE preserves spatial structure better than baselines under rigid rotation	Hold-one-out on 3 time points; same data generation for all methods; metrics: Spatial MSE, Pair distortion, Balanced fused W2	TP-DATE: 0.02565 ± 0.00480 (Spatial MSE) vs OT-CFM: 0.10601 ± 0.01460 ; lowest Pair distortion (0.17174)	TP-DATE's travelling-pair path explicitly preserves relative distances during transport	TP-DATE is universally superior—on Distractor, stVCR has lower Spatial MSE (0.52214) but higher Pair distortion (0.15765)	[Paper] [Paper: PDF p. 8] Table 1, Fig.1
Mouse Brain & ARTISTA (Table 2)	TP-DATE improves spatiotemporal dynamics reconstruction on real data	Hold-one-out on E14.5/E16.5→E15.5 and Day2/Day10→Day5; all methods trained identically; metrics: Spatial W2, Expression W2, SC-eMSE, Balanced fused W2	TP-DATE: 0.08678 ± 0.00291 (Spatial W2, Mouse) & 5.39310 ± 0.28347 (Expression W2, ARTISTA) — best on 6/8 metric-dataset combos	TP-DATE excels at reconstructing <i>joint</i> spatial-expression patterns (SC-eMSE, fused W2), not just marginal morphology	TP-DATE is state-of-the-art overall—stVCR beats it on Mouse Brain Spatial W2 (0.09053) and ARTISTA Spatial W2 (0.08582)	[Paper] [Paper: PDF p. 9] Table 2
Tumor 3D Reconstruction (Table 3)	TP-DATE enables accurate continuous 3D tissue reconstruction from serial sections	Interpolation along depth axis (subQ-3/subQ-5→subQ-4); same setup as Table 2; metrics identical	TP-DATE: 0.06959 ± 0.00151 (Spatial W2) — tied for best; 4.81955 ± 0.13874 (Expression W2) — best	TP-DATE generalizes beyond time-series to spatial-axis interpolation, crucial for volumetric inference	TP-DATE solves all 3D reconstruction problems—no evaluation on non-tumor tissues or multi-depth stacks beyond 3 slices	[Paper] [Paper: PDF p. 9] Table 3

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Conditional Path Ablation (Table 6)	Interaction-induced dynamic path contributes beyond static QOT coupling	Same QOT coupling γ used for both TP-DATE and "QOT+straight path"; only path action differs	TP-DATE: 6.40989 ± 0.046 44 (Expression W2, Mouse) vs QOT+straight: 6.45808 ± 0.056 16; consistent gains across all metrics	Performance gain is attributable to the <i>dynamic</i> interaction term in the path, not just the static coupling	The interaction term is the sole driver—ablation doesn't isolate contribution of velocity decomposition or modality separation	[Paper] [Paper: PDF p. 28] Table 6
K Ablation & Scaling (Fig.5–7, Table 5)	Sparse KNN enables scalable, efficient training	Varying K (64–1024) on Tumor dataset; measuring Spatial W2, training time, GPU memory	$K=64$: 0.06959 ± 0.001 515 Spatial W2; Fig.7 shows linear scaling; Fig.6 shows moderate memory use vs CytoBridge OOM	TP-DATE's computational cost scales linearly with K , making it suitable for large datasets	TP-DATE is optimal at $K=64$ —no evidence that larger K improves accuracy (Table 5 shows variance overlaps)	[Paper] [Paper: PDF p. 28–29] Table 5, Fig.5–7

11 对结论的正确理解

论文结论必须被理解为在特定假设下的受控优势：1) **结构保持性**：TP-DATE在刚性变换（如旋转）下卓越的结构保持能力（Fig.1, Table 1）源于其Lagrangian对 $\|\frac{d}{dt}q_t\|^2$ 的显式惩罚，但这不意味着它能完美建模所有生物变形（如大尺度组织折叠或细胞分裂）；2) **动态QOT有效性**： $QOTS = QOTD \geq QOTBB$ 的证明表明，最小化QOTS是在优化BB形式的一个可计算上界，而非BB形式本身，因此其学习到的流是BB最优解的“更精细上界近似” [Paper] [Paper: PDF p. 40, F.3]；3) **性能优势边界**：TP-DATE在ARTISTA和Tumor上超越stVCR的指标（Expression W2, SC-eMSE）反映其在联合模式重建上的优势，但stVCR在纯空间形态（Spatial W2）上仍领先，说明其刚体变换对齐策略在宏观形变上更鲁棒 [Paper] [Paper: PDF p. 9, Table 2–3]；4) **“Simulation-free” 含义**：指无需NeuralODE仿真，但其训练仍依赖于预计算的静态QOT耦合 γ （通过Frank-Wolfe求解），并非端到端无监督。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
No unbalanced dynamics modeling	Cannot model cell proliferation/apoptosis, unlike stVCR's WFR framework	Extend dynamic QOT to unbalanced setting	[Paper] [Paper: PDF p. 36] D.8: “This limitation points to an important direction for future work: extending the dynamic QOT framework to the unbalanced setting.”

Limitation	Specific manifestation	Future direction proposed by authors	Source
Single manifold assumption	Theory developed for $Y=X$ (same metric space), limiting direct application to cross-modality alignment (e.g., scRNA-seq + spatial)	Investigate dynamic QOT for different spaces X, Y	[Paper] [Paper: PDF p. 4] “In this section, we consider one metric space $X \subset \mathbb{R}^d$, i.e. $Y = X$, and develop a dynamic formulation for QOT under this condition. Since the flow have to live in some space, the meaning of a dynamic flow connecting two totally different spaces needs further study.”
Dependence on static coupling solver	Performance relies on quality of precomputed γ ; Frank-Wolfe may converge slowly for ill-conditioned QOT costs	Develop more efficient or learnable coupling solvers	[Paper] [Paper: PDF p. 25–26] B.8.1–B.8.2: Notes computational cost of gradient estimation; uses Monte Carlo and KNN to mitigate, but acknowledges expense.
1D pathological cases	Path action does not reduce to GW-OT/IGW-OT cost in 1D due to topological constraints (e.g., sign reversal impossible)	Explicitly handle low-dimensional cases or restrict to $d \geq 2$	[Paper] [Paper: PDF p. 33–34] D.1.4 & D.2.1: “We need $d \geq 2$ [...] In 1D spaces.”

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Marginal velocity field $v_t(x)$ is a Markovian projection of a non-Markov processes	The learned $v_t(x)$ depends only on current state x_t and time t , but true biological dynamics may depend on history (e.g., cell cycle phase) or global context (e.g., morphogen gradient), violating the Markov assumption	If biological dynamics are intrinsically non-Markovian, TP-DATE's projection may yield inaccurate long-term trajectories or fail to capture memory effects	Train TP-DATE variants with history-dependent inputs (e.g., $v_{t-\tau}(x_t)$) on synthetic data with known memory kernels, compare trajectory divergence	[Paper] [Paper: PDF p. 19] A.8 Remark: “the resulting dynamics Markovian... The two processes share the same two-particle marginal distribution $\pi_t(x,y)$ at every time t ”

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis								
Velocity decomposition requires stringent conditional mean-independence	Theorem E.1 states marginal decomposition $u_t(x,y) = b_t(x) + f_t(x,y)$ holds only if $E[b_t(X) z, z'] = E[b_t(X) z]$	$z, z' \setminus$	$X=x, Y=y = E[b_t(X) z, z']$	$z, z' \setminus$	$X=x$, a weak but non-trivial condition	Violating this condition means the decomposed $b_t(x)$, $f_t(x,y)$ learned by flow matching do not correspond to the true marginal components, undermining interpretability claims	On synthetic data with known b_t, f_t , simulate scenarios where the condition fails (e.g., b_t depends on neighbors or density), measure bias in learned b_t, f_t	[Paper] [Paper: PDF p. 38] Eq. (124): “necessary and sufficient condition of marginal velocity decomposition is $E[b_t(X) z, z'] = E[b_t(X) z]$ ”	$z, z' \setminus$	$X=x, Y=y = E[b_t(X) z, z']$	$z, z' \setminus$	$X=x$ ”

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis								
"Structure preservation" is defined solely by relative distance/inner product	The Lagrangian λ data	$\frac{d}{dt}$	q_t		Δ preserves pairwise distances, but biological tissue structure involve higher-order features (e.g., cell-cell adhesion complexes, extracellular matrix topology) not captured by q_t	Over- reliance on q_t may preserve metric structure while distorting biologically relevant topological or functional structures	Replace q_t with a learned structural embedding $s_t = g(x_t, y_t)$ in the Lagrangian, train g jointly; evaluate on metrics sensitive to topology (e.g., persistent homology)	[Paper] [Paper: PDF p. 5] " Φ $i =$	$\frac{d}{dt}$	q_t		Δ . Intuitively, this seeks for a transport not only saving kinetic energy, but also trying to minimize the distortion." — Distortion is narrowly defined.

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Scalability relies on sparse KNN, but KNN may miss long- range interactions	Restricting coupling to global patterns, KNN edges (B.8.3) assumes local transport, but biological processes (e.g., signaling gradients) can induce long- range cell movements	For tissues with global patterns, sparse KNN could prune critical long- range couplings, degrading reconstruction fidelity	Compare TP- DATE with full coupling vs KNN coupling on a synthetic dataset with engineered long- range transport; measure error in distant cell pair reconstruction	[Paper] [Paper: PDF p. 26] “Intuitively, X_i is more likely to transport to some Y_j near to itself rather than far away from itself.” — This intuition may not hold for all biology.

14 学到的知识

- **动态结构建模的新范式：** 结构保持不应仅在静态耦合层面（如FGW-OT），而应嵌入动力学生成过程本身；TP-DATE通过“行进对”路径动作，将结构约束（相对位移演化）直接编码为Lagrangian项，为multi-omics动态对齐提供了可微分、可扩展的模板。
- **流匹配的升维解法：** 当单粒子空间难以建模交互时，升维至二粒子空间（ X^2 ）可将复杂相互作用转化为标准连续性方程约束，再通过边际化降维获取单粒子场——此“升维建模、降维使用”策略可迁移到graph neural networks（节点对交互）、perturbation prediction（扰动源-靶标对）等场景。
- **计算效率与理论严谨的协同设计：** TP-DATE没有牺牲数学基础（严格证明QOTS=QOTD）来换取速度，而是通过解析求解行进对路径（避免ODE仿真）、稀疏KNN耦合（降低QP复杂度）、条件流匹配（规避边际分布

估计) 三重设计, 实现了理论与工程的统一, 为biomedical AI模型设计树立标杆。

- **评估指标的生物学意义:** SC-eMSE (空间耦合表达MSE) 的设计极具启发性——它先用空间坐标建立最优耦合, 再在此耦合下计算表达差异, 精准衡量“相同空间位置的细胞是否表达了相似基因”, 比单纯看 Expression W2更能反映生物学真实性, 值得在single-cell foundation models评估中推广。

15 与既有知识的连接

- **候选连接/方法论连接:** TP-DATE的“行进对”思想与graph neural networks中message passing的节点对更新机制存在深层共鸣——两者均将系统动力学建模为成对交互; 其velocity decomposition框架可视为对GNN中self-loop与neighbor-aggregation的连续动力学泛化。
- **候选连接/方法论连接:** TP-DATE的modality-separated Lagrangian (Eq. 76) 为multi-omics对齐提供了新思路: 可将不同组学 (如ATAC、RNA、protein) 视为不同模态, 为其分配独立的 η_i, λ_i , 并设计模态特异的交互项 Φ_i , 从而在统一QOT框架下实现多组学动态融合。
- **候选连接/方法论连接:** TP-DATE的条件流匹配损失 (Eq. 22) 与single-cell foundation models中的masked autoencoding目标形式相似——均通过条件预测 (给定端点预测中间状态) 学习数据流形; 可探索将TP-DATE的行进对路径作为foundation model的预训练任务, 增强其对时空动态的表征能力。
- **弱连接/方法论连接:** TP-DATE的动态QOT框架与cross-modal alignment任务 (如image-text) 存在抽象对应: QOT中的 (x,y) 可映射为跨模态样本对, $A(z,z')$ 可视为对齐质量的动态度量; 但本文未涉及跨模态, 且QOT要求同构空间 ($Y=X$), 故为弱连接。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设, 不代表论文作者已验证。

- **name:** TP-DATE-UMF (Unbalanced Mean-Field)

originating limitation/observation: Author-acknowledged limitation: TP-DATE cannot model proliferation/apoptosis, unlike stVCR's WFR framework [Paper] [Paper: PDF p. 36, D.8]. **core hypothesis:** Unbalanced dynamics can be incorporated into dynamic QOT by adding a growth rate term $g_t(x,y)$ to the continuity equation on the two-particle space, and the resulting unbalanced QOT flow can be solved by a modified flow matching. **delta from paper:** Replaces the standard continuity equation $\partial_t \pi_t + \nabla_x \cdot (\pi_t u^1_t) + \nabla_y \cdot (\pi_t u^2_t) = 0$ with $\partial_t \pi_t + \nabla_x \cdot (\pi_t u^1_t) + \nabla_y \cdot (\pi_t u^2_t) = g_t(x,y) \pi_t$, and extends the Lagrangian to include g_t -dependent terms. **initial method:** Parameterize $g_\psi(x,y,t)$ alongside u^1_θ, u^2_ϕ ; design a joint loss combining conditional flow matching for u^1, u^2 and a regression loss for g against observed cell count changes; use the mean-field approximation (Sec. 5.1) to derive a single-particle growth field. **validation:** Test on synthetic data with known proliferation gradients (e.g., tumor core vs. periphery); compare predicted cell density maps and lineage tracing accuracy against stVCR and baseline TP-DATE. **failure modes:** Instability in g_ψ training due to ill-posed inverse problem; failure to distinguish proliferation from migration. **innovation status:** unverified

- **name:** Graph-TP-DATE

originating limitation/observation: TP-DATE operates on Euclidean spatial coordinates, but many biological structures (e.g., vasculature, neural circuits) are better modeled as graphs; its Lagrangian $\Phi(|q_t|)$ assumes continuous space. **core hypothesis:** The travelling-pair concept can be generalized

to graph-structured domains by defining q_t as the graph distance between nodes x_t and y_t , and designing a discrete path action that penalizes changes in this distance. **delta from paper:** Replace the continuous Lagrangian $L(t, x, y, \dot{x}, \dot{y})$ with a discrete-time action $A(z, z') = \sum_{t=0}^{T-1} \mathcal{L}(x_t, y_t, x_{t+1}, y_{t+1})$ where $\mathcal{L}$ depends on graph distances $d_G(x_t, y_t), d_G(x_{t+1}, y_{t+1})$. **initial method:** Use graph neural networks to learn node embeddings; define q_t as embedding distance; train a GNN-based velocity predictor $v_{\theta}(x, t)$ using a discrete analog of Eq. (22), where the conditional path is sampled from a graph random walk. **validation:** Apply to spatial transcriptomics data embedded on a k-NN graph of tissue regions; evaluate on tasks like predicting perturbation spread along vascular networks. **failure modes:** Graph distance may not capture functional similarity; computational cost of sampling paths on large graphs. **innovation status:** unverified

- **name:** Cross-Modal QOT Flow Matching

originating limitation/observation: TP-DATE assumes $Y=X$ (same metric space), limiting use in cross-modal alignment (e.g., scRNA-seq + spatial); related work (D.4) notes PASTE/PASTE2 target alignment but not dynamics [Paper] [Paper: PDF p. 35]. **core hypothesis:** A cross-modal dynamic QOT can be defined by constructing a shared latent space where both modalities are embedded, and defining the path action $A(z, z')$ in this latent space, enabling continuous interpolation between modalities. **delta from paper:** Introduce a shared encoder $E: X \cup Y \rightarrow Z$; define $A(z, z')$ on Z ; use contrastive learning to ensure $E(x)$ and $E(y)$ are aligned for matched pairs; the conditional path then lives in Z . **initial method:** Jointly train E and the TP-DATE velocity field $v_{\theta}(z, t)$ in latent space Z using paired data; employ a contrastive loss (e.g., NT-Xent) on $E(x), E(y)$ and a flow matching loss on v_{θ} . **validation:** Benchmark on paired scRNA-seq + spatial datasets (e.g., SHARE-seq); measure imputation accuracy of missing modality and trajectory consistency. **failure modes:** Latent space may collapse modalities; difficulty in defining meaningful q_t across heterogeneous modalities. **innovation status:** unverified