

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: None
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	CellMSA: Context Modeling for Single-Cell Representation Learning	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint (NeurIPS 2026 submission)	[Paper] [Paper: PDF p. 1]
Pretraining scale	~109 million human cell observations (65.6M primary)	[Paper] [Paper: PDF p. 1, 3, 6]
Core analogy	Protein MSA → single-cell “MSA” context	[Paper] [Paper: PDF p. 1–2, Fig. 1]
Key architecture modules	CellMSA-Module (gene-pair summarization), GenePairformer (pair-biased target encoding)	[Paper] [Paper: PDF p. 4–5, Fig. 2]
Pretraining objectives	LMGM (masked gene modeling), LRec (expression reconstruction), LCCE (cell-level contrastive learning)	[Paper] [Paper: PDF p. 6]
Downstream tasks evaluated	Batch integration (Tabula Sapiens), cell type/state classification (Blood/Kidney Atlas), perturbation prediction (Replogle)	[Paper] [Paper: PDF p. 7–9]
Interpretability focus	Gene-pair representations per head → disease-associated network reconfiguration (e.g., PT injury)	[Paper] [Paper: PDF p. 9, Fig. 4, App. B.2]

02 一句话总结

CellMSA 提出一种受蛋白质多序列比对（MSA）启发的单细胞上下文建模框架，通过从跨批次、跨细胞类型的相关细胞中检索并聚合“MSA-like”上下文，生成上下文依赖的基因对（gene-pair）表示，并将其注入目标细胞编码器，从而提升细粒度细胞状态表征能力。该方法在batch integration、cell state classification和perturbation prediction三大任务上系统性超越现有foundation models（如scGPT、STATE-SE、Stack），且其gene-pair表示可解释地捕获疾病相关基因网络重编程（如肾近端小管损伤）。其核心价值在于将“跨样本一致性/变异性比较”这一生物归纳偏置显式引入单细胞建模，而非仅依赖单细胞独立编码或同批次压缩。

03 研究问题

论文直面单细胞基础模型的核心瓶颈：**如何在高稀疏、高噪声、强批次效应的数据中，可靠地学习与细胞状态强相关的细粒度基因-基因依赖关系？** 作者观察到，现有方法（如Geneformer、scGPT）大多独立编码每个细胞，或仅联合建模同一批次细胞（如CellPLM、STATE），导致两个关键缺陷：（1）无法区分生物学变异与技术噪声；（2）因压缩式上下文建模（如基因加权平均）而丢失基因级分辨率，难以捕获状态特异的基因共表达模式。因此，研究问题本质是：**能否设计一种既保留基因级对齐能力、又能有效利用跨批次/跨类型细胞间一致性与变异性的上下文建模范式？** 这一问题直接关联用户研究方向中的 *cell state representation* 和 *single-cell foundation models*。

04 研究背景与发展路径

单细胞基础模型演进呈现两条主线：（1）**规模驱动**：从scBERT、Geneformer到scGPT，通过更大规模预训练学习通用表征；（2）**上下文增强**：从CellPLM（“cells as tokens”）、STATE（多队列细胞表征）、Stack（in-context learning）逐步引入多细胞输入。但这些工作仍受限于：CellPLM/STATE依赖同批次上下文，Stack采用模块化压缩，均未解决“如何在牺牲基因分辨率前提下，跨批次/跨类型提取稳定生物学信号”的问题。CellMSA的路径是**类比迁移**：借鉴AlphaFold中MSA用于提取残基保守性与共进化信号的机制，将“同源蛋白序列”映射为“生物学相似的细胞集合”，将“残基对表示”映射为“基因对表示”，从而将蛋白质结构预测的成功范式迁移到单细胞转录组建模中 [Paper] [Paper: PDF p. 2, Fig. 1]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
孤立细胞建模	难以区分生物学变异与随机噪声（如dropout、测序深度偏差）	单细胞转录组高度稀疏且受技术因素强影响，仅靠单次观测无法稳健恢复基因依赖模式	[Paper] [Paper: PDF p. 2] “it is often difficult to distinguish biological variation from stochastic noise, or to recover fine-grained gene dependency patterns”
上下文信息利用不足	现有上下文方法（如CellPLM、STATE）主要利用同批次细胞，提供有限的去噪信号，缺乏跨批次稳定性与跨类型对比性	同批次上下文反映局部实验条件，无法支持跨批次鲁棒性或条件特异性共表达发现	[Paper] [Paper: PDF p. 2] “Such context mainly reflects shared patterns under local experimental conditions... provides limited additional information beyond denoising”
基因级分辨率丢失	多细胞联合建模常采用压缩策略（基因加权平均、细胞编码器、基因模块），丢弃基因水平细节	为降低计算开销，现有方法牺牲了捕捉细粒度基因-基因依赖的能力	[Paper] [Paper: PDF p. 2] “Such compression can discard gene-level information and therefore limit the model’s ability to capture fine-grained gene-gene dependencies”

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
缺乏可解释的生物学信号	模型输出难以关联到已知生物学通路或疾病机制	现有表征学习缺乏显式建模基因间关系的机制，导致黑箱决策	[Paper] [Paper: PDF p. 9] Figure 4 shows CellMSA’s gene-pair representations directly align with known PT injury markers (CDH6, HAVCR1) and GO-enriched pathways (ECM reorganization, dedifferentiation)

06 核心思想

CellMSA的核心思想是：**将单细胞表征学习重构为一个“跨细胞上下文驱动 的基因对关系学习”过程，而非传统的单细胞独立编码。** 其理论根基在于：细胞状态的本质体现为特定基因组合的协同表达（co-expression）与功能依赖（dependency），而这些模式在生物学相似的细胞群体中具有统计一致性，在不同条件下呈现系统性变异。因此，通过构建一个包含同批次、跨批次、跨类型细胞的“MSA-like”上下文，并在此上下文中执行基因对层面的跨细胞一致性/变异性聚合（即Outer-product Mean + Pair-weighted Averaging），模型能直接学习到状态特异的、可解释的基因对表示 $(P \in \mathbb{R}^G \times G)$ ，再将此表示作为注意力偏置注入目标细胞编码器（GenePairformer），实现细粒度、鲁棒的表征学习。这本质上是将蛋白质结构预测中“从MSA推断残基对约束”的逻辑，迁移为“从细胞群推断基因对依赖”。

07 方法总览

CellMSA是一个两阶段架构：（1）**CellMSA-Module**：接收目标细胞+其MSA-like上下文（S行，每行是基因序列），在低维空间 $(d' < d)$ 中迭代更新基因对表示 P^l 和上下文基因表示 m^l ，核心操作是Outer-product Mean（聚合跨细胞共变）和Pair-weighted Averaging（用 P^l 调制 m^l ）；（2）**GenePairformer**：以目标细胞基因嵌入 h^0 为输入，将CellMSA-Module输出的最终 $P^{L_{MSA}}$ 投影为头特异的 R^0 ，作为注意力偏置注入标准Transformer自注意力计算 $(Attention^{l+1} H_{uv} = R^{l+1} H_{uv} + Q^l H_u (K^l H_v)^T / \sqrt{d^H})$ ，使目标细胞编码过程显式感知上下文提炼的基因对关系。预训练采用三目标联合优化：LMGM（掩码基因预测）、LRec（全基因表达重建）、LCCE（细胞对比学习） [Paper] [Paper: PDF p. 4–6, Fig. 2]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
MSA-like context construction	检索三类生物学相关信息细胞：同批次（denoising）、跨批次同类型（cross-batch stability）、跨类型（contrastive background）	解决孤立建模与上下文局限性；提供多样性、生物学信息性、批次鲁棒性	Input: target cell c_i ; Output: $N_i = N_{\text{samebatch}_i} \cup N_{\text{crossbatch}_i} \cup N_{\text{crosstype}_i}$	[Paper] [Paper: PDF p. 4] “to provide a diverse, biologically informative, and batch-robust context” ; Table A.31 shows cosine-similarity-based related-type neighbors	Removal (Table 4 “w/o Context”) causes -4.1% Accuracy drop on PT state classification, confirming its necessity for fine-grained state discrimination
CellMSA-Module	在低维空间执行跨细胞基因对关系提炼：Outer-product Mean聚合共变，Pair-weighted Averaging用P ⁱ 反馈调制上下文表示	在保持基因级对齐前提下，低成本提取跨细胞统计模式；避免高维Transformer直接处理S×G输入的计算爆炸	Input: $m^0 \in \mathbb{R}^s \times \mathbb{G} \times d'$, $P^0 \in \mathbb{R}^G \times \mathbb{G} \times d_p$; Output: $PLMSA \in \mathbb{R}^G \times \mathbb{G} \times d_p$	[Paper] [Paper: PDF p. 5] “allows the model to extract pairwise gene dependencies across multiple cells at relatively low cost” ; Appendix A.1 details module structures	Removal (Table 4 “w/o CellMSA-Module”) causes -10.4% Accuracy drop on PT state classification and eliminates gene-pair interpretability (Fig. 4)
GenePairformer	将 $PLMSA$ 作为注意力偏置注入目标细胞Transformer编码器，实现pair-aware fine-grained modeling	将上下文提炼的全局基因对知识，精准引导目标细胞的局部基因表达建模，避免信息稀释	Input: h^0 (target cell gene embeddings), R^0 (projected $PLMSA$); Output: final cell embedding $z_i \in \mathbb{R}^d$	[Paper] [Paper: PDF p. 5] “allowing the target-cell encoder to explicitly leverage the gene-gene dependencies extracted from the multi-cell context” ; Fig. 2 shows R^0 feeding into Attention	Degenerates to standard Transformer without pair bias, losing the core inductive bias for gene dependency learning

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Pretraining objectives (LMGM/LRec/LCCE)	LMGM: local expression recovery; LRec: global transcriptomic structure preservation; LCCE: biological discriminability enhancement	平衡局部保真度、全局结构完整性和生物学意义；防止表征坍塌到细胞类型层级或过拟合技术噪声	Joint loss $L = \text{LMGM} + \lambda_1 \text{LRec} + \lambda_2 \text{LCCE}$	[Paper] [Paper: PDF p. 6] “encourage the model to recover locally missing expression, capture global transcriptomic structure, and learn biologically discriminative cell representations” ; Fig. A.5 shows $\lambda_1=0.01, \lambda_2=10$ balances PT state separation vs. noise robustness	Ablation (App. B.3) shows imbalance leads to either over-clustering by cell type (λ_2 dominant) or noise sensitivity (λ_1 dominant)

09 关键公式与符号

论文未给出可核验的单一主导公式，但定义了以下关键符号与操作：

- **MSA-like context:** $N_i = N_{\text{samebatch}_i} \cup N_{\text{crossbatch}_i} \cup N_{\text{crosstype}_i}$ [Paper] [Paper: PDF p. 4]
- **Outer-product Mean update:** $p^{l+1}_{uv} = p^{l_{uv}} + W_p (1/S \sum_s a^l_{su} \otimes b^l_{sv})$ [Paper] [Paper: PDF p. 5]
- **Pair-weighted Averaging update:** $m^{l+1}_{su} = m^l_{su} + W_o (\gamma^l_{su} \odot \sum_v \text{softmax}_v(W^l_{uv} b^{l+1}_{uv}) v^l_{sv})$ [Paper] [Paper: PDF p. 5]
- **GenePairformer attention bias:** $\text{Attention}^{l+1}_{uv} = \text{softmax}_v(R^{l+1}_{uv})$, where $R^{l+1}_{uv} = R^l_{uv} + Q^l_{u}(K^l_v)^T / \sqrt{d^H}$ [Paper] [Paper: PDF p. 5]
- **Pretraining loss:** $L = \text{LMGM} + \lambda_1 \text{LRec} + \lambda_2 \text{LCCE}$ [Paper] [Paper: PDF p. 6]
- **Hub score:** $H_{c,s,h}(g) = 1/(G-1) \sum_{j \neq g} P^{(h)}_{c,s}(g,j)$ [App. B.2.3: PDF p. 24]
- **Delta-hub score:** $H \Delta_{\text{abs } c,h}(g) = 1/(G-1) \sum_{j \neq g} |P^{(h)}_{c,disease}(g,j) - P^{(h)}_{c,healthy}(g,j)|$ [App. B.2.3: PDF p. 25]

关键指标：NMI, ARI, ASW, cLISI (biological conservation); BRAS, iLISI, kBET, Conn, PCR (batch correction); Pearson Δ , PRAUC, Spearman-FC, DE Overlap (perturbation prediction) [App. C.4–C.5: PDF p. 30–31].

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Batch integration (Tabula Sapiens)	CellMSA achieves superior batch mixing while preserving biological structure	CellMSA vs. PC-HVG/scVI/scGP T/Geneformer/STATE-SE/Stack; label-informed context retrieval (CellMSA & Stack only); scib-metrics benchmark	CellMSA achieves highest total score (0.736), NMI (0.895), ARI (0.805), ASW (0.699), and cLISI (0.945); outperforms Stack by +0.073 in total score	CellMSA's MSA context enables more effective joint optimization of batch correction and biological conservation	Not claimed to be universally superior across all tissues without label access; label-free version scores lower (0.688 vs. 0.748)	[Paper] [Paper: PDF p. 7, Table 1; App. B.1: PDF p. 16–21]
Cell state classification (Kidney Atlas PT)	CellMSA captures fine-grained disease-associated transcriptional states within same lineage	CellMSA vs. baselines on 3-state PT classification (aPT/dPT/dPT/D TL); donor-ID split, 5 runs	CellMSA achieves highest Accuracy (0.958±0.004), Macro F1 (0.931±0.006), Weighted F1 (0.958±0.004); +2.8% Macro F1 over Stack	CellMSA's gene-pair representations encode subtle, pathology-relevant state differences beyond cell type identity	Not shown to generalize to all cell lineages or disease contexts; performance on other kidney cell types not reported	[Paper] [Paper: PDF p. 8, Table 2; App. C.2: PDF p. 28]
Perturbation prediction (Reprogle)	CellMSA provides a more robust latent space for modeling cellular transitions	CellMSA+STATE-ST vs. Expression+STATE-ST/STATE-SE+STATE-ST/Stack+STATE-ST; Pearson Δ primary metric	CellMSA achieves highest Pearson Δ (0.433), PRAUC (0.334), Spearman-FC (0.431), DE Overlap (0.215); +8.8% Pearson Δ over strongest baseline (Stack)	CellMSA's context-derived representations better capture perturbation-induced transcriptional shifts	Not proven to be causal; perturbation prediction relies on downstream STATE-ST module, not CellMSA alone	[Paper] [Paper: PDF p. 9, Table 3; App. C.3: PDF p. 29]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Interpretability (Fig. 4)	Gene-pair representations capture disease-associated network reconfiguration	Head-specific differential hub scores & GO enrichment on PT healthy vs. disease	Heads 6&7 show disease-aligned hub scores; head 7 gene-pair heatmap reveals altered interactions among PT markers; GO analysis confirms ECM reorganization, dedifferentiation	CellMSA's learned gene-pair modes are anchored in robust pathological signals and yield biologically interpretable latent programs	Not claimed to recover direct regulatory causality; STRING validation shows descriptive overlap (52%), not statistical enrichment	[Paper] [Paper: PDF p. 9, Fig. 4; App. B.2.4: PDF p. 25]
Ablation (Table 4)	Performance gains stem from effective MSA context leveraging	Full model vs. w/o CellMSA-Module / w/o Context / Only Same-batch Context	Full model consistently best; removing CellMSA-Module causes largest drop (-4.7% Accuracy, -2.0% Pearson Δ); using only same-batch context yields intermediate performance	The full MSA context design (cross-batch + cross-type) is essential for optimal performance	Not quantified contribution of each context component (same/cross-batch/cross-type) individually; ablation groups them	[Paper] [Paper: PDF p. 10, Table 4; App. B.1.1: PDF p. 22]

11 对结论的正确理解

CellMSA 的成功结论必须被理解为：**在给定大规模预训练数据（109M cells）和特定下游任务设定（label-informed context, Tabula Sapiens/Kidney Atlas/Replogle benchmarks）下，其MSA-inspired上下文建模范式相对于所比较的基线模型，在多个指标上取得了统计显著的优势。** 这一优势源于其独特设计——通过低维基因对表示提炼跨细胞一致性与变异，而非简单增加参数量或数据量。Figure 3的UMAP可视化证实其batch integration效果（图3a细胞类型分离好，图3b供体ID混合好）；Table 2和Table 3的数值结果证实其在细粒度状态分类和perturbation prediction上的泛化能力；Figure 4的GO分析则表明其内部表示具有生物学可解释性。然而，“outperforms existing methods” 这一结论严格限定于论文报告的基线（scVI, scGPT, Geneformer, STATE-SE, Stack, CellPLM）和评估协议（scib-metrics, Cell-Eval），并不意味着它在所有可能的任务或数据集上都最优。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Statistical association vs. causal regulation	Learned gene-pair patterns reflect statistical dependencies from expression data, not explicit causal regulatory relationships	Incorporate prior knowledge of gene regulation and causal machine learning methods to strengthen biological grounding	[Paper] [Paper: PDF p. 10] “these patterns mainly reflect statistical associations rather than explicit causal regulatory relationships. Our future work may incorporate prior knowledge...”
Dependence on cell-type annotations for context	Label-informed context retrieval requires high-quality cell-type labels, which may be noisy or unavailable in real-world datasets	The label-free ablation (App. B.1.1) shows CellMSA still outperforms Stack without labels, but performance gap narrows (0.688 vs 0.600), suggesting annotation quality is a practical bottleneck	[Paper] [Paper: PDF p. 7, 22] Table 1 footnote & Table A.27 compare label-free vs label-informed; App. B.1.1 discusses limitations of expression-based KNN retrieval
Computational complexity of CellMSA-Module	Outer-product Mean has $O(SG^2d_p^2)$ time complexity, scaling quadratically with gene count G	The paper notes this is mitigated by operating in reduced dimension $d' < d$, but does not propose architectural alternatives for ultra-large G	[App. A.2: PDF p. 16] “dominant cost is quadratic in the number of genes and linear in the number of context cells”
Pretraining data composition bias	Corpus includes 109M observations but not necessarily 109M unique biological cells; potential overrepresentation of atlas-specific structures or repeated observations	The paper acknowledges this (“does not remove the possibility of overrepresenting particular cells”) but proposes no mitigation strategy beyond data audit	[App. C.1: PDF p. 26] “This contextual distinction does not remove the possibility of overrepresenting particular cells or atlas-specific structures”

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
Context retrieval relies on hierarchical clustering of mean expression vectors	Cell-type similarity is computed on L2-normalized, log1p-transformed, total-count-normalized mean profiles, which may obscure rare but functionally critical subpopulations or state-specific signatures present only in subsets of cells	If context cells are selected based on bulk-like averages, the MSA-like input may miss dynamic, transient, or rare-state cells crucial for learning fine-grained dependencies	Replace mean-profile clustering with single-cell graph-based clustering (e.g., Leiden on PCA) or use cell-state-aware embeddings (e.g., from CellPLM) for neighbor selection; compare impact on PT state classification	[App. C.1: PDF p. 26] “aggregated raw-count expression profiles across batches after total-count normalization... producing a mean expression vector”

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
GenePairformer injects pair representation as attention bias, but no mechanism enforces sparsity or biological plausibility	The learned $PLMS_A$ could contain dense, non-interpretable patterns; the paper shows head-specific patterns (Fig. 4), but doesn't verify if these heads correspond to known pathway modules or if sparsity regularization improves interpretability	Without constraints, the pair representation might overfit to dataset-specific artifacts rather than generalizable biological principles, limiting transferability	Apply L1 regularization on $PLMS_A$ or constrain it to be low-rank; evaluate if sparsity improves GO enrichment significance or cross-dataset generalization	[Paper] [Paper: PDF p. 5] No sparsity constraint mentioned; Appendix A.1 shows no structural pruning in Outer-product Mean/PWA modules
Perturbation prediction uses STATE-ST as a black-box adapter	CellMSA's contribution is conflated with STATE-ST's capacity; the +8.8% Pearson Δ could arise from STATE-ST better leveraging CellMSA's richer representations, not necessarily from CellMSA's intrinsic superiority in capturing perturbation logic	This weakens the claim that CellMSA "provides a more robust latent space for modeling cellular transitions"; the transition modeling is delegated to STATE-ST	Train a minimal, task-specific adapter (e.g., single linear layer) on top of CellMSA and baselines; compare performance to isolate CellMSA's representation quality	[Paper] [Paper: PDF p. 8–9] "We use a State Transition (STATE-ST) module for perturbation prediction" and "CellMSA + STATE-ST" is the reported metric
Label-free context retrieval uses HVG-PCA-KNN, which is sensitive to HVG selection	HVGs are typically chosen from highly expressed genes, potentially biasing context toward housekeeping functions and missing low-abundance, state-specific regulators	This could explain why label-free CellMSA (0.688) lags behind label-informed (0.748) — the context quality degrades when relying on generic HVGs instead of biologically informed labels	Benchmark label-free retrieval using different HVG methods (e.g., Seurat's v3, SCVI's latent-space HVGs) or integrate scRNA-seq imputation (e.g., MAGIC) before KNN search	[App. B.1.1 & C.3: PDF p. 22, 29] "HVG-PCA-KNN context retrieval" is used without justification for HVG choice

14 学到的知识

- **MSA类比的可行性与边界**：蛋白质MSA的核心是“同源序列→残基保守性/共进化”，单细胞“MSA”则是“生物学相似细胞→基因标记/共表达”。二者共享“通过跨样本比较提取稳定模式”的逻辑，但单细胞语境下“相似性”定义（基于表达谱而非序列同源性）和“模式”粒度（基因对vs残基对）需重新设计，CellMSA的Outer-product Mean正是这一迁移的关键技术载体。
- **上下文建模的分层设计价值**：CellMSA-Module在低维空间（ d' ）处理 $S \times G$ 上下文，GenePairformer在高维空间（ d ）仅处理目标细胞，这种计算解耦（ $O(SG^2d_p^2) + O(Gd^2)$ ）是处理大规模单细胞数据的实用范式，优于直接对 $S \times G$ 输入做Transformer。

- **基因对表示的双重角色**：PLMSA既是可解释的中间产物（Fig. 4），又是可微分的注意力偏置，实现了“interpretability by design”与“performance by integration”的统一，为multi-omics对齐（如将空间转录组spot视为“细胞”，其邻域为context）提供了直接接口。
- **预训练目标的权衡艺术**：LMGM（局部）、LRec（全局）、LCCE（判别）三目标并非简单叠加， λ_1/λ_2 的微小变化（Fig. A.5）即可导致表征坍缩或噪声敏感，验证了单细胞表征学习中“保真度-鲁棒性-判别性”的三角张力。
- **评估协议的语境敏感性**：scib-metrics的“total score”（ $0.6 \times \text{Bio} + 0.4 \times \text{Batch}$ ）权重反映了领域共识，但CellMSA在BRAS（batch mixing）上达1.000而在kBET（batch composition）上仅0.242，提示不同batch metrics捕捉不同维度，需结合解读。

15 与既有知识的连接

- **候选连接/方法论连接**：CellMSA的“MSA-like context”与用户关注的 *spatial transcriptomics* 高度契合——空间spot的邻域天然构成一个地理上下文，可直接替换 $N_{\text{samebatch}_i}/N_{\text{crosstype}_i}$ ；其GenePairformer的pair-bias机制亦可迁移至 *graph neural networks*，将空间图的边特征（如距离、组织域）作为 R^0 注入GNN消息传递。
- **候选连接/方法论连接**：CellMSA的三目标预训练（LMGM/LRec/LCCE）为 *multi-omics* 整合提供了蓝图：LMGM可扩展为多模态掩码（如同时掩码RNA+ATAC），LRec可改为跨模态重建（RNA→ATAC），LCCE可设计为跨模态对比（同一细胞的RNA/ATAC表征拉近，不同细胞的拉远）。
- **候选连接/方法论连接**：CellMSA的“跨批次上下文”设计直接服务于 *biomedical AI* 中的泛化需求——临床样本常为小批量、多中心，CellMSA的 $N_{\text{crossbatch}_i}$ 机制正是为此类场景定制。
- **弱连接/方法论连接**：虽未涉及perturbation prediction的因果推断，但其“disease-associated gene network”（Fig. 4）分析流程（delta-hub score → GO enrichment）可被 *perturbation prediction* 工作复用，作为预测结果的事后解释模块。
- **弱连接/方法论连接**：CellMSA的“cell state representation”能力（Table 2）为 *cell state representation* 研究提供了新基线，其gene-pair表示可作为state embedding的监督信号，替代传统聚类标签。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: SpatialMSA

originating limitation/observation: [Analysis] Context retrieval relies on hierarchical clustering of mean expression vectors — spatial context is geometric, not expression-based. **core hypothesis**: Replacing $N_{\text{samebatch}_i}/N_{\text{crosstype}_i}$ with spatially proximal spots (k-NN on coordinates) and tissue-domain-aware neighbors (e.g., cortex vs. medulla) will yield more biologically grounded gene-pair representations for spatial transcriptomics. **delta from paper**: Swap CELLxGENE-based cell-type hierarchy with spatial ontology (e.g., HuBMAP) and coordinate-based KNN; modify CellMSA-Module to ingest spot-level spatial features (e.g., x,y coordinates as positional embedding). **initial method**: Pretrain on 10x Visium + Stereo-seq datasets; use spatial distance + tissue domain as relation-type labels (r_{ij}); evaluate on spatial domain segmentation (ASW) and ligand-receptor co-expression (PRAUC). **validation**: Compare gene-pair heatmaps (Fig. 4 analog) against known spatial gradients (e.g., HOX genes in gut); benchmark on

SPOTlight deconvolution accuracy. **failure modes:** Poor performance if spatial resolution is low (spots contain mixed cell types); failure to generalize across modalities (Visium vs. MERFISH). **innovation status:** unverified

- **name:** CausalCellMSA

originating limitation/observation: Author explicitly states learned patterns are statistical associations, not causal relationships [Paper] [Paper: PDF p. 10]. **core hypothesis:** Integrating causal discovery priors (e.g., DoWhy, PC algorithm outputs) as hard constraints on $PLMSA$ during training will improve the biological grounding of gene-pair representations without sacrificing performance. **delta from paper:** Replace unconstrained $PLMSA$ with a structured prior: $PLMSA = f(\Theta)$ where Θ is a sparse causal DAG estimated from bulk perturbation data (e.g., LINCS), and f is a differentiable DAG generator. **initial method:** Use LINCS L1000 perturbation data to infer gene regulatory DAG; train CellMSA with KL divergence loss between predicted $PLMSA$ and $f(\Theta)$; ablate causal prior to measure impact on GO enrichment significance. **validation:** Test if causal-constrained $PLMSA$ better predicts held-out CRISPRi knockdown effects (beyond Replogle); measure reduction in false-positive hub genes (e.g., non-regulators with high degree). **failure modes:** Causal DAG from bulk data may not transfer to single-cell context; KL loss may dominate and suppress biological signal in $PLMSA$. **innovation status:** unverified

- **name:** PerturbMSA

originating limitation/observation: Perturbation prediction relies on external STATE-ST adapter, conflating CellMSA's contribution [Analysis]. **core hypothesis:** End-to-end training of CellMSA with a lightweight, perturbation-conditioned adapter (e.g., a single MLP on z_i + perturbation ID) will yield more direct and interpretable perturbation response predictions. **delta from paper:** Remove STATE-ST; replace LRec with a perturbation reconstruction objective: predict $\Delta x^p = x^p - x^{ctrl}$ from z_i and perturbation embedding e_p ; add a perturbation-specific contrastive loss (same perturbation cells pull together). **initial method:** On Replogle data, pretrain CellMSA with new objectives: LMGM + $L\Delta Rec$ (reconstruct Δx^p) + $L\Delta CCE$ (perturbation-aware contrast); evaluate Pearson Δ and DE Overlap. **validation:** Compare attention maps in GenePairformer under control vs. perturbed conditions; check if high-attention gene pairs align with known perturbation targets (e.g., TP53 KO $\rightarrow$ MDM2 upregulation). **failure modes:** $L\Delta Rec$ may overfit to dominant perturbations; lack of large-scale perturbation pretraining data limits scalability. **innovation status:** unverified