

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: resource
Secondary analytical lens: methods
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	STP-BENCH: A Unified Systematic Benchmark for Virtual Spatial Transcriptomics from Histopathology Images	[Paper] [Paper: PDF p. 1]
Authors	Youngmin Chung, Ji Hun Ha, Andrew H. Song, et al.	[Paper] [Paper: PDF p. 1]
Venue	arXiv preprint	[Paper: URL]
Year	2026	[Paper: Published]
Core contribution	First large-scale, standardized benchmark for virtual ST models, enabling controlled comparison of architectures under unified PFM encoding, multi-granularity biological evaluation, and domain-shift robustness testing	[Paper] [Paper: PDF p. 2–4], [Paper] [Paper: PDF p. 5 Fig. 1], [Paper] [Paper: PDF p. 18–19]
Key datasets	STP-BENCH-INTERNAL (609,024 spots, 6 cancer types, Visium/Xenium); STP-BENCH-EXTERNAL (185,831 spots, same 6 cancers)	[Paper] [Paper: PDF p. 4], [Figure 1b], [Paper] [Paper: PDF p. 21]
Evaluated models	21 models: 14 regression-based, 4 bi-modal retrieval, 3 generative	[Paper] [Paper: PDF p. 6], [Figure 1c], [Paper] [Paper: PDF p. 22]
Primary metric	Pearson Correlation Coefficient (PCC) per gene, averaged across spots → sections → folds → datasets	[Equation 1], [Paper] [Paper: PDF p. 31], [Figure 2a]
Code & data	Publicly released at https://github.com/NEXGEM/STP-Bench and Hugging Face	[Paper] [Paper: PDF p. 37]

02 一句话总结

STP-BENCH 是首个面向 virtual spatial transcriptomics (vST) 的系统性、大规模、标准化基准，它通过统一病理基础模型 (PFM) 编码器解耦架构创新与图像表征能力，揭示多数现有模型未超越线性探针基线；该基准

不仅量化基因级预测精度，更首次在基因集、细胞类型丰度、空间结构域等多生物学粒度上评估下游效用，并系统刻画跨机构、跨组织、跨平台泛化鲁棒性。其核心价值在于提供可复现、可归因、可迁移的评估框架，而非提出新模型——这使其成为 single-cell foundation models、spatial transcriptomics 和 biomedical AI 领域方法验证与迭代的关键基础设施。边界明确：仅覆盖 spot-level vST（非 single-cell resolution），限于 6 种癌症和 2 种平台（Visium/Xenium），未涉及 perturbation prediction 或 cross-modal alignment 的显式建模。

03 研究问题

论文直面一个**评估失焦**问题：virtual ST 领域虽涌现大量模型（回归/检索/生成），但缺乏公平、可控、可复现的基准，导致无法判断性能提升源于架构创新还是图像编码器差异；进而引申出三个子问题：（1）当统一使用 UNiv2 等 PFM 作为 patch encoder 时，现有模型的真实架构优势是否仍成立？（2）哪些基因或基因集能被稳定地从形态学中恢复？这种可预测性是否具有生物学一致性？（3）vST 预测结果能否支撑下游生物分析任务（如 cell type deconvolution、spatial domain identification），且其可靠性是否随数据质量（如 Xenium vs Visium）和域偏移（cross-tissue）而系统性变化？这些问题共同指向一个根本目标：建立一个能分离“表征能力”与“建模能力”、连接“预测精度”与“生物效用”的评估范式。

04 研究背景与发展路径

背景始于 ST 技术的高成本瓶颈与 H&E 图像蕴含转录信息的生物学共识，催生了 virtual ST 这一计算替代路径。发展路径呈现两条交织线索：一是**模型范式演进**——从早期回归模型（ST-Net）扩展至融合邻域/全局上下文（TRIPLEX, DeepSpot）、引入 exemplar 检索（EGN）、CLIP 式双模对齐（BLEEP, STco）及生成建模（STFlow, Stem）；二是**评估范式退化**——既有工作（Wang et al. 2024; HEST-1K）或沿用原生 encoder 导致架构与编码器混淆 [Paper] [Paper: PDF p. 3–4]，或仅用简单回归器测试 PFM embedding 而忽略完整模型链路 [Paper] [Paper: PDF p. 3]，均未能实现“控制变量”式比较。STP-BENCH 的提出正是对这一评估断层的直接回应：它不延续单点模型优化路径，而是构建一个正交于模型开发的基础设施层，将评估本身升格为可被严格定义、测量和质疑的科学活动。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
评估不公平性	模型排名高度依赖所用图像编码器，导致架构贡献被掩盖	“architectural innovations and image encoding have been conflated in previous evaluations”；不同 encoder（ResNet50 vs UNiv2）使 CFANet 排名从第16跃至第6 [Paper] [Paper: PDF p. 2, 9]	[Paper] [Paper: PDF p. 2] “unified morphological encoding substantially re-orders model rankings”；[Figure 2b]; [Paper] [Paper: PDF p. 9] “CFANet... jumped to 6th when using UNiv2”

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
评价维度单一	仅报告 aggregate gene-level PCC，忽略 per-gene 可预测性、基因集功能、下游任务效用	Prior studies “leave the biological reliability... and model robustness... largely unexamined” [Paper] [Paper: PDF p. 3]; “evaluation has been confined to aggregate predictive accuracy” [Paper] [Paper: PDF p. 4]	[Paper] [Paper: PDF p. 3–4]; [Figure 1e-f]; [Paper] [Paper: PDF p. 11–14] gene-wise heatmap & gene set analysis; [Figure 4] cell type & domain evaluation
鲁棒性未知	模型在真实场景（跨医院、跨癌种、跨平台）下的泛化能力未经系统检验	“model robustness under realistic distribution shifts largely unexamined” [Paper] [Paper: PDF p. 3]; “no existing benchmark... assesses model reliability under domain shifts” [Paper] [Paper: PDF p. 4]	[Figure 5a-b]; [Paper] [Paper: PDF p. 17] “cross-institution”, “cross-tissue”, “cross-platform” transfer experiments; [Paper] [Paper: PDF p. 19] “cross-tissue generalization was challenging”
数据驱动瓶颈	性能差异可能源于底层 ST 数据质量（如 transcript counts），而非模型能力	“the quality of the underlying transcript detection plays a role in the model’s predictive performance” [Paper] [Paper: PDF p. 10]; “gene expression prediction gap between platforms” [Paper] [Paper: PDF p. 14]	[Figure 2c-d] NCCHE-LUAD-Xenium (high counts) vs NCCHE-LUAD-Visium (low counts); [Paper] [Paper: PDF p. 10] “marker-gene prediction was substantially weaker” in Visium; [Paper] [Paper: PDF p. 14] “concordance suggests that transcript-level data quality constitutes a key determinant”

06 核心思想

论文的核心思想是：**virtual ST 的评估必须从“黑箱精度竞赛”转向“白盒能力解构”**。这体现为三个相互支撑的支柱：（1）**解耦原则**：强制统一 PFM（如 UNiv2）作为所有兼容模型的 patch encoder，将图像表征能力（encoder）与建模能力（architecture）分离，使模型比较真正反映后者价值；（2）**多粒度验证原则**：拒绝仅用 HMHVG 平均 PCC 定论，转而系统考察基因级（哪些基因可预测）、基因集级（哪些通路可恢复）、细胞级（cell abundance 是否准确）、组织级（spatial domains 是否可识别）的逐层效用，形成从分子到组织的证据链；（3）**现实鲁棒性原则**：将泛化性视为核心指标，设计 cross-institution/tissue/platform 三类域偏移实验，揭示模型优势的适用边界（如 multi-scale 架构在 cross-tissue 下失效），从而指导临床部署而非仅追求内参最优。

07 方法总览

STP-BENCH 的方法论是一个**四层评估栈**：（1）**数据层**：构建 STP-BENCH-INTERNAL（609k spots, 6 cancers, 2 platforms）与 STP-BENCH-EXTERNAL（186k spots, strict train/test separation），统一预处理（Visium patch cropping, Xenium pseudo-spot binning）[Paper] [Paper: PDF p. 4–6, 21–22]；（2）**模型层**：重实现

21 个模型，按架构分为 Regression (14)、Bi-Retrieval (4)、Generative (3)，对兼容者强制替换为 UNIV2 encoder [Paper] [Paper: PDF p. 6–7, 22–29]; (3) **度量层**：主用 PCC (Eq.1)，辅以 MAE (Eq.2) 和 SSIM，覆盖精度、误差、空间结构三维度 [Paper] [Paper: PDF p. 31–32]; (4) **分析层**：执行四大分析模块——内部性能基准 (Fig.2)、基因/基因集剖析 (Fig.3)、下游生物效用 (Fig.4)、鲁棒性与可扩展性 (Fig.5)，每项均基于统一 pipeline 与 cross-validation [Paper] [Paper: PDF p. 7–18]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Unified PFM Encoder (e.g., UNIV2)	Standardizes histology feature extraction across all compatible models	To isolate architectural contribution from encoder quality; prior work conflated them [Paper] [Paper: PDF p. 2, 9]	Input: 224×224 H&E patch; Output: fixed-dim embedding vector	[Figure 2a-b], [Paper] [Paper: PDF p. 7–9], [Paper] [Paper: PDF p. 22–23] "image encoder of each model was replaced with a common PFM"	Model rankings collapse to noise; e.g., CFANet drops from top-6 to bottom-tier without UNIV2 [Figure 2b]
Gene Set Scoring (singscore)	Computes per-spot activity score for GO Biological Process terms from predicted expression	To bridge gene-level prediction to functional pathway recovery, beyond individual gene PCC	Input: predicted & ground-truth spot-by-gene matrix; Output: spot-by-gene-set correlation (PCC)	[Figure 3c-e], [Paper] [Paper: PDF p. 13], [Paper] [Paper: PDF p. 35] "gene set level prediction analysis using singscore"	Loss of biological interpretability; TRIPLEX/DeepSpot advantage over baseline would be invisible at gene-set level [Figure 3c]
Cell Type Deconvolution (Cell2location)	Estimates spatial abundance of cell types from vST profiles	To test if vST preserves cellular composition structure required for downstream analysis	Input: vST expression matrix; Output: per-spot cell-type abundance estimates (vs ground-truth)	[Figure 4a], [Paper] [Paper: PDF p. 14], [Paper] [Paper: PDF p. 35] "applied Cell2location to both true and model-predicted matrices"	Downstream utility claim becomes unsubstantiated; TRIPLEX/DeepSpot superiority in cell abundance correlation vanishes [Figure 4a]
Spatial Domain Identification (SpaGCN)	Clusters spots into spatially contiguous domains from vST profiles	To evaluate if vST captures tissue-level architectural organization, not just molecular signals	Input: vST expression + coordinates; Output: Adjusted Rand Index (ARI) vs reference domains	[Figure 4b-c], [Paper] [Paper: PDF p. 14], [Paper] [Paper: PDF p. 36] "applied SpaGCN to both ground-truth and model-predicted matrices"	Inability to validate spatial coherence; ARI scores for TRIPLEX/DeepSpot on Xenium would lack empirical support [Figure 4c]

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Cross-Tissue Generalization Test	Evaluates model trained on one cancer type (e.g., LUAD) on another (e.g., BRCA)	To quantify the tissue-specificity of morphology-to-expression mapping, a key real-world constraint	Input: model checkpoint trained on source cancer; Output: PCC drop on target cancer (generalization gap)	[Figure 5b middle], [Paper] [Paper: PDF p. 17] "cross-tissue transfer... challenged models to generalize across different anatomical sites"	Over-optimistic deployment guidance; failure to reveal that cross-tissue gap (-0.2 to -0.35) dwarfs cross-institution gap (-0.05 to -0.10) [Figure 5b]

09 关键公式与符号

论文明确给出两个可核验公式：

- **Equation 1** ([Paper] [Paper: PDF p. 31])：Pearson Correlation Coefficient (PCC)，用于 spot-level gene-wise prediction accuracy：
$$\text{PCC}_{g,s} = \frac{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)(y_{i,g} - \bar{y}_g)}{\sqrt{\sum_{i=1}^N (\hat{y}_{i,g} - \bar{\hat{y}}_g)^2 \cdot \sum_{i=1}^N (y_{i,g} - \bar{y}_g)^2}}$$

符号： $\hat{y}_{i,g}$ 为 spot i 上 gene g 的预测 log-normalized 表达； $y_{i,g}$ 为 ground-truth； $\bar{\hat{y}}_g$, $\bar{y}_g$ 为其均值； N 为 spots 数量。
- **Equation 2** ([Paper] [Paper: PDF p. 32])：Mean Absolute Error (MAE)，用于量化预测误差幅度：
$$\text{MAE}_{g,s} = \frac{1}{N} \sum_{i=1}^N |\hat{y}_{i,g} - y_{i,g}|$$

符号同上。无其他可核验公式。关键指标符号：PCC（Pearson Correlation Coefficient）、SSIM（Structural Similarity Index Measure）、MAE（Mean Absolute Error）、ARI（Adjusted Rand Index）、HMHVG（high-mean highly-variable genes）、TME（tumor microenvironment）。所有指标均在 [Paper] [Paper: PDF p. 31–32] 明确定义。

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
UNiv2 vs Native Encoder (Fig.2b)	Unified PFM standardization changes model rankings	Compare CFANet's rank with native encoder (linear projection) vs UNiv2; same dataset (STP-BENCH-INTERNAL), same HMHVG genes	CFANet rank jumps from 16th → 6th with UNiv2	Encoder choice dominates reported architectural gains; fair comparison requires encoder standardization	UNiv2 is universally optimal encoder (not tested across all PFMs in this exp)	[Figure 2b], [Paper] [Paper: PDF p. 9]

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Gene Expression Level Stratification (Fig.2c-d)	Prediction accuracy depends on basal transcript count	Stratify genes into 5 bins by mean expression; compute PCC per bin for NCCHE-LUAD-Xenium/Visium	Strong correlation ($p < 1e-12$) between expression level and PCC; Xenium (high counts) achieves $PCC \approx 0.58$, Visium (low counts) $PCC \approx 0.19$ for markers	Data quality (transcript count) is a primary bottleneck, not just model architecture	All low-expression genes are inherently unpredictable (not tested; some may be predictable with better models)	[Figure 2c-d], [Paper] [Paper: PDF p. 10]
Multi-scale Architecture Advantage (Fig.3b)	TRIPLEX/DeepS pot gain over linear probe is gene-category specific	Compute $\Delta PCC = PCC_{\text{model}} - PCC_{\text{Linear}}_{\text{rProb}}$ for genes with $PCC \geq 0.4$ & $\Delta PCC \geq 0.1$	Top gains in stromal (COL1A1), immune (LAG3), epithelial (AZGP1) genes; TRIPLEX/DeepS pot dominate	Multi-scale context (local+neighbor+global) is critical for genes dependent on meso/macro-scale morphology	This advantage extends to single-cell resolution (not evaluated; STP-BENCH is spot-level)	[Figure 3b], [Paper] [Paper: PDF p. 11–13]
Downstream Utility (Fig.4a)	vST profiles preserve cell-type spatial organization	Apply Cell2location to vST profiles; correlate predicted vs ground-truth cell abundance per cell type	TRIPLEX/DeepS pot achieve highest avg PCC; malignant epithelial/T cells well-recovered, plasma/mast cells poorly recovered	Gene-level accuracy translates to cellular granularity; vST utility is hierarchical	vST can replace true ST for clinical cell typing (not validated; rare populations show low correlation)	[Figure 4a], [Paper] [Paper: PDF p. 14]
Cross-Tissue Generalization (Fig.5b middle)	Morphology-to-expression mapping is highly tissue-specific	Train model on LUAD, test on BRCA; measure PCC drop (generalization gap)	Gap reaches -0.20 to -0.35, far larger than cross-institution gap (-0.05 to -0.10)	Cross-tissue transfer is the most challenging real-world scenario; simple data aggregation harms performance	Domain adaptation can fully close this gap (not tested; inter-cohort scaling showed negative transfer [Fig.5d])	[Figure 5b], [Paper] [Paper: PDF p. 17]

11 对结论的正确理解

论文结论必须被精确限定在其实证范围内：(1) “多数模型未超越线性探针” 仅指在**UNlv2 编码器下、spot-level HMMVG/Marker 基因 PCC** 这一特定评估设置中，不否定其 在其他 encoder、其他基因集、其他任务（如 retrieval）上的价值；(2) “multi-scale 架构优势” 特指对**stromal/immune/epithelial 基因**的预测增益，源于其对 meso/macro-scale 形态的建模能力，而非普适性架构优越；(3) “Xenium 数据质量更高” 是**经验观察**（NCCHE-LUAD-Xenium 平均计数 52.1 vs Visium 9.2），支撑了“数据质量是瓶颈”的推论，但未证明 Xenium 在所有癌种/平台对比中均优；(4) “cross-tissue 泛化最难” 是基于**6 癌种间转移**的实证，不意味着所有跨组织场景均不可行，亦不排除 tissue-aware 方法的潜力；(5) “negative transfer in inter-cohort scaling” 指在**BRCA→LUAD→PRAD 顺序添加**时性能下降，不否定其他数据混合策略（如 curriculum learning）的有效性。所有结论均锚定于 STP-BENCH 的具体设计，不可外推至 single-cell 或非-ST 领域。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited cancer types & platforms	STP-BENCH covers only 6 cancers and 2 ST platforms (Visium/Xenium), constraining generalizability	Extend benchmark to additional tumor types, tissue contexts, and emerging sequencing platforms	[Paper] [Paper: PDF p. 20]
Restricted gene panel	Gene-level analyses focused only on HMMVGs and 16 TME markers; systematic investigation of lowly expressed or functionally diverse genes remains open	Systematic investigation of lowly expressed or functionally diverse genes	[Paper] [Paper: PDF p. 20]
Spot-level resolution	Evaluations performed at spot-level (aggregating multiple cells), not single-cell resolution	Future benchmarking efforts may extend these principles to single-cell ST datasets and models	[Paper] [Paper: PDF p. 20]
No single-cell ST integration	Benchmark does not incorporate single-cell ST data or models, despite increasing availability	Not explicitly stated as future direction, but implied by the limitation on resolution	[Paper] [Paper: PDF p. 20]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
TRIPLEX/DeepSpot's multi-scale advantage may conflate architecture with training data scale	These top performers were trained on the largest internal datasets (e.g., WUSTL-BRCA: 157k spots); their edge could stem from data volume, not architectural design per se	Misattribution could misguide architecture search; users might over-invest in complex multi-scale models when data scaling suffices	Re-train TRIPLEX/DeepSpot on smaller subsets (e.g., 33% of WUSTL-BRCA) and compare to simpler models (e.g., LinearProb) trained on same subset; control for data volume	[Figure 5c] shows intra-cohort scaling yields only marginal gains, but doesn't isolate architecture $\times$ data interaction; [Paper] [Paper: PDF p. 21] notes WUSTL-BRCA is largest cohort
The "universal gene-wise predictability" pattern may be dataset-dependent	The high concordance across models (Fig.3a) is observed on STP-BENCH-INTERNAL, but its stability across vastly different tissue architectures (e.g., brain vs skin) or pathological states (e.g., treatment-naive vs resistant) is untested	If predictability is not universal, gene selection for clinical vST assays must be context-specific, undermining the benchmark's generalizability claim	Evaluate the same 20 models on an external, highly distinct dataset (e.g., melanoma or sarcoma) and compute gene-wise PCC correlation across models; compare to STP-BENCH's p	[Paper] [Paper: PDF p. 11] "gene-wise concordance was consistently observed across additional datasets (Extended Data Fig. 4a)", but those are all within the 6-cancer STP-BENCH scope
Using UNiv2 as the sole PFM for "unified" evaluation ignores encoder heterogeneity	While UNiv2 is state-of-the-art, other PFMs (Virchow2, H-Optimus1) show comparable performance (Fig.2e); ranking models solely on UNiv2 may not reflect their true potential with a better-matched encoder	For users with domain-specific PFMs, STP-BENCH rankings may be suboptimal; benchmark should report encoder $\times$ model interaction	Report full 5×21 matrix of PCC for all 5 encoders (Fig.2e) across all 21 models, not just top-10; perform ANOVA to test encoder $\times$ model interaction significance	[Figure 2e] shows 5 encoders' performance, but only for 10 models; [Paper] [Paper: PDF p. 10] notes Virchow2/H-Optimus1 "achieved the highest and broadly comparable performance"
Cell2location deconvolution on vST may inherit its own biases	Cell2location assumes a linear mixing model and relies on scRNA-seq references; if vST predictions have systematic biases (e.g., over-smoothing), deconvolution errors may reflect the tool's limitations, not vST quality	Downstream utility claims become confounded; a poor Cell2location result doesn't necessarily mean vST failed to capture cell composition	Replace Cell2location with orthogonal deconvolution methods (e.g., SPOTlight, RCTD) and compare correlation trends; or use simulated ground-truth with known cell mixtures	[Paper] [Paper: PDF p. 35] specifies Cell2location parameters but no validation against alternative tools; [Paper] [Paper: PDF p. 20] admits "limitations inherent to deconvolution-based estimation"

14 学到的知识

- **评估即设计**：一个高质量 benchmark 不是数据集堆砌，而是包含数据构造（STP-BENCH-INTERNAL/EXTERNAL 分离）、模型重实现（21 模型统一 pipeline）、度量定义（PCC/SSIM/MAE 三级指标）、分析维度（gene/gene-set/cell/domain/robustness）的完整工程。用户可直接复用其 `HESTData` 兼容格式与 `singscore` 基因集分析流程。
- **PFM 是 vST 的“新基座”**：UNIV2 等 PFM 的引入，使图像编码器从模型附属品升格为独立可评估组件。其性能（Fig.2e）与鲁棒性（Extended Data Fig.5-6）直接决定下游任务上限，提示用户在 single-cell foundation models 中应优先验证 PFM 的跨组织泛化性。
- **基因可预测性存在生物学层级**：并非所有基因同等可预测。Stromal/ECM、immune/inflammation、specialized epithelial 基因构成“高价值靶标”，因其依赖 multi-scale 形态，这为用户设计 perturbation prediction 模型提供了先验知识——应显式建模空间上下文。
- **数据质量是隐性天花板**：Xenium 与 Visium 的性能鸿沟（Fig.2c-d, Fig.4）表明，vST 的终极瓶颈可能不在算法，而在底层 ST 技术的灵敏度。这警示用户：在 multi-omics 整合中，需对不同模态的数据质量进行校准，而非简单拼接。
- **鲁棒性比精度更具部署价值**：Cross-tissue 泛化失败（Fig.5b）远比内部 PCC 差异更致命。用户若构建 spatial transcriptomics 工具，应将 cross-tissue/cross-platform 测试纳入标准开发流程，而非仅优化内参。

15 与既有知识的连接

- **候选连接/方法论连接**：STP-BENCH 的 multi-granularity 评估框架（gene → gene-set → cell → domain）与 single-cell foundation models 的 hierarchical representation learning（如 cell-type → tissue-context）理念相通，但 STP-BENCH 尚未在 single-cell resolution 上验证，故为候选连接。
- **候选连接/方法论连接**：其 cross-platform (Visium→Xenium) 泛化实验与 spatial transcriptomics 领域对 multi-resolution data 对齐（如 Visium spot vs Xenium cell）的需求一致，但 STP-BENCH 仅做 pseudo-spot 转换，未涉及真正的 multi-resolution graph neural networks 建模，故为候选连接。
- **候选连接/方法论连接**：基因集分析（singscore）和下游任务（Cell2location, SpaGCN）的评估逻辑，可迁移到 multi-omics 领域的 cross-modal alignment 评估中——例如，不只看 omics embedding 的 cosine similarity，更要看 alignment 后能否支撑 pathway enrichment 或 cell-type annotation。
- **弱连接/方法论连接**：论文未涉及 perturbation prediction（如 drug response）或 cell state representation（如 trajectory inference），这些是 biomedical AI 的前沿方向，但 STP-BENCH 提供的 robustness analysis（Fig.5）和 gene-set scoring（Fig.3）可作为其评估子模块。
- **弱连接/方法论连接**：其对 encoder-architecture 解耦的强调，与 graph neural networks 中 message-passing mechanism 与 node embedding initialization 的分离思想类似，但未在图结构数据上实践，故为弱连接。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name**: Tissue-Aware PFM Adapter for Cross-Tissue vST

originating limitation/observation: Cross-tissue generalization gap is severe (Fig.5b), and inter-cohort scaling harms performance (Fig.5d), suggesting tissue-specific morphology-to-expression mappings [Paper] [Paper: PDF p. 17, 19]. **core hypothesis:** A lightweight, tissue-specific adapter module inserted between a frozen PFM and the vST predictor can recalibrate morphology features for a target tissue, outperforming both fine-tuning and naive multi-tissue training. **delta from paper:** STP-BENCH treats tissue as a domain shift to be measured; this idea treats it as a modality to be adapted, adding a learnable tissue-conditioned adapter. **initial method:** For each target tissue (e.g., BRCA), add a small MLP adapter (2 layers, 128 dim) to UNiv2 embeddings, conditioned on tissue ID embedding; train only adapter + predictor head on target tissue data. **validation:** Compare adapter vs full fine-tuning vs zero-shot on STP-BENCH-EXTERNAL cross-tissue tasks (Fig.5b); metrics: PCC, ARI, cell abundance PCC. **failure modes:** Adapter overfits to small tissue cohorts; fails when tissue ID embedding lacks discriminative power. **innovation status:** unverified

- **name:** Gene-Set Guided Contrastive Learning for vST

originating limitation/observation: Bi-modal retrieval models (BLEEP, STco) use CLIP-style contrastive loss on spot-level vectors, but gene-set analysis shows functional programs (e.g., T Cell Activation) are recoverable (Fig.3e), suggesting loss should operate at functional level. **core hypothesis:** Replacing spot-level contrastive loss with gene-set-level contrastive loss will improve recovery of biologically coherent pathways, especially for low-expression marker genes. **delta from paper:** STP-BENCH evaluates gene-set recovery post-hoc; this idea integrates gene-set semantics into the training objective itself. **initial method:** For each spot, compute singscore for top K GO terms; use these scores as "functional embeddings"; align H&E patch embeddings with functional embeddings via contrastive loss, alongside original spot-level alignment. **validation:** Train BLEEP variants on STP-BENCH-INTERNAL; evaluate on gene-set PCC (Fig.3c) and marker gene PCC (Fig.2a); ablate functional vs spot-level loss components. **failure modes:** Functional embeddings are noisy for sparse genes; loss conflicts with spot-level alignment, causing optimization instability. **innovation status:** unverified

- **name:** Spatial Graph Refinement for Spot-Level vST Predictions

originating limitation/observation: Models like SEPAL use spatial graphs for refinement, but STP-BENCH shows spatial domain identification (SpaGCN) is highly sensitive to data quality (Fig.4c); current graph construction (e.g., hexagonal neighbors) may be too rigid for irregular tissue boundaries. **core hypothesis:** A dynamic, morphology-aware spatial graph—where edges are learned from H&E patches rather than fixed geometry—will yield more robust spatial refinement, especially on low-quality Visium data. **delta from paper:** STP-BENCH uses fixed neighbor graphs (e.g., "six neighbors for hexagonal Visium geometry" [Paper] [Paper: PDF p. 25]); this replaces it with a learnable, vision-conditioned graph. **initial method:** Replace SEPAL's fixed neighbor graph with a GNN that takes UNiv2 embeddings of center + candidate neighbor spots as input, and predicts edge weights via MLP; use top-k weighted edges for graph convolution. **validation:** Implement in SEPAL; compare on STP-BENCH-INTERNAL Visium cohorts (e.g., NCCHE-LUAD-Visium) for PCC and ARI (Fig.4c); visualize learned adjacency vs ground-truth tissue boundaries. **failure modes:** Graph learning adds significant compute; may overfit to artifact-prone regions. **innovation status:** unverified