

Source coverage: Full paper
Extraction confidence: High
Locator mode: page-grounded
Primary analytical lens: methods
Secondary analytical lens: resource
Context verification: Paper-only
Card completeness: Complete relative to supplied source

01 基本信息

Field	Value	Source
Title	Towards Scalable Context-Aware Single-Cell Spatial Transcriptomics Prediction from Histology Images	[Paper] [Paper: PDF p. 1]
Authors	Zijun Gao, Chunbin Gu, Jinxi Xiang, Xiangde Luo, Pheng-Ann Heng	[Paper] [Paper: PDF p. 1]
Venue	arXiv (NeurIPS 2026 submission)	[Paper] [Paper: PDF p. 1]
Code	https://github.com/zjgao02/CELLO	[Paper] [Paper: PDF p. 1]
Model	hf.co/gaozijun/CELLO	[Paper] [Paper: PDF p. 1]
Data	hf.co/datasets/gaozijun/cello_data	[Paper] [Paper: PDF p. 1]
Core task	Predicting single-cell spatial gene expression ($x_i \in \mathbb{R}^G \geqslant_0$) from H&E image V and cell location $s_i \in \mathbb{R}^2$	[Paper] [Paper: PDF p. 4, Eq. 1]
Key innovation	Single PFM forward pass + grid sampling + distance-decay cross-attention for context-aware cell embedding	[Paper] [Paper: PDF p. 2–4; Fig. 1D, Fig. 2]
Benchmark	10X-Xenium-52: 52 paired Xenium–H&E slides across 12 organs, ~10M cells	[Paper] [Paper: PDF p. 6, 13; Fig. 5]
Evaluation metric	Mean Pearson Correlation Coefficient (PCC) over gene subsets: MPG, HVG, SVG (top-k), and full panel	[Paper] [Paper: PDF p. 5, 17–18; Tables 1, 5, 6, 8]

02 一句话总结

CELLO 提出一种端到端、可扩展的单细胞空间转录组预测框架，通过单次病理基础模型（PFM）前向传播 + 双线性网格采样提取位置特异性细胞特征，并引入距离衰减交叉注意力模块融合局部形态学上下文，从而在保持精确细胞定位的同时避免形态失真与分割误差传递。该方法在 12 器官、52 张 Xenium-H&E 配对切片上显著超越 DeepSpot2Cell 和 UNet3+，ID 设置下 HVG-PCC50 提升 58.5%，OOD 下提升 71.3%，同时实现平均 $14.0\times$ 推理加速（排除上游细胞分割）。其核心价值在于首次系统性解耦“单细胞分辨率”与“计算可扩展性”的矛盾，为 H&E→ST 的临床级部署提供可行路径，但边界明确限定于已配准的细胞中心坐标输入，不处理未配准图像或无监督细胞定位。

03 研究问题

论文直面单细胞尺度 H&E→ST 预测的根本性张力：**如何在不牺牲细胞定位精度、不引入形态失真、不依赖完美细胞掩膜、且可扩展至百万细胞全切片的前提下，构建兼具强视觉表征与空间上下文感知能力的细胞嵌入？** 作者指出，现有两类主流策略均存在不可调和缺陷——基于逐细胞裁剪的方法（如 DeepSpot2Cell）因独立前向传播导致计算爆炸，且裁剪/缩放破坏局部微环境；而基于分割掩膜的方法（如 GHIST/UNet3+）虽保留结构，却缺乏预训练病理基础模型提供的强形态学先验，且将分割误差直接传导至分子预测。因此，研究问题本质是：**能否设计一种架构，在共享 PFM 表征基础上，以亚像素精度锚定细胞位置，并显式建模其空间邻域内的形态学上下文？** 这一问题的提出直接源于 Figure 1B/C 所揭示的 scale mismatch 与 representation gap [Paper] [Paper: PDF p. 3]。

04 研究背景与发展路径

领域演进呈现清晰的“分辨率跃迁”脉络：早期工作（如 [5, 6, 7]）聚焦 spot-level 预测（Visium），受限於细胞异质性掩盖；近期尝试突破分辨率（[14, 15, 16, 17]）仍停留在 superpixel 或 spot-level 弱监督分配，无法输出真实单细胞表达向量；DeepSpot2Cell [18] 首次尝试 cell-level，但采用 naive per-cell crop，陷入计算瓶颈；GHIST [2] 利用掩膜构造细胞感知表征，却未接入 PFM。CELLO 并非简单改进某一支路，而是识别出共性瓶颈——**patch-level PFM 表征与 cell-level 目标间的几何不匹配**——并据此提出新范式：将 PFM 视为连续视觉场（2D token map），用双线性插值实现亚像素查询，再以距离衰减注意力进行上下文精修。这一路径跳出了“裁剪 vs 掩膜”的二元对立，转向“连续场建模”，与 Figure 2 所示的 query-refine 流程完全一致 [Paper] [Paper: PDF p. 4]。

05 论文识别的核心痛点

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Scale mismatch between PFM patch tokens and cell locations	Per-cell cropping/resizing distorts morphology and removes local context; independent forward passes per cell are computationally prohibitive	PFMs are pretrained on regular grids of patches, not irregular cell centroids; naive adaptation ignores geometric continuity of tissue morphology	[Paper] [Paper: PDF p. 2] “Naively applying pathology foundation models faces a scale mismatch... per-cell cropping or resizing distorts morphology” ; Fig. 1B [Paper] [Paper: PDF p. 3]
Representation gap in segmentation-based models	UNet3+ lacks strong pretrained visual representations, leading to insufficient morphological capacity for molecular prediction	Segmentation masks provide structural priors but do not encode rich histological semantics learned by large-scale PFM pretraining	[Paper] [Paper: PDF p. 2] “Conversely, segmentation-based models without strong pretrained visual encoders often lack the morphological representation capacity...” ; Fig. 1C [Paper] [Paper: PDF p. 3]

Pain point	Manifestation	Cause or author explanation	Evidence from the paper
Cascading error propagation from imperfect cell segmentation	Predictions inherit errors from upstream cell boundary masks, limiting robustness	Cell masks are noisy and incomplete, especially in dense or low-contrast regions; model becomes brittle to segmentation quality	[Paper] [Paper: PDF p. 2] “...and inherit errors from imperfect cell boundary masks” ; [Paper] [Paper: PDF p. 23] “obtaining cell locations still relies on cell segmentation”
Ambiguity in contextual scope for gene expression prediction	Global slide-level context (e.g., CLS token) degrades performance, contradicting intuition that broader context helps	Single-cell transcriptomic state is predominantly shaped by fine-grained local microenvironment, not abstract global semantics; CLS token dilutes localized signals	[Paper] [Paper: PDF p. 7–8] “incorporating the CLS token consistently degrades performance” ; Fig. 3B [Paper] [Paper: PDF p. 8]; Table 6/8 [Paper] [Paper: PDF p. 19–20]

06 核心理念

论文的核心思想是 “连续视觉场上的位置锚定与距离感知上下文精修”（Position-anchored querying on continuous visual field + distance-aware contextual refinement）。它拒绝将细胞视为离散对象进行独立编码，而是将 PFM 输出的 2D token map 视为一个连续的、可微分的视觉信号场；每个细胞由其亚像素级坐标 s_i 锚定于此场，通过双线性插值得到初始特征 $q^{(0)}_i$ ，再以该查询为中心，依据欧氏距离施加高斯衰减偏置（ $b_{i,m} \propto -\|s_i - c_m\|^2$ ），引导 cross-attention 优先聚合空间邻近的 patch tokens。这一设计将生物学直觉（细胞状态受邻近微环境调控）直接编码为可学习的归纳偏置，而非依赖模型从数据中隐式学习。Figure 2 的流程图与 Equation 4 的距离衰减项共同构成该思想的完整数学与可视化表达 [Paper] [Paper: PDF p. 4–5]。

07 方法总览

CELLO 是一个三阶段 end-to-end 框架：（1）**视觉特征提取**：使用冻结或渐进解冻的 PFM（如 Virchow2）将 H&E patch V 映射为 2D token map $T \in \mathbb{R}^{L_g \times L_g \times d}$ ，保留几何对应关系；（2）**位置感知细胞查询**：对每个细胞坐标 s_i ，经归一化后通过 GridSample 从 T 中双线性插值获得初始查询 $q^{(0)}_i$ ；（3）**距离感知上下文精修**：以 $q^{(0)}_i$ 为 query，所有 spatial tokens 为 key/value，注入 2D RoPE 编码相对位置，并叠加 Gaussian distance-decay bias $b_{i,m}$ ，输出上下文增强的细胞嵌入 z_i ；最终经 MLP 解码为基因表达向量 $\hat{x}_i$ 。整个流程仅需一次 PFM 前向传播，所有细胞特征并行提取，彻底规避了 per-cell crop 的计算墙 [Paper] [Paper: PDF p. 4–5; Fig. 2]。

08 核心模块拆解

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Grid sampling (bilinear interpolation)	Extracts sub-pixel, location-specific initial feature $q^{(0)}_i$ from shared 2D token map T	To anchor cell representation precisely to its coordinate s_i without cropping/resizing, preserving morphological fidelity and enabling continuous querying	Input: $T \in \mathbb{R}^{L_g \times L_g \times d}$, $\xi_i \in [-1, 1]^2$; Output: $q^{(0)}_i \in \mathbb{R}^d$	[Paper] [Paper: PDF p. 4, Eq. 3]; Fig. 2 “first queries a location-specific cell feature by bilinear interpolation” ; Fig. 1D “uses grid sampling to extract initial feature”	Removal forces discrete token assignment (e.g., nearest neighbor), losing sub-pixel precision and causing quantization error; would degrade localization-sensitive genes (e.g., KRT8, DES in Fig. 4)
Distance-decay cross-attention	Refines $q^{(0)}_i$ by attending over all patch tokens with spatially biased weights, prioritizing nearby tokens	To inject biologically motivated prior that cell state is shaped by local microenvironment, beyond mere location; addresses limitation of Grid baseline which lacks context fusion	Input: $q^{(0)}_i$, T ; Output: $z_i \in \mathbb{R}^d$	[Paper] [Paper: PDF p. 4–5]; Fig. 2 “refines each cell query... where spatially nearby tokens receive a larger prior” ; Table 1 shows Grid < CELLO by 18.6% (ID HVG-PCC50)	
2D RoPE positional encoding	Encodes relative spatial relationships between cell query and image tokens into attention logits	To provide explicit, parameter-free geometric structure to attention, ensuring spatial proximity translates to attention weight without learning bias from scratch	Input: s_i , c_m (token centers); Output: rotary embeddings for Q/K	[Paper] [Paper: PDF p. 5]; “apply 2D RoPE [32] to queries and keys... encodes relative spatial relationships”	Removal would weaken spatial grounding of attention, likely increasing sensitivity to cell localization error (cf. Table 11) and reducing OOD robustness

Module	Function	Why needed	Input and output	Supporting evidence	Known or expected effect of removal
Patch-level Huber loss L_{patch}	Auxiliary loss predicting aggregate patch expression $x_{\text{patch}} = \sum_i x_i$	To encourage cell embeddings to be consistent with coarse-grained tissue-level expression, providing regularization and multi-scale supervision	Input: z_i for all i in patch; Output: $\hat{x}_{\text{patch}}$; Loss: $\text{Huber}(\hat{x}_{\text{patch}}, x_{\text{patch}})$	[Paper] [Paper: PDF p. 5, Eq. 5]; “auxiliary patch-level loss... defined as the sum of all cell-level expression vectors” ; Table 7 shows $\lambda=0.5$ used in main model	Removal ($\lambda=0$) slightly reduces ID PCC (Table 7: 0.5598→0.5447 at HVG-PCC10) but may hurt generalization on sparse/noisy genes; weakens multi-scale consistency

09 关键公式与符号

论文未给出完整可复现的端到端公式，但明确提供了以下关键公式与符号定义，全部可核验：

- **Equation 1:** $f_{\theta} : (V, s_i) \mapsto \hat{x}_i \in \mathbb{R}^{G_{\geq 0}}, i = 1, \dots, N$ —— 任务形式化：给定 H&E 图像 V 和第 i 个细胞位置 s_i ，预测其基因表达向量 $\hat{x}_i$ [Paper] [Paper: PDF p. 4]。
- **Equation 3:** $q^{(\theta)}_i = \text{GridSample}(T, \tilde{s}_i) \in \mathbb{R}^d$ —— 双线性插值查询，其中 T 是 PFM 输出的 2D token map， $\tilde{s}_i$ 是归一化后的细胞坐标 [Paper] [Paper: PDF p. 4]。
- **Equation 4:** $b_{i,m} = -\|s_{\text{loc}_i} - c_m\|^2 / (2p^2)$ —— 距离衰减偏置项， s_{loc_i} 是 patch-local 坐标， c_m 是第 m 个 token 的 pixel-space 中心， p 是 token stride [Paper] [Paper: PDF p. 5]。
- **Equation 5:** $L = L_{\text{cell}} + \lambda L_{\text{patch}}$ —— 加权 Huber 损失， L_{cell} 是细胞级 Huber 损失， L_{patch} 是 patch 级 Huber 损失， $\lambda=0.5$ 是主实验设置 [Paper] [Paper: PDF p. 5; Table 7]。

关键符号：

- v : H&E 图像 patch ($L \times L \times 3$) [Paper] [Paper: PDF p. 3]
- s_i : 第 i 个细胞的全局坐标 $(x_i, y_i) \in \mathbb{R}^2$ ，用于定位 [Paper] [Paper: PDF p. 3]
- T : PFM 输出的 2D token map ($L_g \times L_g \times d$) [Paper] [Paper: PDF p. 4]
- z_i : 经距离衰减 cross-attention 后的最终细胞嵌入 $\in \mathbb{R}^d$ [Paper] [Paper: PDF p. 5]
- PCC-k : Pearson Correlation Coefficient over top-k most predictive (MPG), highly variable (HVG), or spatially variable (SVG) genes [Paper] [Paper: PDF p. 5]

10 实验设计与证据链

Experiment	Claim tested	Comparison and conditions	Result	Supported conclusion	Unsupported stronger conclusion	Source
Table 1 (HVG) & Table 5 (MPG/SVG)	CELLO outperforms baselines on curated gene subsets	ID/OOD settings; same 10X-Xenium-52 benchmark; Virchow2 encoder	CELLO > DeepSpot2Cell by 58.5% (ID HVG-PCC50), 71.3% (OOD HVG-PCC50); > Grid by 18.6% (ID)	CELLO' s architecture (grid sampling + distance-attention) yields superior cell embeddings for high-signal genes	That CELLO dominates <i>all</i> gene types equally — full-panel results (Fig. 6) show gains persist but absolute PCC lower	[Paper] [Paper: PDF p. 6–7, 17–18; Tables 1, 5]
Figure 6 (Full panel)	CELLO' s advantage extends to entire measured gene panel	Same benchmark; evaluation over all genes per sample (280–480)	CELLO achieves highest PCC across all 6 ID tissues and all 6 OOD organs, e.g., +large gains in Breast/Bowel/Lung (ID)	Performance gain is robust beyond hand-selected gene subsets, validating broad utility	That CELLO solves sparsity/noise for <i>all</i> genes — low-PCC values (e.g., OOD avg 0.0916) confirm inherent difficulty	[Paper] [Paper: PDF p. 17–18; Fig. 6]
Figure 3C & Table 9	CELLO is significantly faster than per-cell crop methods	Inference time on 12 test slides; excludes cell segmentation; same GPU (L40S)	CELLO: 67.5 ± 48.8 s/slide; DeepSpot2Cell: 947.2 ± 1068.3 s/slide → $14.0 \times$ speed-up (avg)	Single PFM forward pass + grid sampling enables scalable WSI inference	That CELLO is faster than <i>all</i> segmentation-based methods — UNet3+ time is comparable (73.9 ± 52.1 s)	[Paper] [Paper: PDF p. 8–9, 22; Fig. 3C, Table 9]
Table 11	CELLO is robust to moderate cell localization errors	Perturb centroid coordinates on 3,000 test patches: Gaussian jitter (std 5–80 px) or cell removal (10–40%)	PCC drops only –0.9% at 10 px jitter; –4.6% at 40% cell removal	Architecture tolerates realistic segmentation inaccuracies	That CELLO works with <i>no</i> cell location input — it fundamentally requires s_i [Paper] [Paper: PDF p. 23]	[Paper] [Paper: PDF p. 22; Table 11]
Table 6/8 & Fig. 3B	Global CLS token harms performance	Ablation: fuse zcls with zi via learned gate vs. no fusion; same Virchow2 encoder	CLS fusion reduces average PCC by 13.6% (ID) and 13.1% (OOD); degradation consistent across MPG/HVG/SVG	Single-cell gene expression prediction is driven by fine-grained local context, not global slide semantics	That CLS is <i>always</i> harmful — isolated entries (e.g., OOD HVG-PCC200) show minor gains, but not systematic	[Paper] [Paper: PDF p. 7–8, 17–20; Fig. 3B, Tables 6, 8]

11 对结论的正确理解

论文结论必须严格限定于其证据范围：CELLO 在 **已配准的细胞中心坐标输入、使用 Virchow2 等强 PFM、在 10X-Xenium-52 基准上**，实现了单细胞 H&E→ST 预测的精度与效率帕累托前沿。其“scalable”指代的是**计算复杂度从 $O(N)$ (N =细胞数) 降至 $O(M)$ (M =图像块数)**，而非指模型本身轻量或零样本泛化；其“context-aware”特指**由距离衰减偏置显式编码的局部空间上下文**，而非泛指任何语义上下文；其“state-of-the-art”仅针对所评测的三个基线（DeepSpot2Cell, UNet3+, Grid），不涵盖所有可能方法。Figure 4 的定性结果（如 KRT8, DES 的 sharp recovery）证实了模型对位置敏感基因的有效建模，但 Table 11 显示其性能仍随定位误差单调下降，故“robust”是相对的、有阈值的（<10 px）。任何超出这些边界的推广（如跨平台、无配准、零样本器官迁移）均无本文证据支持。

12 作者明确承认的限制

Limitation	Specific manifestation	Future direction proposed by authors	Source
Limited OOD organ coverage	Several OOD organs (Brain, Bone, Heart, Ovary) represented by only one slide, limiting generalization estimation precision	Collect more paired data covering wider range of tissues and organs	[Paper] [Paper: PDF p. 23]
Dependence on upstream cell segmentation	CELLO requires cell locations (centroids) at inference; predictions inherit segmentation accuracy limitations	Improve accuracy of cell segmentation to reduce bad predictions	[Paper] [Paper: PDF p. 23]
OOD evaluation as case studies	OOD test set contains single slide per unseen organ; Kidney/Liver seen in training under different health conditions	These results are case studies rather than estimates of organ-level generalization	[Paper] [Paper: PDF p. 23]
Benchmark scale	52 samples across 12 organs, though substantial heterogeneity, may not capture full clinical diversity	Not explicitly stated, but implied by call for more data collection	[Paper] [Paper: PDF p. 23]

13 批判性分析

[Analysis] Observation	Potential issue or alternative explanation	Why it matters	How to test it	Basis
CELLO’ s 14.0× speed-up is contingent on the <i>current</i> DeepSpot2Cell implementation using frozen PFM and per-cell crops	If DeepSpot2Cell were end-to-end trainable (fine-tuning PFM per cell), its computational cost would explode, but its accuracy might improve; CELLO’ s advantage may partly stem from trainability, not just architecture	Overstates architectural superiority; conflates design benefit with practical engineering constraint	Train a lightweight, cell-crop PFM adapter (e.g., LoRA) on DeepSpot2Cell and compare accuracy/speed trade-off	[Paper] [Paper: PDF p. 16] “DeepSpot2Cell extracts PFM features independently... fine-tuning... prohibitively expensive” ; [Paper] [Paper: PDF p. 17] “CELLO benefits from task-specific representation adaptation”
Distance-decay bias uses fixed Gaussian kernel (p^2 normalization), but optimal decay scale may vary across tissue types (e.g., dense epithelium vs. loose stroma)	A fixed decay parameter may underfit context in heterogeneous tissues, limiting OOD robustness	Reduces biological plausibility and adaptability; may explain why OOD gains (71.3%) are smaller than ID gains (58.5%) in relative terms	Learn decay scale per tissue type or sample, or use adaptive kernel bandwidth selection	[Paper] [Paper: PDF p. 5, Eq. 4] “normalization by p^2 makes the decay scale relative to the token receptive field size” ; no ablation on decay parameter
The “CLS token harms performance” conclusion is based on fusion via a scalar gate, but other fusion mechanisms (e.g., concatenation + projection, gated linear units) were not explored	The negative result may reflect suboptimal fusion design, not an intrinsic irrelevance of global context	Risks prematurely discarding valuable global information (e.g., tumor grade, tissue inflammation level) that could aid certain genes	Implement and ablate multiple CLS fusion strategies (concat, add, gated) and evaluate on disease-relevant genes (e.g., immune markers)	[Paper] [Paper: PDF p. 7–8] “we learn a scalar gate to adaptively fuse... $g_i = \sigma(\phi g([z_i; z_{cls}]))$ ” ; no alternative designs reported
CELLO’ s reliance on precise cell centroids assumes perfect registration between H&E and ST, but real-world alignment has residual error	Residual misregistration (beyond Table 11’ s artificial jitter) may systematically bias predictions, especially for polarized genes	Undermines clinical applicability where alignment is imperfect; Table 11’ s controlled jitter doesn’ t mimic real misalignment patterns	Quantify real H&E-ST misalignment in HEST-1k, simulate its effect, and test CELLO’ s sensitivity to translation/rotation errors	[Paper] [Paper: PDF p. 13] “HEST-1k uses this alignment, re-estimates the pixel size... we use the HEST-1k registration... perform no additional alignment” ; no analysis of alignment quality

14 学到的知识

- **架构设计原则：**在多尺度生物图像任务中，“连续场建模”（continuous field modeling）优于“离散对象处理”（discrete object handling）——CELLO 将 PFM token map 视为可微分视觉场，用双线性插值实现

亚像素查询，此范式可迁移到其他需要精确定位的任务（如 subcellular protein localization）。

- **上下文注入范式：**显式、可解释的归纳偏置（如 distance-decay bias）比隐式学习更有效——Equation 4 的高斯衰减直接编码生物学先验，其效果（+18.6% PCC）远超复杂黑箱模块，提示在 biomedical AI 中应优先设计物理/生物意义明确的偏置。
- **评估陷阱规避：**必须区分“curated subset performance”与“full-panel robustness”——CELLO 在 HVG/MPG 上大幅领先，但在 full panel (Fig. 6) 上绝对 PCC 仍低（e.g., OOD avg 0.0916），提醒我们不能仅依赖 top-k 指标判断模型实用性。
- **计算-精度权衡真相：**所谓“高效”常依赖于特定 baseline 的工程局限——CELLO 的 $14.0\times$ 优势源于 DeepSpot2Cell 的 frozen PFM 设计；若后者可高效 fine-tune，速度差距将缩小，凸显了公平比较需控制变量（如 trainability）。
- **失败即洞见：**CLS token 的系统性失败（-13.6%）不是缺陷，而是关键发现——它证伪了“global context always helps”，确立了单细胞预测的 locality principle，为后续工作划清了设计边界。

15 与既有知识的连接

- **候选连接/方法论连接：**CELLO 的“grid sampling + distance-attention”与 spatial graph neural networks (GNNs) 高度互补——GNNs 天然建模细胞间空间关系，但缺乏强视觉表征；CELLO 提供的上下文感知细胞嵌入 z_i 可作为 GNN 的初始节点特征，替代手工设计的形态学特征，形成 hybrid architecture（e.g., $z_i \rightarrow$ GNN message passing）。
- **候选连接/方法论连接：**其 distance-decay bias 与 multi-omics integration 中的“spatial proximity weighting”思想一致——在整合 scRNA-seq 与 spatial data 时，常按距离加权邻居贡献；CELLO 将此思想直接嵌入视觉-分子映射，为 cross-modal alignment 提供可微分的空间先验。
- **候选连接/方法论连接：**双线性插值查询机制与 single-cell foundation models 的“cell-centric tokenization”目标相通——当前 scFM 多基于预定义基因程序，CELLO 展示了如何从原始图像中无监督地生成位置锚定的细胞表征，为构建 truly cell-first foundation models 提供视觉侧接口。
- **弱连接/方法论连接：**与 perturbation prediction 的 connection 较弱——CELLO 预测稳态表达，未涉及扰动响应建模；但其上下文感知嵌入 z_i 可作为 perturbation encoder 的输入，将扰动效应置于局部微环境中解读。
- **弱连接/方法论连接：**与 biomedical AI 的通用 connection 体现在“inductive bias design”范式——CELLO 成功验证了将 domain knowledge (local microenvironment matters) 转化为可学习 bias (distance-decay) 的有效性，此范式可推广至 protein structure prediction (evolutionary context) 或 drug discovery (binding pocket geometry)。

16 研究想法

[Hypothesis] 以下研究想法为基于论文证据和局限的可检验假设，不代表论文作者已验证。

- **name:** AdaptiveDecay-CELLO

originating limitation/observation: Fixed Gaussian decay scale (Eq. 4) may not generalize across tissue architectures [Analysis in Sec 13]. **core hypothesis:** Learning tissue-adaptive decay bandwidth improves OOD generalization without sacrificing ID performance. **delta from paper:** Replace fixed p^2 in Eq. 4 with a learnable scalar σ^2 predicted per patch from CLS token or low-res features. **initial method:** Add small MLP (2 layers) to predict σ^2 from z_{cls} ; modify Eq. 4 to $b_{i,m} = -\|s_{loc_i} - c_m\|^2 / (2\sigma^2)$. **validation:**

Compare OOD PCC gain vs. CELLO on Brain/Bone slides; ablate on Table 7' s short runs. **failure modes:** Overfitting to training tissues; σ^2 collapse to constant; increased training instability. **innovation status:** unverified

- **name:** CELLO-GNN

originating limitation/observation: CELLO outputs per-cell z_i but does not model explicit cell-cell interaction graphs [Sec 15 connection]. **core hypothesis:** Injecting GNN message passing over k-NN cell graphs on top of z_i refines predictions for intercellular signaling genes. **delta from paper:** Add one GNN layer (e.g., GraphSAGE) after CELLO' s z_i , using spatial k-NN graph; predict $\hat{x}_i$ from updated node features. **initial method:** For each patch, build $k=5$ NN graph from s_i ; apply GNN; feed updated features to existing MLP head. **validation:** Test on ligand-receptor pairs (e.g., from COMMOT [43]); measure PCC gain on SVG genes vs. CELLO. **failure modes:** Graph sparsity in low-density regions; computational overhead negating CELLO' s speed advantage; over-smoothing. **innovation status:** unverified

- **name:** UnsupervisedLoc-CELLO

originating limitation/observation: CELLO requires ground-truth cell centroids, limiting deployment where segmentation fails [Paper] [Paper: PDF p. 23]. **core hypothesis:** Jointly learning cell detection and expression prediction via differentiable centroid proposal improves robustness to segmentation errors. **delta from paper:** Replace input s_i with learnable, differentiable proposals (e.g., via soft-argmax on cell probability map from auxiliary head). **initial method:** Add light UNet head to predict cell prob map; use soft-argmax to get $\hat{s}_i$; backprop through entire pipeline. **validation:** Compare Table 11' s sensitivity curve — expect flatter degradation beyond 10 px; test on challenging tissues (e.g., Bone). **failure modes:** Training instability from joint optimization; proposal drift away from true centroids; increased inference latency. **innovation status:** unverified