

```
In [2]: import pandas as pd#importing pandas as pd
```

```
In [3]: data=pd.read_csv("/home/placement/Downloads/fiat500.csv")#read data from file as csv
```

```
In [4]: data.describe()#describe data like count,mean,max value
```

Out[4]:

	ID	engine_power	age_in_days	km	previous_owners	lat	lon	price
<b>count</b>	1538.000000	1538.000000	1538.000000	1538.000000	1538.000000	1538.000000	1538.000000	1538.000000
<b>mean</b>	769.500000	51.904421	1650.980494	53396.011704	1.123537	43.541361	11.563428	8576.003901
<b>std</b>	444.126671	3.988023	1289.522278	40046.830723	0.416423	2.133518	2.328190	1939.958641
<b>min</b>	1.000000	51.000000	366.000000	1232.000000	1.000000	36.855839	7.245400	2500.000000
<b>25%</b>	385.250000	51.000000	670.000000	20006.250000	1.000000	41.802990	9.505090	7122.500000
<b>50%</b>	769.500000	51.000000	1035.000000	39031.000000	1.000000	44.394096	11.869260	9000.000000
<b>75%</b>	1153.750000	51.000000	2616.000000	79667.750000	1.000000	45.467960	12.769040	10000.000000
<b>max</b>	1538.000000	77.000000	4658.000000	235000.000000	4.000000	46.795612	18.365520	11100.000000

In [5]: `data.tail(10)#shows top 10 rows`

Out[5]:

	ID	model	engine_power	age_in_days	km	previous_owners	lat	lon	price
<b>1528</b>	1529	lounge	51	2861	126000	1	43.841980	10.51531	5500
<b>1529</b>	1530	lounge	51	731	22551	1	38.122070	13.36112	9900
<b>1530</b>	1531	lounge	51	670	29000	1	45.764648	8.99450	10800
<b>1531</b>	1532	sport	73	4505	127000	1	45.528511	9.59323	4750
<b>1532</b>	1533	pop	51	1917	52008	1	45.548000	11.54947	9900
<b>1533</b>	1534	sport	51	3712	115280	1	45.069679	7.70492	5200
<b>1534</b>	1535	lounge	74	3835	112000	1	45.845692	8.66687	4600
<b>1535</b>	1536	pop	51	2223	60457	1	45.481541	9.41348	7500
<b>1536</b>	1537	lounge	51	2557	80750	1	45.000702	7.68227	5990
<b>1537</b>	1538	pop	51	1766	54276	1	40.323410	17.56827	7900

In [6]: `data1=data.drop(['lat','ID','lon'],axis=1)#remove column of lat,id,lon by using drop function`

In [7]: data1

Out[7]:

	model	engine_power	age_in_days	km	previous_owners	price
0	lounge	51	882	25000	1	8900
1	pop	51	1186	32500	1	8800
2	sport	74	4658	142228	1	4200
3	lounge	51	2739	160000	1	6000
4	pop	73	3074	106880	1	5700
...	...	...	...	...	...	...
1533	sport	51	3712	115280	1	5200
1534	lounge	74	3835	112000	1	4600
1535	pop	51	2223	60457	1	7500
1536	lounge	51	2557	80750	1	5990
1537	pop	51	1766	54276	1	7900

1538 rows × 6 columns

```
In [8]: data2=pd.get_dummies(data1)#where the lounge model it shows"1" other models it shows "0"
data2
```

Out[8]:

	engine_power	age_in_days	km	previous_owners	price	model_lounge	model_pop	model_sport
0	51	882	25000	1	8900	1	0	0
1	51	1186	32500	1	8800	0	1	0
2	74	4658	142228	1	4200	0	0	1
3	51	2739	160000	1	6000	1	0	0
4	73	3074	106880	1	5700	0	1	0
...	...	...	...	...	...	...	...	...
1533	51	3712	115280	1	5200	0	0	1
1534	74	3835	112000	1	4600	1	0	0
1535	51	2223	60457	1	7500	0	1	0
1536	51	2557	80750	1	5990	1	0	0
1537	51	1766	54276	1	7900	0	1	0

1538 rows × 8 columns

```
In [9]: data2.shape#how many rows and columns in the data frame
```

Out[9]: (1538, 8)

```
In [10]: y=data2['price']#removing price from data2 and put in new data frame y
x=data2.drop(['price'],axis=1)#remaining data can be put in another data frame
```

In [11]: `x# to get data in x`

Out[11]:

	engine_power	age_in_days	km	previous_owners	model_lounge	model_pop	model_sport
0	51	882	25000	1	1	0	0
1	51	1186	32500	1	0	1	0
2	74	4658	142228	1	0	0	1
3	51	2739	160000	1	1	0	0
4	73	3074	106880	1	0	1	0
...	...	...	...	...	...	...	...
1533	51	3712	115280	1	0	0	1
1534	74	3835	112000	1	1	0	0
1535	51	2223	60457	1	0	1	0
1536	51	2557	80750	1	1	0	0
1537	51	1766	54276	1	0	1	0

1538 rows × 7 columns

```
In [12]: y# to get data in y
```

```
Out[12]: 0      8900
          1      8800
          2      4200
          3      6000
          4      5700
          ...
        1533    5200
        1534    4600
        1535    7500
        1536    5990
        1537    7900
        Name: price, Length: 1538, dtype: int64
```

```
In [13]: #!/pip install sklearn#installing sklearn command
```

```
In [14]: from sklearn.model_selection import train_test_split
         x_train,x_test,y_train,y_test=train_test_split(x,y,test_size=0.33,random_state=42)#dividing training data ar
```

```
In [15]: x_test.head(5)#display top 5 data in testing data
```

```
Out[15]:
```

	engine_power	age_in_days	km	previous_owners	model_lounge	model_pop	model_sport
481	51	3197	120000	2	0	1	0
76	62	2101	103000	1	0	1	0
1502	51	670	32473	1	1	0	0
669	51	913	29000	1	1	0	0
1409	51	762	18800	1	1	0	0

```
In [16]: y_test.head(5)#display top 5 data in testing data price dataframe
```

```
Out[16]: 481      7900
         76      7900
         1502    9400
         669    8500
         1409    9700
         Name: price, dtype: int64
```

```
In [17]: x_train.head(5)#display top 5 data in training data
```

```
Out[17]:
```

	engine_power	age_in_days	km	previous_owners	model_lounge	model_pop	model_sport
527	51	425	13111	1	1	0	0
129	51	1127	21400	1	1	0	0
602	51	2039	57039	1	0	1	0
331	51	1155	40700	1	1	0	0
323	51	425	16783	1	1	0	0

```
In [18]: y_train.head(5)#display top 5 data in training data price dataframe
```

```
Out[18]: 527      9990
         129      9500
         602      7590
         331      8750
         323      9100
         Name: price, dtype: int64
```

```
In [19]: from sklearn.linear_model import LinearRegression
         reg=LinearRegression()#creating the object of linear Regression
         reg.fit(x_train,y_train)#training and fitting linear Regression using training data
```

```
Out[19]: LinearRegression()
```

```
In [20]: ypred=reg.predict(x_test)#calculating predicting value
```

In [21]: ypred

```
Out[21]: array([ 5867.6503378 ,  7133.70142341,  9866.35776216,  9723.28874535,
 10039.59101162,  9654.07582608,  9673.14563045, 10118.70728123,
  9903.85952664,  9351.55828437, 10434.34963575,  7732.26255693,
  7698.67240131,  6565.95240435,  9662.90103518, 10373.20344286,
  9599.94844451,  7699.34400418,  4941.33017994, 10455.2719478 ,
 10370.51555682, 10391.60424404,  7529.06622456,  9952.37340054,
  7006.13845729,  9000.1780961 ,  4798.36770637,  6953.10376491,
  7810.39767825,  9623.80497535,  7333.52158317,  5229.18705519,
  5398.21541073,  5157.65652129,  8948.63632836,  5666.62365159,
  9822.1231461 ,  8258.46551788,  6279.2040404 ,  8457.38443276,
  9773.86444066,  6767.04074749,  9182.99904787, 10210.05195479,
  8694.90545226, 10328.43369248,  9069.05761443,  8866.7826029 ,
  7058.39787506,  9073.33877162,  9412.68162121, 10293.69451263,
 10072.49011135,  6748.5794244 ,  9785.95841801,  9354.09969973,
  9507.9444386 , 10443.01608254,  9795.31884316,  7197.84932877,
 10108.31707235,  7009.6597206 ,  9853.90699412,  7146.87414965,
  6417.69133992,  9996.97382441,  9781.18795953,  8515.83255277,
  8456.30006203,  6499.76668237,  7768.57829985,  6832.86406122,
  8347.96113362, 10439.02404036,  7356.43463051,  8562.56562053,
  8820.78555100, 10025.02571520,  7270.77100022,  8411.45004000]
```

In [22]: `from sklearn.metrics import r2_score`  
`r2_score(y_test,ypred)#finding the efficiency`

Out[22]: 0.8415526986865394

In [23]: `from sklearn.metrics import mean_squared_error#mean_squared error`  
`a=mean_squared_error(y_test,ypred)`  
`a`

Out[23]: 581887.727391353

In [24]: `import math`  
`math.sqrt(a)#finding the square root of mse(mean squared error))`

Out[24]: 762.8156575420782



```
In [25]: results=pd.DataFrame(columns=['price','predicted'])#creating a data frame called results for given price and  
results['price']=y_test  
results['predicted']=ypred  
results=results.reset_index()  
results['Id']=results.index  
results.head(15)
```

Out[25]:

	index	price	predicted	Id
0	481	7900	5867.650338	0
1	76	7900	7133.701423	1
2	1502	9400	9866.357762	2
3	669	8500	9723.288745	3
4	1409	9700	10039.591012	4
5	1414	9900	9654.075826	5
6	1089	9900	9673.145630	6
7	1507	9950	10118.707281	7
8	970	10700	9903.859527	8
9	1198	8999	9351.558284	9
10	1088	9890	10434.349636	10
11	576	7990	7732.262557	11
12	965	7380	7698.672401	12
13	1488	6800	6565.952404	13
14	1432	8900	9662.901035	14

```
In [26]: results['actual price']=results.apply(lambda column:column.price-column.predicted,axis=1)#getting actual price
```

In [27]: results

Out[27]:

	index	price	predicted	Id	actual price
0	481	7900	5867.650338	0	2032.349662
1	76	7900	7133.701423	1	766.298577
2	1502	9400	9866.357762	2	-466.357762
3	669	8500	9723.288745	3	-1223.288745
4	1409	9700	10039.591012	4	-339.591012
...	...	...	...	...	...
503	291	10900	10032.665135	503	867.334865
504	596	5699	6281.536277	504	-582.536277
505	1489	9500	9986.327508	505	-486.327508
506	1436	6990	8381.517020	506	-1391.517020
507	575	10900	10371.142553	507	528.857447

508 rows × 5 columns