

✓ Congratulations! You passed!

Grade received 90% Latest Submission Grade 90% To pass 80% or higher

Go to next item

1. Suppose your training examples are sentences (sequences of words). Which of the following refers to the j^{th} word in the i^{th} training example?

1 / 1 point

- ☒ $x^{(i)<j>}$
- ☐ $x^{<i>(j)}$
- ☐ $x^{(j)<i>}$
- ☐ $x^{<j>(i)}$


Expand

✓ Correct

We index into the i^{th} row first to get the i^{th} training example (represented by parentheses), then the j^{th} column to get the j^{th} word (represented by the brackets).

2. Consider this RNN:

1 / 1 point



This specific type of architecture is appropriate when:

- ☒ $T_x = T_y$
- ☐ $T_x < T_y$
- ☐ $T_x > T_y$
- ☐ $T_x = 1$


Expand

✓ Correct

It is appropriate when every input should have an output.

3. To which of these tasks would you apply a many-to-one RNN architecture? (Check all that apply).

0 / 1 point



☒ Speech recognition (input an audio clip and output a transcript)

! This should not be selected

This is an example of many-to-many architecture.

☒ Sentiment classification (input a piece of text and output a 0/1 to denote positive or negative sentiment)

✓ Correct

Correct!

☒ Image classification (input an image and output a label)

! This should not be selected

This is an example of one-to-one architecture.

☒ Gender recognition from speech (input an audio clip and output a label indicating the speaker's gender)

✓ Correct

Correct!


[Expand](#)

✗ Incorrect

You chose the extra incorrect answers.

4. You are training this RNN language model.

1 / 1 point



At the t^{th} time step, what is the RNN doing?

☐ Estimating $P(y^{<1>}, y^{<2>}, \dots, y^{<t-1>})$

- ☐ Estimating $P(y^{<t>})$
- ☒ Estimating $P(y^{<t>} | y^{<1>}, y^{<2>}, \dots, y^{<t-1>})$


Expand

✓ Correct

Yes, in a language model we try to predict the next step based on the knowledge of all prior steps.

5. You have finished training a language model RNN and are using it to sample random sentences, as follows:

1 / 1 point



True/False: In this sample sentence, step t uses the probabilities output by the RNN to pick the highest probability word for that time-step. Then it passes the ground-truth word from the training set to the next time-step.

- ☐ True
- ☒ False

Expand

✓ Correct

The probabilities output by the RNN are not used to pick the highest probability word and the ground-truth word from the training set is not the input to the next time-step.

6. True/False: If you are training an RNN model, and find that your weights and activations are all taking on the value of NaN ("Not a Number") then you have a vanishing gradient problem.

1 / 1 point

- ☒ False
- ☐ True

Expand

✓ Correct

Vanishing and exploding gradients are common problems in training RNNs, but in this case, your weights and activations taking on the value of NaN implies you have an exploding gradient problem.

7. Suppose you are training an LSTM. You have a 10000 word vocabulary, and are using an LSTM with 100-dimensional activations $a^{<t>}$. What is the dimension of Γ_u at each time step?

1 / 1 point

- ☐ 1
- ☒ 100
- ☐ 300
- ☐ 10000

 Expand

 Correct

Correct, Γ_u is a vector of dimension equal to the number of hidden units in the LSTM.

8. True/False: In order to simplify the GRU without vanishing gradient problems even when training on very long sequences you should remove the Γ_r i.e., setting $\Gamma_r = 1$ always.

1 / 1 point

- ☒ True
- ☐ False

 Expand

 Correct

If $\Gamma_u=0$ for a timestep, the gradient can propagate back through that timestep without much decay. For the signal to backpropagate without vanishing, we need $c^{<t>}$ to be highly dependent on $c^{<t-1>}$.

9. Here are the equations for the GRU and the LSTM:

1 / 1 point

GRU

$$\tilde{c}^{<t>} = \tanh(W_c[\Gamma_r * c^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[c^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_r = \sigma(W_r[c^{<t-1>}, x^{<t>}] + b_r)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + (1 - \Gamma_u) * c^{<t-1>}$$

$$a^{<t>} = c^{<t>}$$

LSTM

$$\tilde{c}^{<t>} = \tanh(W_c[a^{<t-1>}, x^{<t>}] + b_c)$$

$$\Gamma_u = \sigma(W_u[a^{<t-1>}, x^{<t>}] + b_u)$$

$$\Gamma_f = \sigma(W_f[a^{<t-1>}, x^{<t>}] + b_f)$$

$$\Gamma_o = \sigma(W_o[a^{<t-1>}, x^{<t>}] + b_o)$$

$$c^{<t>} = \Gamma_u * \tilde{c}^{<t>} + \Gamma_f * c^{<t-1>}$$

$$a^{<t>} = \Gamma_o * c^{<t>}$$

From these, we can see that the Update Gate and Forget Gate in the LSTM play a role similar to _____ and _____ in the GRU. What should go in the blanks?

- ☒ Γ_u and $1 - \Gamma_u$
- ☐ Γ_u and Γ_r
- ☐ $1 - \Gamma_u$ and Γ_u
- ☐ Γ_r and Γ_u

 Expand



Correct

Yes, correct!

10. True/False: You would use unidirectional RNN if you were building a model map to show how your mood is heavily dependent on the current and past few days' weather.

1 / 1 point

☐ False

☒ True



Expand



Correct

Your mood is contingent on the current and past few days' weather, not on the current, past, AND future days' weather.