

**Ex No: 9**

**Date:**

## **IMPLEMENT CODE OPTIMIZATION TECHNIQUES CONSTANT FOLDING**

**AIM:**

To write a C program to implement Constant Folding (Code optimization Technique).

**ALGORITHM:**

- The desired header files are declared.
- The two file pointers are initialized one for reading the C program from the file and one for writing the converted program with constant folding.
- The file is read and checked if there are any digits or operands present.
- If there is, then the evaluations are to be computed in switch case and stored.
- Copy the stored data to another file. • Print the copied data file.

**PROGRAM:**

```
#include<stdio.h>
#include<string.h> void main()
{char s[20]; char
flag[20]="//Constant"; char
result,equal,operator; double
op1,op2,interrslt; int a,flag2=0;
FILE *fp1,*fp2; fp1 =
fopen("input.txt","r"); fp2 =
fopen("output.txt","w");
    fscanf(fp1,"%s",s);
    while(!feof(fp1))
    { if(strcmp(s,flag)==0) { flag2 = 1;
        } if(flag2==1)
        { fscanf(fp1,"%s",s);
            result=s[0]; equal=s[1];
            if(isdigit(s[2])&& isdigit(s[4])) { if(s[3]=='+'||'-
                '||'*'||/') {
                    operator=s[3];
                    switch(operator)
                    {case '+':
                            interrslt=(s[2]-48)+(s[4]-48);
                            break;
                        case '-':
                            interrslt=(s[2]-48)-(s[4]-48);
                            break;
                        case '*':
```

```

                                interrslt=(s[2]-48)*(s[4]-48);
                                break;
                                case '/':
                                    interrslt=(s[2]-48)/(s[4]-48);
                                    break;
                                default: interrslt =
                                    0; break; }
                                fprintf(fp2,"/*Constant Folding*/\n");
                                fprintf(fp2,"%c = %lf\n",result,interrslt);
                                flag2 = 0;
                                }
                                } else { fprintf(fp2,"Not
                                    Optimized\n");
                                    fprintf(fp2,"%s\n",s);
                                }
                                } else {
                                    fprintf(fp2,"%s\n",s);
                                }
                                }
                                fscanf(fp1,"%s",s);
                                }
                                fclose(fp1);
                                fclose(fp2);
                                }

```

## OUTPUT:

```

root@localhost-live 261_ex9]# vi input.txt
[root@localhost-live 261_ex9]# vi 261_ex9.c
[root@localhost-live 261_ex9]# cc 261_ex9.c
[root@localhost-live 261_ex9]# ./a.out
[root@localhost-live 261_ex9]# vi output.txt

```

## //output.txt

```

a=7
b=10
c=5
d=7

```

## RESULT: