

```
.....:
Bag.java
.....:
public class Bag <T> {
    protected int packages;
    protected float weight;
    protected DEQ<T> bag;

    public Bag()
    {
        bag = new DEQ<T>();
        packages = 0;
        weight = 0;
    }

    public void pickUpOrder(Sample pack) throws QueueException
    {
        bag.enqueue(pack);
        packages++;
        weight += (pack.getItemWeight() * pack.getItemAmount());
    }

    public void pickUpExpressOrder(Package expPack) {
        bag.enqueueFirst(expPack);
        packages++;
        weight += (expPack.getItemWeight() * expPack.getItemAmount());
    }

    public void displayPackageBag()
    {
        System.out.println("Bag has " + packages + " packages and weighs " + weight + " lbs.");
    }

    public void displaySampleBag(Bag<T> samples)
    {
        System.out.println("Bag has " + samples.packages + " packages and weighs " + samples.weight + " lbs.");
    }

    public Queue<T> getBag()
    {
        return bag;
    }

    public int getPackages()
    {
        return packages;
    }

    public float getWeight()
    {
        return weight;
    }

    public void setPackages(int newPackages)
    {
        packages = newPackages;
    }
}
```

```
public void setWeight(float newWeight)
{
    weight = newWeight;
}

}
.....:
DEQ.java
.....:

public class DEQ<T> extends Queue<T> implements ExtendedQueueInterface<T> {

    public DEQ()
    {
        super();
    }

    @Override
    public void enqueueFirst(Object newItem) throws ExtendedQueueException {
        if(numItems == items.length)
        {
            super.resize();
        }

        front = (front + items.length-1)%items.length;

        items[front] = (T) newItem;
        numItems++;
    }

    @Override
    public T dequeueLast() throws ExtendedQueueException {
        T result = null;
        if(numItems > 0)
        {
            back = (back + items.length-1)%items.length;
            result = items[back];
            items[back] = null;
            numItems--;
        }
        return result;
    }

    @Override
    public T peekLast() throws ExtendedQueueException {
        T result = null;
        if(numItems > 0)
        {
            result = items[(back + items.length-1)%items.length];
        }
        else
        {
            System.out.println("Queue empty!");
        }
        return result;
    }
}
.....:
Driver.java
```

```
.....
/*

 * Purpose: Data Structure and Algorithms Lab 6 Problem 4

 * Status: Complete and thoroughly tested

 * Last update: 03/03/2020

 * Submitted: 03/03/2020

 * Comment: test suite and sample run attached

 * @author: Matthew Ryan

 * @version: 2020.03.03

 */

import java.io.BufferedReader;
import java.io.IOException;
import java.io.InputStreamReader;

public class Driver {
    static BufferedReader stdin = new BufferedReader (new InputStreamReader(System
.in));

    public static <T> void main(String[] args) throws NumberFormatException, IOExc
eption, QueueException {

        Bag<T> bag = new Bag<T>();
        SampleBag<T> samples = new SampleBag<T>();

        boolean switchOn = true;

        System.out.println("\nSelect from the following menu:"
            + "\n\t0. Exit."
            + "\n\t1. Pick up an order."
            + "\n\t2. Drop off an order."
            + "\n\t3. Display number of packages and weight of bag."
            + "\n\t4. Display number of items and weight of the bag
of samples."
            + "\n\t5. Enjoy an item from the bag of samples."
            + "\n\t6. Enjoy all the samples in the bag of samples."
            + "\n\t7. Pick up an express order.");

        while(switchOn == true)
        {
            System.out.print("\nMake your selection now: ");
            int selection = Integer.parseInt(stdin.readLine().trim());
            System.out.println(selection);

            switch(selection)
            {

            case 0:
                switchOn = false;
                System.out.println("Exiting program...Good Bye");
                break;

```

```
            case 1:

                String name = "";
                String sender = "";
                String recipient = "";
                float weight = 0;
                int amount = 0;

                System.out.println("Please specify info: ");

                System.out.print("Item name: ");
                name = stdin.readLine().trim();
                System.out.println(name);

                System.out.print("\nItem weight: ");
                weight = Float.parseFloat(stdin.readLine().trim());
                System.out.println(weight);

                System.out.print("\n# of items: ");
                amount = Integer.parseInt(stdin.readLine().trim());
                System.out.println(amount);

                System.out.print("\nSender: ");
                sender = stdin.readLine().trim();
                System.out.println(sender);

                System.out.print("\nRecipient: ");
                recipient = stdin.readLine().trim();
                System.out.println(recipient);

                Package pack = new Package(name, weight, amount, sender, recipient
);
                bag.pickUpOrder(pack);
                System.out.println("A package of " + name + "s each weighing " + w
eight + " lbs are now in the bag.");
                break;
            case 2:

                if (bag.getBag().isEmpty())
                {
                    System.out.println("No deliveries to process!");
                }
                else
                {
                    Package dropOff = (Package) bag.getBag().dequeue();

                    float newWeight = bag.getWeight() - (dropOff.getItemWeight() *
dropOff.getItemAmount());
                    int newPackages = bag.getPackages()-1;

                    bag.setWeight(newWeight);
                    bag.setPackages(newPackages);

                    System.out.print("Here is your package " + dropOff.getItemRece
iver() + ". May I keep a sample (Y/N)? ");
                    String response = stdin.readLine();
                    System.out.print(response);

                    while(! (response.toUpperCase().equals("Y") || (response.toUpp

```

```

erCase().equals("N"))))
{
    System.out.print("Please say (Y)es or (No)! ");
    response = stdin.readLine().trim();
    System.out.println(response);
}

System.out.println("\nYour package contains: ");

if(dropOff.getItemAmount() == 1)
{
    System.out.println("A " + dropOff.getItemName() + " weighi
ng " + dropOff.getItemWeight()
+ " from " + dropOff.getItemSender() +
" to " + dropOff.getItemReceiver());
}
else
{
    System.out.println(dropOff.getItemAmount() + " " + dropOff
.getItemName()
+ "s each weighing " + dropOff.getItemW
eight()
+ " from " + dropOff.getItemSender() +
" to " + dropOff.getItemReceiver());
}

if((response.toUpperCase().equals("Y")))
{
    System.out.println(" Thanks for letting me keep a " + drop
Off.getItemName() + "!");
    Package sample = new Package(dropOff.getItemName().toStrin
g(), dropOff.getItemWeight(), 1, dropOff.getItemSender(), dropOff.getItemReceiver(
));
    samples.pickUpOrder(sample);
}
else
{
    System.out.println(" Thanks anyway.");
}
}

break;
case 3:
    System.out.println("Bag has " + bag.getPackages() + " packages and
weights " + bag.getWeight() + " lbs.");
    break;
case 4:
    System.out.println("Sample bag has " + samples.getPackages() + " p
ackages and weights " + samples.getWeight() + " lbs.");
    break;
case 5:
    if(bag.getBag().isEmpty())
    {
        System.out.println("No samples to enjoy!");
    }
    else
    {
        Package sample = (Package) samples.getBag().pop();

        float newWeight = samples.getWeight() - sample.getItemWeight()
;

```

```

int newPackages = samples.getPackages()-1;

samples.setWeight(newWeight);
samples.setPackages(newPackages);

System.out.println("This " + sample.getItemName() + " is amazi
ng! I love free stuff!");
}
break;
case 6:
    if(samples.getBag().isEmpty())
    {
        System.out.println("Sample bag is already empty.");
    }
    else
    {
        samples.getBag().popAll();
        samples.setPackages(0);
        samples.setWeight(0);
        System.out.println("Sample bag has been emptied.");
    }
    break;
case 7:

    String expName = "";
    String expSender = "";
    String expRecipient = "";
    float expWeight = 0;
    int expAmount = 0;

    System.out.println("Please specify express package info: ");

    System.out.print("Item name: ");
    expName = stdin.readLine().trim();
    System.out.println(expName);

    System.out.print("\nItem weight: ");
    expWeight = Float.parseFloat(stdin.readLine().trim());
    System.out.println(expWeight);

    System.out.print("\n# of items: ");
    expAmount = Integer.parseInt(stdin.readLine().trim());
    System.out.println(expAmount);

    System.out.print("\nSender: ");
    expSender = stdin.readLine().trim();
    System.out.println(expSender);

    System.out.print("\nRecipient: ");
    expRecipient = stdin.readLine().trim();
    System.out.println(expRecipient);

    Package expPack = new Package(expName, expWeight, expAmount, expSe
nder, expRecipient);
    bag.pickUpExpressOrder(expPack);
    System.out.println("A package of " + expName + " each weighing " +
expWeight + " lbs are now in the bag.");
    break;
default:
    break;

```

```

    }
}

}

}

.....
ExtendedQueueException.java
.....

public class ExtendedQueueException extends RuntimeException {

    public ExtendedQueueException(String s) {
        super(s);
    } // end constructor
} // end ExtendedQueueException:::
ExtendedQueueInterface.java
.....

public interface ExtendedQueueInterface<T> extends QueueInterface<T> {
    public void enqueueFirst(T newItem) throws ExtendedQueueException;
    public T dequeueLast() throws ExtendedQueueException;
    public T peekLast() throws ExtendedQueueException;
} // end ExtendedQueueInterface
.....
Node.java
.....
public class Node<T> {
    private T item;
    private Node<T> next;

    public Node(T newItem) {
        item = newItem;
        next = null;
    } // end constructor

    public Node(T newItem, Node<T> nextNode) {
        item = newItem;
        next = nextNode;
    } // end constructor

    public void setItem(T newItem) {
        item = newItem;
    } // end setItem

    public T getItem() {
        return item;
    } // end getItem

    public void setNext(Node<T> nextNode) {
        next = nextNode;
    } // end setNext

    public Node<T> getNext() {
        return next;
    } // end getNext
} // end class Node:::
Package.java
.....

public class Package extends Sample {

```

```

    public Package(String name, float weight, int amount, String sender, String receiver)
    {
        super(name, weight, amount, sender, receiver);
    }
}
.....
QueueException.java
.....
public class QueueException extends Throwable {

    public QueueException(String s) {
        super(s);
    } // end constructor
} // end QueueException:::
QueueInterface.java
.....
public interface QueueInterface<T> {

    public boolean isEmpty();
    // Determines whether a queue is empty.
    // Precondition: None.
    // Postcondition: Returns true if the queue is empty;
    // otherwise returns false.

    public void enqueue(T newItem) throws QueueException;
    // Adds an item at the back of a queue.
    // Precondition: newItem is the item to be inserted.
    // Postcondition: If the operation was successful, newItem
    // is at the back of the queue. Some implementations
    // may throw QueueException if newItem cannot be added
    // to the queue.

    public T dequeue() throws QueueException;
    // Retrieves and removes the front of a queue.
    // Precondition: None.
    // Postcondition: If the queue is not empty, the item that
    // was added to the queue earliest is removed. If the queue is
    // empty, the operation is impossible and QueueException is thrown.

    public void dequeueAll();
    // Removes all items of a queue.
    // Precondition: None.
    // Postcondition: The queue is empty.

    public T peek() throws QueueException;
    // Retrieves the item at the front of a queue.
    // Precondition: None.
    // Postcondition: If the queue is not empty, the item
    // that was added to the queue earliest is returned.
    // If the queue is empty, the operation is impossible
    // and QueueException is thrown.

    public String toString();
} // end QueueInterface

.....
Queue.java
.....

public class Queue<T> implements QueueInterface<T> {

```

```

protected int numItems;
protected int front;
protected int back;
protected T[] items;

public Queue()
{
    numItems = 0;
    back = 0;
    front = 0;
    items = (T[]) new Object[3];
}

@Override
public boolean isEmpty() {
    return (numItems == 0);
}

@Override
public void enqueue(Object newItem) throws QueueException {
    if(numItems == items.length)
    {
        resize();
    }
    items[back] = (T) newItem;
    back = (back+1)%items.length;
    numItems++;
}

@Override
public T dequeue() throws QueueException {
    T result = null;
    if(numItems > 0)
    {
        result = items[front];
        items[front] = null;
        front = (front + 1)%items.length;
        numItems--;
    }
    return result;
}

@Override
public void dequeueAll() {
    numItems = 0;
    back = 0;
    front = 0;
    items = (T[]) new Object[3];
}

@Override
public T peek() throws QueueException {
    T result = null;
    if(numItems > 0)
    {
        result = items[front];
    }
    else
    {
        System.out.println("Queue empty!");
    }
}

```

```

    }
    return result;
}

public String toString()
{
    StringBuilder builder = new StringBuilder();
    String toReturn = "";
    int counter = 0;

    for(int i = front; counter < numItems; counter++)
    {
        String build = items[i].toString() + " ";
        builder.append(build);
        i = ((i+1)%items.length);
    }

    return toReturn = builder.toString();
}

protected void resize() {
    T[] temp = (T[]) new Object[items.length+1];
    System.out.println();
    int counter = 0;
    for(int i = front; counter < numItems; counter++)
    {
        temp[counter] = items[i];
        i = (i+1) % items.length;
    }

    items = temp;
    front = 0;
    back = numItems;
}

}
:::::::::::
QueueSLS.java
:::::::::::

public class QueueSLS<T> implements QueueInterface {

    Node<T> front;
    Node<T> back;

    public QueueSLS()
    {
        front = null;
        back = null;
    }

    @Override
    public boolean isEmpty() {

        if(front == null)

```

```

    {
        return true;
    }
    else
    {
        return false;
    }
}

@Override
public void enqueue(Object newItem) throws QueueException {
    if(back == null)
    {
        front = back = new Node(newItem);
    }
    else
    {
        Node temp = new Node(newItem);
        back.setNext(temp);
        back = temp;
    }
}

@Override
public Object dequeue() throws QueueException {

    Object result = null;

    if(front.getNext() != null)
    {
        result = front.getItem();
        front = front.getNext();
        if(front == null)
        {
            back = null;
        }
    }

    return result;
}

@Override
public void dequeueAll() {
    front = null;
    back = null;
}

@Override
public Object peek() throws QueueException {
    return front.getItem();
}

public String toString()
{
    Node<T> next = front;
    StringBuilder builder = new StringBuilder();
    String toReturn = "";

    while(next != null)
    {
        String name = next.getItem().toString() + " ";
        builder.append(name);

```

```

        next = next.getNext();
    }
    toReturn = builder.toString();

    return toReturn;
}

}

SampleBag.java
SampleBag.java

public class SampleBag<T> {

    private int packages;
    private float weight;
    private StackSLS<T> bag;

    public SampleBag()
    {
        bag = new StackSLS<T>();
        packages = 0;
        weight = 0;
    }

    public void pickUpOrder(Sample pack) throws QueueException
    {
        bag.push(pack);
        packages++;
        weight += (pack.getItemWeight() * pack.getItemAmount());
    }

    public void displayPackageBag()
    {
        System.out.println("Bag has " + packages + " packages and weighs " + weight + " lbs.");
    }

    public void displaySampleBag(Bag<T> samples)
    {
        System.out.println("Bag has " + samples.packages + " packages and weighs " + samples.weight + " lbs.");
    }

    public StackSLS<T> getBag()
    {
        return bag;
    }

    public int getPackages()
    {
        return packages;
    }

    public float getWeight()
    {
        return weight;
    }
}

```

```
}

public void setPackages(int newPackages)
{
    packages = newPackages;
}

public void setWeight(float newWeight)
{
    weight = newWeight;
}

}

:::::::::::::
Sample.java
:::::::::::::
public class Sample {

    private String itemName;
    private float itemWeight;
    private int itemAmount;
    private String itemSender;
    private String itemReceiver;

    public Sample(String name, float weight, int amount, String sender, String receiver)
    {
        itemName = name;
        itemWeight = weight;
        itemAmount = amount;
        itemSender = sender;
        itemReceiver = receiver;
    }

    public String getItemName() {
        return itemName;
    }

    public void setItemName(String itemName) {
        this.itemName = itemName;
    }

    public float getItemWeight() {
        return itemWeight;
    }

    public void setItemWeight(float itemWeight) {
        this.itemWeight = itemWeight;
    }

    public int getItemAmount() {
        return itemAmount;
    }

    public void setItemAmount(int itemAmount) {
        this.itemAmount = itemAmount;
    }

    public String getItemSender() {
        return itemSender;
    }
}
```

```
public void setItemSender(String itemSender) {
    this.itemSender = itemSender;
}

public String getItemReceiver() {
    return itemReceiver;
}

public void setItemReceiver(String itemReceiver) {
    this.itemReceiver = itemReceiver;
}

}

:::::::::::::
StackException.java
:::::::::::::
public class StackException
    extends java.lang.RuntimeException {
    public StackException(String s) {
        super(s);
    } // end constructor
} // end StackException:::::::::::::
StackInterface.java
:::::::::::::
public interface StackInterface<T> {
    public boolean isEmpty();
    // Determines whether the stack is empty.
    // Precondition: None.
    // Postcondition: Returns true if the stack is empty;
    // otherwise returns false.

    public void popAll();
    // Removes all the items from the stack.
    // Precondition: None.
    // PostCondition: Stack is empty.

    public void push(T newItem) throws StackException;
    // Adds an item to the top of a stack.
    // Precondition: newItem is the item to be added.
    // Postcondition: If insertion is successful, newItem
    // is on the top of the stack.
    // Exception: Some implementations may throw
    // StackException when newItem cannot be placed on
    // the stack.

    public T pop() throws StackException;
    // Removes the top of a stack.
    // Precondition: None.
    // Postcondition: If the stack is not empty, the item
    // that was added most recently is removed from the
    // stack.
    // Exception: Throws StackException if the stack is
    // empty.

    public T peek() throws StackException;
    // Retrieves the top of a stack.
    // Precondition: None.
    // Postcondition: If the stack is not empty, the item
    // that was added most recently is returned. The
    // stack is unchanged.
    // Exception: Throws StackException if the stack is
    // empty.
}
```

```

    public String toString();
} // end StackInterface::::::::::::
StackSLS.java
::::::::::::

public class StackSLS<T> implements StackInterface {

    private Node top;

    public <T> StackSLS()
    {
        top = null;
    }

    @Override
    public boolean isEmpty() {
        if(top == null)
        {
            return true;
        }
        else
        {
            return false;
        }
    }

    @Override
    public void popAll() {
        top = null;
    }

    @Override
    public void push(Object newItem) throws StackException {
        top = new Node(newItem, top);
    }

    @Override
    public T pop() throws StackException {
        T result = null;
        if(top != null)
        {
            result = (T) top.getItem();
            top = top.getNext();
        }
        return result;
    }

    @Override
    public T peek() throws StackException {
        T result = null;
        if(top != null)
        {
            result = (T) top.getItem();
        }
        return result;
    }

    public String toString()
    {
        Node<T> next = top;
        StringBuilder builder = new StringBuilder();
        String toReturn = "";

```

```

        while(next != null)
        {
            String name = next.getItem().toString() + " ";
            builder.append(name);
            next = next.getNext();
        }
        toReturn = builder.toString();

        return toReturn;
    }
}
::::::::::::
output.txt
::::::::::::

Select from the following menu:
    0. Exit.
    1. Pick up an order.
    2. Drop off an order.
    3. Display number of packages and weight of bag.
    4. Display number of items and weight of the bag of samples.
    5. Enjoy an item from the bag of samples.
    6. Enjoy all the samples in the bag of samples.
    7. Pick up an express order.

Make your selection now: 3
Bag has 0 packages and weights 0.0 lbs.

Make your selection now: 4
Sample bag has 0 packages and weights 0.0 lbs.

Make your selection now: 5
No samples to enjoy!

Make your selection now: 6
Sample bag is already empty.

Make your selection now: 2
No deliveries to process!

Make your selection now: 1
Please specify info:
Item name: apple

Item weight: 0.6

# of items: 10

Sender: Pickachu

Recipient: Mew
A package of apples each weighing 0.6 lbs are now in the bag.

Make your selection now: 3
Bag has 1 packages and weights 6.0 lbs.

Make your selection now: 4
Sample bag has 0 packages and weights 0.0 lbs.

Make your selection now: 1

```


Please specify info:
Item name: orange

Item weight: 0.85

of items: 14

Sender: Bulbasaur

Recipient: Abra
A **package** of oranges each weighing 0.85 lbs are now in the bag.

Make your selection now: 7
Please specify express **package** info:
Item name: pear

Item weight: 0.9

of items: 7

Sender: Abra

Recipient: Kadabra
A **package** of pear each weighing 0.9 lbs are now in the bag.

Make your selection now: 7
Please specify express **package** info:
Item name: mango

Item weight: 0.3

of items: 12

Sender: Victini

Recipient: Meloetta

A **package** of mango each weighing 0.3 lbs are now in the bag.

Make your selection now: 3
Bag has 4 packages and weights 27.800001 lbs.

Make your selection now: 4
Sample bag has 0 packages and weights 0.0 lbs.

Make your selection now: 2
Here is your **package** Meloetta. May I keep a sample (Y/N)? Y
Your **package** contains:
12 mangos each weighing 0.3 from Victini to Meloetta
Thanks **for** letting me keep a mango!

Make your selection now: 4
Sample bag has 1 packages and weights 0.3 lbs.

Make your selection now: 3
Bag has 3 packages and weights 24.2 lbs.

Make your selection now: 1
Please specify info:
Item name: cookie

Item weight: 0.1

of items: 50

Sender: Charizard

Recipient: Squirtle
A **package** of cookies each weighing 0.1 lbs are now in the bag.

Make your selection now: 1
Please specify info:
Item name: banana

Item weight: 0.5

of items: 22

Sender: Clefairy

Recipient: Vulpix

A **package** of bananas each weighing 0.5 lbs are now in the bag.

Make your selection now: 4
Sample bag has 1 packages and weights 0.3 lbs.

Make your selection now: 3
Bag has 5 packages and weights 40.2 lbs.

Make your selection now: 2
Here is your **package** Kadabra. May I keep a sample (Y/N)? N
Your **package** contains:
7 pears each weighing 0.9 from Abra to Kadabra
Thanks anyway.

Make your selection now: 4
Sample bag has 1 packages and weights 0.3 lbs.

Make your selection now: 3
Bag has 4 packages and weights 33.9 lbs.

Make your selection now: 2
Here is your **package** Mew. May I keep a sample (Y/N)? Y
Your **package** contains:
10 apples each weighing 0.6 from Pikachu to Mew
Thanks **for** letting me keep a apple!

Make your selection now: 4
Sample bag has 2 packages and weights 0.90000004 lbs.

Make your selection now: 3
Bag has 3 packages and weights 27.900002 lbs.

Make your selection now: 5
This apple is amazing! I love free stuff!

Make your selection now: 3
Bag has 3 packages and weights 27.900002 lbs.

Make your selection now: 4
Sample bag has 1 packages and weights 0.3 lbs.

Make your selection now: 6

Sample bag has been emptied.

Make your selection now: 1

Please specify info:

Item name: granola

Item weight: 0.5

of items: 25

Sender: Jigglypuff

Recipient: Meowth

A **package** of granolas each weighing 0.5 lbs are now in the bag.

Make your selection now: 7

Please specify express **package** info:

Item name: watermelon

Item weight: 3.7

of items: 3

Sender: Slowpoke

Recipient: Slowbro

A **package** of watermelon each weighing 3.7 lbs are now in the bag.

Make your selection now: 2

Here is your **package** Slowbro. May I keep a sample (Y/N)? Y

Your **package** contains:

3 watermelons each weighing 3.7 from Slowpoke to Slowbro

Thanks **for** letting me keep a watermelon!

Make your selection now: 3

Bag has 4 packages and weights 40.4 lbs.

Make your selection now: 4

Sample bag has 1 packages and weights 3.7 lbs.

Make your selection now: 5

This watermelon is amazing! I love free stuff!

Make your selection now: 0

Exiting program...Good Bye