Network Computing courses

Maël Auzias

ENSIBS - UBS

October 2014



Figure: teaching.auzias.net



Course details

Objectives

- How do *computers* communicate?
- What are the mechanisms under an HTTP request or a telegram message?
- Networks are all around us, better study them!



Course details



Evaluation

- Short test at the beginning of every lesson (5 min)?
- Project
- Final exam (1 hour)
- All same weighting

Material

 Slides available at teaching.auzias.net (github too)



Definitions and presentation Network classification HTTP request/response example Models overview (OSI and TCP/IP)

Presentation Outline

- Introduction
 - Definitions and presentation
 - Network classification
 - HTTP request/response example
 - Models overview (OSI and TCP/IP)
- 2 Layers
 - Physical
 - Data Link
 - Network
 - Transport
 - Session
 - Presentation
 - Application



Definitions and presentation

Network classification HTTP request/response example Models overview (OSI and TCP/IP)

Definitions

• Network: an interconnected group or system

- Network: an interconnected group or system
- Internet: world wide interconnected system of networks RFC791 (September 1981)

- Network: an interconnected group or system
- Internet: world wide interconnected system of networks RFC791 (September 1981)
- IP: Internet Protocol provides the functions necessary to deliver a package of bits from a source to a destination over a network

- Network: an interconnected group or system
- Internet: world wide interconnected system of networks RFC791 (September 1981)
- IP: Internet Protocol provides the functions necessary to deliver a package of bits from a source to a destination over a network
- (world wide) Web: network consisting of a collection of Internet websites using HTTP

 HTTP: Hypertext Transfer Protocol, application-level protocol for distributed, collaborative, hypermedia information systems draft HTTP2 (July 2014)

- HTTP: Hypertext Transfer Protocol, application-level protocol for distributed, collaborative, hypermedia information systems draft HTTP2 (July 2014)
- FTP: File Transfer Protocol promotes sharing of files, encourages the use of remote computers RFC959 (October 1985)

Models overview (OSI and TCP/IP)

- HTTP: Hypertext Transfer Protocol, application-level protocol for distributed, collaborative, hypermedia information systems draft HTTP2 (July 2014)
- FTP: File Transfer Protocol promotes sharing of files, encourages the use of remote computers RFC959 (October 1985)
- TCP: Transmission Control Protocol is intended for use as a highly reliable host-to-host RFC761 (January 1980)

- HTTP: Hypertext Transfer Protocol, application-level protocol for distributed, collaborative, hypermedia information systems draft HTTP2 (July 2014)
- FTP: File Transfer Protocol promotes sharing of files, encourages the use of remote computers RFC959 (October 1985)
- TCP: Transmission Control Protocol is intended for use as a highly reliable host-to-host RFC761 (January 1980)
- UDP: User Datagram Protocol provides a procedure for application programs to send messages to other programs with a minimum of protocol mechanism RFC768 (August 1980)

- **HTTP:** Hypertext Transfer **Protocol**, application-level protocol for distributed, collaborative, hypermedia information systems draft HTTP2 (July 2014)
- FTP: File Transfer Protocol promotes sharing of files, encourages the use of remote computers RFC959 (October 1985)
- TCP: Transmission Control Protocol is intended for use as a highly reliable host-to-host RFC761 (January 1980)
- UDP: User Datagram Protocol provides a procedure for application programs to send messages to other programs with a minimum of protocol mechanism RFC768 (August 1980)
- **RFC:** Request For Comments (Internet Draft (ID), RFC, Internet Standard)

Definitions and presentation

Network classification HTTP request/response example Models overview (OSI and TCP/IP)

Definitions

• Router: network hardware providing routing services

- Router: network hardware providing routing services
- Routing: algorithm processed to decide where to forward a packet

- Router: network hardware providing routing services
- Routing: algorithm processed to decide where to forward a packet
- Forwarding: action of moving a packet from one NIC to another

- Router: network hardware providing routing services
- Routing: algorithm processed to decide where to forward a packet
- Forwarding: action of moving a packet from one NIC to another
- NIC: Network Interface Card
- Switch (hub): network hardware connecting systems using packet switching

- Router: network hardware providing routing services
- Routing: algorithm processed to decide where to forward a packet
- Forwarding: action of moving a packet from one NIC to another
- NIC: Network Interface Card
- Switch (hub): network hardware connecting systems using packet switching
- Packet switching: forward-like method regardless of the content (destination-based)

- Router: network hardware providing routing services
- Routing: algorithm processed to decide where to forward a packet
- Forwarding: action of moving a packet from one NIC to another
- NIC: Network Interface Card
- Switch (hub): network hardware connecting systems using packet switching
- Packet switching: forward-like method regardless of the content (destination-based)
- NAT: Network Address Translation, router modifying IP address into another IP address.

Definitions and presentation

Network classification HTTP request/response example Models overview (OSI and TCP/IP)

Definitions

 Node (network): any entity that can send packets to/receive packets from a network through a NIC

- Node (network): any entity that can send packets to/receive packets from a network through a NIC
- Client: computer able to send requests to a server

- Node (network): any entity that can send packets to/receive packets from a network through a NIC
- Client: computer able to send requests to a server
- Request: application message destined for a server (order)

- Node (network): any entity that can send packets to/receive packets from a network through a NIC
- Client: computer able to send requests to a server
- Request: application message destined for a server (order)
- Server: computer able to respond a client's requests

- Node (network): any entity that can send packets to/receive packets from a network through a NIC
- Client: computer able to send requests to a server
- Request: application message destined for a server (order)
- Server: computer able to respond a client's requests
- Response: application message destined for a client (result)

- Node (network): any entity that can send packets to/receive packets from a network through a NIC
- Client: computer able to send requests to a server
- Request: application message destined for a server (order)
- Server: computer able to respond a client's requests
- Response: application message destined for a client (result)
- Fat client: application where most functions are processed by the client itself

- Node (network): any entity that can send packets to/receive packets from a network through a NIC
- Client: computer able to send requests to a server
- **Request: application message** destined for a server (*order*)
- Server: computer able to respond a client's requests
- Response: application message destined for a client (result)
- Fat client: application where most functions are processed by the client itself
- Thin client: application where most functions are carried out on a central server



• BAN: Body Area Network

• BAN: Body Area Network

• PAN: Personal Area Networks

• BAN: Body Area Network

• PAN: Personal Area Networks

• (W)LAN: (Wireless) Local Area Networks (home, office,

school or airport)

- BAN: Body Area Network
- PAN: Personal Area Networks
- **(W)LAN:** (Wireless) Local Area Networks (home, office, school or airport)
- MAN: Metropolitan Area Networks, can cover a whole city

- BAN: Body Area Network
- PAN: Personal Area Networks
- **(W)LAN:** (Wireless) Local Area Networks (home, office, school or airport)
- MAN: Metropolitan Area Networks, can cover a whole city
- WAN: Wide Area Networks cover a broad area (Internet)




Figure: upload.wikimedia.org



 Point-to-point: two entities directly connected to each other (tunnel).

- Point-to-point: two entities directly connected to each other (tunnel).
- Ring: data go around the ring, unidirectional way network.

- Point-to-point: two entities directly connected to each other (tunnel).
- Ring: data go around the ring, unidirectional way network.
- Mesh: all nodes cooperate in the distribution of data in the network¹.

- Point-to-point: two entities directly connected to each other (tunnel).
- Ring: data go around the ring, unidirectional way network.
- Mesh: all nodes cooperate in the distribution of data in the network¹.
- **Star:** all messages go through the same central node, reducing network failure.

- Point-to-point: two entities directly connected to each other (tunnel).
- Ring: data go around the ring, unidirectional way network.
- Mesh: all nodes cooperate in the distribution of data in the network¹.
- Star: all messages go through the same central node, reducing network failure.
- Fully connected: all nodes are connected to all other nodes.

- Point-to-point: two entities directly connected to each other (tunnel).
- Ring: data go around the ring, unidirectional way network.
- Mesh: all nodes cooperate in the distribution of data in the network¹.
- Star: all messages go through the same central node, reducing network failure.
- Fully connected: all nodes are connected to all other nodes.
- **Line:** bidirectional link between two nodes. Node can only send packet going through its neighbors.

- Point-to-point: two entities directly connected to each other (tunnel).
- Ring: data go around the ring, unidirectional way network.
- Mesh: all nodes cooperate in the distribution of data in the network¹.
- Star: all messages go through the same central node, reducing network failure.
- Fully connected: all nodes are connected to all other nodes.
- **Line:** bidirectional link between two nodes. Node can only send packet going through its neighbors.
- Bus: all nodes are connected to the same media. Only one can send a packet at a time, which all others then receive.



- Point-to-point: two entities directly connected to each other (tunnel).
- Ring: data go around the ring, unidirectional way network.
- Mesh: all nodes cooperate in the distribution of data in the network¹.
- **Star:** all messages go through the same central node, reducing network failure.
- Fully connected: all nodes are connected to all other nodes.
- **Line:** bidirectional link between two nodes. Node can only send packet going through its neighbors.
- Bus: all nodes are connected to the same media. Only one can send a packet at a time, which all others then receive.
- Tree: hierarchical topology, such as a binary tree.




Figure: Disconnected MANET illustration [1]




Figure: Store-carry-and-forward [1]




Figure: Store-carry-and-forward [1]




Figure: Store-carry-and-forward [1]




Figure: Store-carry-and-forward [1]

Definitions and presentation Network classification HTTP request/response example Models overview (OSI and TCP/IP)

HTTP request/response example

Enter getbootstrap.com in your browser

HTTP request/response example

Enter getbootstrap.com in your browser

Source	Destination	Protocol	Length	Info
192.168.0.48				Standard query 0x4797 A getbootstrap.com
208.67.222.222	192.168.0.48	DNS	108	Standard query response 0x4797 A 192.30.252.154 A 192.30.252.153

Figure: DNS request/response

HTTP request/response example


Enter getbootstrap.com in your browser

5	Source	Destination	Protocol	Length	Info
	208.67.222.222	192.168.0.48	DNS	108	Standard query response 0x4797 A 192.30.252.154 A 192.30.252.153


Figure: DNS request/response

Source	Destination	Protocol	Length Info
127.0.0.1			74 36159 > http [SYN] Seq=0 Win=43690 Len=0 MSS=65495 SACK_PERM=1 TSval=12
127.0.0.13	127.0.0.1	TCP	74 http > 36159 [SYN, ACK] Seq=0 Ack=1 Win=43690 Len=0 MSS=65495 SACK_PERM
127.0.0.1	127.0.0.13	TCP	66 36159 > http [ACK] Seq=1 Ack=1 Win=43776 Len=0 TSval=122257 TSecr=12225
127.0.0.1	127.0.0.13	HTTP	356 GET /index.html HTTP/1.1
127.0.0.13	127.0.0.1	TCP	66 http > 36159 [ACK] Seq=1 Ack=291 Win=44800 Len=0 TSval=122259 TSecr=122
127.0.0.13	127.0.0.1	HTTP	354 HTTP/1.1 200 OK (text/html)
127.0.0.1	127.0.0.13	TCP	66 36159 > http [ACK] Seq=291 Ack=289 Win=44800 Len=0 TSval=122259 TSecr=1
127.0.0.1	127.0.0.13	HTTP	357 GET /favicon.ico HTTP/1.1
127.0.0.13	127.0.0.1	HTTP	565 HTTP/1.1 404 Not Found (text/html)
127.0.0.1	127.0.0.13	TCP	66 36159 > http [ACK] Seq=582 Ack=788 Win=45952 Len=0 TSval=122269 TSecr=1

How do messages reach their destination?



More like this...






Maël Auzias

How does it work? From signal to application...


- > 7 Application
- **Presentation**
- 5 Session
- **4** Transport
- Network
- **Data Link**
- 1 Physical




Nth layer communicate with Nth layer..



.. thanks to 3-th layers



One single protocol, one single layer



Definitions and presentation Network classification HTTP request/response example Models overview (OSI and TCP/IP)

Encapsulation




Figure: Encapsulation

Presentation Outline

- Introduction
 - Definitions and presentation
 - Network classification
 - HTTP request/response example
 - Models overview (OSI and TCP/IP)
- 2 Layers
 - Physical
 - Data Link
 - Network
 - Transport
 - Session
 - Presentation
 - Application



Introduction Layers Conclusion Physical
Data Link
Network
Transport
Session
Presentation
Application

Aims

• Interface data link layer,

Aims

- Interface data link layer,
- (De)Encode,

Aims

- Interface data link layer,
- (De)Encode,
- Transmit: 1 after 0 (after 0 or 1, after 0... or 1)

Physical
Data Link
Network
Transport
Session
Presentation
Application

Hardware medium

• IEEE 802.3 (a.k.a. Ethernet): <100Gbit/s

- IEEE 802.3 (a.k.a. Ethernet): <100Gbit/s
- IEEE 802.11 (a.k.a. Wi-Fi): <50 Mbit/s (802.11ad goes up to 6.75 Gbit/s)

- IEEE 802.3 (a.k.a. Ethernet): <100Gbit/s
- IEEE 802.11 (a.k.a. Wi-Fi): <50 Mbit/s (802.11ad goes up to 6.75 Gbit/s)
- IEEE 802.15.1 (a.k.a. Bluetooth): <1 Mbit/s

- IEEE 802.3 (a.k.a. Ethernet): <100Gbit/s
- IEEE 802.11 (a.k.a. Wi-Fi): <50 Mbit/s (802.11ad goes up to 6.75 Gbit/s)
- IEEE 802.15.1 (a.k.a. Bluetooth): <1 Mbit/s
- IEEE 802.15.4 (a.k.a. ZigBee): <250 kbit/s

- IEEE 802.3 (a.k.a. Ethernet): <100Gbit/s
- IEEE 802.11 (a.k.a. Wi-Fi): <50 Mbit/s (802.11ad goes up to 6.75 Gbit/s)
- IEEE 802.15.1 (a.k.a. Bluetooth): <1 Mbit/s
- IEEE 802.15.4 (a.k.a. ZigBee): <250 kbit/s
- IEEE 802.16 (a.k.a. Wi-Max): <40 Mbit/s

- IEEE 802.3 (a.k.a. Ethernet): <100Gbit/s
- IEEE 802.11 (a.k.a. Wi-Fi): <50 Mbit/s (802.11ad goes up to 6.75 Gbit/s)
- IEEE 802.15.1 (a.k.a. Bluetooth): <1 Mbit/s
- IEEE 802.15.4 (a.k.a. ZigBee): <250 kbit/s
- IEEE 802.16 (a.k.a. Wi-Max): <40 Mbit/s
- IEEE 1394 (a.k.a. Firewire): <3200 Mbit/s

- IEEE 802.3 (a.k.a. Ethernet): <100Gbit/s
- IEEE 802.11 (a.k.a. Wi-Fi): <50 Mbit/s (802.11ad goes up to 6.75 Gbit/s)
- IEEE 802.15.1 (a.k.a. Bluetooth): <1 Mbit/s
- IEEE 802.15.4 (a.k.a. ZigBee): <250 kbit/s
- IEEE 802.16 (a.k.a. Wi-Max): <40 Mbit/s
- IEEE 1394 (a.k.a. Firewire): <3200 Mbit/s
- USB, serial port such as RS-232...



Hardware medium: IEEE 802.3 (Ethernet)



Figure: RJ45 connector

Hardware medium: IEEE 802.15.1 (Bluetooth)



Figure: Bluetooth card

Hardware medium: IEEE 802.15.4 (ZigBee)



Figure: ZigBee card



Hardware medium: IEEE 802.16 (Wi-Max)



Figure: Wi-Max antenna

Hardware medium: IEEE 1394 (Firewire)



Figure: Firewire connector

Physical
Data Link
Network
Transport
Session
Presentation
Application

Encoding

• MLT3 (Multi-Level Transmit): state change for 1s over 3 levels, stay in the same state for 0s

- MLT3 (Multi-Level Transmit): state change for 1s over 3 levels, stay in the same state for 0s
- AMI (Alternate Mark Inversion): state 0 for 0s, state +/-1 for 1s

- MLT3 (Multi-Level Transmit): state change for 1s over 3 levels, stay in the same state for 0s
- AMI (Alternate Mark Inversion): state 0 for 0s, state +/-1 for 1s
- Manchester: voltage transition (rising/falling edge mean 1/0)

- MLT3 (Multi-Level Transmit): state change for 1s over 3 levels, stay in the same state for 0s
- AMI (Alternate Mark Inversion): state 0 for 0s, state +/-1 for 1s
- Manchester: voltage transition (rising/falling edge mean 1/0)
- BMC (Biphase Mark Code): change its state for 1s, stay on the same state for 0s

- MLT3 (Multi-Level Transmit): state change for 1s over 3 levels, stay in the same state for 0s
- AMI (Alternate Mark Inversion): state 0 for 0s, state +/-1 for 1s
- Manchester: voltage transition (rising/falling edge mean 1/0)
- BMC (Biphase Mark Code): change its state for 1s, stay on the same state for 0s
- and so on...



Encoding: Multi-Level Transmit




Figure: Multi-Level Transmit

Encoding: Alternate Mark Inversion




Figure: Alternate Mark Inversion

Encoding: Manchester




Figure: Manchester

Encoding: Biphase Mark Code




Figure: Biphase Mark Code

Transmitting




Figure: Amplitude and phase modulation

Physical
Data Link
Network
Transport
Session
Presentation
Application

Error detection

• Repetition (hum...)

Physical
Data Link
Network
Transport
Session
Presentation
Application

- Repetition (hum...)
- Parity (XOR)

- Repetition (hum...)
- Parity (XOR)
- Checksum

- Repetition (hum...)
- Parity (XOR)
- Checksum
- CRC (Cyclic redundancy check): with a polynomial divison

- Repetition (hum...)
- Parity (XOR)
- Checksum
- CRC (Cyclic redundancy check): with a polynomial divison
- Hash

- Repetition (hum...)
- Parity (XOR)
- Checksum
- CRC (Cyclic redundancy check): with a polynomial divison
- Hash
- and so on...

Physical
Data Link
Network
Transport
Session
Presentation
Application

Error correcting

• not done yet...

Physical
Data Link
Network
Transport
Session
Presentation
Application

Physical Data Link Network Transport Session Presentation Application

Physical
Data Link
Network
Transport
Session
Presentation
Application

Physical Data Link Network Transport Session Presentation Application

Physical Data Link Network Transport Session Presentation Application

Physical Data Link Network Transport Session Presentation Application

Physical Data Link Network Transport Session Presentation Application

References



Maurice J. Khabbaz, Assi Chadi M., and Fawaz Wissam F.

Disruption-Tolerant Networking: A Comprehensive Survey on Recent Developments and Persisting Challenges.

IEEE communications surveys and tutorials, 2012.