

Survey paper published to the
International Journal of Scientific & Engineering Research
-IJSER (ISSN 2229-5518)

In the year 2002 it was observed that the nvidia's server was crashed and later when they performed routine checks on the server it was observed that an unusual unified resource locator hit the server with the slug parameter "x25" later the server was again crashed because of the "FDDI" slug parameter, the data was being read illegitimately by a 3rd party user (Perpetrator) and the data was being over written on the server by stealing all the confidential data from it. Another incident which resembles this happened in the year 2004 where the trial versions of the Facebook was being run, the message was being read by another perpetrator from the server using the slug parameters "IPid" and "rangingdistance" as the perpetrator was involved in this attack this was well know as MIM attack AKA "Man-in-the-middle Attack". When the social media era has hit the teen in the year 2008, the internet was full of Facebook and other social media applications. This was the great chance for the hacker who try to look authentic and steal the data from the authentic users illegitimately and black mail them, basically the hackers try to make the target to beleive that the page or platform that they are using is authentic and let them enter their sensitive data like passwords, credit card details and etc. The most "Phishing and spear phishing attacks" were hit by the slug parameters which try to spoof a website or a web application like e-sell, amazon and all the other e selling platform applications, the survey the conducted gave shocking results as most of them spoofed e-cart application with the parameters "tcpchecksum" and "mtcp", amazon platform was spoofed with the following flags "controlflags" &"tcpoffset", facebook was spoofed with the flag"tcpport". "Drive-by attack" refers to a cyberattack in which a malicious script causes a program to download and install itself on a user device, without explicit permission from the user, the intel serverin the year 2010 was crashed as the malicious script was installing all the applications which are capable of exploiting the server and steal the important information from it. The links followed these flags "ICMPID","udptraffic", "udpunicorn", "datagramid", "NTP","RIP", "TFTP". "Password attack" is a typical attack vector used to compromise user account authentication. As one of the most prominent

application security concerns, it's responsible for most data breaches worldwide. Password breaches have far-reaching repercussions. Done using Brute force attack, Dictionary attack, Keyloggers, Credential stuffing. The phishing attack URL had the following flags "GETID","POSTID", "openBSD","appid", "sessionid","transid" & "physicalid". SQL injection (SQLi) is a cyberattack that injects malicious SQL code into an application, allowing the attacker to view or modify a database. According to the Open Web Application Security Project, injection attacks, which include SQL injections, were the third most serious web application security risk in 2021, "SQL injection attack" the servers were hit by the following flags "SYN","ACK","synpacket","sycookies". "Cross-site scripting (XSS) attack" is the group exploited an XSS vulnerability in a JavaScript library called Feedify, which was used on the British Airway website. Attackers modified the script to send customer data to a malicious server, which used a domain name similar to British Airways - the servers were hit by having the following flags in it "serverattack","serverid","blockbankwidth". "Eavesdropping attack" occurs when a hacker intercepts, deletes, or modifies data that is transmitted between two devices. Eavesdropping, also known as sniffing or snooping, relies on unsecured network communications to access data in transit between devices, example to listen secretly to the private conversation of others. To gain access to private electronic communications, as through wiretapping or the interception of e-mail or cell phone calls. The links follow these flags "monlist", "getmonlist","NTPserver". "Birthday attack" is a type of cryptographic attack that relies on the birthday paradox to find a collision in a hash function. A hash function is a mathematical function that takes an input (called a message) and produces a fixed-size output (called a hash value or hash): "portid","FTPID","tryion","fragflag" flags in the ULR."Teardrop attack" is a denial-of-service (DoS) attack that involves sending fragmented packets to a target machine. Since the machine receiving such packets cannot reassemble them due to a bug in TCP/IP fragmentation reassembly, the packets overlap one another, crashing the target network device. This attack happens when the server is hit by the following flags "malwareid", "gethttpid", "httpid".