

SIMPLE FIELD CHECKLIST

Check the Pixel. Write down what you see.

This guide is for one short, supervised test. You do not need to know Android. A technical helper prepares the device; you and an observer watch what happens on the screen.

Safety first

Do not flash an ISO, install a custom ROM, reformat, root, or factory-reset the Pixel unless an authorized device procedure specifically tells the helper to do so.

This test package is local-only. It does not send messages, use the network, find your location, or capture evidence.

1 Write down the run

DATE

RUN NAME OR ID

YOUR NAME

OBSERVER'S NAME

DEVICE

Google Pixel 8a

ANDROID

Stock Android · API 35

2 Stop if any of these are true

- ☐ The device is not a Google Pixel 8a with Android API 35.
- ☐ The device is not the approved managed test phone.
- ☐ The helper cannot authorize it with ADB, or only an emulator is available.
- ☐ The chosen cover app is missing or will not open like a normal app.

When in doubt, stop. Write "NO-GO" and ask the person who manages the test device. Do not make up a result from a screenshot or emulator.

3 Get the phone ready

Ask the technical helper to do the items in the green box. You only need to check each box when the helper says it is done.

Technical helper — please do these checks

- ☐ Confirm JDK 17, Android SDK/API 35, Android build tools, Gradle, and ADB are installed.
- ☐ Confirm one authorized device appears: Google Pixel 8a, Android API 35.
- ☐ Confirm the managed-device / device-owner status using the approved test-device procedure.
- ☐ Build and install the disposable Gate 0A test package.

HELPER COMMANDS — COPY EXACTLY

```
java -version
gradle --version
adb version
adb devices -l
adb shell getprop ro.product.model
adb shell getprop ro.build.version.sdk

cd artifacts/covert-alert-system/android-test-package
gradle :app:assembleDebug && adb install -r app/build/outputs/apk/debug/app-
debug.apk
```

4 Choose the cover app

Choose a normal, harmless app that is already on the Pixel. The proxy should open this app after the shortcut is pressed.

COVER APP NAME AND PACKAGE NAME

- ☐ The cover app is installed.
- ☐ The helper saved its exact package name in **CAS Pixel Gate 0A**.
- ☐ The helper confirmed the cover app has a normal launcher button.

5 Pin the shortcut

1. In CAS Pixel Gate 0A, choose **Request pinned proxy shortcut**.
2. Accept the request in the Pixel launcher.
3. Look at the home screen and confirm the shortcut is really there.

If the shortcut is not visible, stop. A button press or screenshot is not proof that the launcher pinned it.

6 Run the five checks

For every row, press the pinned shortcut and write what you saw. The observer should watch the phone with you.

A Cold start	Start from the agreed ready state. Press the shortcut once.	Result / time: _____
B Warm start	Without rebooting, press the shortcut again.	Result / time: _____
C Locked phone	Lock the phone, then use the shortcut as instructed.	Result / time: _____
D After restart	Restart the phone using the approved procedure. Wait until it is ready, then press the shortcut.	Result / time: _____
E Repeat test	Ask the helper to repeat the shortcut at least 200 times. Write the number completed and any first failure.	Count / result: _____

Technical helper — record the timings

Run the supplied measurement script. It records the local proxy timing and does not send messages or change device policy.

```
cd artifacts/covert-alert-system/android-test-package
bash scripts/measure-gate0a.sh gate0a-<RUN-ID>.log
```

For the 200 repeats, the helper should use the approved repeat procedure and save its timing log. Do not replace physical results with emulator timings.

7 Observer check

Ask an ordinary observer to look at the phone. Check each item only after it was actually seen.

- ☐ The cover app looks normal.
- ☐ Home behaves normally.
- ☐ Settings → App info looks expected.
- ☐ Quick Settings looks expected.
- ☐ Back behaves normally.
- ☐ Recents has no stray test card.
- ☐ Notifications look expected.
- ☐ No extra screen, wrong app, or dead end appeared.

OBSERVER NOTES

8 Save and hand in the results

- On the Gate 0A test package, press **Copy JSON report**.
- Save the copied text as gate0a-<RUN-ID>-report.json.
- Ask the helper to save the timing log beside it.
- In the CAS console, open **Feasibility gates** → **Import Gate 0A report**.
- Choose the JSON file and press **Validate & import report**.
- Attach the JSON, timing log, and these notes to the run.

Important: importing a report does not create a pass. It stays **INCONCLUSIVE** until a person reviews the physical observations.

9 Final result

CHOOSE ONE	WHY?
☐ GO — every required check passed	
☐ NO-GO — something was blocked or failed	
☐ INCONCLUSIVE — more review is needed	