

Московский Авиационный Институт
(Национальный Исследовательский Университет)

Кафедра: 806 «Вычислительная математика и программирование»
Факультет: «Прикладная математика и физика»
Дисциплина: «Объектно-ориентированное программирование»

Лабораторная работа №9.
Тема: «Лямбда выражения»

Группа: 8О-408Б
Студент: Забарин Никита Игоревич
Преподаватель: Поповкин Александр Викторович
Вариант: №26

Москва
2017

Цель работы

Целью лабораторной работы является:

- Знакомство с лямбда-выражениями

Задание

Используя структуры данных, разработанные для лабораторной работы №6 (контейнер первого уровня и классы-фигуры) необходимо разработать:

- Контейнер второго уровня с использованием шаблонов.
- Реализовать с помощью лямбда-выражений набор команд, совершающих операции над контейнером 1-го уровня:
 - Генерация фигур со случайным значением параметров;
 - Печать контейнера на экран;
 - Удаление элементов со значением площади меньше определенного числа;
- В контейнер второго уровня поместить цепочку команд.
- Реализовать цикл, который проходит по всем командам в контейнере второго уровня и выполняет их, применяя к контейнеру первого уровня.

Для создания потоков использовать механизмы:

- future
- packaged_task/async

Для обеспечения потоко-безопасности структур данных использовать:

- mutex
- lock_guard

Нельзя использовать:

- Стандартные контейнеры std.

Выводы

Листинг

```
queue_item_impl.cpp:
template <class T>
QueueItem<T>::QueueItem(const std::shared_ptr<T>& item)
{
    m_item = item;
}

template <class T>
void QueueItem<T>::setNext(std::shared_ptr<QueueItem<T>> next)
{
    m_next = next;
}

template <class T>
std::shared_ptr<QueueItem<T>> QueueItem<T>::getNext()
{
    return m_next;
}

template <class T>
std::shared_ptr<T> QueueItem<T>::getItem() const
{

```

```

        return m_item;
    }

```

trapezoid.h:

```

#ifndef TRAPEZOID_H
#define TRAPEZOID_H

```

```

#include <iostream>
#include "figure.h"

```

```

class Trapezoid : public Figure

```

```

{

```

```

public:

```

```

    Trapezoid();
    Trapezoid(double sideA, double sideB, double height);
    Trapezoid(std::istream& is);

```

```

    void print() const override;
    double area() const override;

```

```

    Trapezoid& operator = (const Trapezoid& other);
    bool operator == (const Trapezoid& other) const;

```

```

    void* operator new (size_t size);
    void operator delete (void* p);

```

```

    friend std::ostream& operator << (std::ostream& os, const Trapezoid& trapezoid);
    friend std::istream& operator >> (std::istream& is, Trapezoid& trapezoid);

```

```

private:

```

```

    double m_sideA;
    double m_sideB;
    double m_height;

```

```

};

```

```

#endif

```

list_item.h:

```

#ifndef LIST_ITEM_H
#define LIST_ITEM_H

```

```

#include <memory>

```

```

template <class T>

```

```

class ListItem

```

```

{

```

```

public:

```

```

    ListItem(const std::shared_ptr<T>& item);

```

```

    void setPrev(std::shared_ptr<ListItem<T>> prev);
    void setNext(std::shared_ptr<ListItem<T>> next);
    std::shared_ptr<ListItem<T>> getPrev();
    std::shared_ptr<ListItem<T>> getNext();
    std::shared_ptr<T> getItem() const;

```

```

private:

```

```

    std::shared_ptr<T> m_item;
    std::shared_ptr<ListItem<T>> m_prev;
    std::shared_ptr<ListItem<T>> m_next;

```

```

};

```

```

#include "list_item_impl.cpp"

```

```
#endif
```

```
queue_item.h:
```

```
#ifndef QUEUE_ITEM_H
```

```
#define QUEUE_ITEM_H
```

```
#include <memory>
```

```
template <class T>
```

```
class QueueItem
```

```
{
```

```
public:
```

```
    QueueItem(const std::shared_ptr<T>& item);
```

```
    void setNext(std::shared_ptr<QueueItem<T>> next);
```

```
    std::shared_ptr<QueueItem<T>> getNext();
```

```
    std::shared_ptr<T> getItem() const;
```

```
private:
```

```
    std::shared_ptr<T> m_item;
```

```
    std::shared_ptr<QueueItem<T>> m_next;
```

```
};
```

```
#include "queue_item_impl.cpp"
```

```
#endif
```

```
list_impl.cpp:
```

```
template <class T>
```

```
List<T>::List()
```

```
{
```

```
    m_size = 0;
```

```
}
```

```
template <class T>
```

```
List<T>::~~List()
```

```
{
```

```
    while (size() > 0)
```

```
        erase(begin());
```

```
}
```

```
template <class T>
```

```
void List<T>::add(const std::shared_ptr<T>& item)
```

```
{
```

```
    std::shared_ptr<ListItem<T>> itemPtr = std::make_shared<ListItem<T>>(item);
```

```
    if (m_size == 0)
```

```
    {
```

```
        m_begin = itemPtr;
```

```
        m_end = m_begin;
```

```
    }
```

```
    else
```

```
    {
```

```
        itemPtr->setPrev(m_end);
```

```
        m_end->setNext(itemPtr);
```

```
        m_end = itemPtr;
```

```
    }
```

```
    ++m_size;
```

```
}
```

```
template <class T>
```

```
void List<T>::erase(const Iterator<ListItem<T>, T>& it)
```

```

{
    if (m_size == 1)
    {
        m_begin = nullptr;
        m_end = nullptr;
    }
    else
    {
        std::shared_ptr<ListItem<T>> left = it.getItem()->getPrev();
        std::shared_ptr<ListItem<T>> right = it.getItem()->getNext();
        std::shared_ptr<ListItem<T>> mid = it.getItem();

        mid->setPrev(nullptr);
        mid->setNext(nullptr);

        if (left != nullptr)
            left->setNext(right);
        else
            m_begin = right;

        if (right != nullptr)
            right->setPrev(left);
        else
            m_end = left;
    }

    --m_size;
}

template <class T>
unsigned int List<T>::size() const
{
    return m_size;
}

template <class T>
Iterator<ListItem<T>, T> List<T>::get(unsigned int index) const
{
    if (index >= size())
        return end();

    Iterator<ListItem<T>, T> it = begin();

    while (index > 0)
    {
        ++it;
        --index;
    }

    return it;
}

template <class T>
Iterator<ListItem<T>, T> List<T>::begin() const
{
    return Iterator<ListItem<T>, T>(m_begin);
}

template <class T>
Iterator<ListItem<T>, T> List<T>::end() const
{
    return Iterator<ListItem<T>, T>(nullptr);
}

```

```

template <class K>
std::ostream& operator << (std::ostream& os, const List<K>& list)
{
    if (list.size() == 0)
    {
        os << "=====" << std::endl;
        os << "List is empty" << std::endl;
    }
    else
        for (std::shared_ptr<K> item : list)
            item->print();

    return os;
}

```

square.h:

```

#ifndef SQUARE_H
#define SQUARE_H

```

```

#include <iostream>
#include "figure.h"

```

```

class Square : public Figure

```

```

{
public:
    Square();
    Square(double side);
    Square(std::istream& is);

    void print() const override;
    double area() const override;

    Square& operator = (const Square& other);
    bool operator == (const Square& other) const;

    void* operator new (size_t size);
    void operator delete (void* p);

    friend std::ostream& operator << (std::ostream& os, const Square& square);
    friend std::istream& operator >> (std::istream& is, Square& square);

```

```

private:

```

```

    double m_side;

```

```

};

```

```

#endif

```

trapezoid.cpp:

```

#include "trapezoid.h"

```

```

Trapezoid::Trapezoid()

```

```

{
    m_sideA = 0.0;
    m_sideB = 0.0;
    m_height = 0.0;
}

```

```

Trapezoid::Trapezoid(double sideA, double sideB, double height)

```

```

{
    m_sideA = sideA;
    m_sideB = sideB;
    m_height = height;
}

```

```

}

Trapezoid::Trapezoid(std::istream& is)
{
    is >> *this;
}

void Trapezoid::print() const
{
    std::cout << *this;
}

double Trapezoid::area() const
{
    return m_height * (m_sideA + m_sideB) / 2.0;
}

Trapezoid& Trapezoid::operator = (const Trapezoid& other)
{
    if (&other == this)
        return *this;

    m_sideA = other.m_sideA;
    m_sideB = other.m_sideB;
    m_height = other.m_height;

    return *this;
}

bool Trapezoid::operator == (const Trapezoid& other) const
{
    return m_sideA == other.m_sideA && m_sideB == other.m_sideB && m_height == other.m_height;
}

void* Trapezoid::operator new (size_t size)
{
    return Figure::allocator.allocate();
}

void Trapezoid::operator delete (void* p)
{
    Figure::allocator.deallocate(p);
}

std::ostream& operator << (std::ostream& os, const Trapezoid& trapezoid)
{
    os << "=====" << std::endl;
    os << "Figure type: trapezoid" << std::endl;
    os << "Side A size: " << trapezoid.m_sideA << std::endl;
    os << "Side B size: " << trapezoid.m_sideB << std::endl;
    os << "Height: " << trapezoid.m_height << std::endl;

    return os;
}

std::istream& operator >> (std::istream& is, Trapezoid& trapezoid)
{
    std::cout << "=====" << std::endl;
    std::cout << "Enter side A: ";
    is >> trapezoid.m_sideA;
    std::cout << "Enter side B: ";
    is >> trapezoid.m_sideB;
    std::cout << "Enter height: ";

```

```

        is >> trapezoid.m_height;

    return is;
}

```

allocator.h:

```

#ifndef ALLOCATOR_H
#define ALLOCATOR_H

#include <cstdlib>
#include "list.h"

#define R_CAST(__ptr, __type) reinterpret_cast<__type>(__ptr)

class Allocator
{
public:
    Allocator(unsigned int blockSize, unsigned int count);
    ~Allocator();

    void* allocate();
    void deallocate(void* p);
    bool hasFreeBlocks() const;

private:
    void* m_memory;
    List<unsigned int> m_freeBlocks;
};

#endif

```

rectangle.h:

```

#ifndef RECTANGLE_H
#define RECTANGLE_H

#include <iostream>
#include "figure.h"

class Rectangle : public Figure
{
public:
    Rectangle();
    Rectangle(double sideA, double sideB);
    Rectangle(std::istream& is);

    void print() const override;
    double area() const override;

    Rectangle& operator = (const Rectangle& other);
    bool operator == (const Rectangle& other) const;

    void* operator new (size_t size);
    void operator delete (void* p);

    friend std::ostream& operator << (std::ostream& os, const Rectangle& rectangle);
    friend std::istream& operator >> (std::istream& is, Rectangle& rectangle);

private:
    double m_sideA;
    double m_sideB;
};

#endif

```



```

allocator.cpp:
#include "allocator.h"

Allocator::Allocator(unsigned int blockSize, unsigned int count)
{
    m_memory = malloc(blockSize * count);

    for (unsigned int i = 0; i < count; ++i)
        m_freeBlocks.add(std::make_shared<unsigned int>(i * blockSize));
}

Allocator::~Allocator()
{
    free(m_memory);
}

void* Allocator::allocate()
{
    void* res = R_CAST(R_CAST(m_memory, char*) + **m_freeBlocks.get(0), void*);

    m_freeBlocks.erase(m_freeBlocks.begin());

    return res;
}

void Allocator::deallocate(void* p)
{
    unsigned int offset = R_CAST(p, char*) - R_CAST(m_memory, char*);

    m_freeBlocks.add(std::make_shared<unsigned int>(offset));
}

bool Allocator::hasFreeBlocks() const
{
    return m_freeBlocks.size() > 0;
}

queue_impl.cpp:
template <class T>
Queue<T>::Queue()
{
    m_size = 0;
}

template <class T>
Queue<T>::~~Queue()
{
    while (size() > 0)
        pop();
}

template <class T>
void Queue<T>::push(const std::shared_ptr<T>& item)
{
    std::shared_ptr<QueueItem<T>> itemPtr = std::make_shared<QueueItem<T>>(item);

    if (m_size == 0)
    {
        m_front = itemPtr;
        m_end = m_front;
    }
    else

```

```

        {
            m_end->setNext(itemPtr);
            m_end = itemPtr;
        }

        ++m_size;
    }

template <class T>
void Queue<T>::pop()
{
    if (m_size == 1)
    {
        m_front = nullptr;
        m_end = nullptr;
    }
    else
        m_front = m_front->getNext();

    --m_size;
}

template <class T>
unsigned int Queue<T>::size() const
{
    return m_size;
}

template <class T>
std::shared_ptr<T> Queue<T>::front() const
{
    return m_front->getItem();
}

template <class T>
Iterator<QueueItem<T>, T> Queue<T>::begin() const
{
    return Iterator<QueueItem<T>, T>(m_front);
}

template <class T>
Iterator<QueueItem<T>, T> Queue<T>::end() const
{
    return Iterator<QueueItem<T>, T>(nullptr);
}

template <class K>
std::ostream& operator << (std::ostream& os, const Queue<K>& queue)
{
    if (queue.size() == 0)
    {
        os << "=====" << std::endl;
        os << "Queue is empty" << std::endl;
    }
    else
        for (std::shared_ptr<K> item : queue)
            item->print();

    return os;
}

```

list_item_impl.cpp:
template <class T>

```

ListItem<T>::ListItem(const std::shared_ptr<T>& item)
{
    m_item = item;
}

template <class T>
void ListItem<T>::setPrev(std::shared_ptr<ListItem<T>> prev)
{
    m_prev = prev;
}

template <class T>
void ListItem<T>::setNext(std::shared_ptr<ListItem<T>> next)
{
    m_next = next;
}

template <class T>
std::shared_ptr<ListItem<T>> ListItem<T>::getPrev()
{
    return m_prev;
}

template <class T>
std::shared_ptr<ListItem<T>> ListItem<T>::getNext()
{
    return m_next;
}

template <class T>
std::shared_ptr<T> ListItem<T>::getItem() const
{
    return m_item;
}

```

figure.h:

```

#ifndef FIGURE_H
#define FIGURE_H

```

```

#include "allocator.h"

```

```

class Figure
{
public:
    virtual ~Figure() {}
    virtual void print() const = 0;
    virtual double area() const = 0;

    static Allocator allocator;
};

```

```

#endif

```

iterator_impl.cpp:

```

template <class N, class T>
Iterator<N, T>::Iterator(const std::shared_ptr<N>& item)
{
    m_item = item;
}

```

```

template <class N, class T>
std::shared_ptr<N> Iterator<N, T>::getItem() const
{

```

```

        return m_item;
    }

template <class N, class T>
std::shared_ptr<T> Iterator<N, T>::operator * ()
{
    return m_item->getItem();
}

template <class N, class T>
std::shared_ptr<T> Iterator<N, T>::operator -> ()
{
    return m_item->getItem();
}

template <class N, class T>
Iterator<N, T> Iterator<N, T>::operator ++ ()
{
    m_item = m_item->getNext();

    return *this;
}

template <class N, class T>
Iterator<N, T> Iterator<N, T>::operator ++ (int index)
{
    Iterator tmp(m_item);

    m_item = m_item->getNext();

    return tmp;
}

template <class N, class T>
bool Iterator<N, T>::operator == (const Iterator& other) const
{
    return m_item == other.m_item;
}

template <class N, class T>
bool Iterator<N, T>::operator != (const Iterator& other) const
{
    return !(*this == other);
}

queue.h:
#ifndef QUEUE_H
#define QUEUE_H

#include <iostream>
#include "queue_item.h"
#include "iterator.h"

template <class T>
class Queue
{
public:
    Queue();
    ~Queue();

    void push(const std::shared_ptr<T>& item);
    void pop();
    unsigned int size() const;

```

```

std::shared_ptr<T> front() const;

Iterator<QueueItem<T>, T> begin() const;
Iterator<QueueItem<T>, T> end() const;

template <class K>
friend std::ostream& operator << (std::ostream& os, const Queue<K>& queue);

private:
    std::shared_ptr<QueueItem<T>> m_front;
    std::shared_ptr<QueueItem<T>> m_end;
    unsigned int m_size;
};

#include "queue_impl.cpp"

#endif

square.cpp:
#include "square.h"

Square::Square()
{
    m_side = 0.0;
}

Square::Square(double side)
{
    m_side = side;
}

Square::Square(std::istream& is)
{
    is >> *this;
}

void Square::print() const
{
    std::cout << *this;
}

double Square::area() const
{
    return m_side * m_side;
}

Square& Square::operator = (const Square& other)
{
    if (&other == this)
        return *this;

    m_side = other.m_side;

    return *this;
}

bool Square::operator == (const Square& other) const
{
    return m_side == other.m_side;
}

void* Square::operator new (size_t size)
{

```

```

        return Figure::allocator.allocate();
    }

void Square::operator delete (void* p)
{
    Figure::allocator.deallocate(p);
}

std::ostream& operator << (std::ostream& os, const Square& square)
{
    os << "=====" << std::endl;
    os << "Figure type: square" << std::endl;
    os << "Side size: " << square.m_side << std::endl;

    return os;
}

std::istream& operator >> (std::istream& is, Square& square)
{
    std::cout << "=====" << std::endl;
    std::cout << "Enter side: ";
    is >> square.m_side;

    return is;
}

list.h:
#ifndef LIST_H
#define LIST_H

#include <iostream>
#include "list_item.h"
#include "iterator.h"

template <class T>
class List
{
public:
    List();
    ~List();

    void add(const std::shared_ptr<T>& item);
    void erase(const Iterator<ListItem<T>, T>& it);
    unsigned int size() const;
    Iterator<ListItem<T>, T> get(unsigned int index) const;

    Iterator<ListItem<T>, T> begin() const;
    Iterator<ListItem<T>, T> end() const;

    template <class K>
    friend std::ostream& operator << (std::ostream& os, const List<K>& list);

private:
    std::shared_ptr<ListItem<T>> m_begin;
    std::shared_ptr<ListItem<T>> m_end;
    unsigned int m_size;
};

#include "list_impl.cpp"

#endif

makefile:

```

```
CC = g++
CFLAGS = -std=c++11 -Wall -Werror -Wno-sign-compare -Wno-unused-result -pthread
FILES = main.cpp square.cpp rectangle.cpp trapezoid.cpp figure.cpp allocator.cpp
PROG = lab9
```

```
all:
    $(CC) $(CFLAGS) -o $(PROG) $(FILES)
```

```
clean:
    rm $(PROG)
```

```
main.cpp:
#include <functional>
#include <random>
#include <chrono>
#include <string>
#include <mutex>
#include <thread>
#include "queue.h"
#include "square.h"
#include "rectangle.h"
#include "trapezoid.h"
```

```
typedef std::function<void(void)> Command;
```

```
int main()
{
    Queue<Figure> q;
    List<Command> cmds;
    List<std::string> cmdsNames;
    std::mutex mtx;

    Command cmdInsert = [&]()
    {
        std::lock_guard<std::mutex> guard(mtx);

        unsigned int seed = std::chrono::system_clock::now().time_since_epoch().count();

        std::default_random_engine generator(seed);
        std::uniform_int_distribution<int> distrFigureType(1, 3);
        std::uniform_int_distribution<int> distrFigureParam(1, 10);

        std::cout << "=====" << std::endl;
        std::cout << "Command: insert" << std::endl;

        switch (distrFigureType(generator))
        {
            case 1:
            {
                std::cout << "=====" << std::endl;
                std::cout << "Inserted: square" << std::endl;

                double side = distrFigureParam(generator);

                q.push(std::shared_ptr<Square>(new Square(side)));

                break;
            }

            case 2:
            {
                std::cout << "=====" << std::endl;
                std::cout << "Inserted: rectangle" << std::endl;
```

```

        double sideA = distrFigureParam(generator);
        double sideB = distrFigureParam(generator);

        q.push(std::shared_ptr<Rectangle>(new Rectangle(sideA, sideB)));

        break;
    }

    case 3:
    {
        std::cout << "=====" << std::endl;
        std::cout << "Inserted: trapezoid" << std::endl;

        double sideA = distrFigureParam(generator);
        double sideB = distrFigureParam(generator);
        double height = distrFigureParam(generator);

        q.push(std::shared_ptr<Trapezoid>(new Trapezoid(sideA, sideB, height)));

        break;
    }
}

};

Command cmdErase = [&]()
{
    std::lock_guard<std::mutex> guard(mtx);

    const double AREA = 24.0;

    std::cout << "=====" << std::endl;
    std::cout << "Command: erase" << std::endl;

    if (q.size() == 0)
    {
        std::cout << "=====" << std::endl;
        std::cout << "Queue is empty" << std::endl;
    }
    else
    {
        std::shared_ptr<Figure> first = q.front();

        while (true)
        {
            bool isRemoved = false;

            for (auto figure : q)
            {
                if (figure->area() < AREA)
                {
                    std::cout << "=====" << std::endl;
                    std::cout << "Removed" << std::endl;

                    figure->print();
                    std::cout << "Area: " << figure->area() << std::endl;

                    q.pop();
                    isRemoved = true;

                    break;
                }
            }
        }
    }
}

```



```

                if (!isRemoved)
                    break;
            }
        }
};

Command cmdPrint = [&]()
{
    std::lock_guard<std::mutex> guard(mtx);

    std::cout << "=====" << std::endl;
    std::cout << "Command: print" << std::endl;

    for (auto figure : q)
    {
        figure->print();

        std::cout << "Area: " << figure->area() << std::endl;
    }
};

while (true)
{
    unsigned int action;

    std::cout << "=====" << std::endl;
    std::cout << "Menu:" << std::endl;
    std::cout << "1) Add command" << std::endl;
    std::cout << "2) Erase command" << std::endl;
    std::cout << "3) Execute commands" << std::endl;
    std::cout << "4) Print commands" << std::endl;
    std::cout << "0) Quit" << std::endl;
    std::cin >> action;

    if (action == 0)
        break;

    if (action > 4)
    {
        std::cout << "Error: invalid action" << std::endl;

        continue;
    }

    switch (action)
    {
        case 1:
        {
            unsigned int commandType;

            std::cout << "=====" << std::endl;
            std::cout << "1) Insert" << std::endl;
            std::cout << "2) Erase" << std::endl;
            std::cout << "3) Print" << std::endl;
            std::cout << "0) Quit" << std::endl;
            std::cin >> commandType;

            if (commandType > 0)
            {
                if (commandType > 3)
                {
                    std::cout << "Error: invalid command type" << std::endl;

```

```

        continue;
    }

    switch (commandType)
    {
        case 1:
        {
            cmds.add(std::shared_ptr<Command>(&cmdInsert, []
            cmdsNames.add(std::shared_ptr<std::string>(new

(Command*){}));
std::string("Insert")));

            break;
        }

        case 2:
        {
            cmds.add(std::shared_ptr<Command>(&cmdErase, []
            cmdsNames.add(std::shared_ptr<std::string>(new

(Command*){}));
std::string("Erase")));

            break;
        }

        case 3:
        {
            cmds.add(std::shared_ptr<Command>(&cmdPrint, []
            cmdsNames.add(std::shared_ptr<std::string>(new

(Command*){}));
std::string("Print")));

            break;
        }
    }

    break;
}

case 2:
{
    unsigned int commandIndex;

    std::cout << "=====" << std::endl;
    std::cout << "Command index: ";
    std::cin >> commandIndex;

    if (commandIndex >= cmds.size())
    {
        std::cout << "Error: invalid command index" << std::endl;

        continue;
    }

    cmds.erase(cmds.get(commandIndex));
    cmdsNames.erase(cmdsNames.get(commandIndex));

    break;
}

case 3:

```

```

        {
            Queue<std::thread> ths;

            for (auto cmd : cmds)
                ths.push(std::shared_ptr<std::thread>(new std::thread(*cmd)));

            for (auto th : ths)
                th->join();

            break;
        }

    case 4:
    {
        std::cout << "=====" << std::endl;

        if (cmds.size() == 0)
            std::cout << "Commands list is empty" << std::endl;
        else
            for (auto cmdName : cmdsNames)
                std::cout << *cmdName << std::endl;

        break;
    }
}

return 0;
}

```

rectangle.cpp:
#include "rectangle.h"

```

Rectangle::Rectangle()
{
    m_sideA = 0.0;
    m_sideB = 0.0;
}

```

```

Rectangle::Rectangle(double sideA, double sideB)
{
    m_sideA = sideA;
    m_sideB = sideB;
}

```

```

Rectangle::Rectangle(std::istream& is)
{
    is >> *this;
}

```

```

void Rectangle::print() const
{
    std::cout << *this;
}

```

```

double Rectangle::area() const
{
    return m_sideA * m_sideB;
}

```

```

Rectangle& Rectangle::operator = (const Rectangle& other)
{
    if (&other == this)

```

```

        return *this;

        m_sideA = other.m_sideA;
        m_sideB = other.m_sideB;

        return *this;
}

bool Rectangle::operator == (const Rectangle& other) const
{
    return m_sideA == other.m_sideA && m_sideB == other.m_sideB;
}

void* Rectangle::operator new (size_t size)
{
    return Figure::allocator.allocate();
}

void Rectangle::operator delete (void* p)
{
    Figure::allocator.deallocate(p);
}

std::ostream& operator << (std::ostream& os, const Rectangle& rectangle)
{
    os << "=====" << std::endl;
    os << "Figure type: rectangle" << std::endl;
    os << "Side A size: " << rectangle.m_sideA << std::endl;
    os << "Side B size: " << rectangle.m_sideB << std::endl;

    return os;
}

std::istream& operator >> (std::istream& is, Rectangle& rectangle)
{
    std::cout << "=====" << std::endl;
    std::cout << "Enter side A: ";
    is >> rectangle.m_sideA;
    std::cout << "Enter side B: ";
    is >> rectangle.m_sideB;

    return is;
}

```

figure.cpp:
#include "figure.h"

Allocator Figure::allocator(32, 100);

iterator.h:
#ifndef ITERATOR_H
#define ITERATOR_H

```

template <class N, class T>
class Iterator
{
public:
    Iterator(const std::shared_ptr<N>& item);

    std::shared_ptr<N> getItem() const;

    std::shared_ptr<T> operator * ();
    std::shared_ptr<T> operator -> ();

```

```
Iterator operator ++ ();  
Iterator operator ++ (int index);  
bool operator == (const Iterator& other) const;  
bool operator != (const Iterator& other) const;
```

```
private:
```

```
    std::shared_ptr<N> m_item;
```

```
};
```

```
#include "iterator_impl.cpp"
```

```
#endif
```