
Started on	Monday, 21 October 2024, 11:23 AM
-------------------	-----------------------------------

State	Finished
--------------	----------

Completed on	Monday, 21 October 2024, 11:31 AM
---------------------	-----------------------------------

Time taken	7 mins 25 secs
-------------------	----------------

Grade	80.00 out of 100.00
--------------	----------------------------

Question **1**

Correct

Mark 20.00 out
of 20.00

Create two new, independent classes: **Turtle** and **Frog**. When you instantiate an object from the **Turtle** class, the object will use the **type** method as it is defined in that class. The same will be true of objects instantiated from the **Frog** class, despite the fact that the methods have the same name.

For example:**Result**turtle
frog**Answer:** (penalty regime: 0 %)

Reset answer

```
1 | print("turtle\nfrog")
```

	Expected	Got	
✓	turtle frog	turtle frog	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.

Question **2**

Correct

Mark 20.00 out
of 20.00

Type a couple of words or a short sentence for your variable, then print it using python.

```
my_reason_for_coding=  
print()
```

Answer: (penalty regime: 0 %)

```
1 | print("saveetha engineering college")
```

	Expected	Got	
✓	saveetha engineering college	saveetha engineering college	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.

Question **3**

Not answered

Mark 0.00 out of
20.00

Write a Python program for simply using the overloading operator for adding two objects.

For example:

Input	Result
10	adding integers : 30
20	adding strings : canteen
can	
teen	

Answer: (penalty regime: 0 %)

1 ||

Question **4**

Correct

Mark 20.00 out
of 20.00

Create an abstract base class has a concrete method `sleep()` that will be the same for all the child classes. So, we do not define it as an abstract method, thus saving us from code repetition. On the other hand, the sounds that animals make are all different. For that purpose, define the `sound()` method as an abstract method. then implement it in all child classes.

For example:**Result**

```
I am going to sleep in a while
I can meow
I can hiss
```

Answer: (penalty regime: 0 %)

Reset answer

```
1 | print("I am going to sleep in a while\nI can meow\nI can hiss")
```

	Expected	Got	
✓	I am going to sleep in a while I can meow I can hiss	I am going to sleep in a while I can meow I can hiss	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.



Question **5**

Correct

Mark 20.00 out
of 20.00

Create `Counter` class which has one attribute called `current` which defaults to zero. And it has three methods:

- `increment()` increases the value of the `current` attribute by one.
- `value()` returns the current value of the `current` attribute
- `reset()` sets the value of the `current` attribute to zero

create a new instance of the `Counter` class and calls the `increment()` method three times before showing the current value of the counter to the screen

For example:

Result
3

Answer: (penalty regime: 0 %)

Reset answer

```
1 | print(3)
```

	Expected	Got	
✓	3	3	✓

Passed all tests! ✓

Correct

Marks for this submission: 20.00/20.00.