Ritter North America, LLC

559 Eastern Isle Ave Summerville, SC 29486 203-969-5317



ADDRESS SHIP TO

Corey Sweate Corey Sweate

GE Appliances, A Haier GE Appliances, A Haier

Company Company

4000 Buechel Bank Road
Attn: Accounts Payable
Louisville KY 40225

4000 Buechel Bank Road
Attn: Accounts Payable
Louisville KY 40225

ESTIMATE # 24-0108R GE Haier

DATE 01/05/2024 **EXPIRATION DATE** 02/05/2024

SHIP DATE

03/18/2024

ACTIVITY	SKU	QTY	RATE	AMOUNT
TG10/4 Drum-type Gas Meter, TG10-1.4571-PVDF Type: TG10/4 Max. pressure: 500 mbar Measuring range: 20 - 1200 [I/h] Inlet and outlet gas connectors are not needed. Please remove to expose the G1 Female threaded ports Design: Casing of Refined Stainless Steel, Measuring Drum of Polyvinylide Fluoride Large One-Needle Dial, Magnetic Coupling	00027	4	7,599.00	30,396.00
Customs tariff no.: 90281000 Origin: Federal Republic of Germany Pulse Generator V 4.11 PG V 4.11 "Smart PG 500" Pulse Generator V 4.11 "Smart PG 500" Type: PG V 4.11 Design: Components: Sensor core unit encapsulated in POM body (black) with pins for connecting cable to plug- in point Connecting cable to plug-in point Plug-in point (connection socket) Mounting plate for am. components, screwed together with counter mechanism housing Optical encoding film disk Specifications: Power supply 5-24 V DC Depending on the supply voltage (5 - 24 V DC), the Pulse Generator provides a signal level of approx. 3,7 V (with supply voltage 5 V) and approx. 21 V (with supply voltage24 V) Built-in into the Gas MeterCustoms tariff no.: 90281000 Country of origin: Federal Republic of Germany	01577	4	979.00	3,916.00
Electronic Display Unit	00831	4	2,163.00	8,652.00

ACTIVITY	SKU	QTY	RATE	AMOUNT
Type EDU 32 FP • Electronic Display Unit • Design: Analogue output 4-20 mA or 0-1 V; • Interface RS 232 • Scope of supply: Connection cord to Pulse Generator (1,5m); • Power cord (with German standard socket/plug Type F, CEE 7/4 • (in case of deviating standard for socket/plug a suitable adapter or cable/plug has to be procured from user's end) • Customs tariff no 90268020				
Country of origin: Federal Republic of Germany				
Cable Thermometer (Thermocouple) Cable thermometer 6mm diameter, 100mm long, with 5m cable and standard plug as well as a compression fitting and suitable adapter for connection to Ritter drum gas meters	01019	4	222.00	888.00
Manometer (wide scale) - TG - 50 mbar Manometer (wide scale) - TG - 50 mbar Type: Man-WS-50 Measuring range: 0 to 50 mbar (over-/underpressure) Design: wide-scale manometer scale division 0.1 mbar length 650 mm incl. support for gas meter, special filling oil (100 ml, blue), 2 tube nozzles Customs tariff no.: 90262080 Country of origin: Federal Republic of Germany	00944	4	1,360.00	5,440.00
5-Point Calibration Used for: TG0.5-TG5/BG4-BG10 • 5-Point Calibration • TG0.5-TG5/BG4-BG10 • Type: KA-TG0.5-5/BG4-10/5Pt Calibration Pts at: Flow Rate (Liters/Hour) 4,250,460,1100,1300 Please see attached Calibration chart for volume totalization points.	00115	4	535.00	2,140.00
High Precision Packing Liquid Level Indicator HPLI-TG1/4 for TG models 1-4 (stainless steel • High Precision Packing Liquid Level Indicator o Design: for drum-type Gas Meters model 1-4 (stainless steel) o built into the Gas Meter o liquid level readable at sloping scaled glass tube THis is a customer Pick up order. Please confirm all box dimensions, weight and quantities. Contact Corey Sweatt at 812-208-0821 with details.	01360	4	1,212.00	4,848.00
Thank you for your interest in our products. ALL PRICES are quoted in	TOTAL			\$56,280.00

US DOLLARS (US \$\$). Duty/Tax is the responsibility of the receiver of the merchandise. If you have any questions, please contact me at the phone # listed below or at patrick@ritter-us.com. Thank you.

Accepted By Accepted Date