EnvBusMon - [Logging, Msg Decode View] File Edit View Window Help ▼ 🙀 🙀 Medium ▼ 00 50 00 00 00 d0 00 03 ff 57 T Factory Test Mode ▼ system wide Factory Test Mode, system wide, Rep \wedge 07/17/24 05:22:01.024 [IDLE] Info1 = 007/17/24 05:22:06.125 272 Factory Test Mode, 00h (make unique Info2 = 80 'P'07/17/24 05:22:06.158 [IDLE] Info3 = 007/17/24 05:22:11.258 272 Factory Test Mode, 00h (make unique Info4 = 0Info16 = 14Info5 = 007/17/24 05:22:11.292 Info6 = 20807/17/24 05:22:16.384 272 Factory Test Mode, 00h (make unique Info7 = 007/17/24 05:22:16.417 [IDLE] Info8 = 307/17/24 05:22:21.514 272 Factory Test Mode, 00h (make unique Info9 = 25507/17/24 05:22:21.547 [IDLE] Ambient F Info10 = 8707/17/24 05:22:26.658 273 Factory Test Mode, 00h (make unique Chamber temp Infol1 = 1707/17/24 05:22:27.192 3 DHW Demand, water heater, Query 6 = 176FInfo12 = 6 07/17/24 05:22:27.877 3 DHW Demand, water heater, Report Bin # Info13 = 207/17/24 05:22:27.910 [IDLE] LDO state 4 = cooling Infol4 = 407/17/24 05:22:31.801 126 Factory Test Mode, 00h (make unique MV on/off time Info15 = 007/17/24 05:22:31.835 [IDLE] Ohr Info16 = 16 16min 07/17/24 05:22:36.936 272 Factory Test Mode, 00h (make unique Bucket 0 for Amb > 40 to <=60 Info17 = 127 07/17/24 05:22:36.969 [IDLE] 255 = invalid Info18 = 25507/17/24 05:22:42.041 272 Factory Test Mode, 00h (make unique Info19 = 127 Bucket 1 for Amb > 60 to <=80 07/17/24 05:22:42.075 [IDLE] Info20 = 255 07/17/24 05:22:47.175 273 Factory Test Mode, 00h (make unique Bucket 2 for Amb > 80 to <=100 Info21 = 17 07/17/24 05:22:47.208 [IDLE] 6 = 176F Info22 = 6 07/17/24 05:22:52.293 272 Factory Test Mode, 00h (make unique Info23 = 127 Bucket 1 for Amb > 100 to <=120 07/17/24 05:22:52.326 [IDLE] Info24 = 255 07/17/24 05:22:57.425 272 Factory Test Mode, 00h (make unique Info25 = 17 Tmax after 30 min warmup 07/17/24 05:22:57.459 [IDLE] Info26 = 607/17/24 05:23:02.567 272 Factory Test Mode, 00h (make unique Tstart after @ start of warmup Info27 = 14[IDLE] 07/17/24 05:23:02.600 Info28 = 307/17/24 05:23:07.709 273 Factory Test Mode, 00h (make unique Info29 = 1 Ignition state see table 07/17/24 05:23:07.743 [IDLE] Info30 = 007/17/24 05:23:12.828 272 Factory Test Mode, 00h (make unique $Inf \odot 31 = 40$ '(' Delta to be used for LDO comparison Info16 = 1507/17/24 05:23:12.861 [IDLE] 07/17/24 05:23:17.951 272 Factory Test Mode, 00h (make unique 07/17/24 05:23:17.985 [IDLE] 07/17/24 05:23:23.050 272 Factory Test Mode, 00h (make unique 07/17/24 05:23:23.084 [IDLE] 07/17/24 05:23:28.208 273 Factory Test Mode, 00h (make unique 07/17/24 05:23:28.742 3 DHW Demand, water heater, Query 07/17/24 05:23:29.424 3 DHW Demand, water heater, Report

07/17/24 05:23:29.457 [IDLE]

126 Factory Test Mode, 00h (make unique

07/17/24 05:23:33.341

07/17/04 05:00:00 075