


CS178: Machine Learning and Data Mining

Linear Regression

Prof. Erik Sudderth



Some materials courtesy Alex Ihler & Sameer Singh

CS178 Zoom Lectures

CS178 [zoom](#) lectures are recorded by the instructor (the recording feature is disabled for students). Recordings are posted to [YuJa](#), and only available to CS178 students and staff. To ask questions during lecture, you may:

- Use the **Raise Hand** feature. Prof. Sudderth will then call on you by name, unmute your microphone, and let you ask a question. *Your question will be recorded. Please be respectful of your instructor and classmates.*
- Use the [Q&A Window](#) to type a question. Prof. Sudderth will read your question to the class before answering it, but *will not personally identify you.*

Machine Learning

Linear Regression via Least Squares

Gradient Descent Algorithms

Direct Minimization of Squared Error

Regression with Non-linear Features


Bias, Variance, & Validation

Regularized Linear Regression


Supervised learning

- Notation

- Features x
- Targets y
- Predictions $\hat{y} = f(x ; \theta)$
- Parameters θ



Linear regression



“Predictor”:
Evaluate line:

$$r = \theta_0 + \theta_1 x_1$$

return r

- Define form of function $f(x)$ explicitly
- Find a good $f(x)$ within that family

Notation

$$\hat{y}(x) = \theta_0 + \theta_1 x_1 + \theta_2 x_2 + \dots$$

Define “feature” $x_0 = 1$ (constant)

Then


$$\hat{y}(x) = \theta x^T$$

$$\begin{aligned}\underline{\theta} &= [\theta_0, \dots, \theta_n] \\ \underline{x} &= [1, x_1, \dots, x_n]\end{aligned}$$


Supervised learning

- Notation

- Features x
- Targets y
- Predictions $\hat{y} = f(x ; \theta)$
- Parameters θ



Measuring error



Mean squared error

- How can we quantify the error?

$$\begin{aligned}\text{MSE, } J(\underline{\theta}) &= \frac{1}{m} \sum_j (y^{(j)} - \hat{y}(x^{(j)}))^2 \\ &= \frac{1}{m} \sum_j (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T})^2\end{aligned}$$

- Could choose something else, of course...
 - Computationally convenient (more later)
 - Measures the variance of the residuals
 - Corresponds to likelihood under Gaussian model of “noise”

$$\mathcal{N}(y ; \mu, \sigma^2) = \frac{1}{\sqrt{2\pi\sigma^2}} \exp \left\{ -\frac{1}{2\sigma^2} (y - \mu)^2 \right\}$$

MSE cost function

$$\begin{aligned}\text{MSE}, J(\underline{\theta}) &= \frac{1}{m} \sum_j (y^{(j)} - \hat{y}(x^{(j)}))^2 \\ &= \frac{1}{m} \sum_j (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T})^2\end{aligned}$$

- Rewrite using matrix form

$$\begin{aligned}\underline{\theta} &= [\theta_0, \dots, \theta_n] \\ \underline{y} &= [y^{(1)}, \dots, y^{(m)}]^T\end{aligned}$$

$$\underline{X} = \begin{bmatrix} x_0^{(1)} & \dots & x_n^{(1)} \\ \vdots & \ddots & \vdots \\ x_0^{(m)} & \dots & x_n^{(m)} \end{bmatrix}$$


$$J(\underline{\theta}) = \frac{1}{m} (\underline{y}^T - \underline{\theta} \underline{X}^T) \cdot (\underline{y}^T - \underline{\theta} \underline{X}^T)^T$$

```
# Python / NumPy:  
e = Y - X.dot( theta.T );  
J = e.T.dot( e ) / m # = np.mean( e ** 2 )
```





Supervised learning

- Notation

- Features x
- Targets y
- Predictions $\hat{y} = f(x ; \theta)$
- Parameters θ




Visualizing the cost function



Finding good parameters

- Want to find parameters which minimize our error...
- Think of a cost “surface”: error residual for that θ ...



Machine Learning

Linear Regression via Least Squares

Gradient Descent Algorithms


Direct Minimization of Squared Error

Regression with Non-linear Features

Bias, Variance, & Validation


Regularized Linear Regression

Gradient descent




- How to change θ to improve $J(\theta)$?
- Choose a direction in which $J(\theta)$ is decreasing

Gradient descent



- How to change θ to improve $J(\theta)$?
- Choose a direction in which $J(\theta)$ is decreasing
- Derivative $\frac{\partial J(\theta)}{\partial \theta}$
- Positive => increasing
- Negative => decreasing

Gradient descent in more dimensions



- Gradient vector


$$\nabla J(\underline{\theta}) = \left[\frac{\partial J(\underline{\theta})}{\partial \theta_0} \quad \frac{\partial J(\underline{\theta})}{\partial \theta_1} \quad \dots \right]$$

Indicates direction of steepest ascent
(negative = steepest descent)

Gradient descent

- Initialization
- Step size α
 - Can change over iterations
- Gradient direction
- Stopping condition

```
Initialize θ  
Do{  
    θ ← θ - α∇θJ(θ)  
} while (||∇θJ|| > ε)
```



Gradient for the MSE

- MSE $J(\underline{\theta}) = \frac{1}{m} \sum_j (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T})^2$

- $\nabla J = ?$

$$J(\underline{\theta}) = \frac{1}{m} \sum_j (y^{(j)} - \theta_0 \underline{x}_0^{(j)} - \theta_1 \underline{x}_1^{(j)} - \dots)^2$$

$e_j(\underline{\theta})$

$$\frac{\partial J}{\partial \theta_0} = \frac{\partial}{\partial \theta_0} \frac{1}{m} \sum_j (e_j(\underline{\theta}))^2$$

$$= \frac{1}{m} \sum_j \frac{\partial}{\partial \theta_0} (e_j(\underline{\theta}))^2$$

$$= \frac{1}{m} \sum_j 2e_j(\underline{\theta}) \frac{\partial}{\partial \theta_0} e_j(\underline{\theta})$$

$$\frac{\partial}{\partial \theta_0} e_j(\underline{\theta}) = \frac{\partial}{\partial \theta_0} y^{(j)} - \frac{\partial}{\partial \theta_0} \theta_0 \underline{x}_0^{(j)} - \frac{\partial}{\partial \theta_0} \theta_1 \underline{x}_1^{(j)} - \dots$$

0

0

$$= -x_0^{(j)}$$

Gradient for the MSE

- MSE $J(\underline{\theta}) = \frac{1}{m} \sum_j (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T})^2$

- $\nabla J = ?$

$$J(\underline{\theta}) = \frac{1}{m} \sum_j (y^{(j)} - \theta_0 \underline{x}_0^{(j)} - \theta_1 \underline{x}_1^{(j)} - \dots)^2$$

$e_j(\theta)$

$$\nabla J(\underline{\theta}) = \begin{bmatrix} \frac{\partial J}{\partial \theta_0} & \frac{\partial J}{\partial \theta_1} & \dots \end{bmatrix}$$

$$= \begin{bmatrix} \frac{2}{m} \sum_j -e_j(\theta) x_0^{(j)} & \frac{2}{m} \sum_j -e_j(\theta) x_1^{(j)} & \dots \end{bmatrix}$$

Gradient descent

- Initialization
- Step size α
 - Can change over iterations
- Gradient direction
- Stopping condition

```
Initialize θ  
Do{  
    θ ← θ - α∇θJ(θ)  
} while (||∇θJ|| > ε)
```

$$J(\underline{\theta}) = \frac{1}{m} \sum_j (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T})^2$$

$$\nabla J(\underline{\theta}) = -\frac{2}{m} \sum_j (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T}) \cdot [x_0^{(j)} x_1^{(j)} \dots]$$

Error magnitude &
direction for datum j Sensitivity to
each param

Derivative of MSE

- Rewrite using matrix form

$$\nabla J(\underline{\theta}) = -\frac{2}{m} \sum_j (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T}) \cdot [x_0^{(j)} x_1^{(j)} \dots]$$

$$\underline{\theta} = [\theta_0, \dots, \theta_n]$$

Error magnitude &
direction for datum j

Sensitivity to
each θ_i



$$\underline{y} = [y^{(1)} \dots, y^{(m)}]^T$$

$$\nabla J(\underline{\theta}) = -\frac{2}{m} (\underline{y}^T - \underline{\theta} \underline{X}^T) \cdot \underline{X}$$

$$\underline{X} = \begin{bmatrix} x_0^{(1)} & \dots & x_n^{(1)} \\ \vdots & \ddots & \vdots \\ x_0^{(m)} & \dots & x_n^{(m)} \end{bmatrix}$$


```
e = Y - X.dot(theta.T) # error residual
DJ = -e.dot(X) * 2.0/m # compute the gradient
theta -= alpha * DJ      # take a step
```

Gradient descent on cost function



Comments on gradient descent

- Very general algorithm
 - We'll see it many times
- Local minima
 - Sensitive to starting point



Comments on gradient descent

- Very general algorithm
 - We'll see it many times
- Local minima
 - Sensitive to starting point
- Step size
 - Too large? Too small? Automatic ways to choose?
 - May want step size to decrease with iteration
 - Common choices:
 - Fixed
 - Linear: $C/\text{iteration}$
 - Line search / backoff (Armijo, etc.)
 - Newton's method



Stochastic / Online gradient descent

- MSE

$$J(\underline{\theta}) = \frac{1}{m} \sum_j J_j(\underline{\theta}), \quad J_j(\underline{\theta}) = (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T})^2$$

- Gradient



$$\nabla J(\underline{\theta}) = \frac{1}{m} \sum_j \nabla J_j(\underline{\theta}) \quad \nabla J_j(\underline{\theta}) = (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T}) \cdot [x_0^{(j)} x_1^{(j)} \dots]$$

- Stochastic (or “online”) gradient descent:
 - Use updates based on individual datum j , chosen at random
 - At optima, $\mathbb{E}[\nabla J_j(\underline{\theta})] = \nabla J(\underline{\theta}) = 0$
(average over the data)

Online gradient descent



- Update based on one datum, and its residual, at a time

```
Initialize θ  
Do {  
    for j=1:m  
        θ ← θ - α∇θJj(θ)  
} while (not done)
```





Online gradient descent

```
Initialize θ  
Do {  
    for j=1:m  
        θ ← θ - α∇θJj(θ)  
} while (not done)
```





Online gradient descent

```
Initialize θ  
Do {  
    for j=1:m  
        θ ← θ - α∇θJj(θ)  
} while (not done)
```





Online gradient descent

```
Initialize θ  
Do {  
    for j=1:m  
        θ ← θ - α∇θJj(θ)  
} while (not done)
```





Online gradient descent

```
Initialize θ  
Do {  
    for j=1:m  
        θ ← θ - α∇θJj(θ)  
} while (not done)
```



Online gradient descent

```
Initialize θ  
Do {  
    for j=1:m  
        θ ← θ - α∇θJj(θ)  
} while (not done)
```



Online gradient descent

```
Initialize θ  
Do {  
    for j=1:m  
        θ ← θ - α∇θJj(θ)  
} while (not done)
```

$$J_j(\underline{\theta}) = (y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T})^2$$

$$\nabla J_j(\underline{\theta}) = -2(y^{(j)} - \underline{\theta} \cdot \underline{x}^{(j)T}) \cdot [x_0^{(j)} x_1^{(j)} \dots]$$

- **Benefits**
 - Lots of data = many more updates per pass
 - Computationally faster
- **Drawbacks**
 - No longer strictly “descent”
 - Stopping conditions may be harder to evaluate
(Can use “running estimates” of J(.), etc.)

Machine Learning

Linear Regression via Least Squares

Gradient Descent Algorithms

Direct Minimization of Squared Error


Regression with Non-linear Features

Bias, Variance, & Validation

Regularized Linear Regression

MSE Minimum

- Consider a simple problem
 - One feature, two data points
 - Two unknowns: θ_0, θ_1
 - Two equations:
$$y^{(1)} = \theta_0 + \theta_1 x^{(1)}$$
$$y^{(2)} = \theta_0 + \theta_1 x^{(2)}$$



- Can solve this system directly:
$$\underline{y}^T = \underline{\theta} \underline{X}^T \quad \Rightarrow \quad \hat{\underline{\theta}} = \underline{y}^T (\underline{X}^T)^{-1}$$
- However, most of the time, $m > n$
 - There may be no linear function that hits all the data exactly
 - Instead, solve directly for minimum of MSE function

MSE Minimum


$$\nabla J(\underline{\theta}) = -\frac{2}{m}(\underline{y}^T - \underline{\theta} \underline{X}^T) \cdot \underline{X} = \underline{0}$$

- Simplify with some algebra:

$$\underline{y}^T \underline{X} - \underline{\theta} \underline{X}^T \cdot \underline{X} = \underline{0}$$

$$\underline{y}^T \underline{X} = \underline{\theta} \underline{X}^T \cdot \underline{X}$$

$$\underline{\theta} = \underline{y}^T \underline{X} (\underline{X}^T \underline{X})^{-1}$$



- $\underline{X} (\underline{X}^T \underline{X})^{-1}$ is called the “pseudo-inverse”
- If \underline{X}^T is square and full rank, this is the inverse
- If $m > n$: overdetermined; gives minimum MSE fit

Python MSE

- This is easy to solve in Python / NumPy...

$$\underline{\theta} = \underline{y}^T \underline{X} (\underline{X}^T \underline{X})^{-1}$$

```
# y = np.matrix( [[y1], ... , [ym]] )
# X = np.matrix( [[x1_0 ... x1_n], [x2_0 ... x2_n], ...] )
```


```
# Solution 1: "manual"
th = y.T * X * np.linalg.inv(X.T * X)
```

```
# Solution 2: "least squares solve"
th = np.linalg.lstsq(X, Y)
```

Normal equations

$$\nabla J(\underline{\theta}) = 0 \quad \Rightarrow \quad (\underline{y}^T - \underline{\theta} \underline{X}^T) \cdot \underline{X} = 0$$


- Interpretation:
 - $(\underline{y} - \underline{\theta} \underline{X}) = (\underline{y} - \hat{\underline{y}})$ is the vector of errors in each example
 - \underline{X} are the features we have to work with for each example
 - Dot product = 0: orthogonal




$$\begin{aligned}\underline{y}^T &= [y^{(1)} \dots y^{(m)}] \\ \underline{x}_i &= [x_i^{(1)} \dots x_i^{(m)}]\end{aligned}$$

Effects of MSE choice

- Sensitivity to outliers



L1 error: Mean Absolute Error



Cost functions for regression


$$\ell_2 : (y - \hat{y})^2 \quad (\text{MSE})$$

$$\ell_1 : |y - \hat{y}| \quad (\text{MAE})$$

Something else entirely...

$$c - \log(\exp(-(y - \hat{y})^2) + c) \quad (\text{??})$$

Arbitrary functions cannot be solved in closed form
- use gradient descent



$$\leftarrow (y - \hat{y}) \rightarrow$$

Machine Learning

Linear Regression via Least Squares

Gradient Descent Algorithms



Direct Minimization of Squared Error

Regression with Non-linear Features

Bias, Variance, & Validation

Regularized Linear Regression

More dimensions?





$$\hat{y}(x) = \underline{\theta} \cdot \underline{x}^T$$

$$\underline{\theta} = [\theta_0 \ \theta_1 \ \theta_2]$$

$$\underline{x} = [1 \ x_1 \ x_2]$$

Nonlinear functions

- What if our hypotheses are not lines?
 - Ex: higher-order polynomials




(c) Alexander Ihler

Nonlinear functions

- Single feature x , predict target y :


$$D = \{(x^{(j)}, y^{(j)})\}$$

$$\hat{y}(x) = \theta_0 + \theta_1 x + \theta_2 x^2 + \theta_3 x^3$$



Add features:

$$D = \{([x^{(j)}, (x^{(j)})^2, (x^{(j)})^3], y^{(j)})\}$$



$$\hat{y}(x) = \theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_3$$

Linear regression in new features




- Sometimes useful to think of “feature transform”

$$\Phi(x) = [1, x, x^2, x^3, \dots]$$

$$\hat{y}(x) = \underline{\theta} \cdot \Phi(x)$$

Higher-order polynomials

- Fit in the same way
- More “features”







Features

- In general, can use any features we think are useful
- Other information about the problem
 - Anything you can encode as fixed-length vectors of numbers
- Polynomial functions
 - Features $[1, x, x^2, x^3, \dots]$
- Other functions
 - $1/x, \sqrt{x}, x_1 * x_2, \dots$
- “Linear regression” = linear in the parameters
 - Features we can make as complex as we want!



Higher-order polynomials

- Are more features better?
- “Nested” hypotheses
 - 2nd order more general than 1st,
 - 3rd order more general than 2nd, ...
- Fits the observed data better





Overfitting and complexity

- More complex models will always fit the training data better
- But they may “overfit” the training data, learning complex relationships that are not really present




Test data

- After training the model
- Go out and get more data from the world
 - New observations (x,y)
- How well does our model perform?



Training versus test error

- Plot MSE as a function of model complexity
 - Polynomial order
- Decreases
 - More complex function fits training data better
- What about new data?
 - 0th to 1st order
 - Error decreases
 - Underfitting
 - Higher order
 - Error increases
 - Overfitting



Machine Learning

Linear Regression via Least Squares

Gradient Descent Algorithms

Direct Minimization of Squared Error


Regression with Non-linear Features

Bias, Variance, & Validation


Regularized Linear Regression

Inductive bias


- The assumptions needed to predict examples we haven't seen
- Makes us “prefer” one model over another
- Polynomial functions; smooth functions; etc
- Some bias is necessary for learning!




Bias & variance




Three different possible data sets:




Bias & variance



Three different possible data sets:



Each would give
different
predictors for any
polynomial degree:






Detecting overfitting

- Overfitting effect
 - Do better on training data than on future data
 - Need to choose the “right” complexity
- One solution: “Hold-out” data
- Separate our data into two sets
 - Training
 - Test
- Learn only on training data
- Use test data to estimate generalization quality
 - Model selection
- All good competitions use this formulation
 - Often multiple splits: one by judges, then another by you

Model selection


- Which of these models fits the data best?
 - $p=0$ (constant); $p=1$ (linear); $p=3$ (cubic); ...
- Or, should we use KNN? Other methods?
- Model selection problem
 - Can't use training data to decide (esp. if models are nested!)
- Want to estimate $\mathbb{E}_{(x,y)}[J(y, \hat{y}(x; D))]$

J = loss function (MSE)
 D = training data set



Hold-out method

- Validation data
 - “Hold out” some data for evaluation (e.g., 70/30 split)
 - Train only on the remainder
- Some problems, if we have few data:
 - Few data in hold-out: noisy estimate of the error
 - More hold-out data leaves less for training!




$x^{(i)}$	$y^{(i)}$
88	79
32	-2
27	30
68	73
7	-16
20	43
53	77
17	16
87	94

Training data


Validation data

Cross-validation method


- K-fold cross-validation
 - Divide data into K disjoint sets
 - Hold out one set ($= M / K$ data) for evaluation
 - Train on the others ($= M * (K-1) / K$ data)



Split 1:
MSE = 331.8



Split 2:
MSE = 361.2



Split 3:
MSE = 669.8


3-Fold X-Val MSE
= 464.1

Training
data
Validation
data


$x^{(i)}$	$y^{(i)}$
88	79
32	-2
27	30
68	73
7	-16
20	43
53	77
17	16
87	94

Cross-validation method


- K-fold cross-validation
 - Divide data into K disjoint sets
 - Hold out one set ($= M / K$ data) for evaluation
 - Train on the others ($= M * (K-1) / K$ data)



Split 1:
MSE = 280.5



Split 2:
MSE = 3081.3



Split 3:
MSE = 1640.1

3-Fold X-Val MSE
= 1667.3

Training
data
Validation
data

$x^{(i)}$	$y^{(i)}$
88	79
32	-2
27	30
68	73
7	-16
20	43
53	77
17	16
87	94


Cross-validation

- Advantages:
 - Lets us use more (M) validation data
(= less noisy estimate of test performance)
- Disadvantages:
 - More work
 - Trains K models instead of just one
 - Doesn't evaluate any *particular* predictor
 - Evaluates K different models & averages
 - Scores *hyperparameters / procedure*, not an actual, specific predictor!
- Also: still estimating error for $M' < M$ data...

Learning curves


- Plot performance as a function of training size
 - Assess impact of fewer data on performance

Ex: $MSE_0 - MSE$ (regression)
or $1 - Err$ (classification)
- Few data
 - More data significantly improve performance
- “Enough” data
 - Performance saturates
- If slope is high, decreasing m (for validation / cross-validation) might have a big impact...




Leave-one-out cross-validation

- When $K=M$ (# of data), we get
 - Train on all data except one
 - Evaluate on the left-out data
 - Repeat M times (each data point held out once) and average



$MSE = \dots$



$MSE = \dots$

\vdots

→ LOO X-Val MSE
 $= \dots$

Training data
Validation data

$x^{(i)}$	$y^{(i)}$
88	79
32	-2
27	30
68	73
7	-16
20	43
53	77
17	16
87	94

Cross-validation Issues

- Need to balance:
 - Computational burden (multiple trainings)
 - Accuracy of estimated performance / error
- Single hold-out set:
 - Estimates performance with $M' < M$ data (important? learning curve?)
 - Need enough data to trust performance estimate
 - Estimates performance of a particular, trained learner
- K-fold cross-validation
 - K times as much work, computationally
 - Better estimates, still of performance with $M' < M$ data
- Leave-one-out cross-validation
 - M times as much work, computationally
 - $M' \approx M-1$, but overall error estimate may have high variance

Machine Learning

Linear Regression via Least Squares

Gradient Descent Algorithms

Direct Minimization of Squared Error


Regression with Non-linear Features

Bias, Variance, & Validation


Regularized Linear Regression

What to do about under/overfitting?


- Ways to increase complexity?
 - Add features, parameters
 - We'll see more...
- Ways to decrease complexity?
 - Remove features (“feature selection”)
 - “Fail to fully memorize data”
 - Partial training
 - Regularization




0th Order Polynomial




1st Order Polynomial




3rd Order Polynomial



9th Order Polynomial



Estimated Polynomial Coefficients



Regularization

- Can modify our cost function J to add “preference” for certain parameter values

$$J(\underline{\theta}) = \frac{1}{2} (\underline{y} - \underline{\theta} \underline{X}^T) \cdot (\underline{y} - \underline{\theta} \underline{X}^T)^T + \alpha \theta \theta^T$$

L_2 penalty:
“Ridge regression”

- New solution (derive the same way)

$$\underline{\theta} = \underline{y} \underline{X} (\underline{X}^T \underline{X} + \alpha \underline{I})^{-1}$$


- Problem is now well-posed for any degree

$$\theta \theta^T = \sum_i \theta_i^2$$


- Notes:

- “Shrinks” the parameters toward zero
 - Alpha large: we prefer small theta to small MSE
 - Regularization term is independent of the data: paying more attention reduces our model variance


Regression: Zero Regularization




Regression: Moderate Regularization



Regression: Big Regularization



Impact of Regularization Parameter




Estimated Polynomial Coefficients

<i>Estimated Regression Coefficients θ</i>	α zero	α medium	α big
	0.35	0.35	0.13
232.37		4.74	-0.05
-5321.83		-0.77	-0.06
48568.31		-31.97	-0.05
-231639.30		-3.89	-0.03
640042.26		55.28	-0.02
-1061800.52		41.32	-0.01
1042400.18		-45.95	-0.00
-557682.99		-91.53	0.00
125201.43		72.68	0.01

Regularization


- Compare between unreg. & reg. results



Different regularization functions

- More generally, for the L_p regularizer: $\left(\sum_i |\theta_i|^p \right)^{\frac{1}{p}}$


Isosurfaces: $\|\theta\|_p = \text{constant}$



L_0 = limit as p goes to 0 : “number of nonzero weights”, a natural notion of complexity


Different regularization functions

- More generally, for the L_p regularizer: $\left(\sum_i |\theta_i|^p \right)^{\frac{1}{p}}$





Regularization: L_2 vs L_1

- Estimate balances data term & regularization term




Regularization: L_2 vs L_1

- Estimate balances data term & regularization term
- Lasso tends to generate sparser solutions than a quadratic regularizer.



Gradient-Based Optimization

- L_2 makes (all) coefficients smaller
- L_1 makes (some) coefficients exactly zero: *feature selection*




Objective Function:

$$f(\theta_i) = |\theta_i|^p$$

Negative Gradient:

$$-f'(\theta_i)$$



(Informal intuition: Gradient of L_1 objective not defined at zero)