MODULE *Broadcast*

The specification caputers the *DAG* base best effort broadcast to disseminate shares over a peer to peer network.

First pass - We assume no processes failures or messages lost.

EXTENDS *Naturals*, *Sequences*

CONSTANT

Proc, Set of processes
Data,
Nbrs

VARIABLES

sent, Set of messages sent by processes to their neighbours
recv Set of messages received by processes

$Message \triangleq [from : Proc,\ data : Data]$

$Init \triangleq$
$\land\ sent = [m \in Message \mapsto \{\}]$
$\land\ recv = [m \in Message \mapsto \{\}]$

$TypeInvariant \triangleq$
$\land\ sent \in [Message \to Proc]$
$\land\ recv \in [Message \to Proc]$

Send(m, p) - send message m to neighbour q

$Send(m, p) \triangleq$
$\land\ m.from \neq p$
$\land\ m.from \notin sent[m]$
$\land\ \langle m.from, p\rangle \in Nbrs$
$\land\ sent' = [sent \text{ EXCEPT } ![m] = @ \cup \{p\}]$
$\land$ UNCHANGED $\langle recv\rangle$

Recv(m, q) - receive message m at q. This can be received from forwards

$Recv(m, q) \triangleq$
$\land\ q \notin recv[m]$
$\land\ recv' = [recv \text{ EXCEPT } ![m] = @ \cup \{q\}]$
$\land$ UNCHANGED $\langle sent\rangle$

Forward(m, p, q) - forward message m from p to q
- enabling condition - m has been sent by some process, q has received the message, q is not the sender
- effect - p forwards the message m to its nbrs

$Forward(m, p, q) \triangleq$
$\land\ p \neq q$

$\land \langle p,\ q\rangle \in Nbrs$
$\land p \in recv[m]$ p has received m
$\land sent' = [sent \text{ EXCEPT } ![m] = @ \cup \{q\}]$
$\land$ UNCHANGED $\langle recv\rangle$

$Next \triangleq$
$\exists\, p \in Proc,\ q \in Proc,\ m \in Message :$
$\lor Send(m,\ p)$
$\lor Recv(m,\ p)$
$\lor Forward(m,\ p,\ q)$

$Spec \triangleq Init \land \Box[Next]_{\langle sent,\ recv\rangle}$

THEOREM $Spec \Rightarrow \Box TypeInvariant$

---

* Modification History
* Last modified *Tue Mar* 07 19:40:05 *CET* 2023 by *kulpreet*
* Created Sun *Mar* 05 15:04:04 *CET* 2023 by *kulpreet*