

---

MODULE *Broadcast*

---

The specification captures the *DAG* base best effort broadcast to disseminate shares over a peer to peer network.

First pass - We assume no processes failures or messages lost.

EXTENDS *Naturals, Sequences*

CONSTANT

*Proc*    Set of processes

VARIABLES

*sent*,    Set of messages sent by all processes  
*recv*,    Set of messages received by all processes  
*acks*    Set of acknowledgments for messages

$Message \triangleq [op : \{\text{"send"}\}, from : Proc, seqNo : Nat]$   
 $\cup [op : \{\text{"recv"}\}, from : Proc, seqNo : Nat]$

---

Initially, no messages have been sent, received or acknowledged.

$INIT \triangleq$   
 $\wedge sent = \langle \rangle$   
 $\wedge recv = [m \in Message \mapsto \{\}]$   
 $\wedge acks = [m \in Message \mapsto \{\}]$

Type invariants

*sent* is a sequence of messages  
*recv* is a function from *Message* to procs that have received the message  
*acks* is a function from *Message* to procs that have implicitly acked it

$TypeInvariant \triangleq$   
 $\wedge sent \in Seq(Message)$   
 $\wedge recv \in [Message \rightarrow Proc]$   
 $\wedge acks \in [Message \rightarrow Proc]$

---

$NEXT \triangleq \{\}$

---

\ \* Modification History  
\ \* Last modified *Mon Mar 06 09:39:52 CET 2023* by *kulpreet*  
\ \* Created *Sun Mar 05 15:04:04 CET 2023* by *kulpreet*