

Ethereum SLIP-39 Account Generation

Perry Kundert

2021-12-20 10:55:00

Creating Ethereum, Bitcoin and other accounts is complex and fraught with potential for loss of funds.

A BIP-39 seed recovery phrase helps, but a **single** lapse in security dooms the account (and all derived accounts, in fact). If someone finds your recovery phrase (or you lose it), the accounts derived from that seed are *gone*.

The SLIP-39 standard allows you to split the seed between 1, 2, or more groups of several mnemonic recovery phrases. This is better, but creating such accounts is difficult; presently, only the Trezor supports these, and they can only be created "manually". Writing down 5 or more sets of 20 words is difficult, error-prone and time consuming.

The python-slip39 project exists to assist in the safe creation and documentation of Ethereum HD Wallet seeds and derived accounts, with various SLIP-39 sharing parameters. It generates the new random wallet seed, and generates standard Ethereum account(s) (at derivation path `m/44'/60'/0'/0/0` by default) and Bitcoin accounts (at derivation path `=m/44'/0'/0'/0/0` by default), with wallet address and QR code, produces the required SLIP-39 phrases, and outputs a single PDF containing all the required printable cards to document the seed (and the specified derived accounts).

On an secure (ideally air-gapped) computer, new seeds can safely be generated and the PDF saved to a USB drive for printing (or directly printed without the file being saved to disk.). Presently, `slip39` can output example ETH, BTC, LTC and DOGE addresses derived from the seed, to illustrate what accounts are associated with the backed-up seed. Recovery of the seed to a Trezor is simple, by entering the mnemonics right on the device.

Contents

1 Security with Availability	2
1.1 Shamir's Secret Sharing System (SSSS)	2

2	SLIP-39 Account Creation, Recovery and Address Generation	3
2.1	Creating New SLIP-39 Recoverable Seeds	4
2.2	Recovery & Re-Creation	5
2.3	Generation of Addresses	8
2.4	Recovery Mnemonic Cards PDF	9
2.5	The <code>slip39</code> module API	9
3	Conversion from BIP-39 to SLIP-39	13
3.1	BIP-39 vs. SLIP-39 Incompatibility	13
3.2	BIP-39 vs SLIP-39 Key Derivation Summary	17
4	Dependencies	18
4.1	The <code>python-shamir-mnemonic</code> API	18

1 Security with Availability

For both BIP-39 and SLIP-39, a 128-bit random "seed" is the source of an unlimited sequence of Ethereum HD Wallet accounts. Anyone who can obtain this seed gains control of all Ethereum, Bitcoin (and other) accounts derived from it, so it must be securely stored.

Losing this seed means that all of the HD Wallet accounts are permanently lost. Therefore, it must be backed up reliably, and be readily accessible.

Therefore, we must:

- Ensure that nobody untrustworthy can recover the seed, but
- Store the seed in many places with several (some perhaps untrustworthy) people.

How can we address these conflicting requirements?

1.1 Shamir's Secret Sharing System (SSSS)

Satoshi Lab's (Trezor) SLIP-39 uses SSSS to distribute the ability to recover the key to 1 or more "groups". Collecting the mnemonics from the required number of groups allows recovery of the seed. For BIP-39, the number of groups is always 1, and the number of mnemonics required for that group is always 1.

For SLIP-39, a "group_threshold" of how many groups must be successfully collected to recover the key. Then key is (conceptually) split between 1 or more groups (not really; each group's data alone gives away no information about the key).

For example, you might have First, Second, Fam and Fren groups, and decide that any 2 groups can be combined to recover the key. Each group has members with varying levels of trust and persistence, so have different number of Members, and differing numbers Required to recover that group's data:

Group	Required		Members	Description
First	1	/	1	Stored at home
Second	1	/	1	Stored in office safe
Fam	2	/	4	Distributed to family members
Fren	2	/	6	Distributed to friends and associates

The account owner might store their First and Second group data in their home and office safes. These are 1/1 groups (1 required, and only 1 member, so each of these are 1-card groups.)

If the account needs to be recovered, collecting the First and Second cards from the home and office safe is sufficient to recover the seed, and re-generate the HD Wallet accounts.

Only 2 Fam member's cards must be collected to recover the Fam group's data. So, if the HD Wallet owner loses their home and First group card in a fire, they could get the Second group card from the office safe, and 2 cards from Fam group members, and recover the wallet.

If catastrophe strikes and the owner dies, and the heirs don't have access to either the First (at home) or Second (at the office), they can collect 2 Fam cards and 2 Fren cards (at the funeral, for example), completing the Fam and Fren groups' data, and recover the HD Wallet account. Since Frens are less likely to persist long term (and are also less likely to know each-other), we'll require a lower proportion of them to be collected.

2 SLIP-39 Account Creation, Recovery and Address Generation

Generating a new SLIP-39 encoded seed is easy, with results available as PDF and text. Any number of accounts can be generated from this seed, and it can be recovered by collecting the desired groups of recover card phrases. The default recovery groups are as described above.

2.1 Creating New SLIP-39 Recoverable Seeds

Run the following to obtain a PDF file containing index cards with the default SLIP-39 groups for the account named "Personal"; insert a USB drive to collect the output, and run:

```
$ python3 -m pip install slip39 # Install slip39 in Python3
$ cd /Volumes/USBDRIVE/        # Change current directory to USB
$ python3 -m slip39 Personal    # Or just run "slip39 Personal"
2021-12-25 11:10:38 slip39      ETH m/44'/60'/0'/0/0 : 0xb44A2011A99596671d5952CdC22816089f142FB3
2021-12-25 11:10:38 slip39      Wrote SLIP-39-encoded wallet for 'Personal' to:\
Personal-2021-12-22+15.45.36-0xb44A2011A99596671d5952CdC22816089f142FB3.pdf
```

The resultant PDF will be output into the designated file.

This PDF file can be printed on 3x5 index cards, or on regular paper or card stock and the cards can be cut out (`--card credit`, `business`, and `half` or `full` (page) are also available, as well as custom "`(<h>,<w>),<margin>`").

To get the data printed on the terminal as in this example (so you could write it down on cards instead), add a `-v` (to see it logged in a tabular format), or `--text` to have it printed to stdout in full lines (ie. for pipelining to other programs).

2.1.1 slip39 Synopsis

The full command-line argument synopsis for `slip39` is:

```
slip39 --help | sed 's/~/: /' # (just so output formatting looks correct)

usage: slip39 [-h] [-v] [-q] [-o OUTPUT] [-t THRESHOLD] [-g GROUP] [-f FORMAT]
              [-c CRYPTOCURRENCY] [-j JSON] [-s SECRET] [--bits BITS]
              [--passphrase PASSPHRASE] [-C CARD] [--paper PAPER] [--no-card]
              [--text]
              [names ...]
```

Create and output SLIP39 encoded Ethereum wallet(s) to a PDF file.

positional arguments:

names Account names to produce

optional arguments:

-h, --help show this help message and exit
-v, --verbose Display logging information.
-q, --quiet Reduce logging output.
-o OUTPUT, --output OUTPUT
Output PDF to file or '-' (stdout); formatting w/
name, date, time, crypto, path and address allowed
-t THRESHOLD, --threshold THRESHOLD
Number of groups required for recovery (default: half
of groups, rounded up)
-g GROUP, --group GROUP

```

        A group name[<require>]<size> (default: <size> = 1,
        <require> = half of <size>, rounded up, eg.
        'Fren(3/5)' ).
-f FORMAT, --format FORMAT
        Specify default crypto address formats: legacy,
        segwit, bech32; default ETH:legacy, BTC:bech32,
        LTC:bech32, DOGE:legacy
-c CRYPTOCURRENCY, --cryptocurrency CRYPTOCURRENCY
        A crypto name and optional derivation path
        ('../<range>/<range>' allowed); defaults:
        ETH:m/44'/60'/0'/0/0, BTC:m/84'/0'/0'/0/0,
        LTC:m/84'/2'/0'/0/0, DOGE:m/44'/3'/0'/0/0
-j JSON, --json JSON
        Save an encrypted JSON wallet for each Ethereum
        address w/ this password, '-' reads it from stdin
        (default: None)
-s SECRET, --secret SECRET
        Use the supplied 128-, 256- or 512-bit hex value as
        the secret seed; '-' reads it from stdin (eg. output
        from slip39.recover)
--bits BITS
        Ensure that the seed is of the specified bit length;
        128, 256, 512 supported.
--passphrase PASSPHRASE
        Encrypt the master secret w/ this passphrase, '-'
        reads it from stdin (default: None/'')
-C CARD, --card CARD
        Card size; credit, index, business, half or
        '<h>,<w>,<margin>' (default: index)
--paper PAPER
        Paper size (default: Letter)
--no-card
        Disable PDF SLIP-39 mnemonic card output
--text
        Enable textual SLIP-39 mnemonic output to stdout

```

2.2 Recovery & Re-Creation

Later, if you need to recover the wallet seed, keep entering SLIP-39 mnemonics into `slip39-recovery` until the secret is recovered (invalid/duplicate mnemonics will be ignored):

```

$ python3 -m slip39.recovery # (or just "slip39-recovery")
Enter 1st SLIP-39 mnemonic: ab c
Enter 2nd SLIP-39 mnemonic: veteran guilt acrobat romp burden campus purple webcam uncover ...
Enter 3rd SLIP-39 mnemonic: veteran guilt acrobat romp burden campus purple webcam uncover ...
Enter 4th SLIP-39 mnemonic: veteran guilt beard romp dragon island merit burden aluminum worthy ...
2021-12-25 11:03:33 slip39.recovery Recovered SLIP-39 secret; Use: python3 -m slip39 --secret ...
383597fd63547e7c9525575decd413f7

```

Finally, re-create the wallet seed, perhaps including an encrypted JSON wallet file for import of some accounts into a software wallet:

```

slip39 --secret 383597fd63547e7c9525575decd413f7 --json password 2>&1

2022-01-17 19:22:00 slip39      It is recommended to not use '-s|--secret <hex>'; specify '-' to read from inp
2022-01-17 19:22:00 slip39      ETH    m/44'/60'/0'/0/0    : 0xb44A2011A99596671d5952CdC22816089f142FB3
2022-01-17 19:22:00 slip39      BTC    m/84'/0'/0'/0/0    : bc1qcupw7k8enymvsa7w35j5hq4ergtvus3zk8a8s
2022-01-17 19:22:00 slip39      It is recommended to not use '-j|--json <password>'; specify '-' to read from
2022-01-17 19:22:01 slip39      Wrote JSON SLIP39's encrypted ETH wallet 0xb44A2011A99596671d5952CdC22816089f1
2022-01-17 19:22:01 slip39      Wrote SLIP39-encoded wallet for '' to: SLIP39-2022-01-17+19.22.00-ETH-0xb44A20

```

2.2.1 slip39.recovery Synopsis

```
slip39-recovery --help          | sed 's/~/: /' # (just so output formatting looks correct)
```

usage: slip39-recovery [-h] [-v] [-q] [-b] [-m MNEMONIC] [-p PASSPHRASE]

Recover and output secret seed from SLIP39 or BIP39 mnemonics

optional arguments:

```
-h, --help            show this help message and exit
-v, --verbose         Display logging information.
-q, --quiet           Reduce logging output.
-b, --bip39          Recover 512-bit secret seed from BIP-39 mnemonics
-m MNEMONIC, --mnemonic MNEMONIC
                        Supply another SLIP-39 (or a BIP-39) mnemonic phrase
-p PASSPHRASE, --passphrase PASSPHRASE
                        Decrypt the master secret w/ this passphrase, '-'
                        reads it from stdin (default: None/'' )
```

If you obtain a threshold number of SLIP-39 mnemonics, you can recover the original secret seed, and re-generate one or more Ethereum wallets from it.

Enter the mnemonics when prompted and/or via the command line with `-m |--mnemonic "..."`.

The master secret seed can then be used to generate a new SLIP-39 encoded wallet:

```
python3 -m slip39 --secret = "ab04...7f"
```

BIP-39 wallets can be backed up as SLIP-39 wallets, but only at the cost of 59-word SLIP-39 mnemonics. This is because the `*output*` 512-bit BIP-39 seed must be stored in SLIP-39 -- not the `*input*` 128-, 160-, 192-, 224-, or 256-bit entropy used to create the original BIP-39 mnemonic phrase.

2.2.2 Pipelining slip39.recovery | slip39 --secret -

The tools can be used in a pipeline to avoid printing the secret. Here we generate some mnemonics, sorting them in reverse order so we need more than just the first couple to recover. Observe the Ethereum wallet address generated.

Then, we recover the master secret seed in hex with `slip39-recovery`, and finally send it to `slip39 --secret -` to re-generate the same wallet as we originally created.

```
( python3 -m slip39 --text --no-card -v \
  | sort -r \
  | python3 -m slip39.recovery \
  | python3 -m slip39 --secret - --no-card -q ) 2>&1
```

```
2022-01-17 19:22:02 slip39          First(1/1): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/4)
2022-01-17 19:22:02 slip39          1st  1 similar      8 forbid      15 cubic
2022-01-17 19:22:02 slip39          2 steady       9 ruler       16 hearing
2022-01-17 19:22:02 slip39          3 acrobat     10 timely     17 formal
2022-01-17 19:22:02 slip39          4 romp        11 loud       18 clinic
2022-01-17 19:22:02 slip39          5 become      12 living     19 drove
2022-01-17 19:22:02 slip39          6 crazy       13 ruler      20 galaxy
2022-01-17 19:22:02 slip39          7 writing      14 duke
2022-01-17 19:22:02 slip39          Second(1/1): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/4)
2022-01-17 19:22:02 slip39          1st  1 similar      8 short       15 regret
```

2022-01-17 19:22:02 slip39	2 steady	9 angel	16 pumps
2022-01-17 19:22:02 slip39	3 beard	10 response	17 result
2022-01-17 19:22:02 slip39	4 romp	11 true	18 spill
2022-01-17 19:22:02 slip39	5 deliver	12 weapon	19 aunt
2022-01-17 19:22:02 slip39	6 regular	13 dominant	20 mobile
2022-01-17 19:22:02 slip39	7 hormone	14 wrote	
2022-01-17 19:22:02 slip39	Fam(2/4): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6)		
2022-01-17 19:22:02 slip39	1st 1 similar	8 liberty	15 smith
2022-01-17 19:22:02 slip39	2 steady	9 founder	16 knit
2022-01-17 19:22:02 slip39	3 ceramic	10 treat	17 realize
2022-01-17 19:22:02 slip39	4 roster	11 graduate	18 remind
2022-01-17 19:22:02 slip39	5 actress	12 vexed	19 salt
2022-01-17 19:22:02 slip39	6 husband	13 merit	20 debris
2022-01-17 19:22:02 slip39	7 agree	14 math	
2022-01-17 19:22:02 slip39	2nd 1 similar	8 diploma	15 material
2022-01-17 19:22:02 slip39	2 steady	9 orbit	16 payroll
2022-01-17 19:22:02 slip39	3 ceramic	10 strategy	17 sled
2022-01-17 19:22:02 slip39	4 scared	11 says	18 olympic
2022-01-17 19:22:02 slip39	5 aide	12 result	19 easy
2022-01-17 19:22:02 slip39	6 upstairs	13 bike	20 clothes
2022-01-17 19:22:02 slip39	7 losing	14 royal	
2022-01-17 19:22:02 slip39	3rd 1 similar	8 flip	15 expect
2022-01-17 19:22:02 slip39	2 steady	9 squeeze	16 garlic
2022-01-17 19:22:02 slip39	3 ceramic	10 magazine	17 scroll
2022-01-17 19:22:02 slip39	4 shadow	11 element	18 listen
2022-01-17 19:22:02 slip39	5 animal	12 scout	19 buyer
2022-01-17 19:22:02 slip39	6 hearing	13 flame	20 average
2022-01-17 19:22:02 slip39	7 again	14 bracelet	
2022-01-17 19:22:02 slip39	4th 1 similar	8 undergo	15 argue
2022-01-17 19:22:02 slip39	2 steady	9 away	16 rhyme
2022-01-17 19:22:02 slip39	3 ceramic	10 remember	17 reward
2022-01-17 19:22:02 slip39	4 sister	11 threaten	18 pancake
2022-01-17 19:22:02 slip39	5 auction	12 material	19 overall
2022-01-17 19:22:02 slip39	6 twice	13 spill	20 brother
2022-01-17 19:22:02 slip39	7 lobe	14 formal	
2022-01-17 19:22:02 slip39	Fren(2/6): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6)		
2022-01-17 19:22:02 slip39	1st 1 similar	8 rich	15 superior
2022-01-17 19:22:02 slip39	2 steady	9 metric	16 grocery
2022-01-17 19:22:02 slip39	3 decision	10 level	17 slim
2022-01-17 19:22:02 slip39	4 roster	11 royal	18 step
2022-01-17 19:22:02 slip39	5 bolt	12 should	19 engage
2022-01-17 19:22:02 slip39	6 check	13 prevent	20 nuclear
2022-01-17 19:22:02 slip39	7 club	14 story	
2022-01-17 19:22:02 slip39	2nd 1 similar	8 smart	15 credit
2022-01-17 19:22:02 slip39	2 steady	9 brave	16 soldier
2022-01-17 19:22:02 slip39	3 decision	10 stick	17 engage
2022-01-17 19:22:02 slip39	4 scared	11 extend	18 aide
2022-01-17 19:22:02 slip39	5 burning	12 formal	19 shaft
2022-01-17 19:22:02 slip39	6 genuine	13 kidney	20 grill
2022-01-17 19:22:02 slip39	7 flip	14 review	
2022-01-17 19:22:02 slip39	3rd 1 similar	8 unhappy	15 fawn
2022-01-17 19:22:02 slip39	2 steady	9 legs	16 always
2022-01-17 19:22:02 slip39	3 decision	10 diagnose	17 swing
2022-01-17 19:22:02 slip39	4 shadow	11 teaspoon	18 solution
2022-01-17 19:22:02 slip39	5 apart	12 true	19 flexible
2022-01-17 19:22:02 slip39	6 pencil	13 avoid	20 adult

```

2022-01-17 19:22:02 slip39          7 quick      14 become
2022-01-17 19:22:02 slip39          1 similar    8 ounce      15 petition
2022-01-17 19:22:02 slip39    4th  2 steady     9 amuse      16 river
2022-01-17 19:22:02 slip39          3 decision  10 heat      17 fiber
2022-01-17 19:22:02 slip39          4 sister    11 image     18 auction
2022-01-17 19:22:02 slip39          5 activity  12 justice   19 standard
2022-01-17 19:22:02 slip39          6 total     13 tactics   20 withdraw
2022-01-17 19:22:02 slip39          7 slavery    14 injury
2022-01-17 19:22:02 slip39    5th  1 similar    8 careful    15 premium
2022-01-17 19:22:02 slip39          2 steady     9 python     16 bulb
2022-01-17 19:22:02 slip39          3 decision  10 usual     17 corner
2022-01-17 19:22:02 slip39          4 smug       11 unknown   18 permit
2022-01-17 19:22:02 slip39          5 civil      12 luxury    19 elder
2022-01-17 19:22:02 slip39          6 detailed  13 problem   20 imply
2022-01-17 19:22:02 slip39          7 genuine   14 famous
2022-01-17 19:22:02 slip39    6th  1 similar    8 human      15 frost
2022-01-17 19:22:02 slip39          2 steady     9 document   16 priority
2022-01-17 19:22:02 slip39          3 decision  10 prayer    17 parcel
2022-01-17 19:22:02 slip39          4 spew       11 laundry   18 jerky
2022-01-17 19:22:02 slip39          5 dance      12 branch    19 slavery
2022-01-17 19:22:02 slip39          6 intend     13 laundry   20 marvel
2022-01-17 19:22:02 slip39          7 careful   14 diagnose
2022-01-17 19:22:02 slip39    ETH   m/44'/60'/0'/0/0 : 0xF01ADbb293FD8C07776eF46CB9a22348ebd5D96
2022-01-17 19:22:02 slip39    BTC   m/84'/0'/0'/0/0 : bc1qjm85zqhzqt93ummd8qxecynfpmf7r8463jzzga
2022-01-17 19:22:02 slip39.recovery Recovered 128-bit SLIP-39 secret with 4 (1st, 2nd, 7th, 8th) of 8 supplied

```

2.3 Generation of Addresses

For systems that require a stream of groups of wallet Addresses (eg. for preparing invoices for clients, with a choice of cryptocurrency payment options), `slip-generator` can produce a stream of groups of addresses.

2.3.1 slip39-generator Synopsis

```
slip39-generator --help | sed 's/~/: /' # (just so output formatting looks correct)
```

```

usage: slip39-generator [-h] [-v] [-q] [-s SECRET] [-f FORMAT]
                        [-c CRYPTOCURRENCY] [-a ADDRESS] [-b BAUDRATE]
                        [-e ENCRYPT] [--decrypt ENCRYPT] [--enumerated]
                        [--no-enumerate] [--receive] [--corrupt CORRUPT]

```

Generate public wallet address(es) from a secret seed

optional arguments:

```

-h, --help            show this help message and exit
-v, --verbose         Display logging information.
-q, --quiet           Reduce logging output.
-s SECRET, --secret SECRET
                        Use the supplied 128-, 256- or 512-bit hex value as
                        the secret seed; '-' (default) reads it from stdin
                        (eg. output from slip39.recover)
-f FORMAT, --format FORMAT
                        Specify default crypto address formats: legacy,
                        segwit, bech32; default ETH:legacy, BTC:bech32,
                        LTC:bech32, DOGE:legacy
-c CRYPTOCURRENCY, --cryptocurrency CRYPTOCURRENCY

```



```

        A crypto name and optional derivation path (default:
        "ETH:{Account.path_default('ETH')}"), optionally w/
        ranges, eg: ETH:../0/-
-a ADDRESS, --address ADDRESS
        Modify all cryptocurrency paths by replacing the final
        address segment w/ the supplied range, eg. '-',
        meaning [0,...)
-b BAUDRATE, --baudrate BAUDRATE
        Set the baud rate of the serial device (default:
        115200)
-e ENCRYPT, --encrypt ENCRYPT
        Secure the channel from errors and/or prying eyes with
        ChaCha20Poly1305 encryption w/ this password; '-'
        reads from stdin
--decrypt ENCRYPT
--enumerated
        Include an enumeration in each record output (required
        for --encrypt)
--no-enumerate
        Disable enumeration of output records
--receive
        Receive a stream of slip.generator output
--corrupt CORRUPT
        Corrupt a percentage of output symbols

```

Once you have a secret seed (eg. from `slip39.recovery`), you can generate a sequence of HD wallet addresses from it. Emits rows in the form:

```
<enumeration> [<address group(s)>]
```

If the output is to be transmitted by an insecure channel (eg. a serial port), which may insert errors or allow leakage, it is recommended that the records be encrypted with a cryptographic function that includes a message authentication code. We use ChaCha20Poly1305 with a password and a random nonce generated at program start time. This nonce is incremented for each record output.

Since the receiver requires the nonce to decrypt, and we do not want to separately transmit the nonce and supply it to the receiver, the first record emitted when `--encrypt` is specified is the random nonce, encrypted with the password, itself with a known nonce of all 0 bytes. The plaintext data is random, while the nonce is not, but since this construction is only used once, it should be satisfactory. This first nonce record is transmitted with an enumeration prefix of "nonce".

2.4 Recovery Mnemonic Cards PDF

This is what the output SLIP-39 mnemonic cards PDF looks like:

2.5 The slip39 module API

Provide SLIP-39 Mnemonic set creation from a 128-bit master secret, and recovery of the secret from a subset of the provided Mnemonic set.

2.5.1 `slip39.create`

Creates a set of SLIP-39 groups and their mnemonics.

SLIP39 First(1/1) for:

Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6)

ETH m/44'/60'/0'/0/0: 0x8686D2cb685A934233eB8a4907d17e45257eBaD0

- | | | |
|------------|-------------|-------------|
| 1 guard | 8 change | 15 geology |
| 2 roster | 9 pleasure | 16 timely |
| 3 acrobat | 10 cradle | 17 carve |
| 4 romp | 11 ultimate | 18 believe |
| 5 arcade | 12 costume | 19 wildlife |
| 6 simple | 13 prepare | 20 prize |
| 7 magazine | 14 jacket | |



SLIP39 Fam(1/4) for:

Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6)

ETH m/44'/60'/0'/0/0: 0x8686D2cb685A934233eB8a4907d17e45257eBaD0

- | | | |
|------------|-------------|-------------|
| 1 guard | 8 argue | 15 yoga |
| 2 roster | 9 decision | 16 freshman |
| 3 ceramic | 10 burden | 17 dress |
| 4 roster | 11 spider | 18 plunge |
| 5 disease | 12 climate | 19 calcium |
| 6 elite | 13 deliver | 20 junction |
| 7 industry | 14 upstairs | |



Figure 1: SLIP39 Mnemonic Cards PDF

Key	Description
name	Who/what the account is for
group_threshold	How many groups' data is required to recover the account(s)
groups	Each group's description, as {"<group>":(<required>, <members>), ...}
master_secret	128-bit secret (default: from secrets.token_bytes)
passphrase	An optional additional passphrase required to recover secret (default: "")
iteration_exponent	For encrypted secret, exponentially increase PBKDF2 rounds (default: 1)
cryptopaths	A number of crypto names, and their derivation paths]

Outputs a `slip39.Details` namedtuple containing:

Key	Description
name	(same)
group_threshold	(same)
groups	Like groups, w/ <members> = ["<mnemonics>", ...]
accounts	Resultant list of groups of accounts

This is immediately usable to pass to `slip39.output`.

```
import codecs
import random

#
# NOTE:
#
# We turn off randomness here during SLIP-39 generation to get deterministic phrases;
# during normal operation, secure entropy is used during mnemonic generation, yielding
# random phrases, even when the same seed is used multiple times.
#
import shamir_mnemonic
shamir_mnemonic.shamir.RANDOM_BYTES = lambda n: b'\00' * n

import slip39

cryptopaths      = [("ETH","m/44'/60'/0'/0/-2"), ("BTC","m/44'/0'/0'/0/-2")]
master_secret    = b'\xFF' * 16
passphrase       = b""
create_details    = slip39.create(
    "Test", 2, { "Mine": (1,1), "Fam": (2,3) },
    master_secret=master_secret, passphrase=passphrase, cryptopaths=cryptopaths )

[
    [
        f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" if l_n == 0 else ""
    ] + words
    for g_name,(g_of,g_mnems) in create_details.groups.items()
    for g_n,mnem in enumerate( g_mnems )
    for l_n,(line,words) in enumerate(slip39.organize_mnemonic(
        mnem, label=f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" ))
]
```

0	1	2	3
Mine(1/1) #1:	1 academic 2 acid 3 acrobat 4 easy 5 change 6 injury 7 painting	8 safari 9 drug 10 browser 11 trash 12 fridge 13 busy 14 finger	15 standard 16 angry 17 similar 18 aspect 19 smug 20 violence
Fam(2/3) #1:	1 academic 2 acid 3 beard 4 echo 5 crystal 6 machine 7 bolt	8 prevent 9 mouse 10 daughter 11 ancient 12 fortune 13 ruin 14 warmth	15 dwarf 16 dream 17 flavor 18 oral 19 chest 20 marathon
Fam(2/3) #2:	1 academic 2 acid 3 beard 4 email 5 dive 6 warn 7 ranked	8 prune 9 pickup 10 device 11 device 12 peanut 13 enemy 14 graduate	15 briefing 16 often 17 escape 18 sprinkle 19 segment 20 devote
Fam(2/3) #3:	1 academic 2 acid 3 beard 4 entrance 5 alarm 6 health 7 discuss	8 dining 9 invasion 10 bumpy 11 identify 12 anxiety 13 august 14 sunlight	15 intimate 16 satoshi 17 hobo 18 ounce 19 both 20 award

Add the resultant HD Wallet addresses:

```
[
    [ account.path, account.address ]
    for group in create_details.accounts
    for account in group
]
```

0	1
m/44'/60'/0'/0/0	0x824b174803e688dE39aF5B3D7Cd39bE6515A19a1
m/44'/0'/0'/0/0	1MAjc529bjmkC1iCXTw2XMHL2zof5StqdQ
m/44'/60'/0'/0/1	0x8D342083549C635C0494d3c77567860ee7456963
m/44'/0'/0'/0/1	1BGwDuVPJeXDG9upaHvVPds5MXwkTjZoav
m/44'/60'/0'/0/2	0x52787E24965E1aBd691df77827A3CfA90f0166AA
m/44'/0'/0'/0/2	1L64uW2jKB3d1mWvfzTGwZPTGg9qPCaQFM

2.5.2 slip39.output

Key	Description
name	(same as <code>slip39.create</code>)
group_threshold	(same as <code>slip39.create</code>)
groups	Like groups, w/ <code><members> = ["<mnemonics>", ...]</code>
accounts	Resultant <code>{ "path": Account, ... }</code>
card_format	'index', '(<h>,<w>),<margin>', ...
paper_format	'Letter', ...

Produce a PDF containing all the SLIP-39 details for the account.

```
slip32.output( *create_details )
```

2.5.3 slip39.recover

Takes a number of SLIP-39 mnemonics, and if sufficient `group_threshold` groups' mnemonics are present (and the options `passphrase` is supplied), the `master_secret` is recovered. This can be used with `slip39.accounts` to directly obtain any `Account` data.

Note that the passphrase is **not** checked; entering a different passphrase for the same set of mnemonics will recover a **different** wallet! This is by design; it allows the holder of the SLIP-39 mnemonic phrases to recover a "decoy" wallet by supplying a specific passphrase, while protecting the "primary" wallet.

Therefore, it is **essential** to remember any non-default (empty) passphrase used, separately and securely. Take great care in deciding if you wish to use a passphrase with your SLIP-39 wallet!

Key	Description
mnemonics	["<mnemonics>", ...]
passphrase	Optional passphrase to decrypt secret

```
recoverydecoy      = slip39.recover(
    create_details.groups['Mine'][1][:] + create_details.groups['Fam'][1][:2],
    passphrase=b"wrong!"
)
recoverydecoyhex    = codecs.encode( recoverydecoy, 'hex_codec' ).decode( 'ascii' )

recoveryvalid      = slip39.recover(
    create_details.groups['Mine'][1][:] + create_details.groups['Fam'][1][:2],
    passphrase=passphrase
)
recoveryvalidhex    = codecs.encode( recoveryvalid, 'hex_codec' ).decode( 'ascii' )

[[ f"{len(recoverydecoy)*8}-bit secret w/ decoy password recovered:" ]] + [
    [ f"{recoverydecoyhex[b*32:b*32+32]}" ]
    for b in range( len( recoverydecoyhex ) // 32 )
] + [[ f"{len(recoveryvalid)*8}-bit secret recovered:" ]] + [
    [ f"{recoveryvalidhex[b*32:b*32+32]}" ]
    for b in range( len( recoveryvalidhex ) // 32 )
]

0
-----
128-bit secret w/ decoy password recovered:
2e522cea2b566840495c220cf79c756e
128-bit secret recovered:
ffffffffffffffffffffffff
```

3 Conversion from BIP-39 to SLIP-39

If we already have a BIP-39 wallet, it would certainly be nice to be able to create nice, safe SLIP-39 mnemonics for it, and discard the unsafe BIP-39 mnemonics we have lying around, just waiting to be accidentally discovered and the account compromised!

3.1 BIP-39 vs. SLIP-39 Incompatibility

Unfortunately, it is **not possible** to cleanly convert a BIP-39 derived wallet into a SLIP-39 wallet. Both of these techniques preserve "entropy" (random) bits, but these bits are used **differently** – and incompatibly – to derive the resultant Ethereum wallets.

The best we can do is to preserve the 512-bit **output** of the BIP-39 mnemonic phrase as a set of 512-bit SLIP-39 mnemonics.

3.1.1 BIP-39 Entropy to Mnemonic

BIP-39 uses a single set of 12, 15, 18, 21 or 24 BIP-39 words to carefully preserve a specific 128 to 256 bits of initial entropy. Here's a 128-bit (12-word) example using some fixed "entropy" 0xFFFF..FFFF:

```
from mnemonic import Mnemonic
bip39_english = Mnemonic("english")
entropy = b'\xFF' * 16
entropy_mnemonic = bip39_english.to_mnemonic( entropy )
[[entropy_mnemonic]]
```

0

zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong

Each word is one of a corpus of 2048 words; therefore, each word encodes 11 bits ($2048 = 2^{11}$) of entropy. So, we provided 128 bits, but $12 \times 11 = 132$. So where does the extra 4 bits of data come from?

It comes from the first few bits of a SHA256 hash of the entropy, which is added to the end of the supplied 128 bits, to reach the required 132 bits: $132 / 11 == 12$ words.

This last 4 bits (up to 8 bits, for a 256-bit 24-word BIP-39) is checked, when validating the BIP-39 mnemonic. Therefore, making up a random BIP-39 mnemonic will succeed only 1 / 16 times on average, due to an incorrect checksum 4-bit ($16 == 2^4$). Lets check:

```
def random_words( n, count=100 ):
    for _ in range( count ):
        yield ' '.join( random.choice( bip39_english.wordlist ) for _ in range( n ))

successes = sum(
    bip39_english.check( m )
    for i,m in enumerate( random_words( 12, 10000 ))) / 100
[[ f"Valid random 12-word mnemonics:" ]] + [
    [ f"{successes}%" ]] + [
    [ f"~ 1/{100/successes:.3}" ]]
```

0

Valid random 12-word mnemonics:

6.38%

~ 1/15.7

Sure enough, about 1/16 random 12-word phrases are valid BIP-39 mnemonics. OK, we've got the contents of the BIP-39 phrase dialed in. How is it used to generate accounts?

3.1.2 BIP-39 Mnemonic to Seed

Unfortunately, we do **not** use the carefully preserved 128-bit entropy to generate the wallet! Nope, it is stretched to a 512-bit seed using PBKDF2 HMAC SHA512. The normalized **text** (*not the entropy bytes*) of the 12-word mnemonic is then used (with a salt of "mnemonic" plus an optional passphrase, "" by default), to obtain the seed:

```
seed = bip39_english.to_seed( entropy_mnemonic )
seedhex = codecs.encode( seed, 'hex_codec' ).decode( 'ascii' )
[[ f"{len(seed)*8}-bit seed:" ]] + [
    [ f"{seedhex[b*32:b*32+32]}" ]
    for b in range( len( seedhex ) // 32 )
]
```

```

0
-----
512-bit seed:
b6a6d8921942dd9806607ebc2750416b
289adea669198769f2e15ed926c3aa92
bf88ece232317b4ea463e84b0fcd3b53
577812ee449ccc448eb45e6f544e25b6

```

3.1.3 BIP-39 Seed to Address

Finally, this 512-bit seed is used to derive HD wallet(s). The HD Wallet key derivation process consumes whatever seed entropy is provided (512 bits in the case of BIP-39), and uses HMAC SHA512 with a prefix of b"Bitcoin seed" to stretch the supplied seed entropy to 64 bytes (512 bits). Then, the HD Wallet **path** segments are iterated through, permuting the first 32 bytes of this material as the key with the second 32 bytes of material as the chain node, until finally the 32-byte (256-bit) Ethereum account private key is produced. We then use this private key to compute the rest of the Ethereum account details, such as its public address.

```

path = "m/44'/60'/0'/0/0"
eth_hd = slip39.account( seed, 'ETH', path )

[[ f"{len(key)*8}-bit derived key at path {path!r}:" ]] + [
  [ f"{keyhex}" ]] + [
  [ "... yields ..." ]] + [
  [ f"Ethereum address: {eth_hd.address}" ]
]
```

```

0
-----
256-bit derived key at path "m/44'/60'/0'/0/0":
7af65ba4dd53f23495dcb04995e96f47c243217fc279f10795871b725cd009ae
... yields ...
Ethereum address: 0xfc2077CA7F403cBECA41B1B0F62D91B5EA631B5E

```

Thus, we see that while the 12-word BIP-39 mnemonic careful preserves the original 128-bit entropy, this data is not directly used to derive the wallet private key and address. Also, since an irreversible hash is used to derive the seed from the mnemonic, we can't reverse the process on the seed to arrive back at the BIP-39 mnemonic phrase.

3.1.4 SLIP-39 Entropy to Mnemonic

Just like BIP-39 carefully preserves the original 128-bit entropy bytes in a single 12-word mnemonic phrase, SLIP-39 preserves the original 128-bit entropy in a *set* of 30-word mnemonic phrases.

```

name,thrs,grps,acct = slip39.create(
    "Test", 2, { "Mine": (1,1), "Fam": (2,3) }, entropy )
[[ f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" if l_n == 0 else "" ] + words
  for g_name,(g_of,g_mnems) in grps.items()
  for g_n,mnem in enumerate( g_mnems )
  for l_n,(line,words) in enumerate(slip39.organize_mnemonic(
    mnem, rows=7, cols=3, label=f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" ))
]
```

0	1	2	3
Mine(1/1) #1:	1 academic	8 safari	15 standard
	2 acid	9 drug	16 angry
	3 acrobat	10 browser	17 similar
	4 easy	11 trash	18 aspect
	5 change	12 fridge	19 smug
	6 injury	13 busy	20 violence
	7 painting	14 finger	
Fam(2/3) #1:	1 academic	8 prevent	15 dwarf
	2 acid	9 mouse	16 dream
	3 beard	10 daughter	17 flavor
	4 echo	11 ancient	18 oral
	5 crystal	12 fortune	19 chest
	6 machine	13 ruin	20 marathon
	7 bolt	14 warmth	
Fam(2/3) #2:	1 academic	8 prune	15 briefing
	2 acid	9 pickup	16 often
	3 beard	10 device	17 escape
	4 email	11 device	18 sprinkle
	5 dive	12 peanut	19 segment
	6 warn	13 enemy	20 devote
	7 ranked	14 graduate	
Fam(2/3) #3:	1 academic	8 dining	15 intimate
	2 acid	9 invasion	16 satoshi
	3 beard	10 bumpy	17 hobo
	4 entrance	11 identify	18 ounce
	5 alarm	12 anxiety	19 both
	6 health	13 august	20 award
	7 discuss	14 sunlight	

Since there is some randomness used in the SLIP-39 mnemonics generation process, we would get a **different** set of words each time for the fixed "entropy" 0xFFFF.FF used in this example (if we hadn't manually disabled entropy for `shamir_mnemonic`, above), but we will **always** derive the same Ethereum account 0x824b..19a1 at the specified HD Wallet derivation path.

```
[[ "Crypto", "HD Wallet Path:", "Ethereum Address:" ]] + [
  [ account.crypto, account.path, account.address ]
  for group in create_details.accounts
  for account in group
]
```

0	1	2
Crypto	HD Wallet Path:	Ethereum Address:
ETH	m/44'/60'/0'/0/0	0x824b174803e688dE39aF5B3D7Cd39bE6515A19a1
BTC	m/44'/0'/0'/0/0	1MAjc529bjmkC1iCXTw2XMHL2zof5StqdQ
ETH	m/44'/60'/0'/0/1	0x8D342083549C635C0494d3c77567860ee7456963
BTC	m/44'/0'/0'/0/1	1BGwDuVPJeXDG9upaHvVPds5MXwkTjZoav
ETH	m/44'/60'/0'/0/2	0x52787E24965E1aBd691df77827A3CfA90f0166AA
BTC	m/44'/0'/0'/0/2	1L64uW2jKB3d1mWvfzTGwZPTGg9qPCaQFM

3.1.5 SLIP-39 Mnemonic to Seed

Lets prove that we can actually recover the **original** entropy from the SLIP-39 recovery mnemonics; in this case, we've specified a SLIP-39 group_threshold of 2 groups, so we'll use 1 mnemonic from Mine, and 2 from Fam:

```
_,mnem_mine = grps['Mine']
```



```

_,mnem_fam      = grps['Fam']
recseed         = slip39.recover( mnem_mine + mnem_fam[:2] )
recseedhex      = codecs.encode( recseed, 'hex_codec' ).decode( 'ascii' )

[[ f"{len(recseed)*8}-bit seed:" ]] + [
  [ f"{recseedhex[b*32:b*32+32]}" ]
    for b in range( len( recseedhex ) // 32 )
]

0
-----
128-bit seed:
ffffffffffffffffffffffff

```

3.1.6 SLIP-39 Seed to Address

And we'll use the same style of code as for the BIP-39 example above, to derive the Ethereum address **directly** from this recovered 128-bit seed:

```

receth = slip39.account( recseed, 'ETH', path )
[[ f"{len(receth.key)*4}-bit derived key at path {path!r}:" ]] + [
  [ f"{receth.key}" ] ] + [
  [ "... yields ..." ] ] + [
  [ f"Ethereum address: {receth.address}" ]
]

0
-----
256-bit derived key at path "m/44'/60'/0'/0/0":
6a2ec39aab88ec0937b79c8af6aaf2fd3c909e9a56c3ddd32ab5354a06a21a2b
... yields ...
Ethereum address: 0x824b174803e688dE39aF5B3D7Cd39bE6515A19a1

```

And we see that we obtain the same Ethereum address `0x824b..1a2b` as we originally got from `slip39.create` above. However, this is **not** the Ethereum wallet address obtained from BIP-39 with exactly the same `0xFFFF...FF` entropy, which was `0xfc20..1B5E`. This is due to the fact that BIP-39 does not use the recovered entropy to produce the seed like SLIP-39 does, but applies additional one-way hashing of the mnemonic to produce the seed.

3.2 BIP-39 vs SLIP-39 Key Derivation Summary

At no time in BIP-39 account derivation is the original 128-bit mnemonic entropy used directly in the derivation of the wallet key. This differs from SLIP-39, which directly uses the 128-bit mnemonic entropy recovered from the SLIP-39 Shamir's Secret Sharing System recovery process to generate each HD Wallet account's private key.

Furthermore, there is no point in the BIP-39 entropy to account generation where we **could** introduce a known 128-bit seed and produce a known Ethereum wallet from it, other than as the very beginning.

3.2.1 BIP-39 Backup via SLIP-39

There is one approach which can preserve an original BIP-39 wallet address, using SLIP-39 mnemonics.

It is clumsy, as it preserves the BIP-39 **output** 512-bit stretched seed, and the resultant 59-word SLIP-39 mnemonics cannot be used (at present) with the Trezor hardware wallet. They can, however, be used to recover the HD wallet private keys without access to the original BIP-39 mnemonic phrase – you could generate and distribute a set of more secure SLIP-39 mnemonic phrases, instead of trying to secure the original BIP-39 mnemonic.

We'll use `slip39.recovery --bip39 ...` to recover the 512-bit stretched seed from BIP-39:

```
( python3 -m slip39.recovery --bip39 \
  --mnemonic "zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong"
) 2>&1
```

```
2022-01-17 19:22:09 slip39.recovery Recovered 512-bit BIP-39 secret from english mnemonic
b6a6d8921942dd9806607ebc2750416b289adea669198769f2e15ed926c3aa92bf88ece232317b4ea463e84b0fcd3b53577812ee449ccc448eb
```

Then we can generate a 59-word SLIP-39 mnemonic set from the 512-bit secret:

```
( python3 -m slip39.recovery --bip39 \
  --mnemonic "zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong" \
  | python3 -m slip39 --secret - --no-card ) 2>&1
```

```
2022-01-17 19:22:09 slip39.recovery Recovered 512-bit BIP-39 secret from english mnemonic
2022-01-17 19:22:10 slip39          ETH      m/44'/60'/0'/0/0      : 0xfc2077CA7F403cBECA41B1B0F62D91B5EA631B5E
2022-01-17 19:22:10 slip39          BTC      m/84'/0'/0'/0/0      : bc1qk0a9hr7wjfxeezn9nwenw9flhq0tmsf6vsgnn2
```

This 0xfc20...1B5E address is the same Ethereum address as is recovered on a Trezor using this BIP-39 mnemonic phrase.

4 Dependencies

Internally, python-slip39 project uses Trezor's python-shamir-mnemonic to encode the seed data, and the Ethereum project's eth-account to convert seeds to Ethereum accounts.

4.1 The python-shamir-mnemonic API

To use it directly, obtain , and install it, or run `python3 -m pip install shamir-mnemonic`.

```
$ shamir create custom --group-threshold 2 --group 1 1 --group 1 1 --group 2 5 --group 3 6
Using master secret: 87e39270d1d1976e9ade9cc15a084c62
Group 1 of 4 - 1 of 1 shares required:
merit aluminum acrobat romp capacity leader gray dining thank rhyme escape genre havoc furl breathe class pitch loc
Group 2 of 4 - 1 of 1 shares required:
merit aluminum beard romp briefing email member flavor disaster exercise cinema subject perfect facility genius bik
Group 3 of 4 - 2 of 5 shares required:
merit aluminum ceramic roster already cinema knit cultural agency intimate result ivory makeup lobe jerky theory ga
merit aluminum ceramic scared beam findings expand broken smear cleanup enlarge coding says destroy agency emperor
merit aluminum ceramic shadow cover smith idle vintage mixture source dish squeeze stay wireless likely privacy imp
merit aluminum ceramic sister duke relate elite ruler focus leader skin machine mild envelope wrote amazing justice
merit aluminum ceramic smug buyer taxi amazing marathon treat clinic rainbow destroy unusual keyboard thumb story l
Group 4 of 4 - 3 of 6 shares required:
merit aluminum decision round bishop wrote belong anatomy spew hour index fishing lecture disease cage thank fantas
merit aluminum decision scatter carpet spine ruin location forward priest cage security careful emerald screw adult
merit aluminum decision shaft arcade infant argue elevator imply obesity oral venture afraid slice raisin born nerv
merit aluminum decision skin already fused tactics skunk work floral very gesture organize puny hunting voice pytho
merit aluminum decision snake cage premium aide wealthy viral chemical pharmacy smoking inform work cubic ancestor
merit aluminum decision spider boundary lunar staff inside junior tendency sharp editor trouble legal visual tricyc
```