

Ethereum SLIP-39 Account Generation

Perry Kundert

2021-12-20 10:55:00

Creating Ethereum, Bitcoin and other accounts is complex and fraught with potential for loss of funds.

A BIP-39 seed recovery phrase helps, but a **single** lapse in security dooms the account (and all derived accounts, in fact). If someone finds your recovery phrase (or you lose it), the accounts derived from that seed are *gone*.

The SLIP-39 standard allows you to split the seed between 1, 2, or more groups of several mnemonic recovery phrases. This is better, but creating such accounts is difficult; presently, only the Trezor supports these, and they can only be created "manually". Writing down 5 or more sets of 20 words is difficult, error-prone and time consuming.

The python-slip39 project exists to assist in the safe creation and documentation of Ethereum HD Wallet seeds and derived accounts, with various SLIP-39 sharing parameters. It generates the new random wallet seed, and generates the expected standard Ethereum account(s) (at derivation path `m/44'/60'/0'/0/0` by default) and Bitcoin accounts (at derivation path `m/84'/0'/0'/0/0` by default), with wallet address and QR code (compatible with Trezor derivations). It produces the required SLIP-39 phrases, and outputs a single PDF containing all the required printable cards to document the seed (and the specified derived accounts).

On an secure (ideally air-gapped) computer, new seeds can safely be generated and the PDF saved to a USB drive for printing (or directly printed without the file being saved to disk.). Presently, `slip39` can output example ETH, BTC, LTC and DOGE addresses derived from the seed, to illustrate what accounts are associated with the backed-up seed. Recovery of the seed to a Trezor is simple, by entering the mnemonics right on the device.

Contents

1 Security with Availability

2

1.1	Shamir's Secret Sharing System (SSSS)	3
2	SLIP-39 Account Creation, Recovery and Address Generation	4
2.1	Creating New SLIP-39 Recoverable Seeds	4
2.2	The macOS SLIP39.app GUI App	4
2.3	The Python <code>slip39</code> CLI	6
2.4	Recovery & Re-Creation	7
2.5	Generation of Addresses	10
2.6	The <code>slip39</code> module API	12
3	Conversion from BIP-39 to SLIP-39	14
3.1	BIP-39 vs. SLIP-39 Incompatibility	14
3.2	BIP-39 vs SLIP-39 Key Derivation Summary	18
4	Building & Installing	19
4.1	The <code>slip39</code> Module	19
4.2	The <code>slip39</code> GUI	19
5	Dependencies	20
5.1	The <code>python-shamir-mnemonic</code> API	20

1 Security with Availability

For both BIP-39 and SLIP-39, a 128-bit random "seed" is the source of an unlimited sequence of Ethereum HD Wallet accounts. Anyone who can obtain this seed gains control of all Ethereum, Bitcoin (and other) accounts derived from it, so it must be securely stored.

Losing this seed means that all of the HD Wallet accounts are permanently lost. Therefore, it must be backed up reliably, and be readily accessible.

Therefore, we must:

- Ensure that nobody untrustworthy can recover the seed, but
- Store the seed in many places with several (some perhaps untrustworthy) people.

How can we address these conflicting requirements?

1.1 Shamir's Secret Sharing System (SSSS)

Satoshi Lab's (Trezor) SLIP-39 uses SSSS to distribute the ability to recover the key to 1 or more "groups". Collecting the mnemonics from the required number of groups allows recovery of the seed. For BIP-39, the number of groups is always 1, and the number of mnemonics required for that group is always 1.

For SLIP-39, a "group_threshold" of how many groups must be successfully collected to recover the key. Then key is (conceptually) split between 1 or more groups (not really; each group's data alone gives away no information about the key).

For example, you might have First, Second, Fam and Frens groups, and decide that any 2 groups can be combined to recover the key. Each group has members with varying levels of trust and persistence, so have different number of Members, and differing numbers Required to recover that group's data:

Group	Required		Members	Description
First	1	/	1	Stored at home
Second	1	/	1	Stored in office safe
Fam	2	/	4	Distributed to family members
Frens	3	/	6	Distributed to friends and associates

The account owner might store their First and Second group data in their home and office safes. These are 1/1 groups (1 required, and only 1 member, so each of these are 1-card groups.)

If the account needs to be recovered, collecting the First and Second cards from the home and office safe is sufficient to recover the seed, and re-generate the HD Wallet accounts.

Only 2 Fam member's cards must be collected to recover the Fam group's data. So, if the HD Wallet owner loses their home and First group card in a fire, they could get the Second group card from the office safe, and 2 cards from Fam group members, and recover the wallet.

If catastrophe strikes and the owner dies, and the heirs don't have access to either the First (at home) or Second (at the office), they can collect 2 Fam cards and 3 Frens cards (at the funeral, for example), completing the Fam and Frens groups' data, and recover the HD Wallet account. Since Frens are less likely to persist long term (and are also less likely to know each-other), we'll require a lower proportion of them to be collected.

2 SLIP-39 Account Creation, Recovery and Address Generation

Generating a new SLIP-39 encoded seed is easy, with results available as PDF and text. Any number of accounts can be generated from this seed, and it can be recovered by collecting the desired groups of recover card phrases. The default recovery groups are as described above.

2.1 Creating New SLIP-39 Recoverable Seeds

This is what the first page of the output SLIP-39 mnemonic cards PDF looks like:

Run the following to obtain a PDF file containing index cards with the default SLIP-39 groups for a new account seed named "Personal"; insert a USB drive to collect the output, and run:

```
$ python3 -m pip install slip39          # Install slip39 in Python3
$ cd /Volumes/USBDRIVE/                 # Change current directory to USB
$ python3 -m slip39 Personal              # Or just run "slip39 Personal"
2021-12-25 11:10:38 slip39               ETH m/44'/60'/0'/0/0      : 0xb44A2011A99596671d5952CdC22816089f142FB3
2021-12-25 11:10:38 slip39               Wrote SLIP-39-encoded wallet for 'Personal' to:\
Personal-2021-12-22+15.45.36-0xb44A2011A99596671d5952CdC22816089f142FB3.pdf
```

The resultant PDF will be output into the designated file.

This PDF file can be printed on 3x5 index cards, or on regular paper or card stock and the cards can be cut out (`--card credit`, `business`, and `half` (page) are also available, as well as custom "`(<h>,<w>),<margin>`").

To get the data printed on the terminal as in this example (so you could write it down on cards instead), add a `-v` (to see it logged in a tabular format), or `--text` to have it printed to stdout in full lines (ie. for pipelining to other programs).

2.2 The macOS SLIP39.app GUI App

If you prefer a graphical user-interface, try the macOS app. You can run it directly if you install Python 3.9+ from python.org/downloads or using `homebrew brew install python-tk@3.9` (or higher, eg. `@3.10`). Then, start the GUI in a variety of ways:

```
slip39-gui
python -m slip39.gui
```

Alternatively, download and install the macOS GUI App: github.com/pjkundert/python-slip-39/releases.

You will need to authorize it to run in System Preferences / Security & Privacy / Privacy.









<p>SLIP39 First(1/1) for: Personal Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6) ETH m/44/160/0/0/0: 0a824b174803d688e39af583d7c0398e6615a19a1 BTC m/44/160/0/0/0: bc1q9ysq3q2y4wvskzszqzpfam7h3uaf6d</p>  	<p>SLIP39 Second(1/1) for: Personal Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6) ETH m/44/160/0/0/0: 0a824b174803d688e39af583d7c0398e6615a19a1 BTC m/44/160/0/0/0: bc1q9ysq3q2y4wvskzszqzpfam7h3uaf6d</p>  
<p>1 friar 8 tendency 15 spit 2 garlic 9 move 16 society 3 acrobat 10 obesity 17 mountain 4 romp 11 jury 18 presence 5 describe 12 spirit 19 diminish 6 ceramic 13 bike 20 forbid 7 season 14 username</p>	<p>1 friar 8 harvest 15 soul 2 garlic 9 epidemic 16 smoking 3 beard 10 fishing 17 alcohol 4 romp 11 emerald 18 document 5 company 12 violence 19 script 6 traveler 13 float 20 secret 7 society 14 overall</p>
<p>SLIP39 Fam(1/4) for: Personal Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6) ETH m/44/160/0/0/0: 0a824b174803d688e39af583d7c0398e6615a19a1 BTC m/44/160/0/0/0: bc1q9ysq3q2y4wvskzszqzpfam7h3uaf6d</p>  	<p>SLIP39 Fam(2/4) for: Personal Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Fren(2/6) ETH m/44/160/0/0/0: 0a824b174803d688e39af583d7c0398e6615a19a1 BTC m/44/160/0/0/0: bc1q9ysq3q2y4wvskzszqzpfam7h3uaf6d</p>  
<p>1 friar 8 dryer 15 response 2 garlic 9 ordinary 16 exchange 3 ceramic 10 golden 17 square 4 roster 11 declare 18 wisdom 5 daughter 12 viral 19 blind 6 speak 13 eyebrow 20 desire 7 editor 14 muscle</p>	<p>1 friar 8 webcam 15 faint 2 garlic 9 identify 16 fantasy 3 ceramic 10 task 17 energy 4 scared 11 increase 18 slice 5 adorn 12 eraser 19 rapids 6 brave 13 prevent 20 duration 7 theater 14 repeat</p>

Figure 1: SLIP39 Cards PDF (from --secret ffff...ffff)

2.3 The Python slip39 CLI

From the command line, you can create SLIP-39 seed Mnemonic card PDFs.

2.3.1 slip39 Synopsis

The full command-line argument synopsis for slip39 is:

```
slip39 --help | sed 's/~/: /' # (just so output formatting looks correct)

usage: slip39 [-h] [-v] [-q] [-o OUTPUT] [-t THRESHOLD] [-g GROUP] [-f FORMAT]
             [-c CRYPTOCURRENCY] [-j JSON] [-s SECRET] [--bits BITS]
             [--passphrase PASSPHRASE] [-C CARD] [--paper PAPER] [--no-card]
             [--text]
             [names ...]
```

Create and output SLIP39 encoded Ethereum wallet(s) to a PDF file.

positional arguments:

names Account names to produce

options:

```
-h, --help show this help message and exit
-v, --verbose Display logging information.
-q, --quiet Reduce logging output.
-o OUTPUT, --output OUTPUT
            Output PDF to file or '-' (stdout); formatting w/
            name, date, time, crypto, path, address allowed
-t THRESHOLD, --threshold THRESHOLD
            Number of groups required for recovery (default: half
            of groups, rounded up)
-g GROUP, --group GROUP
            A group name[<require>[/<size>] (default: <size> = 1,
            <require> = half of <size>, rounded up, eg.
            'Frens(3/5)' ).
-f FORMAT, --format FORMAT
            Specify default crypto address formats: legacy,
            segwit, bech32; default ETH:legacy, BTC:bech32,
            LTC:bech32, DOGE:legacy
-c CRYPTOCURRENCY, --cryptocurrency CRYPTOCURRENCY
            A crypto name and optional derivation path
            ('../<range>/<range>' allowed); defaults:
            ETH:m/44'/60'/0'/0'/0, BTC:m/84'/0'/0'/0'/0,
            LTC:m/84'/2'/0'/0'/0, DOGE:m/44'/3'/0'/0'/0
-j JSON, --json JSON Save an encrypted JSON wallet for each Ethereum
            address w/ this password, '-' reads it from stdin
            (default: None)
-s SECRET, --secret SECRET
            Use the supplied 128-, 256- or 512-bit hex value as
            the secret seed; '-' reads it from stdin (eg. output
            from slip39.recover)
--bits BITS Ensure that the seed is of the specified bit length;
            128, 256, 512 supported.
--passphrase PASSPHRASE
            Encrypt the master secret w/ this passphrase, '-'
            reads it from stdin (default: None/ '')
-C CARD, --card CARD Card size; index, credit, business, half or
```

```

'(<h>,<w>),<margin>' (default: index)
--paper PAPER          Paper size (default: Letter)
--no-card              Disable PDF SLIP-39 mnemonic card output
--text                Enable textual SLIP-39 mnemonic output to stdout

```

2.4 Recovery & Re-Creation

Later, if you need to recover the wallet seed, keep entering SLIP-39 mnemonics into `slip39-recovery` until the secret is recovered (invalid/duplicate mnemonics will be ignored):

```

$ python3 -m slip39.recovery # (or just "slip39-recovery")
Enter 1st SLIP-39 mnemonic: ab c
Enter 2nd SLIP-39 mnemonic: veteran guilt acrobat romp burden campus purple webcam uncover ...
Enter 3rd SLIP-39 mnemonic: veteran guilt acrobat romp burden campus purple webcam uncover ...
Enter 4th SLIP-39 mnemonic: veteran guilt beard romp dragon island merit burden aluminum worthy ...
2021-12-25 11:03:33 slip39.recovery Recovered SLIP-39 secret; Use: python3 -m slip39 --secret ...
383597fd63547e7c9525575decd413f7

```

Finally, re-create the wallet seed, perhaps including an encrypted JSON wallet file for import of some accounts into a software wallet:

```
slip39 --secret 383597fd63547e7c9525575decd413f7 --json password 2>&1
```

```

2022-02-12 15:51:03 slip39          It is recommended to not use '-s|--secret <hex>'; specify '-' to read from inp
2022-02-12 15:51:03 slip39          ETH    m/44'/60'/0'/0/0    : 0xb44A2011A99596671d5952CdC22816089f142FB3
2022-02-12 15:51:03 slip39          BTC    m/84'/0'/0'/0/0    : bc1qcupw7k8enymvsa7w35j5hq4ergtvus3zk8a8s
2022-02-12 15:51:04 slip39          It is recommended to not use '-j|--json <password>'; specify '-' to read from
2022-02-12 15:51:04 slip39          Wrote JSON SLIP39's encrypted ETH wallet 0xb44A2011A99596671d5952CdC22816089f1
2022-02-12 15:51:05 slip39          Wrote SLIP39-encoded wallet for 'SLIP39' to: SLIP39-2022-02-12+15.51.04-ETH-0x

```

2.4.1 slip39.recovery Synopsis

```
slip39-recovery --help | sed 's/~/: /' # (just so output formatting looks correct)
```

```
usage: slip39-recovery [-h] [-v] [-q] [-b] [-m MNEMONIC] [-p PASSPHRASE]
```

Recover and output secret seed from SLIP39 or BIP39 mnemonics

options:

```

-h, --help          show this help message and exit
-v, --verbose       Display logging information.
-q, --quiet         Reduce logging output.
-b, --bip39        Recover 512-bit secret seed from BIP-39 mnemonics
-m MNEMONIC, --mnemonic MNEMONIC
                    Supply another SLIP-39 (or a BIP-39) mnemonic phrase
-p PASSPHRASE, --passphrase PASSPHRASE
                    Decrypt the master secret w/ this passphrase, '-'
                    reads it from stdin (default: None/''')

```

If you obtain a threshold number of SLIP-39 mnemonics, you can recover the original secret seed, and re-generate one or more Ethereum wallets from it.

Enter the mnemonics when prompted and/or via the command line with `-m |--mnemonic "..."`.

The master secret seed can then be used to generate a new SLIP-39 encoded wallet:

```
python3 -m slip39 --secret = "ab04...7f"
```

BIP-39 wallets can be backed up as SLIP-39 wallets, but only at the cost of 59-word SLIP-39 mnemonics. This is because the *output* 512-bit BIP-39 seed must be stored in SLIP-39 -- not the *input* 128-, 160-, 192-, 224-, or 256-bit entropy used to create the original BIP-39 mnemonic phrase.

2.4.2 Pipelining slip39.recovery | slip39 --secret -

The tools can be used in a pipeline to avoid printing the secret. Here we generate some mnemonics, sorting them in reverse order so we need more than just the first couple to recover. Observe the Ethereum wallet address generated.

Then, we recover the master secret seed in hex with slip39-recovery, and finally send it to slip39 --secret - to re-generate the same wallet as we originally created.

```
( python3 -m slip39 --text --no-card -v \
  | sort -r \
  | python3 -m slip39.recovery \
  | python3 -m slip39 --secret - --no-card -q ) 2>&1
```

2022-02-12 15:51:05 slip39	First(1/1): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Frens(3/6)
2022-02-12 15:51:05 slip39	1st 1 retailer 8 verdict 15 physics
2022-02-12 15:51:05 slip39	2 merit 9 squeeze 16 emerald
2022-02-12 15:51:05 slip39	3 acrobat 10 simple 17 unknown
2022-02-12 15:51:05 slip39	4 romp 11 swing 18 engage
2022-02-12 15:51:05 slip39	5 closet 12 geology 19 prize
2022-02-12 15:51:05 slip39	6 sled 13 oven 20 island
2022-02-12 15:51:05 slip39	7 lend 14 adapt
2022-02-12 15:51:05 slip39	Second(1/1): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Frens(3/6)
2022-02-12 15:51:05 slip39	1st 1 retailer 8 change 15 center
2022-02-12 15:51:05 slip39	2 merit 9 cage 16 ceiling
2022-02-12 15:51:05 slip39	3 beard 10 pipeline 17 moisture
2022-02-12 15:51:05 slip39	4 romp 11 ordinary 18 auction
2022-02-12 15:51:05 slip39	5 airline 12 rhythm 19 stadium
2022-02-12 15:51:05 slip39	6 tactics 13 crisis 20 style
2022-02-12 15:51:05 slip39	7 texture 14 rumor
2022-02-12 15:51:05 slip39	Fam(2/4): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Frens(3/6)
2022-02-12 15:51:05 slip39	1st 1 retailer 8 volume 15 smirk
2022-02-12 15:51:05 slip39	2 merit 9 debris 16 parcel
2022-02-12 15:51:05 slip39	3 ceramic 10 mustang 17 literary
2022-02-12 15:51:05 slip39	4 roster 11 rebuild 18 species
2022-02-12 15:51:05 slip39	5 center 12 hazard 19 diet
2022-02-12 15:51:05 slip39	6 mixed 13 company 20 usher
2022-02-12 15:51:05 slip39	7 admit 14 disease
2022-02-12 15:51:05 slip39	2nd 1 retailer 8 solution 15 cowboy
2022-02-12 15:51:05 slip39	2 merit 9 valuable 16 imply
2022-02-12 15:51:05 slip39	3 ceramic 10 body 17 realize
2022-02-12 15:51:05 slip39	4 scared 11 junk 18 biology
2022-02-12 15:51:05 slip39	5 bedroom 12 sympathy 19 canyon
2022-02-12 15:51:05 slip39	6 forbid 13 birthday 20 epidemic
2022-02-12 15:51:05 slip39	7 grumpy 14 darkness
2022-02-12 15:51:05 slip39	3rd 1 retailer 8 review 15 harvest
2022-02-12 15:51:05 slip39	2 merit 9 quiet 16 rapids
2022-02-12 15:51:05 slip39	3 ceramic 10 maximum 17 pencil
2022-02-12 15:51:05 slip39	4 shadow 11 daughter 18 finger

2022-02-12 15:51:05 slip39	5 again	12 alcohol	19 jump
2022-02-12 15:51:05 slip39	6 careful	13 alarm	20 require
2022-02-12 15:51:05 slip39	7 shaft	14 boring	
2022-02-12 15:51:05 slip39	4th 1 retailer	8 network	15 market
2022-02-12 15:51:05 slip39	2 merit	9 impact	16 grief
2022-02-12 15:51:05 slip39	3 ceramic	10 average	17 music
2022-02-12 15:51:05 slip39	4 sister	11 theory	18 miracle
2022-02-12 15:51:05 slip39	5 destroy	12 provide	19 fact
2022-02-12 15:51:05 slip39	6 spew	13 detect	20 adorn
2022-02-12 15:51:05 slip39	7 primary	14 activity	
2022-02-12 15:51:05 slip39	Frens(3/6): Recover w/ 2 of 4 groups First(1), Second(1), Fam(2/4), Frens(3		
2022-02-12 15:51:05 slip39	1st 1 retailer	8 ruin	15 idea
2022-02-12 15:51:05 slip39	2 merit	9 peasant	16 arena
2022-02-12 15:51:05 slip39	3 decision	10 large	17 numb
2022-02-12 15:51:05 slip39	4 round	11 adapt	18 making
2022-02-12 15:51:05 slip39	5 dining	12 painting	19 visual
2022-02-12 15:51:05 slip39	6 both	13 penalty	20 darkness
2022-02-12 15:51:05 slip39	7 paces	14 race	
2022-02-12 15:51:05 slip39	2nd 1 retailer	8 crunch	15 unfold
2022-02-12 15:51:05 slip39	2 merit	9 width	16 wine
2022-02-12 15:51:05 slip39	3 decision	10 leaves	17 teammate
2022-02-12 15:51:05 slip39	4 scatter	11 filter	18 employer
2022-02-12 15:51:05 slip39	5 cricket	12 remind	19 viral
2022-02-12 15:51:05 slip39	6 weapon	13 inside	20 valuable
2022-02-12 15:51:05 slip39	7 admit	14 morning	
2022-02-12 15:51:05 slip39	3rd 1 retailer	8 erode	15 likely
2022-02-12 15:51:05 slip39	2 merit	9 obtain	16 distance
2022-02-12 15:51:05 slip39	3 decision	10 crisis	17 valid
2022-02-12 15:51:05 slip39	4 shaft	11 deploy	18 ordinary
2022-02-12 15:51:05 slip39	5 dish	12 isolate	19 exotic
2022-02-12 15:51:05 slip39	6 piece	13 news	20 walnut
2022-02-12 15:51:05 slip39	7 species	14 greatest	
2022-02-12 15:51:05 slip39	4th 1 retailer	8 picture	15 calcium
2022-02-12 15:51:05 slip39	2 merit	9 salary	16 smart
2022-02-12 15:51:05 slip39	3 decision	10 spill	17 lunch
2022-02-12 15:51:05 slip39	4 skin	11 group	18 fancy
2022-02-12 15:51:05 slip39	5 closet	12 genre	19 exchange
2022-02-12 15:51:05 slip39	6 episode	13 evaluate	20 cluster
2022-02-12 15:51:05 slip39	7 execute	14 empty	
2022-02-12 15:51:05 slip39	5th 1 retailer	8 blessing	15 quick
2022-02-12 15:51:05 slip39	2 merit	9 ladybug	16 formal
2022-02-12 15:51:05 slip39	3 decision	10 closet	17 render
2022-02-12 15:51:05 slip39	4 snake	11 health	18 shame
2022-02-12 15:51:05 slip39	5 diminish	12 plastic	19 firm
2022-02-12 15:51:05 slip39	6 predator	13 webcam	20 artist
2022-02-12 15:51:05 slip39	7 analysis	14 laundry	
2022-02-12 15:51:05 slip39	6th 1 retailer	8 warmth	15 crystal
2022-02-12 15:51:05 slip39	2 merit	9 coastal	16 primary
2022-02-12 15:51:05 slip39	3 decision	10 style	17 satoshi
2022-02-12 15:51:05 slip39	4 spider	11 early	18 already
2022-02-12 15:51:05 slip39	5 credit	12 prospect	19 finger
2022-02-12 15:51:05 slip39	6 emperor	13 crowd	20 spark
2022-02-12 15:51:05 slip39	7 moment	14 garbage	
2022-02-12 15:51:05 slip39	ETH	m/44'/60'/0'/0/0	: 0xF76ADcd2B185fe84A6D0F50813508275d8797f74
2022-02-12 15:51:05 slip39	BTC	m/84'/0'/0'/0/0	: bc1qulxr6td2pm2k7apz0t6l9pcuemjj9ezclq2fmx
2022-02-12 15:51:05 slip39.recovery	Recovered 128-bit SLIP-39 secret with 5 (1st, 2nd, 3rd, 7th, 8th) of 8 supp		

2.5 Generation of Addresses

For systems that require a stream of groups of wallet Addresses (eg. for preparing invoices for clients, with a choice of cryptocurrency payment options), `slip-generator` can produce a stream of groups of addresses.

2.5.1 slip39-generator Synopsis

```
slip39-generator --help --version          | sed 's/~/: /' # (just so output formatting looks correct)
```

```
usage: slip39-generator [-h] [-v] [-q] [-s SECRET] [-f FORMAT]
                        [-c CRYPTOCURRENCY] [-p PATH] [-d DEVICE]
                        [-b BAUDRATE] [-e ENCRYPT] [--decrypt ENCRYPT]
                        [--enumerated] [--no-enumerate] [--receive]
                        [--corrupt CORRUPT]
```

Generate public wallet address(es) from a secret seed

options:

```
-h, --help            show this help message and exit
-v, --verbose          Display logging information.
-q, --quiet            Reduce logging output.
-s SECRET, --secret SECRET
                        Use the supplied 128-, 256- or 512-bit hex value as
                        the secret seed; '-' (default) reads it from stdin
                        (eg. output from slip39.recover)
-f FORMAT, --format FORMAT
                        Specify default crypto address formats: legacy,
                        segwit, bech32; default ETH:legacy, BTC:bech32,
                        LTC:bech32, DOGE:legacy
-c CRYPTOCURRENCY, --cryptocurrency CRYPTOCURRENCY
                        A crypto name and optional derivation path (default:
                        "ETH:{Account.path_default('ETH')}"), optionally w/
                        ranges, eg: ETH:../0/-
-p PATH, --path PATH  Modify all derivation paths by replacing the final
                        segment(s) w/ the supplied range(s), eg. '.../1/-'
                        means .../1/[0,...)
-d DEVICE, --device DEVICE
                        Use this serial device to transmit (or --receive)
                        records
-b BAUDRATE, --baudrate BAUDRATE
                        Set the baud rate of the serial device (default:
                        115200)
-e ENCRYPT, --encrypt ENCRYPT
                        Secure the channel from errors and/or prying eyes with
                        ChaCha20Poly1305 encryption w/ this password; '-'
                        reads from stdin
--decrypt ENCRYPT
--enumerated           Include an enumeration in each record output (required
                        for --encrypt)
--no-enumerate         Disable enumeration of output records
--receive              Receive a stream of slip.generator output
--corrupt CORRUPT     Corrupt a percentage of output symbols
```

Once you have a secret seed (eg. from `slip39.recovery`), you can generate a sequence of HD wallet addresses from it. Emits rows in the form:

<enumeration> [<address group(s)>]

If the output is to be transmitted by an insecure channel (eg. a serial port), which may insert errors or allow leakage, it is recommended that the records be encrypted with a cryptographic function that includes a message authentication code. We use ChaCha20Poly1305 with a password and a random nonce generated at program start time. This nonce is incremented for each record output.

Since the receiver requires the nonce to decrypt, and we do not want to separately transmit the nonce and supply it to the receiver, the first record emitted when --encrypt is specified is the random nonce, encrypted with the password, itself with a known nonce of all 0 bytes. The plaintext data is random, while the nonce is not, but since this construction is only used once, it should be satisfactory. This first nonce record is transmitted with an enumeration prefix of "nonce".

2.5.2 Producing Addresses

Addresses can be produced in plaintext or encrypted, and output to stdout or to a serial port.

```
slip39-generator --secret ffffffffffffffffffffffffffff --path './-3' | sed 's/~:/ /' # (just so ou
0: [{"ETH", "m/44'/60'/0'/0/0", "0x824b174803e688dE39aF5B3D7Cd39bE6515A19a1"}, {"BTC", "m/84'/0'/0'/0/0", "bc1q9ysc
1: [{"ETH", "m/44'/60'/0'/0/1", "0x8D342083549C635C0494d3c77567860ee7456963"}, {"BTC", "m/84'/0'/0'/0/1", "bc1qneec6
2: [{"ETH", "m/44'/60'/0'/0/2", "0x52787E24965E1aBd691df77827A3CfA90f0166AA"}, {"BTC", "m/84'/0'/0'/0/2", "bc1q2snj
3: [{"ETH", "m/44'/60'/0'/0/3", "0xc2442382Ae70c77d6B6840EC6637dB2422E1D44e"}, {"BTC", "m/84'/0'/0'/0/3", "bc1qxwek
```

To produce accounts from a BIP-39 or SLIP-39 seed, recover it using slip39-recovery.

Here's an example of recovering a test BIP-39 seed; note that it yields the well-known ETH 0xfc20...1B5E and BTC bc1qk0...gmn2 accounts associated with this test Mnemonic:

```
slip39-recovery --bip39 --mnemonic 'zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong' \
| slip39-generator --secret - --path './-3' | sed 's/~:/ /' # (just so ou
0: [{"ETH", "m/44'/60'/0'/0/0", "0xfc2077CA7F403cBECA41B1B0F62D91B5EA631B5E"}, {"BTC", "m/84'/0'/0'/0/0", "bc1qk0a9
1: [{"ETH", "m/44'/60'/0'/0/1", "0xd1a7451beB6FE0326b4B78e3909310880B781d66"}, {"BTC", "m/84'/0'/0'/0/1", "bc1qkd33
2: [{"ETH", "m/44'/60'/0'/0/2", "0x578270B5E5B53336baC354756b763b309eCA90Ef"}, {"BTC", "m/84'/0'/0'/0/2", "bc1qvr7e
3: [{"ETH", "m/44'/60'/0'/0/3", "0x909f59835A5a120EafE1c60742485b7ff0e305da"}, {"BTC", "m/84'/0'/0'/0/3", "bc1q6t9v
```

We can encrypt the output, to secure the sequence (and due to integrated MACs, ensures no errors occur over an insecure channel like a serial cable):

```
slip39-recovery --bip39 --mnemonic 'zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong' \
| slip39-generator --secret - --path './-3' --encrypt 'password' | sed 's/~:/ /' # (just so ou

nonce: b1ffedce81e159263ea69eea8d6878278cf898cc1cdcdb9b3777bcdd
0: 9b76065c05953497f0666e194139d3548db2fe72c55e8beb71b1cedf196c55a4883187467cd4a2ba5ae3748661c036ac896273176cd5
1: 823b6c53b121ed8eb6061e7b8ecc7cab7b09a49cfe92c92aec6c43172b953a6ad2926b79c831359b86207d2e0a88cab0b92d1c0d423c
2: 3894035224fd451202631b59aa7d6e67e1b69955105a9eb8b8ec9003ca70a50612fcaded25a3f074b478fed142c3521b1c05a744cf3c
3: af4230fcfc5a0228599c49ec10e43aaa40364cf22d2fe42a82bb7215e47eeeba13f3d3baa64deeb69e0e10db1e9dcd494e6c447e50a7
```

On the receiving computer, we can decrypt and recover the stream of accounts from the wallet seed; any rows with errors are ignored:

```
slip39-recovery --bip39 --mnemonic 'zoo zoo zoo zoo zoo zoo zoo zoo wrong' \
| slip39-generator --secret - --path './-3' --encrypt 'password' \
| slip39-generator --receive --decrypt 'password' | sed 's/~:/ /' # (just so ou
0: [{"ETH", "m/44'/60'/0'/0/0", "0xfc2077CA7F403cBECA41B1B0F62D91B5EA631B5E"}, {"BTC", "m/84'/0'/0'/0/0", "bc1qk0a9
1: [{"ETH", "m/44'/60'/0'/0/1", "0xd1a7451beB6FE0326b4B78e3909310880B781d66"}, {"BTC", "m/84'/0'/0'/0/1", "bc1qkd33
2: [{"ETH", "m/44'/60'/0'/0/2", "0x578270B5E5B53336baC354756b763b309eCA90Ef"}, {"BTC", "m/84'/0'/0'/0/2", "bc1qvr7e
3: [{"ETH", "m/44'/60'/0'/0/3", "0x909f59835A5a120EafE1c60742485b7ff0e305da"}, {"BTC", "m/84'/0'/0'/0/3", "bc1q6t9v
```

2.6 The slip39 module API

Provide SLIP-39 Mnemonic set creation from a 128-bit master secret, and recovery of the secret from a subset of the provided Mnemonic set.

2.6.1 slip39.create

Creates a set of SLIP-39 groups and their mnemonics.

Key	Description
name	Who/what the account is for
group_threshold	How many groups' data is required to recover the account(s)
groups	Each group's description, as {"<group>":(<required>, <members>), ...}
master_secret	128-bit secret (default: from secrets.token_bytes)
passphrase	An optional additional passphrase required to recover secret (default: "")
iteration_exponent	For encrypted secret, exponentially increase PBKDF2 rounds (default: 1)
cryptopaths	A number of crypto names, and their derivation paths]
strength	Desired master_secret strength, in bits (default: 128)

Outputs a slip39.Details namedtuple containing:

Key	Description
name	(same)
group_threshold	(same)
groups	Like groups, w/ <members> = ["<mnemonics>", ...]
accounts	Resultant list of groups of accounts

This is immediately usable to pass to slip39.output.

```
import codecs
import random

#
# NOTE:
#
# We turn off randomness here during SLIP-39 generation to get deterministic phrases;
# during normal operation, secure entropy is used during mnemonic generation, yielding
# random phrases, even when the same seed is used multiple times.
#
import shamir_mnemonic
shamir_mnemonic.shamir.RANDOM_BYTES = lambda n: b'\00' * n

import slip39

cryptopaths      = [("ETH", "m/44'/60'/0'/0/-2"), ("BTC", "m/44'/0'/0'/0/-2")]
master_secret    = b'\xFF' * 16
passphrase       = b""
create_details    = slip39.create(
    "Test", 2, { "Mine": (1,1), "Fam": (2,3) },
    master_secret=master_secret, passphrase=passphrase, cryptopaths=cryptopaths )

[
    [
        f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" if l_n == 0 else ""
    ] + words
    for g_name, (g_of, g_mnems) in create_details.groups.items()
    for g_n, mnem in enumerate( g_mnems )
    for l_n, (line, words) in enumerate(slip39.organize_mnemonic(
        mnem, label=f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" ))
]
```

0	1	2	3
Mine(1/1) #1:	1 academic 2 acid 3 acrobat 4 easy 5 change 6 injury 7 painting	8 safari 9 drug 10 browser 11 trash 12 fridge 13 busy 14 finger	15 standard 16 angry 17 similar 18 aspect 19 smug 20 violence
Fam(2/3) #1:	1 academic 2 acid 3 beard 4 echo 5 crystal 6 machine 7 bolt	8 prevent 9 mouse 10 daughter 11 ancient 12 fortune 13 ruin 14 warmth	15 dwarf 16 dream 17 flavor 18 oral 19 chest 20 marathon
Fam(2/3) #2:	1 academic 2 acid 3 beard 4 email 5 dive 6 warn 7 ranked	8 prune 9 pickup 10 device 11 device 12 peanut 13 enemy 14 graduate	15 briefing 16 often 17 escape 18 sprinkle 19 segment 20 devote
Fam(2/3) #3:	1 academic 2 acid 3 beard 4 entrance 5 alarm 6 health 7 discuss	8 dining 9 invasion 10 bumpy 11 identify 12 anxiety 13 august 14 sunlight	15 intimate 16 satoshi 17 hobo 18 ounce 19 both 20 award

Add the resultant HD Wallet addresses:

```
[
    [ account.path, account.address ]
    for group in create_details.accounts
    for account in group
]
```

0	1
m/44'/60'/0'/0/0	0x824b174803e688dE39aF5B3D7Cd39bE6515A19a1
m/44'/0'/0'/0/0	bc1qm5ua96hx30snwrwsfnv97q96h53l86ded7wmjl
m/44'/60'/0'/0/1	0x8D342083549C635C0494d3c77567860ee7456963
m/44'/0'/0'/0/1	bc1qwz6v9z49z8mk5ughj7r78hjsp45jsxgzh29lnh
m/44'/60'/0'/0/2	0x52787E24965E1aBd691df77827A3CfA90f0166AA
m/44'/0'/0'/0/2	bc1q690m430qu29auyefarwfrvfumncunvyw6v53n9

2.6.2 slip39.output

Key	Description
name	(same as <code>slip39.create</code>)
group_threshold	(same as <code>slip39.create</code>)
groups	Like groups, w/ <code><members> = ["<mnemonics>", ...]</code>
accounts	Resultant <code>{ "path": Account, ... }</code>
card_format	'index', '(<h>,<w>),<margin>', ...
paper_format	'Letter', ...

Produce a PDF containing all the SLIP-39 details for the account.

```
slip32.output( *create_details )
```

2.6.3 slip39.recover

Takes a number of SLIP-39 mnemonics, and if sufficient `group_threshold` groups' mnemonics are present (and the options `passphrase` is supplied), the `master_secret` is recovered. This can be used with `slip39.accounts` to directly obtain any `Account` data.

Note that the passphrase is **not** checked; entering a different passphrase for the same set of mnemonics will recover a **different** wallet! This is by design; it allows the holder of the SLIP-39 mnemonic phrases to recover a "decoy" wallet by supplying a specific passphrase, while protecting the "primary" wallet.

Therefore, it is **essential** to remember any non-default (empty) passphrase used, separately and securely. Take great care in deciding if you wish to use a passphrase with your SLIP-39 wallet!

Key	Description
mnemonics	["<mnemonics>", ...]
passphrase	Optional passphrase to decrypt secret

```
recoverydecoy      = slip39.recover(
    create_details.groups['Mine'][1][:] + create_details.groups['Fam'][1][:2],
    passphrase=b"wrong!"
)
recoverydecoyhex    = codecs.encode( recoverydecoy, 'hex_codec' ).decode( 'ascii' )

recoveryvalid      = slip39.recover(
    create_details.groups['Mine'][1][:] + create_details.groups['Fam'][1][:2],
    passphrase=passphrase
)
recoveryvalidhex    = codecs.encode( recoveryvalid, 'hex_codec' ).decode( 'ascii' )

[[ f"{len(recoverydecoy)*8}-bit secret w/ decoy password recovered:" ]] + [
    [ f"{recoverydecoyhex[b*32:b*32+32]}" ]
    for b in range( len( recoverydecoyhex ) // 32 )
] + [[ f"{len(recoveryvalid)*8}-bit secret recovered:" ]] + [
    [ f"{recoveryvalidhex[b*32:b*32+32]}" ]
    for b in range( len( recoveryvalidhex ) // 32 )
]

0
-----
128-bit secret w/ decoy password recovered:
2e522cea2b566840495c220cf79c756e
128-bit secret recovered:
ffffffffffffffffffffffff
```

3 Conversion from BIP-39 to SLIP-39

If we already have a BIP-39 wallet, it would certainly be nice to be able to create nice, safe SLIP-39 mnemonics for it, and discard the unsafe BIP-39 mnemonics we have lying around, just waiting to be accidentally discovered and the account compromised!

3.1 BIP-39 vs. SLIP-39 Incompatibility

Unfortunately, it is **not possible** to cleanly convert a BIP-39 derived wallet into a SLIP-39 wallet. Both of these techniques preserve "entropy" (random) bits, but these bits are used **differently** – and incompatibly – to derive the resultant Ethereum wallets.

The best we can do is to preserve the 512-bit **output** of the BIP-39 mnemonic phrase as a set of 512-bit SLIP-39 mnemonics.

3.1.1 BIP-39 Entropy to Mnemonic

BIP-39 uses a single set of 12, 15, 18, 21 or 24 BIP-39 words to carefully preserve a specific 128 to 256 bits of initial entropy. Here's a 128-bit (12-word) example using some fixed "entropy" 0xFFFF..FFFF:

```
from mnemonic import Mnemonic
bip39_english = Mnemonic("english")
entropy = b'\xFF' * 16
entropy_mnemonic = bip39_english.to_mnemonic( entropy )
[
    [ entropy_mnemonic ]
]
```

0

zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong

Each word is one of a corpus of 2048 words; therefore, each word encodes 11 bits ($2048 = 2^{11}$) of entropy. So, we provided 128 bits, but $12 \times 11 = 132$. So where does the extra 4 bits of data come from?

It comes from the first few bits of a SHA256 hash of the entropy, which is added to the end of the supplied 128 bits, to reach the required 132 bits: $132 / 11 == 12$ words.

This last 4 bits (up to 8 bits, for a 256-bit 24-word BIP-39) is checked, when validating the BIP-39 mnemonic. Therefore, making up a random BIP-39 mnemonic will succeed only $1 / 16$ times on average, due to an incorrect checksum 4-bit ($16 == 2^4$). Lets check:

```
def random_words( n, count=100 ):
    for _ in range( count ):
        yield ' '.join( random.choice( bip39_english.wordlist ) for _ in range( n ) )

successes = sum(
    bip39_english.check( m )
    for i,m in enumerate( random_words( 12, 10000 ) ) ) / 100

[[ f"Valid random 12-word mnemonics:" ]] + [
    [ f"{successes}%" ]] + [
    [ f"~ 1/{100/successes:.3}" ]]
```

0

Valid random 12-word mnemonics:

6.74%

~ 1/14.8

Sure enough, about 1/16 random 12-word phrases are valid BIP-39 mnemonics. OK, we've got the contents of the BIP-39 phrase dialed in. How is it used to generate accounts?

3.1.2 BIP-39 Mnemonic to Seed

Unfortunately, we do **not** use the carefully preserved 128-bit entropy to generate the wallet! Nope, it is stretched to a 512-bit seed using PBKDF2 HMAC SHA512. The normalized **text** (*not the entropy bytes*) of the 12-word mnemonic is then used (with a salt of "mnemonic" plus an optional passphrase, "" by default), to obtain the seed:

```
seed = bip39_english.to_seed( entropy_mnemonic )
seedhex = codecs.encode( seed, 'hex_codec' ).decode( 'ascii' )
[
    [ f"{len(seed)*8}-bit seed:" ]] + [
    [ f"{seedhex[b*32:b*32+32]}" ]]
    for b in range( len( seedhex ) // 32 )
]
```

```

0
-----
512-bit seed:
b6a6d8921942dd9806607ebc2750416b
289adea669198769f2e15ed926c3aa92
bf88ece232317b4ea463e84b0fcd3b53
577812ee449ccc448eb45e6f544e25b6

```

3.1.3 BIP-39 Seed to Address

Finally, this 512-bit seed is used to derive HD wallet(s). The HD Wallet key derivation process consumes whatever seed entropy is provided (512 bits in the case of BIP-39), and uses HMAC SHA512 with a prefix of b"Bitcoin seed" to stretch the supplied seed entropy to 64 bytes (512 bits). Then, the HD Wallet **path** segments are iterated through, permuting the first 32 bytes of this material as the key with the second 32 bytes of material as the chain node, until finally the 32-byte (256-bit) Ethereum account private key is produced. We then use this private key to compute the rest of the Ethereum account details, such as its public address.

```

path = "m/44'/60'/0'/0/0"
eth_hd = slip39.account( seed, 'ETH', path )
[
  [ f"{len(eth_hd.key)*4}-bit derived key at path {path!r}:" ] + [
    [ f"{eth_hd.key}" ] ] + [
    [ "... yields ..." ] ] + [
    [ f"Ethereum address: {eth_hd.address}" ]
  ]
]

```

```

0
-----
256-bit derived key at path "m/44'/60'/0'/0/0":
7af65ba4dd53f23495dcb04995e96f47c243217fc279f10795871b725cd009ae
... yields ...
Ethereum address: 0xfc2077CA7F403cBECA41B1B0F62D91B5EA631B5E

```

Thus, we see that while the 12-word BIP-39 mnemonic careful preserves the original 128-bit entropy, this data is not directly used to derive the wallet private key and address. Also, since an irreversible hash is used to derive the seed from the mnemonic, we can't reverse the process on the seed to arrive back at the BIP-39 mnemonic phrase.

3.1.4 SLIP-39 Entropy to Mnemonic

Just like BIP-39 carefully preserves the original 128-bit entropy bytes in a single 12-word mnemonic phrase, SLIP-39 preserves the original 128-bit entropy in a *set* of 30-word mnemonic phrases.

```

name,thrs,grps,acct = slip39.create(
    "Test", 2, { "Mine": (1,1), "Fam": (2,3) }, entropy )
[
  [ f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" if l_n == 0 else "" ] + words
  for g_name,(g_of,g_mnems) in grps.items()
  for g_n,mnem in enumerate( g_mnems )
  for l_n,(line,words) in enumerate(slip39.organize_mnemonic(
    mnem, rows=7, cols=3, label=f"{g_name}({g_of}/{len(g_mnems)}) #{g_n+1}:" ))
]

```


0	1	2	3
Mine(1/1) #1:	1 academic	8 safari	15 standard
	2 acid	9 drug	16 angry
	3 acrobat	10 browser	17 similar
	4 easy	11 trash	18 aspect
	5 change	12 fridge	19 smug
	6 injury	13 busy	20 violence
	7 painting	14 finger	
Fam(2/3) #1:	1 academic	8 prevent	15 dwarf
	2 acid	9 mouse	16 dream
	3 beard	10 daughter	17 flavor
	4 echo	11 ancient	18 oral
	5 crystal	12 fortune	19 chest
	6 machine	13 ruin	20 marathon
	7 bolt	14 warmth	
Fam(2/3) #2:	1 academic	8 prune	15 briefing
	2 acid	9 pickup	16 often
	3 beard	10 device	17 escape
	4 email	11 device	18 sprinkle
	5 dive	12 peanut	19 segment
	6 warn	13 enemy	20 devote
	7 ranked	14 graduate	
Fam(2/3) #3:	1 academic	8 dining	15 intimate
	2 acid	9 invasion	16 satoshi
	3 beard	10 bumpy	17 hobo
	4 entrance	11 identify	18 ounce
	5 alarm	12 anxiety	19 both
	6 health	13 august	20 award
	7 discuss	14 sunlight	

Since there is some randomness used in the SLIP-39 mnemonics generation process, we would get a **different** set of words each time for the fixed "entropy" 0xFFFF.FF used in this example (if we hadn't manually disabled entropy for `shamir_mnemonic`, above), but we will **always** derive the same Ethereum account 0x824b..19a1 at the specified HD Wallet derivation path.

```
[
  [ "Crypto", "HD Wallet Path:", "Ethereum Address:" ]
] + [
  [ account.crypto, account.path, account.address ]
  for group in create_details.accounts
  for account in group
]
```

0	1	2
Crypto	HD Wallet Path:	Ethereum Address:
ETH	m/44'/60'/0'/0/0	0x824b174803e688dE39aF5B3D7Cd39bE6515A19a1
BTC	m/44'/0'/0'/0/0	bc1qm5ua96hx30snwrwsfnv97q96h53l86ded7wmjl
ETH	m/44'/60'/0'/0/1	0x8D342083549C635C0494d3c77567860ee7456963
BTC	m/44'/0'/0'/0/1	bc1qwz6v9z49z8mk5ughj7r78hjsp45jsxgzh29lnh
ETH	m/44'/60'/0'/0/2	0x52787E24965E1aBd691df77827A3CfA90f0166AA
BTC	m/44'/0'/0'/0/2	bc1q690m430qu29auyefarwfrvfumncunvyw6v53n9

3.1.5 SLIP-39 Mnemonic to Seed

Lets prove that we can actually recover the **original** entropy from the SLIP-39 recovery mnemonics; in this case, we've specified a SLIP-39 group_threshold of 2 groups, so we'll use 1 mnemonic from Mine, and 2 from Fam:

```

_,mnem_mine      = grps['Mine']
_,mnem_fam       = grps['Fam']
recseed          = slip39.recover( mnem_mine + mnem_fam[:2] )
recseedhex       = codecs.encode( recseed, 'hex_codec' ).decode( 'ascii' )
[
  [ f"{len(recseed)*8}-bit seed:" ]
] + [
  [ f"{recseedhex[b*32:b*32+32]}" ]
    for b in range( len( recseedhex ) // 32 )
]

0
-----
128-bit seed:
ffffffffffffffffffffffff

```

3.1.6 SLIP-39 Seed to Address

And we'll use the same style of code as for the BIP-39 example above, to derive the Ethereum address **directly** from this recovered 128-bit seed:

```

receth = slip39.account( recseed, 'ETH', path )
[
  [ f"{len(receth.key)*4}-bit derived key at path {path!r}:" ] ] + [
  [ f"{receth.key}" ] ] + [
  [ "... yields ..." ] ] + [
  [ f"Ethereum address: {receth.address}" ]
]

0
-----
256-bit derived key at path "m/44'/60'/0'/0/0":
6a2ec39aab88ec0937b79c8af6aaf2fd3c909e9a56c3ddd32ab5354a06a21a2b
... yields ...
Ethereum address: 0x824b174803e688dE39aF5B3D7Cd39bE6515A19a1

```

And we see that we obtain the same Ethereum address **0x824b...1a2b** as we originally got from `slip39.create` above. However, this is **not** the Ethereum wallet address obtained from BIP-39 with exactly the same `0xFFFF...FF` entropy, which was `0xfc20...1B5E`. This is due to the fact that BIP-39 does not use the recovered entropy to produce the seed like SLIP-39 does, but applies additional one-way hashing of the mnemonic to produce the seed.

3.2 BIP-39 vs SLIP-39 Key Derivation Summary

At no time in BIP-39 account derivation is the original 128-bit mnemonic entropy used directly in the derivation of the wallet key. This differs from SLIP-39, which directly uses the 128-bit mnemonic entropy recovered from the SLIP-39 Shamir's Secret Sharing System recovery process to generate each HD Wallet account's private key.

Furthermore, there is no point in the BIP-39 entropy to account generation where we **could** introduce a known 128-bit seed and produce a known Ethereum wallet from it, other than as the very beginning.

3.2.1 BIP-39 Backup via SLIP-39

There is one approach which can preserve an original BIP-39 wallet address, using SLIP-39 mnemonics.

It is clumsy, as it preserves the BIP-39 **output** 512-bit stretched seed, and the resultant 59-word SLIP-39 mnemonics cannot be used (at present) with the Trezor hardware wallet. They can, however, be used to recover the HD wallet private keys without access to the original BIP-39

mnemonic phrase – you could generate and distribute a set of more secure SLIP-39 mnemonic phrases, instead of trying to secure the original BIP-39 mnemonic.

We'll use `slip39.recovery --bip39 ...` to recover the 512-bit stretched seed from BIP-39:

```
( python3 -m slip39.recovery --bip39 \
  --mnemonic "zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong"
) 2>&1
```

```
2022-02-12 15:51:15 slip39.recovery Recovered 512-bit BIP-39 secret from english mnemonic
b6a6d8921942dd9806607ebc2750416b289adea669198769f2e15ed926c3aa92bf88ece232317b4ea463e84b0fcd3b53577812ee449ccc448eb
```

Then we can generate a 59-word SLIP-39 mnemonic set from the 512-bit secret:

```
( python3 -m slip39.recovery --bip39 \
  --mnemonic "zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo zoo wrong" \
  | python3 -m slip39 --secret - --no-card
) 2>&1
```

```
2022-02-12 15:51:15 slip39.recovery Recovered 512-bit BIP-39 secret from english mnemonic
2022-02-12 15:51:16 slip39          ETH    m/44'/60'/0'/0/0    : 0xfc2077CA7F403cBECA41B1B0F62D91B5EA631B5E
2022-02-12 15:51:16 slip39          BTC    m/84'/0'/0'/0/0    : bc1qk0a9hr7wjfxeeenz9nwenw9flhq0tmsf6vsqnn2
```

This `0xfc20...1B5E` address is the same Ethereum address as is recovered on a Trezor using this BIP-39 mnemonic phrase.

4 Building & Installing

The `python-slip39` project is tested under both homebrew:

```
$ brew install python-tk@3.9
```

and using the official python.org/downloads installer.

Either of these methods will get you a `python3` executable running version 3.9+, usable for running the `slip39` module, and the `slip39.gui` GUI.

4.1 The slip39 Module

To build the wheel and install `slip39` manually:

```
$ git clone git@github.com:pjkundert/python-slip39.git
$ make -C python-slip39 install
```

To install from Pypi, including the optional requirements to run the `PySimpleGUI/tkinter` GUI, support serial I/O, and to support creating encrypted Ethereum JSON wallets:

```
$ python3 -m pip install slip39[gui,serial,json]
```

4.2 The slip39 GUI

To install from Pypi, including the optional requirements to run the `PySimpleGUI/tkinter` GUI:

```
$ python3 -m pip install slip39[gui]
```

Then, there are several ways to run the GUI:

```
$ python3 -m slip39.gui      # Execute the python slip39.gui module main method
$ slip39-gui                # Run the main function provided by the slip39.gui module
```

4.2.1 The macOS SLIP39.app GUI

You can build the native macOS SLIP39.app App.

This requires the official python.org/downloads installer; the homebrew python-tk@3.9 will not work for building the native app using either PyInstaller. (The py2app approach doesn't work in either version of Python).

```
$ git clone git@github.com:pjkundert/python-slip39.git
$ make -C python-slip39 app
```

5 Dependencies

Internally, python-slip39 project uses Trezor's python-shamir-mnemonic to encode the seed data to SLIP-39 phrases, python-hdwallet to convert seeds to ETH, BTC, LTC and DOGE wallets, and the Ethereum project's eth-account to produce encrypted JSON wallets for specified Ethereum accounts.

5.1 The python-shamir-mnemonic API

To use it directly, obtain , and install it, or run `python3 -m pip install shamir-mnemonic`.

```
$ shamir create custom --group-threshold 2 --group 1 1 --group 1 1 --group 2 5 --group 3 6
Using master secret: 87e39270d1d1976e9ade9cc15a084c62
Group 1 of 4 - 1 of 1 shares required:
merit aluminum acrobat romp capacity leader gray dining thank rhyme escape genre havoc furl breathe class pitch loc
Group 2 of 4 - 1 of 1 shares required:
merit aluminum beard romp briefing email member flavor disaster exercise cinema subject perfect facility genius bik
Group 3 of 4 - 2 of 5 shares required:
merit aluminum ceramic roster already cinema knit cultural agency intimate result ivory makeup lobe jerky theory ga
merit aluminum ceramic scared beam findings expand broken smear cleanup enlarge coding says destroy agency emperor
merit aluminum ceramic shadow cover smith idle vintage mixture source dish squeeze stay wireless likely privacy imp
merit aluminum ceramic sister duke relate elite ruler focus leader skin machine mild envelope wrote amazing justice
merit aluminum ceramic smug buyer taxi amazing marathon treat clinic rainbow destroy unusual keyboard thumb story l
Group 4 of 4 - 3 of 6 shares required:
merit aluminum decision round bishop wrote belong anatomy spew hour index fishing lecture disease cage thank fantas
merit aluminum decision scatter carpet spine ruin location forward priest cage security careful emerald screw adult
merit aluminum decision shaft arcade infant argue elevator imply obesity oral venture afraid slice raisin born nerv
merit aluminum decision skin already fused tactics skunk work floral very gesture organize puny hunting voice pytho
merit aluminum decision snake cage premium aide wealthy viral chemical pharmacy smoking inform work cubic ancestor
merit aluminum decision spider boundary lunar staff inside junior tendency sharp editor trouble legal visual tricyc
```