# Development of a payment channel over the Bitcoin network

Final degree project

David Lozano Jarque <br/>
<br/>bitcoin@davidlj95.com>

5<sup>th</sup> July 2017



# Outline

- Introduction
  - What is Bitcoin
  - How does Bitcoin work?
  - The scalability problem
- Bitcoin & Smart Contracts
  - Transactions at low-level detail
  - Bitcoin's scripting language
  - What is a payment channel?
- Unidirectional payment channels
  - Scheme
  - Implementation
- 4 Bidirectional payment channels
  - Scheme
  - Implementation
  - Problem: channel reseting
- 5 The Bitcoin framework
- 6 Conclusions



# Bitcoin's appearance

#### The creator

Satoshi Nakamoto @ Cryptography (metzdowd.com) November 1st, 2008

#### Bitcoin P2P e-cash paper

Satoshi Nakamoto Sat, 01 Nov 2008 16:16:33 -0700

I've been working on a new electronic cash system that's fully peer-to-peer, with no trusted third party.

The paper is available at: http://www.bitcoin.org/bitcoin.pdf

The main properties:

Double-spending is prevented with a peer-to-peer network.

No mint or other trusted parties.

Participants can be anonymous. New coins are made from Hashcash style proof-of-work.

The proof-of-work for new coin generation also powers the network to prevent double-spending.

Bitcoin: A Peer-to-Peer Electronic Cash System

#### Bitcoin: A Peer-to-Peer Electronic Cash System

Satoshi Nakamoto satoshin@gmx.com www.bitcoin.org

Abstract. A purely peer-to-peer version of electronic cash would allow online payments to be sent directly from one party to another without going through a financial institution. Digital signatures provide part of the solution, but the main benefits are lost if a trusted third party is still required to prevent double-spending. We propose a solution to the double-spending problem using a peer-to-peer network. The network timestamps transactions by hashing them into an ongoing chain of hash-based proof-of-work, forming a record that cannot be changed without redoing the proof-of-work. The longest chain not only serves as proof of the sequence of events witnessed, but proof that it came from the largest pool of CPU power. As long as a majority of CPU power is controlled by nodes that are not cooperating to attack the network, they'll generate the longest chain and outpace attackers. The network itself requires minimal structure. Messages are broadcast on a best effort basis, and nodes can leave and rejoin the network at will, accepting the longest proof-of-work chain as proof of what happened while they were gone.

## Definition of Bitcoin

P2P network that allows payments between users without a trusted third party

## Definition of Bitcoin

P2P network that allows payments between users without a trusted third party

## **Features**

• Public ledger of transactions

#### Definition of Bitcoin

P2P network that allows payments between users without a trusted third party

- Public ledger of transactions
- Public ledger using blockchain technology

#### Definition of Bitcoin

P2P network that allows payments between users without a trusted third party

- Public ledger of transactions
- Public ledger using blockchain technology
- Consensus via proof-of-work algorithm

#### Definition of Bitcoin

P2P network that allows payments between users without a trusted third party

- Public ledger of transactions
- Public ledger using blockchain technology
- Consensus via proof-of-work algorithm
- Cryptography-enforced (digital ECDSA signatures & hash functions)

#### Definition of Bitcoin

P2P network that allows payments between users without a trusted third party

- Public ledger of transactions
- Public ledger using blockchain technology
- Consensus via proof-of-work algorithm
- Cryptography-enforced (digital ECDSA signatures & hash functions)
- No trusted 3rd party (Pure P2P)

How do we move currency?

# What is a Bitcoin transaction?

Message specifying the transfer of currency units (called bitcoins)

#### What is a Bitcoin transaction?

Message specifying the transfer of currency units (called bitcoins)

## Transaction fields

A transaction moves currency units given an input to a new output

• version

## What is a Bitcoin transaction?

Message specifying the transfer of currency units (called bitcoins)

## Transaction fields

- version
- inputs

## What is a Bitcoin transaction?

Message specifying the transfer of currency units (called bitcoins)

## Transaction fields

- version
- inputs
- outputs

## What is a Bitcoin transaction?

Message specifying the transfer of currency units (called bitcoins)

## Transaction fields

- version
- inputs
- outputs
- locktime

#### What is a Bitcoin transaction?

Message specifying the transfer of currency units (called bitcoins)

## Transaction fields

- version
- inputs
- outputs
- locktime

## What is a Bitcoin transaction?

Message specifying the transfer of currency units (called *bitcoins*)

# Transaction fields

A transaction moves currency units given an input to a new output

- version
- inputs
- outputs
- locktime

# Basic Bitcoin transaction

version	inputs	outputs	locktime
	.,,		
version	Alice	Bob	locktime

Where do we store transactions?

# **Blocks**

# What is a Bitcoin block?

Collection of transactions

# **Blocks**

# What is a Bitcoin block?

Collection of transactions

## Basic Bitcoin block

		_
Ma	aic	number

Block size

Block header

Number of transactions

#### Transactions

version	inputs	outputs	locktime
version	inputs	outputs	locktime
version	inputs	outputs	locktime

. . .

Where do we store blocks?

# Blockchain


# Bitcoin's blockchain

Distributed and replicated database containing a collection of blocks, each one linked to the previous one using **their hashes** forming a **chain** 

# Blockchain

## Bitcoin's blockchain

Distributed and replicated database containing a collection of blocks, each one linked to the previous one using **their hashes** forming a **chain** 



# Blockchain

## Rewards

Appending a new block to the chain is rewarded with **newly generated currency units** with a *no-input* transaction called a **generation transaction** 

Who decides who can create next block?

# Consensus

# Proof-of-work

Piece of data difficult to generate but easy to verify it meets certain requirements

# Consensus


## Proof-of-work

Piece of data difficult to generate but easy to verify it meets certain requirements

# Bitcoin's proof-of-work

Field in block's header must contain a hash of the block itself whose value is less than a dynamically adjusted value

# Proof-of-work



How to handle everything?

# A Bitcoin client

Software that allows to operate on the Bitcoin network, handling all data structures and network messages

## A Bitcoin client

Software that allows to operate on the Bitcoin network, handling all data structures and network messages

#### **Features**

• Receive and broadcasts messages (transactions, blocks, ...)

#### A Bitcoin client

Software that allows to operate on the Bitcoin network, handling all data structures and network messages

- Receive and broadcasts messages (transactions, blocks, ...)
- 2 Stores and shares the blockchain

#### A Bitcoin client

Software that allows to operate on the Bitcoin network, handling all data structures and network messages

- Receive and broadcasts messages (transactions, blocks, ...)
- 2 Stores and shares the blockchain
- 3 Handles keys and creates payment transactions

#### A Bitcoin client

Software that allows to operate on the Bitcoin network, handling all data structures and network messages

- Receive and broadcasts messages (transactions, blocks, ...)
- 2 Stores and shares the blockchain
- 3 Handles keys and creates payment transactions

# A Bitcoin client

Software that allows to operate on the Bitcoin network, handling all data structures and network messages

- Receive and broadcasts messages (transactions, blocks, ...)
- 2 Stores and shares the blockchain
- 3 Handles keys and creates payment transactions
- \*Feature (2) just in full-nodes

#### A Bitcoin client

Software that allows to operate on the Bitcoin network, handling all data structures and network messages

## Featur<u>es</u>

- Receive and broadcasts messages (transactions, blocks, ...)
- 2 Stores and shares the blockchain
- 4 Handles keys and creates payment transactions

## Most used client


Bitcoin Core (bitcoin.org) is the most used Bitcoin client (85% of nodes in the network)

<sup>\*</sup>Feature (2) just in full-nodes


What is the limit of the technology?

### Blockchain size

### Blockchain size over time (KBytes/years)



### Blockchain size



Current blockchain size is approximately 120GB



### Blockchain size

### Increasing transaction demand

As Bitcoin becomes more popular, more users arrive therefore more transactions need to be processed

### Throughput limits

Because of the protocol, blocks must

#### Throughput limits

Because of the protocol, blocks must

 Appear every 10 minutes (approximately) due to proof-of-work difficulty adjustment

#### Throughput limits

Because of the protocol, blocks must


- Appear every 10 minutes (approximately) due to proof-of-work difficulty adjustment
- 2 1MB maximum block size to control the blockchain growth rate

2009

2010


2011

2012



2013

2017



Approximately 2.000 transactions per block



### Bitcoin's transaction throughput

#### Bitcoin's transaction throughput

$$\frac{2.000~tx}{1~block}$$
  $\times$ 

#### Bitcoin's transaction throughput

$$\frac{2.000~tx}{1~block} \times \frac{1~block}{10~minutes} \times$$

### Bitcoin's transaction throughput

$$\frac{2.000~tx}{1~block} \times \frac{1~block}{10~minutes} \times \frac{1~minute}{60~sec.} \approx$$

#### Bitcoin's transaction throughput

Using previous information:

$$\frac{2.000~tx}{1~block} \times \frac{1~block}{10~minutes} \times \frac{1~minute}{60~sec.} \approx$$

3 transactions per second

#### Bitcoin's transaction throughput

Using previous information:

$$\frac{2.000~tx}{1~block} imes \frac{1~block}{10~minutes} imes \frac{1~minute}{60~sec.} \approx$$

3 transactions per second

### VISA's transaction throughput

According to an IBM's studio performed in August of 2010:

#### Bitcoin's transaction throughput

Using previous information:

$$\frac{2.000~tx}{1~block} imes \frac{1~block}{10~minutes} imes \frac{1~minute}{60~sec.} \approx$$

3 transactions per second

### VISA's transaction throughput

According to an IBM's studio performed in August of 2010:

24.000 transactions per second

What can we do?

Several solutions have been proposed:

Several solutions have been proposed:

1 Increase block size: Bitcoin Unlimited (1 to 8 MB)

### Several solutions have been proposed:

- Increase block size: Bitcoin Unlimited (1 to 8 MB)
- Reduce transaction size: SegWit.co (do not store transaction signatures, also fixes malleability issues)

### Several solutions have been proposed:

- Increase block size: Bitcoin Unlimited (1 to 8 MB)
- Reduce transaction size: SegWit.co (do not store transaction signatures, also fixes malleability issues)
- Oecrease the demand of transactions: Payment channels

### Outline

- Introduction
  - What is Bitcoin
  - How does Bitcoin work?
  - The scalability problem
- Bitcoin & Smart Contracts
  - Transactions at low-level detail
  - Bitcoin's scripting language
  - What is a payment channel?
- Unidirectional payment channels
  - Scheme
  - Implementation
- 4 Bidirectional payment channels
  - Scheme
  - Implementation
  - Problem: channel reseting
- 5 The Bitcoin framework
- 6 Conclusions



#### Transaction fields

Fields of a transaction are:

• version

#### Transaction fields

Fields of a transaction are:

- version
- inputs

#### Transaction fields

Fields of a transaction are:

- version
- inputs
- outputs

#### Transaction fields

Fields of a transaction are:

- version
- inputs
- outputs
- locktime

#### Transaction fields

Fields of a transaction are:

- version
- inputs
- outputs
- locktime

### Basic Bitcoin transaction

version	inputs	outputs	locktime
version	Alice	Bob	locktime

### Extra "fields"

All transactions have an id (also called  $t \times ld$ ), that is the double SHA-256 hash of the transaction bytes

How are inputs and outputs specified?

### Input fields

#### Input fields

An input consists of the following fields:

• previousOutput\*: An output to be spent (combination of a txld and output number)

#### Input fields

- previousOutput\*: An output to be spent (combination of a txld and output number)
- 2 scriptSig: Script necessary to authorize the output spend

#### Input fields


- previousOutput\*: An output to be spent (combination of a txld and output number)
- 2 scriptSig: Script necessary to authorize the output spend
- **3** sequence: Number of the transaction in order to enable replacements

#### Input fields

- previousOutput\*: An output to be spent (combination of a txld and output number)
- 2 scriptSig: Script necessary to authorize the output spend
- **3** sequence: Number of the transaction in order to enable replacements

#### Input fields

- previousOutput\*: An output to be spent (combination of a txld and output number)
- 2 scriptSig: Script necessary to authorize the output spend
- **3 sequence**: Number of the transaction in order to enable replacements
- \* output must not be spent by any other transaction (also called UTXO)



### Output fields

## Output fields

An output consists of the following fields:

• value: number of currency units to be sent to the output

#### Output fields


- value: number of currency units to be sent to the output
- escriptPubKey: Script specificating the conditions for the output to be spent

#### Output fields

- value: number of currency units to be sent to the output
- escriptPubKey: Script specificating the conditions for the output to be spent

#### Output fields

- value: number of currency units to be sent to the output
- ScriptPubKey: Script specificating the conditions for the output to be spent



How do the scripts work?

## Bitcoin scripting language

Specificic scripting language for Bitcoin protocol (in transactions)

Simple

#### Bitcoin scripting language

Specificic scripting language for Bitcoin protocol (in transactions)

- Simple
- Stack-based (processed from left to right)

## Bitcoin scripting language

Specificic scripting language for Bitcoin protocol (in transactions)

- Simple
- Stack-based (processed from left to right)
- Purposefully not Turing-complete (with no loops)

## Bitcoin scripting language

Specificic scripting language for Bitcoin protocol (in transactions)

- Simple
- Stack-based (processed from left to right)
- Purposefully not Turing-complete (with no loops)

### Bitcoin scripting language

Specificic scripting language for Bitcoin protocol (in transactions)

- Simple
- Stack-based (processed from left to right)
- Purposefully not Turing-complete (with no loops)

## Technically

Sequentially read 1-byte opcodes that can perform arithmetical operations, store data into the stack, cryptographic operations and some logic and flow control operations

## Transactions and scripts

#### Transactions validity

In order for a transaction to be valid it must:

• Valid inputs: Inputs must refer to existing and non-spent outputs (UTXO)

## Transactions and scripts

#### Transactions validity

In order for a transaction to be valid it must:

- Valid inputs: Inputs must refer to existing and non-spent outputs (UTXO)
- 2 Valid amounts: Outputs' amounts must be less or equal to the inputs amounts

## Transactions and scripts

#### Transactions validity

In order for a transaction to be valid it must:

- Valid inputs: Inputs must refer to existing and non-spent outputs (UTXO)
- Valid amounts: Outputs' amounts must be less or equal to the inputs amounts
- Valid scripts: The input script followed by the output script referred by the input must execute successfully and leave a non-empty stack

# Standard scripts: P2PKH

## P2PKH: pay-to-public-key-hash

The output script (scriptPubKey) requires the input script (scriptSig) to specify a public key whose hash matches the specified and sign the spending transaction with that public key

# Standard scripts: P2PKH

#### P2PKH: pay-to-public-key-hash

The output script (*scriptPubKey*) requires the input script (*scriptSig*) to specify a public key whose hash matches the specified and sign the spending transaction with that public key

### P2PKH sample

scriptPubKey: OP\_DUP OP\_HASH160 <pubKeyHash>
 OP\_EQUALVERIFY OP\_CHECKSIG

# Standard scripts: P2PKH

## P2PKH: pay-to-public-key-hash

The output script (scriptPubKey) requires the input script (scriptSig) to specify a public key whose hash matches the specified and sign the spending transaction with that public key

### P2PKH sample

- scriptSig: <signature> <pubKey>
- scriptPubKey: OP\_DUP OP\_HASH160 <pubKeyHash> OP\_EQUALVERIFY OP\_CHECKSIG

# Standard scripts: P2SH

## P2SH: pay-to-script-hash

The output script (*scriptPubKey*) requires the input script (*scriptSig*) to specify a **redeem script** that succesfully executes and whose hash matches the specified one

# Standard scripts: P2SH

### P2SH: pay-to-script-hash

The output script (*scriptPubKey*) requires the input script (*scriptSig*) to specify a **redeem script** that successfully executes and whose hash matches the specified one

#### P2SH sample

scriptPubKey: OP\_HASH160 <redeemScript\_hash> OP\_EQUAL

# Standard scripts: P2SH

### P2SH: pay-to-script-hash

The output script (*scriptPubKey*) requires the input script (*scriptSig*) to specify a **redeem script** that successfully executes and whose hash matches the specified one

## P2SH sample

- scriptSig: [<data>] <redeemScript>
- scriptPubKey: OP\_HASH160 <redeemScript\_hash> OP\_EQUAL

## **Smart Contracts**

#### **Smart Contracts**

Computer protocols intended to facilitate, verify or enforce the negotiation or performance of a contract

## **Smart Contracts**

#### **Smart Contracts**

Computer protocols intended to facilitate, verify or enforce the negotiation or performance of a contract

#### Smart Contracts in Bitcoin

Creation of *redeemScripts* redeemable using P2SH script sets in transactions.

## Smart Contracts

#### **Smart Contracts**

Computer protocols intended to facilitate, verify or enforce the negotiation or performance of a contract

### Smart Contracts in Bitcoin

Creation of *redeemScripts* redeemable using P2SH script sets in transactions.

redeemScripts are Bitcoin's smart contracts

What can we do with Smart Contracts?

What can we do with Smart Contracts? Payment channels

# What is a Payment channel?

#### Payment channel

Set of techniques designed to allow users to make multiple Bitcoin transactions without committing all of them to the Bitcoin block chain

# What is a Payment channel?

## Payment channel

Set of techniques designed to allow users to make multiple Bitcoin transactions without committing all of them to the Bitcoin block chain

#### Off-chain transactions

Bitcoin transactions that are not committed to the Bitcoin blockchain but would be valid if they were committed

#### Scheme

#### Scheme

All payment channels follow a basic scheme:

**1** Funding: Some funds are locked so they can be moved with payments during the channel operation

#### Scheme

- Funding: Some funds are locked so they can be moved with payments during the channel operation
- ② Payment: Locked funds are moved to pay to a party of the channel

#### Scheme

- Funding: Some funds are locked so they can be moved with payments during the channel operation
- 2 Payment: Locked funds are moved to pay to a party of the channel
- **3** Closure: Funds are unlocked and returned to the channel parties with the final balance after all payments

#### Scheme

- Funding: Some funds are locked so they can be moved with payments during the channel operation
- 2 Payment: Locked funds are moved to pay to a party of the channel
- **3** Closure: Funds are unlocked and returned to the channel parties with the final balance after all payments

#### Scheme

All payment channels follow a basic scheme:

- Funding: Some funds are locked so they can be moved with payments during the channel operation
- Payment: Locked funds are moved to pay to a party of the channel
- Olosure: Funds are unlocked and returned to the channel parties with the final balance after all payments

#### Which transactions are off-chain?

All payment transactions are off-chain

## Outline

- Introduction
  - What is Bitcoin
  - How does Bitcoin work?
  - The scalability problem
- Bitcoin & Smart Contracts
  - Transactions at low-level detail
  - Bitcoin's scripting language
  - What is a payment channel?
- Unidirectional payment channels
  - Scheme
  - Implementation
- 4 Bidirectional payment channels
  - Scheme
  - Implementation
  - Problem: channel reseting
- 5 The Bitcoin framework
- 6 Conclusions



What does a unidirectional payment channel allows us to do?

## Unidirectional payment channel

#### What allows to do?

Incrementally pay amounts of funds from one party to another

## Unidirectional payment channel

#### What allows to do?

Incrementally pay amounts of funds from one party to another

#### For instance...

We will create a channel to allow **Alice** pay **Bob** incremental amounts of funds

#### What do we need to do?

#### What do we need to do?

Lock funds into the channel so:

**1** Both must authorize a payment:

#### What do we need to do?

- O Both must authorize a payment:
  - Alice must want to pay some amount to Bob (Bob can not pay hisself)

#### What do we need to do?

- O Both must authorize a payment:
  - Alice must want to pay some amount to Bob (Bob can not pay hisself)
  - Bob must authorize payments in order to check funds are send to him (and not to Alice)

#### What do we need to do?

- O Both must authorize a payment:
  - Alice must want to pay some amount to Bob (Bob can not pay hisself)
  - Bob must authorize payments in order to check funds are send to him (and not to Alice)
- 2 Refunds must be possible if a party does not cooperate

#### What do we need to do?

- O Both must authorize a payment:
  - Alice must want to pay some amount to Bob (Bob can not pay hisself)
  - Bob must authorize payments in order to check funds are send to him (and not to Alice)
- 2 Refunds must be possible if a party does not cooperate

#### What do we need to do?

Lock funds into the channel so:

- Both must authorize a payment:
  - Alice must want to pay some amount to Bob (Bob can not pay hisself)
  - Bob must authorize payments in order to check funds are send to him (and not to Alice)
- 2 Refunds must be possible if a party does not cooperate

#### How to refund

Lock the funds for an amount of time, so after that time (called the *channel expiry time*) the funds are given back to the funder

### Ways to lock funds

In order to accomplish both properties to lock funds, we can:

### Ways to lock funds

In order to accomplish both properties to lock funds, we can:

Create a funding transaction and a time-locked refund transaction

### Ways to lock funds

In order to accomplish both properties to lock funds, we can:

- Create a funding transaction and a time-locked refund transaction
- 2 Create a *smart* funding transaction with the time-lock integrated in the *smart* contract

#### What do we need to do?

#### What do we need to do?

In order to create a payment transaction, as both users must authorize payments:

• Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)

#### What do we need to do?

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him

#### What do we need to do?

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him
- If Alice wants to pay more, repeats the first step with more funds (spending the same funding transaction)

#### What do we need to do?

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him
- If Alice wants to pay more, repeats the first step with more funds (spending the same funding transaction)

#### What do we need to do?

In order to create a payment transaction, as both users must authorize payments:

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him
- If Alice wants to pay more, repeats the first step with more funds (spending the same funding transaction)

### Replace by economical incentive

Bob will keep the latest payment transaction and discard previous ones, as the last will be the one that pays more to him

### Closure

#### What do we need to do?

Two situations can appear when closing the channel:

• Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction is broadcasted, spending the funding transaction and closing the channel.

## Closure

#### What do we need to do?

Two situations can appear when closing the channel:

- Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction is broadcasted, spending the funding transaction and closing the channel.
- No cooperation: if Bob disappears, Alice will broadcast a refund transaction to recover the locked funds

# Locking the funds

### Ways to lock funds

In order to accomplish both properties to lock funds, we can:

- Create a funding transaction and a time-locked refund transaction
- 2 Create a *smart* funding transaction with the time-lock integrated in the *smart* contract

# Locking the funds


### Ways to lock funds


In order to accomplish both properties to lock funds, we can:

- Create a funding transaction and a time-locked refund transaction
- 2 Create a smart funding transaction with the time-lock integrated in the smart contract

### The implementation

With the BIP-65, an opcode appeared to create time-locked smart contracts, so we can create a *smart* funding transaction with the time lock integrated





#### Funding smart contract

As we said, we need to design a *redeemScript* in order to create a Bitcoin smart contract:

#### Funding smart contract

As we said, we need to design a *redeemScript* in order to create a Bitcoin smart contract:

```
OP_IF <time>
OP_CHECKLOCKTIMEVERIFY OP_DROP
<PubKeyAlice_1> OP_CHECKSIG
OP_ELSE
OP_2 <PubKeyAlice_2> <PubKeyBob> OP_2 OP_CHECKMULTISIG
OP_ENDIF
```

#### Funding smart contract

As we said, we need to design a *redeemScript* in order to create a Bitcoin smart contract:

OP\_2 <PubKeyAlice\_2> <PubKeyBob> OP\_2 OP\_CHECKMULTISIG OP\_ENDIF

## Technically...

As we are creating a P2SH, then the output script must be:

OP\_HASH160 <redeemScript\_hash> OP\_EQUAL



#### What do we need to do?

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him
- If Alice wants to pay more, repeats the first step with more funds (spending the same funding transaction)

#### What do we need to do?


In order to create a payment transaction, as both users must authorize payments:

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him
- If Alice wants to pay more, repeats the first step with more funds (spending the same funding transaction)

### The implementation

Alice creates a transaction that spends the funding transaction, with two outputs: one with some amount for Bob and the rest for herself

## Payment transaction



## Payment transaction

### Spending funding smart contract

We now need to spend the redeemScript

## Payment transaction

### Spending funding smart contract

We now need to spend the redeemScript

### Technically...

As we are spending a P2SH, then the input script must be:

#### What do we need to do?

Two situations can appear when closing the channel:

• Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction is broadcasted, spending the funding transaction and closing the channel.

#### What do we need to do?

Two situations can appear when closing the channel:

- Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction is broadcasted, spending the funding transaction and closing the channel.
- 2 No cooperation: if Bob disappears, Alice will broadcast a refund transaction to recover the locked funds

#### What do we need to do?

Two situations can appear when closing the channel:

- Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction is broadcasted, spending the funding transaction and closing the channel.
- 2 No cooperation: if Bob disappears, Alice will broadcast a refund transaction to recover the locked funds


#### What do we need to do?

Two situations can appear when closing the channel:

- Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction is broadcasted, spending the funding transaction and closing the channel.
- No cooperation: if Bob disappears, Alice will broadcast a refund transaction to recover the locked funds

#### Graceful closure

Bob simply broadcasts the latest payment transaction once signed and before channel expiry time



### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time

### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time

### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time


#### Technically...

As we are spending a P2SH, then the input script must be:

What if we want Bob to pay Alice too?

### Outline

- Introduction
  - What is Bitcoin
  - How does Bitcoin work?
  - The scalability problem
- Bitcoin & Smart Contracts
  - Transactions at low-level detail
  - Bitcoin's scripting language
  - What is a payment channel?
- Unidirectional payment channels
  - Scheme
  - Implementation
- 4 Bidirectional payment channels
  - Scheme
  - Implementation
  - Problem: channel reseting
- The Bitcoin framework
- 6 Conclusions



# Bidirectional payment channel

#### What allows to do?

Incrementally pay amounts of funds from one party to another and viceversa

# Bidirectional payment channel

#### What allows to do?

Incrementally pay amounts of funds from one party to another and viceversa

#### For instance...

We will create a channel to allow **Alice** pay **Bob** incremental amounts of funds **and viceversa** 

# Bidirectional payment channels' scheme

#### Source

#### Obtained from

A Fast and Scalable Payment Network with Bitcoin Duplex Micropayment Channels - Christian Decker & Roger Wattenhofer

# Bidirectional payment channels' scheme

#### Source

Obtained from

A Fast and Scalable Payment Network with Bitcoin Duplex Micropayment Channels - Christian Decker & Roger Wattenhofer

#### Idea

Use two unidirectional channels, one in each way with an invalidation tree to perform resets

# Locking the funds

### Ways to lock funds

In order to accomplish both properties to lock funds, we can:

- Create a funding transaction and a time-locked refund transaction
- 2 Create a *smart* funding transaction with the time-lock integrated in the *smart* contract

# Locking the funds


#### Ways to lock funds

In order to accomplish both properties to lock funds, we can:

- Create a funding transaction and a time-locked refund transaction
- 2 Create a *smart* funding transaction with the time-lock integrated in the *smart* contract

### The implementation

We can still use BIP-65 to create a time-locking smart contract



### Funding smart contract

Same as unidirectional channel, but with two outputs

#### Funding smart contract

Same as unidirectional channel, but with two outputs

### Alice to Bob output

```
OP_IF <time> OP_CHECKLOCKTIMEVERIFY OP_DROP <PubKeyAlice_1> OP_CHECKSIG OP_ELSE OP_2 <PubKeyAlice_2> <PubKeyBob_1> OP_2 OP_CHECKMULTISIG OP_ENDIF
```

#### Funding smart contract

Same as unidirectional channel, but with two outputs

- Alice to Bob output
  - OP\_IF <time> OP\_CHECKLOCKTIMEVERIFY OP\_DROP <PubKeyAlice\_1> OP\_CHECKSIG OP\_ELSE OP\_2 <PubKeyAlice\_2> <PubKeyBob\_1> OP\_2 OP\_CHECKMULTISIG OP\_ENDIF
- Bob to Alice output

```
OP_IF <time> OP_CHECKLOCKTIMEVERIFY OP_DROP
<PubKeyBob_2> OP_CHECKSIG OP_ELSE OP_2 <PubKeyAlice_3>
<PubKeyBob_3> OP_2 OP_CHECKMULTISIG OP_ENDIF
```

#### Funding smart contract

Same as unidirectional channel, but with two outputs

- Alice to Bob output
  - OP\_IF <time> OP\_CHECKLOCKTIMEVERIFY OP\_DROP <PubKeyAlice\_1> OP\_CHECKSIG OP\_ELSE OP\_2 <PubKeyAlice\_2> <PubKeyBob\_1> OP\_2 OP\_CHECKMULTISIG OP\_ENDIF
- Bob to Alice output

```
OP_IF <time> OP_CHECKLOCKTIMEVERIFY OP_DROP
<PubKeyBob_2> OP_CHECKSIG OP_ELSE OP_2 <PubKeyAlice_3>
<PubKeyBob_3> OP_2 OP_CHECKMULTISIG OP_ENDIF
```

#### Funding smart contract

Same as unidirectional channel, but with two outputs

### Alice to Bob output

```
OP_IF <time> OP_CHECKLOCKTIMEVERIFY OP_DROP <PubKeyAlice_1> OP_CHECKSIG OP_ELSE OP_2 <PubKeyAlice_2> <PubKeyBob_1> OP_2 OP_CHECKMULTISIG OP_ENDIF
```

### Bob to Alice output

```
OP_IF <time> OP_CHECKLOCKTIMEVERIFY OP_DROP <PubKeyBob_2> OP_CHECKSIG OP_ELSE OP_2 <PubKeyAlice_3> <PubKeyBob_3> OP_2 OP_CHECKMULTISIG OP_ENDIF
```

### Technically...

As we are creating a P2SH, then the outputs' script must be:

```
OP_HASH160 <redeemScript_hash> OP_EQUAL
```

# Paying funds

#### What do we need to do?

In order to create a payment transaction, as both users must authorize payments:

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him
- If Alice wants to pay more, repeats the first step with more funds (spending the same funding transaction)

# Paying funds


#### What do we need to do?

In order to create a payment transaction, as both users must authorize payments:

- Alice creates and signs a transaction paying some of the locked funds to Bob (and the rest to Alice as return)
- 2 Bob stores the partially signed transaction that pays some amount of money to him
- If Alice wants to pay more, repeats the first step with more funds (spending the same funding transaction)

### The implementation

Same of a unidirectional payment channel, but Bob can pay Alice too using his channel



### Spending funding smart contract

We now need to spend the redeemScript

### Spending funding smart contract

We now need to spend the redeemScript

• Alice to Bob output
• OP\_0 <sig\_Alice> <sig\_Bob> OP\_0

### Technically...

As we are spending a P2SH, then the input script must be:

OP\_0 <sig\_Alice> <sig\_Bob> OP\_0 <redeemScript>

### Spending funding smart contract

We now need to spend the redeemScript

- Alice to Bob output
   OP\_0 <sig\_Alice> <sig\_Bob> OP\_0
- ② Bob to Alice output
  OP\_0 <sig\_Alice> <sig\_Bob> OP\_0

### Technically...

As we are spending a P2SH, then the input script must be:

OP\_O <sig\_Alice> <sig\_Bob> OP\_O <redeemScript>

#### What do we need to do?

Two situations can appear when closing the channel:

- Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction of each output is broadcasted, spending the funding transaction and closing the channel.
- No cooperation: if any of the parties do not cooperate, they can broadcast a refund transaction to recover their locked funds


#### What do we need to do?

Two situations can appear when closing the channel:

- Graceful closure: the channel has been operated and the expiry time is close, so latest payment transaction of each output is broadcasted, spending the funding transaction and closing the channel.
- No cooperation: if any of the parties do not cooperate, they can broadcast a refund transaction to recover their locked funds

### Graceful closure

Alice and Bob simply broadcast the latest payment transaction once signed and before channel expiry time



### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time

### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time

• Alice to Bob output refund <sig\_Alice> OP\_1

### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time

- Alice to Bob output refund <sig\_Alice> OP\_1
- Bob to Alice output refund <sig\_Bob> OP\_1

### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time

- Alice to Bob output refund <sig\_Alice> OP\_1
- Bob to Alice output refund <sig\_Bob> OP\_1

### Spending funding smart contract (refund)

We now need to spend the redeemScript after the lock time

- Alice to Bob output refund <sig\_Alice> OP\_1
- ② Bob to Alice output refund
  <sig\_Bob> OP\_1

### Technically...


As we are spending a P2SH, then the input script must be:

What if one of the payment channels gets exhausted?

What if one of the payment channels gets exhausted?

# Channel resetting

### Channel resetting



# Channel resetting

### Channels are exhausted

Both parties own the same amount of funds as at the beginning of the channel but their respective payment channels have been exhausted. No more incremental payments can be performed

# Resetting by invalidation trees

#### Invalidation tree

Tree of transactions that use the timelock field to invalidate old branches of the tree and be able to create new ones with an updated status of the balances

# Resetting by invalidation trees


#### Invalidation tree

Tree of transactions that use the timelock field to invalidate old branches of the tree and be able to create new ones with an updated status of the balances


## Replace by timelock

Create timelocked transactions so that when using timelocks nearer to the present invalidate transactions with later timelocks


# An invalidation tree reset example



# An invalidation tree reset example



# An invalidation tree reset example



## Basic duplex channel vs Resetable duplex channel

• More complex to use BIP-65\*: As the tree requires linking P2SH single outputs, using BIP-65 to create a timelock contract is more complex to implement

## Basic duplex channel vs Resetable duplex channel

• More complex to use BIP-65\*: As the tree requires linking P2SH single outputs, using BIP-65 to create a timelock contract is more complex to implement

## Basic duplex channel vs Resetable duplex channel

• More complex to use BIP-65\*: As the tree requires linking P2SH single outputs, using BIP-65 to create a timelock contract is more complex to implement \*this would require to generate two outputs and inputs in each first tree node with all data required

4□ > 4□ > 4 = > 4 = > = 9 < ○</p>

# Basic duplex channel vs Resetable duplex channel

- More complex to use BIP-65\*: As the tree requires linking P2SH single outputs, using BIP-65 to create a timelock contract is more complex to implement \*this would require to generate two outputs and inputs in each first tree node with all data required
- More transactions needed: in order to create the tree (be careful with signing order of all parties to prevent attacks)

# Basic duplex channel vs Resetable duplex channel

- More complex to use BIP-65\*: As the tree requires linking P2SH single outputs, using BIP-65 to create a timelock contract is more complex to implement \*this would require to generate two outputs and inputs in each first tree node with all data required
- More transactions needed: in order to create the tree (be careful with signing order of all parties to prevent attacks)
- Reduced expiry time: each tree branch reduces the channel's effective expiry time

#### Pros

• **Simple to create**: no complex transactions needed, unlike the *Lightning Network* smart contracts

#### Pros

- **Simple to create**: no complex transactions needed, unlike the *Lightning Network* smart contracts
- No extra data exchange: unlike the Lightning Network, the protocol does not require to exchange secrets or additional data

#### Pros

- **Simple to create**: no complex transactions needed, unlike the *Lightning Network* smart contracts
- No extra data exchange: unlike the Lightning Network, the protocol does not require to exchange secrets or additional data

#### Pros

- **Simple to create**: no complex transactions needed, unlike the *Lightning Network* smart contracts
- No extra data exchange: unlike the Lightning Network, the protocol does not require to exchange secrets or additional data

#### Cons

 Reducing expiry time: the more resets needed, the more the effective expiry time is reduced (more invalidating branches and leafs)

#### Pros

- **Simple to create**: no complex transactions needed, unlike the *Lightning Network* smart contracts
- No extra data exchange: unlike the Lightning Network, the protocol does not require to exchange secrets or additional data

#### Cons

- Reducing expiry time: the more resets needed, the more the effective expiry time is reduced (more invalidating branches and leafs)
- Need to store more transactions: in other solutions for duplex payment channel, like the *Lightning Network*, just the latest payment transaction must be saved, and not an entire tree.

# Outline

- Introduction
  - What is Bitcoin
  - How does Bitcoin work?
  - The scalability problem
- Bitcoin & Smart Contracts
  - Transactions at low-level detail
  - Bitcoin's scripting language
  - What is a payment channel?
- Unidirectional payment channels
  - Scheme
  - Implementation
- 4 Bidirectional payment channels
  - Scheme
  - Implementation
  - Problem: channel reseting
- 5 The Bitcoin framework
- 6 Conclusions



# Developing problems

# Problems when implementing the channel

• Lack of documentation: Bitcoin is missing from good quality, low-level protocol implementation details. Most accurate information is spread around Q&A sites, *Bitcoin Wiki* and *Bitcoin Core's client* C++ code

# Developing problems

# Problems when implementing the channel

- Lack of documentation: Bitcoin is missing from good quality, low-level protocol implementation details. Most accurate information is spread around Q&A sites, Bitcoin Wiki and Bitcoin Core's client C++ code
- Lack of low-level, documented libraries: There are very few libraries that handle the Bitcoin protocol complexities (no library found to create raw transaction signatures with a customized transaction)

#### Solution: our own Bitcoin framework

All what we\* learned was implemented in our own Bitcoin framework that has:

• Designed for ease of use: Design & Software design patterns

#### Solution: our own Bitcoin framework

All what we\* learned was implemented in our own Bitcoin framework that has:

- Designed for ease of use: Design & Software design patterns
- OOP and puzzle-friendliness principles: Modulable and serializable / deserializable patterns

\*developed along Carlos González Cebrecos

#### Solution: our own Bitcoin framework

All what we\* learned was implemented in our own Bitcoin framework that has:

- Designed for ease of use: Design & Software design patterns
- OOP and puzzle-friendliness principles: Modulable and serializable / deserializable patterns
- Extensive documentation: Every method is well documented

\*developed along Carlos González Cebrecos

#### Solution: our own Bitcoin framework

All what we\* learned was implemented in our own Bitcoin framework that has:

- Designed for ease of use: Design & Software design patterns
- OOP and puzzle-friendliness principles: Modulable and serializable / deserializable patterns
- Extensive documentation: Every method is well documented
- Extensively tested: All code has been tested with other libraries & Bitcoin Core client

<sup>\*</sup>developed along Carlos González Cebrecos

#### Fork of the Bitcoin framework

The channel was implemented in a script after forking the framework and can be operated from the CLI passing the required parameters (funds amount, pub/priv keys, previous inputs, ...)

#### Fork of the Bitcoin framework

The channel was implemented in a script after forking the framework and can be operated from the CLI passing the required parameters (funds amount, pub/priv keys, previous inputs, ...)

#### Channel lacks ease of use

Because focused on the **channel protocol's design to enhace security**, no time was missing to automate the operatibility of the channel:

• Bitcoin Core RPC: to automate transaction broadcasting, UTXO detection, balance detection, fee calculation, ...

#### Fork of the Bitcoin framework

The channel was implemented in a script after forking the framework and can be operated from the CLI passing the required parameters (funds amount, pub/priv keys, previous inputs, ...)

#### Channel lacks ease of use

Because focused on the **channel protocol's design to enhace security**, no time was missing to automate the operatibility of the channel:

- Bitcoin Core RPC: to automate transaction broadcasting, UTXO detection, balance detection, fee calculation, ...
- Channel state storage: automatically store in the user's computer the state of the channel

## Fork of the Bitcoin framework

The channel was implemented in a script after forking the framework and can be operated from the CLI passing the required parameters (funds amount, pub/priv keys, previous inputs, ...)

#### Channel lacks ease of use

Because focused on the **channel protocol's design to enhace security**, no time was missing to automate the operatibility of the channel:

- Bitcoin Core RPC: to automate transaction broadcasting, UTXO detection, balance detection, fee calculation, ...
- Channel state storage: automatically store in the user's computer the state of the channel
- **Graphical UI:** enable every Bitcoin user enjoy the payment channels' potential

# Outline

- Introduction
  - What is Bitcoin
  - How does Bitcoin work?
  - The scalability problem
- Bitcoin & Smart Contracts
  - Transactions at low-level detail
  - Bitcoin's scripting language
  - What is a payment channel?
- Unidirectional payment channels
  - Scheme
  - Implementation
- 4 Bidirectional payment channels
  - Scheme
  - Implementation
  - Problem: channel reseting
- 5 The Bitcoin framework
- 6 Conclusions



## Along this project, I've learned:

 Low-level understanding of the Bitcoin protocol: By learning how to implement Smart Contracts on Bitcoin and creating the framework to ease those smart contracts creation

## Along this project, I've learned:

- Low-level understanding of the Bitcoin protocol: By learning how to implement Smart Contracts on Bitcoin and creating the framework to ease those smart contracts creation
- Bitcoin lacks of low-level extensive documentation:
   Developing in Bitcoin has no formal, low-level detailed guide and most advanced features can just be learned by inspecting the Bitcoin Core C++ code

## Along this project, I've learned:

- Low-level understanding of the Bitcoin protocol: By learning how to implement Smart Contracts on Bitcoin and creating the framework to ease those smart contracts creation
- Bitcoin lacks of low-level extensive documentation:
   Developing in Bitcoin has no formal, low-level detailed guide and most advanced features can just be learned by inspecting the Bitcoin Core C++ code
- Payment Channels are the future of Bitcoin: Maybe
   Lightning Network has a better structure and protocol
   implementation, but what is crystal clear is that multi-hop
   duplex payment channels are the Bitcoin's future after
   SegWit.co activates in the mainnet allowing a secure
   implementation of them.

# Thanks for your time and attention

# Thanks for your time and attention

Q&A round

## For more information

## The project work compilation

Documentation:

https://davidlj95.com/smart-payment-channel Code:

https://github.com/davidlj95/smart-payment-channel

## For more information

## The project work compilation

Documentation:

https://davidlj95.com/smart-payment-channel

https://github.com/davidlj95/smart-payment-channel

#### The Bitcoin framework

https://github.com/uab-projects/btc-payment-channels

## For more information

## The project work compilation

Documentation:

https://davidlj95.com/smart-payment-channel

https://github.com/davidlj95/smart-payment-channel

#### The Bitcoin framework

https://github.com/uab-projects/btc-payment-channels Test it!:

pip install bitcoin-framework