FLAGSHIP RESEARCH PROPOSAL PORTFOLIO & PUBLICATION GRADE

ResistoDiff-3D

A Multi-Scale Structural Physics & Geometric Deep Learning Framework for Predicting Antimicrobial Resistance Mutational Escape Trajectories and De Novo Counter-Inhibitor Design

Principal Investigator: Vishal B (SASTRA University)

Target Vectors: AMR, Structural Bio, Generative AI

Document Ref: RD3D-2026-SPEC-V1

1. Project Overview & Identity

Official Title: `ResistoDiff-3D: An Integrated SE(3)-Equivariant Graph Diffusion and Protein Language Framework for Simulating Epistatic Mutational Escape and Co-Designing Allosteric AMR Counter-Inhibitors`

Codename: `Project ResistoDiff / ResistoEngine`

Core Mission: To transition drug discovery from a *reactive chemical patching paradigm* into a *proactive co-evolutionary computational workflow* that anticipates bacterial mutational escape trajectories before clinical deployment.

2. Problem Statement & Mathematical Formulation

Antimicrobial Resistance (AMR) is projected to cause 10 million deaths annually by 2050. Current antibiotic development operates on a reactive linear model: a target enzyme is identified, a small-molecule inhibitor is synthesized, the compound enters clinical use, and bacterial target mutations render the drug ineffective within years.

The Three Foundational Technical Bottlenecks

1. **High-Dimensional Epistatic Escape Landscapes:** Single-point mutation predictors (ΔΔG) fail because resistance often emerges via multi-site epistatic networks—where secondary mutations compensate for catalytic penalties incurred by primary resistance mutations.
2. **Loss of Active-Site Competitive Affinity:** Competitive inhibitors become ineffective when target active sites mutate to induce steric hindrance while retaining catalytic activity for natural substrates (e.g., TEM-1 → KPC-2/NDM-1 β-lactamases).
3. **Static Structural Assumptions:** AlphaFold and ESMFold model ground-state static structures, ignoring dynamic conformational ensembles and transient allosteric pockets that open during catalytic cycles.

3. Existing Solutions & Comparative Matrix

Platform / Tool	Primary Methodology	Key Strengths	Critical Limitations & Research Gaps
AlphaFold 3 / **ESMFold**	Multi-chain Transformer / Single-sequence PLM	Unprecedented static 3D structure prediction accuracy.	Cannot model evolutionary mutational escape trajectories or predict dynamic ensembles under drug selection pressure.
RFdiffusion / **AntiFold**	SE(3) Equivariant Diffusion for Protein Backbones	High success rate in designing novel protein binders.	Unaware of bacterial fitness landscapes; cannot co-design small molecules/peptides against dynamic allosteric pockets.
FoldX 5 / **Rosetta**	Empirical force fields & rotamer optimization	Gold standard physical baseline for single point ΔΔG.	Extreme computational complexity; scales poorly ($O(N^2)$); fails to capture multi-site epistatic interaction networks.
DiffDock / **TxGNN**	Score-based ligand docking / Knowledge Graphs	Rapid docking & target interaction mapping.	Assumes rigid/static binding pockets; fails when point mutations alter active site geometry or loop dynamics.

4. Proposed Innovations & Mathematical Core

`ResistoDiff-3D` unifies evolutionary sequence modeling, dynamic structural physics, and geometric generative AI into three pipeline modules:

Module 1: Structural Epistatic Fitness Engine (SEFE)

Simulates bacterial mutational escape paths using Monte Carlo Tree Search (MCTS) guided by a multi-objective structural fitness function $F(x, S)$:

$$F(x, S) = w_1 \cdot \Delta\Delta G_{fold}(x) + w_2 \cdot \Delta\Delta G_{catalysis}(x, S_{native}) - w_3 \cdot \Delta\Delta G_{binding}(x, I_{current}) + w_4 \cdot H_{coevol}(x)$$

Where x is the mutant sequence, S_{native} is the natural substrate, $I_{current}$ is the active inhibitor, and H_{coevol} represents evolutionary co-coupling constraints derived from Evolutionary Direct Coupling Analysis (DCA) and ESM-3 pseudo-log-likelihood ratios.

Module 2: Dynamic Allosteric Cryptic Pocket Miner (DAPM)

Integrates coarse-grained Molecular Dynamics (OpenMM) with Equivariant Graph Neural Networks (EGNNs) to map evolutionarily conserved, functionally essential hinge regions that open into "cryptic pockets" under dynamic motion, avoiding the high-mutation active site.


Module 3: Allosteric SE(3)-Equivariant Counter-Inhibitor Diffuser (A-SE3Diff)

A continuous score-based generative diffusion model operating directly in 3D Euclidean space $E(3)$. Conditioned on the geometric point cloud of the identified cryptic allosteric pocket, A-SE3Diff solves the reverse SDE:

$$dx_t = f(x_t, t)dt + g(t)dw_t$$

Generating 3D atomic coordinates $x \in \mathbb{R}^{N \times 3}$ and discrete atom types $h \in \mathbb{R}^{N \times K}$ simultaneously inside the moving target protein.

5. System Architecture



6. Deep AI & Algorithmic Components

- **Protein Language Models (ESM-2 / ESM-3):** Extract sequence-level zero-shot mutation effect predictions via log-likelihood ratios:

  $$\Delta score(x_i \rightarrow y_i) = log\ P(x_i = y_i \mid x_{\setminus i}) - log\ P(x_i = x_i^{wt} \mid x_{\setminus i})$$

- **E(n)-Equivariant Graph Neural Networks (EGNNs):** Guarantee rotational and translational equivariance over 3D protein atomic positions while performing message passing.
- **Monte Carlo Tree Search (MCTS):** Traverses the high-dimensional mutational tree (20^N) where nodes represent target protein variants and actions represent single amino acid substitutions.

7. Biological Focus Systems

1. **Class A β-Lactamases (TEM-1, KPC-2):** Active-site Ser70 attack; single/double mutations (e.g., Gly238S) expand active pocket to hydrolyze 3rd-gen carbapenems.
2. **Metallo-β-Lactamases (NDM-1, VIM-2):** Dual Zinc active sites; resistant to classic serine inhibitors. Target: conservative inter-domain hinge loops (Loop 3 / Loop 10).
3. **DNA Gyrase (GyrA / ParC):** Quinolone Resistance-Determining Region (QRDR) mutations disrupt water-mediated magnesium bridges. Target: GyrA-DNA interface allosteric pockets.

8. Technology Stack Summary

Category	Selected Technologies & Frameworks
Languages	Python 3.11+ (Core ML), C++20 (CUDA kernels), Rust (High-speed parsing), TypeScript (Frontend)
AI / ML Frameworks	PyTorch 2.3+, PyTorch Geometric (PyG), Hugging Face Transformers, OpenMM
Cheminformatics	RDKit, BioPython, Open Babel, MDAnalysis, AutoDock Vina/GPU, ESMFold CLI
Databases & Cloud	PostgreSQL with `pgvector`, Neo4j, Redis, MinIO, Docker, Ray Cluster, Nextflow

9. Datasets & Preprocessing Pipelines

- **CARD (Comprehensive Antibiotic Resistance Database):** Mapped for curated AMR mutant gene sequences and resistance ontology profiles.
- **MaveDB:** Deep Mutational Scanning (DMS) datasets providing empirical fitness and functional score labels.
- **PDBbind / ChEMBL:** Mapped protein-ligand crystal complexes used for initial EGNN geometric pre-training.

10. Multi-Phase Development Roadmap

Phase	Title & Scope	Key Deliverables
Phase 1	MVP Benchmark Pipeline (Months 1–4)	FoldX/ESM-2 baseline mutation scorer; CARD parser; PyG EGNN baseline.
Phase 2	SEFE Engine Development (Months 5–8)	MCTS sequence-structure trajectory search; integration with MaveDB TEM-1 benchmark.
Phase 3	Allosteric Pocket & Diffusion (Months 9–14)	OpenMM dynamic ensemble generator; SE(3) continuous ligand diffusion model.
Phase 4	Validation & Publication (Months 15–20)	AutoDock GPU + Free Energy Perturbation (FEP) validation; write paper & release AMR-Bench.
Phase 5	Platform & Scale (Months 21–24)	Mol* Web dashboard; cloud execution engine; academic wet-lab collaboration.

11. Curriculum & Learning Roadmap

Core Competency Matrix for Mastery

- **Math Foundations:** Group Theory, Lie Groups, SE(3) Transformations, Stochastic Differential Equations (SDEs).
- **Geometric DL:** Equivariant Neural Networks (EGNN/SE(3)-Transformer), Continuous Diffusion Models.
- **Structural Bio & Physics:** Force Fields (AMBER/CHARMM), Statistical Mechanics, Free Energy Perturbation (ΔΔG).
- **Key Papers:** Satorras et al. (EGNN, ICML), Hoogeboom et al. (EDM, NeurIPS), Marks et al. (Protein Coevolution, Nature Reviews).

12. Comprehensive Risk Analysis & Mitigation Matrix

Risk Domain	Potential Failure Mode	Mitigation Strategy
Computational Cost	MCTS + MD trajectory generation too slow.	Use coarse-grained MD (Martini forcefield) & train GNN surrogate flexibility models.
Data Bias	Structural PDB data skewed to static active sites.	Apply Boltzmann-weighted ensemble sampling over dynamic MD trajectories.
Generative Validity	Diffusion produces synthesizably impossible molecules.	Enforce automated RDKit synthetic accessibility filters (SA Score < 4.5, Lipinski Rules).
Biosecurity (DURC)	Escape prediction misused to engineer pathogens.	Incorporate explicit safety filters; restrict model scope to non-pathogenicity research vectors.

13. Portfolio & Career Impact Strategy

- **For MSc / PhD Applications (Europe/US):** Establishes elite positioning for institutions like Cambridge, ETH Zurich, TU Munich, Uppsala, or Karolinska by proving mastery over Geometric Deep Learning and Structural Biology.
- **For Industry R&D (Isomorphic Labs, DeepMind, Flagship Pioneering):** Directly addresses major industrial drug discovery bottlenecks (flexibility and drug resistance), showcasing production-level engineering.

14. Commercial & Publication Vision

Target Venues: NeurIPS (AI for Science), ICLR, ISMB, *Nature Machine Intelligence*.
Commercial Vehicle: "Resisto-Therapeutics" SaaS platform for pharmaceutical R&D, providing pre-synthesis resistance trajectory screening to prevent multi-million-dollar clinical trial drug failure.

15. Foundational Python Codebase Implementation

Below is the production-grade foundational backbone for the SE(3)-Equivariant Graph Neural Network Layer (`resistodiff/models/egnn.py`):

```
import torch
import torch.nn as nn
from typing import Tuple, Optional

class EGNNMessagePassingLayer(nn.Module):
    def __init__(self, node_feat_dim: int, edge_feat_dim: int, hidden_dim: int):
        super(EGNNMessagePassingLayer, self).__init__()
        self.node_feat_dim = node_feat_dim
        self.edge_feat_dim = edge_feat_dim
        self.hidden_dim = hidden_dim

        # Edge MLP: inputs node_i, node_j, distance^2, edge_attr
        self.edge_mlp = nn.Sequential(
            nn.Linear(node_feat_dim * 2 + 1 + edge_feat_dim, hidden_dim),
            nn.SiLU(),
            nn.Linear(hidden_dim, hidden_dim),
            nn.SiLU()
        )

        # Coordinate MLP
        self.coord_mlp = nn.Sequential(
            nn.Linear(hidden_dim, hidden_dim),
            nn.SiLU(),
            nn.Linear(hidden_dim, 1, bias=False)
        )

        # Node MLP
        self.node_mlp = nn.Sequential(
            nn.Linear(node_feat_dim + hidden_dim, hidden_dim),
            nn.SiLU(),
            nn.Linear(hidden_dim, node_feat_dim)
        )

    def forward(
        self,
        h: torch.Tensor,
        x: torch.Tensor,
        edge_index: torch.Tensor,
        edge_attr: Optional[torch.Tensor] = None
    ) -> Tuple[torch.Tensor, torch.Tensor]:
        row, col = edge_index[0], edge_index[1]

        # Pairwise distance squared (SE(3) invariant)
        coord_diff = x[row] - x[col]
        radial = torch.sum(coord_diff ** 2, dim=-1, keepdim=True)

        if edge_attr is not None:
            edge_inputs = torch.cat([h[row], h[col], radial, edge_attr], dim=-1)
        else:
            edge_inputs = torch.cat([h[row], h[col], radial], dim=-1)

        msg_edge = self.edge_mlp(edge_inputs)

        # Update 3D Coordinates (Equivariant transformation)
        coord_matrix = coord_diff * self.coord_mlp(msg_edge)
        coord_update = torch.zeros_like(x)
        coord_update.index_add_(0, row, coord_matrix)
        x_updated = x + coord_update

        # Aggregate node messages
        msg_agg = torch.zeros(h.size(0), self.hidden_dim, device=h.device)
        msg_agg.index_add_(0, row, msg_edge)

        # Update Node Features (Invariant transformation)
```

```
        node_inputs = torch.cat([h, msg_agg], dim=-1)
        h_updated = self.node_mlp(node_inputs) + h  # Residual connection

        return h_updated, x_updated

class ResistoEGNNEncoder(nn.Module):
    def __init__(self, in_node_dim: int, hidden_dim: int, num_layers: int = 4):
        super(ResistoEGNNEncoder, self).__init__()
        self.embedding = nn.Linear(in_node_dim, hidden_dim)
        self.layers = nn.ModuleList([
            EGNNMessagePassingLayer(node_feat_dim=hidden_dim, edge_feat_dim=0,
hidden_dim=hidden_dim)
            for _ in range(num_layers)
        ])

    def forward(self, h: torch.Tensor, x: torch.Tensor, edge_index: torch.Tensor) ->
Tuple[torch.Tensor, torch.Tensor]:
        h = self.embedding(h)
        for layer in self.layers:
            h, x = layer(h, x, edge_index)
        return h, x
```

16. Personalization & Resource Strategy (Vishal B Alignment)

Operational Execution Plan Tailored for Vishal B

- **SASTRA Academic Synergy:** Leverage wet-lab knowledge of bacterial targets (*E. coli*, *K. pneumoniae*) to ground biological features while building computational modules.
- **Hardware Execution Strategy:**
  - *Local WSL2 / RTX Environment:* Data parsing, ESM-2 inference, PyG structural graph generation, and unit tests.
  - *Cloud / Cluster Allocation:* Run ESM-3 embeddings, full OpenMM trajectories, and continuous diffusion training on Google Colab / GPU clusters.
- **3-Year Growth Vector:** B.Sc. 3rd Year (Phase 1/2 MVP) → M.Sc. in Europe (Phase 3/4 Publication) → PhD/Venture Initiation (Phase 5 Platform Scale).