

Aim:

Write code to calculate **roots** of a **quadratic equation**.

Write a class `QuadraticRoots` with `main` method. The method receives three arguments, write code to parse them into `double` type.

For example:

if the values 2, 5, 3 are passed as arguments, then the output should be **First root is : -1.0 Second root is : -1.5**
If the values 3, 2, 1 are passed then the output should be **Roots are imaginary**
Similarly, if the values 2, 4, 2 are passed then the output should be **Roots are equal and value is : -1.0**

Note: Make sure to use the `print()` and not the `println()` method.

Note: Please don't change the package name.

Source Code:

`q10851/QuadraticRoots.java`

```
package q10851;
class QuadraticRoots
{
    double a,b,c;
    void getData(String c1,String c2,String c3)
    {
        a=Double.valueOf(c1);
        b=Double.valueOf(c2);
        c=Double.valueOf(c3);
    }
    void roots()
    {
        double d;
        if(a==0)
        {
            double root;
            root=-c/b;
            System.out.print("linear equation "+root);
        }
        else{
            d=(b*b)-(4*a*c);
            if(d==0){double root=-b/(2*a);
                System.out.println("Roots are equal and value is : "+root);
            }
        }
        else if(d>0)
        {
            double r1,r2;
            r1=(-b+Math.sqrt(d))/(2*a);
            r2=(-b-Math.sqrt(d))/(2*a);
        }
    }
}
```

```

}
else
    System.out.print("Roots are imaginary");
}
}
public static void main(String a[])
{
    QuadraticRoots r=new QuadraticRoots();
    r.getData(a[0],a[1],a[2]);
    r.roots();
}
}

```

Execution Results - All test cases have succeeded!

| Test Case - 1 |
|--|
| User Output |
| First root is : -0.6047152924789525 Second root is : -1.3952847075210475 |

| Test Case - 2 |
|-------------------------------------|
| User Output |
| Roots are equal and value is : -1.0 |

| Test Case - 3 |
|---------------------|
| User Output |
| Roots are imaginary |