

**Aim:**

The `addNodes()` function creates a new list and adds elements to the list until delimiter `-1` is occurred.

Fill in the missing code in the below functions `addNodes(NODE first, int x)` and `traverseList(NODE first)` in the file `CreateAndAddNodes.c`.

**Source Code:**SingleLL1.c

```
#include<stdio.h>
#include<stdlib.h>

#include "CreateAndAddNodes.c"

void main() {
    NODE first = NULL;
    int x;
    printf("Enter elements up to -1 : ");
    scanf("%d", &x);
    while (x != -1) {
        first = addNodes(first, x);
        scanf("%d", &x);
    }
    if (first == NULL) {
        printf("Single Linked List is empty\n");
    } else {
        printf("The elements in SLL are : ");
        traverseList(first);
    }
}
```

CreateAndAddNodes.c

```
struct node {
    int data;
    struct node *next;
};
typedef struct node *NODE;
NODE first = NULL;
NODE createNode() {
    NODE temp;
    temp = (NODE)malloc(sizeof(struct node));
    temp -> next = NULL;
    return temp;
}

NODE addNodes(NODE first, int x) {
    NODE temp;
    temp = createNode();
    temp -> data = x;
    if(first == NULL){
```

```

        first = temp;
    } else {
        NODE lastNode = first;
        while(lastNode -> next != NULL){
            lastNode = lastNode -> next;
        }
        lastNode -> next = temp;
    }
    return first;
}

void traverseList(NODE first) {
    if(first == NULL){
        printf("List is Empty.");
    } else {
        NODE temp = first;
        while (temp != NULL) {
            printf("%d --> ", temp -> data);
            temp = temp -> next;
        }
        printf("NULL\n" );
    }
}
}

```

### Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Enter elements up to -1 : 9 18 27 36 45 -1
The elements in SLL are : 9 --> 18 --> 27 --> 36 --> 45 --> NULL

Test Case - 2
User Output
Enter elements up to -1 : 12 14 19 23 -1
The elements in SLL are : 12 --> 14 --> 19 --> 23 --> NULL