

Week-3: Activity Questions

Week-3: Activity Questions

Problem 1

Question

Answer

Problem 2

Question

Answer

Problem 3

Question

Answer

Problem 4

Question

Answer

Problem 5

Question

Answer

Problem 6

Question

Answer

Problem 7

Question

Answer

Problem 8

Question

Answer

Problem 9

Question

Answer

Problem 10

Question

Answer

Problem 11

Question

Answer

Problem 12

Question

Answer

Problem 13

Question

Answer

Problem 14

Question

Answer

Problem 15

Question

Answer

Problem 16

Question

Answer
Problem 17
Question
Answer
Problem 18
Question
Answer
Problem 19
Question
Answer
Problem 20
Question
Answer
Problem 21
Question
Answer
Problem 22
Question
Answer
Problem 23
Question
Answer
Problem 24
Question
Answer
Solution
Problem 25
Question
Answer
Problem 26
Question
Answer
Problem 27
Question
Answer
Problem 28
Question
Answer
Problem 29
Question
Answer
Problem 1
Question
Answer
Problem 2
Question
Answer
Problem 3
Question
Answer
Problem 4
Question
Answer

Problem 1

Question

Write a code using a while loop that adds all odd numbers from 1 to 100 (inclusive).

Answer

```
1  n=1
2  total=0
3  while(n<=100):
4      if n%2!=0:
5          total+=n
6      n+=1
7  print(total)
```

or

```
1  n=1
2  total=0
3  while(n<=100):
4      total+=n
5      n+=2
6  print(total)
```

Problem 2

Question

Write a program using loop to print first 10 even numbers in reverse order.

Answer

Using for loop:

```
1  for num in range(20, 0, -2):  
2      print(num)
```

Using while loop

```
1  num = 20  
2  while num > 0:  
3      print(num)  
4      num = num - 2
```

Problem 3

Question

Write a program to accept the positive integer `n` from the user and print the average of all number's factorial from 1 to `n`.

Answer

```
1  n = int(input())
2  total = 0
3  for i in range(1,n+1):
4      fact = 1
5      j = 1
6      while j <= i:
7          fact *= j
8          j += 1
9      total += fact
10
11 avg = total / n
12 print(avg)
```

or

```
1  n = int(input())
2  i = 1
3  total = 0
4  while i <= n:
5      fact = 1
6      for j in range(1,i+1):
7          fact *= j
8      total += fact
9      i += 1
10 avg = total / n
11 print(avg)
```

Problem 4

Question

Write a program to accept the positive integer `n` from the user and print counting of numbers which are not prime from 1 to `n`.

Answer

```
1  n = int(input())
2  count = 1
3  for num in range(2,n+1):
4      flag = True
5      for j in range (2,num):
6          if num % j == 0:
7              flag = False
8              break
9      if flag == False:
10         count += 1
11 print(count)
```

Problem 5

Question

Write a program to accept the string `s` from the user and print all alphabets in one line separated by , before first occurrence of vowel .

Answer

```
1 s = input()
2 pos = 0
3 vowels = 'aeiouAEIOU'
4 while pos < len(s) and s[pos] not in vowels:
5     if s[pos].isalpha() == True:
6         print(s[pos] , end = ",")
7     pos += 1
```

Problem 6

Question

Write a program to accept the two positive integers `start` and `stop` where `0 < start < stop ≤ 100` print all numbers from start to stop both inclusive with following constraints.

- If the number is divisible by 3 print `Divisible by 3` at the place of number.
- If the number is divisible by 5 print `Divisible by 5` at the place of number.
- If the number is divisible by 10 print `Divisible by 10` at the place of number.
- If the number is divisible by any of two from 3, 5 and 10, print nothing, just skip.
- If the number is divisible by all (3, 5 and 10), stop printing the number.
- If the number is not divisible by any of (3, 5 and 10), just print the number as it is.

Answer

```
1 start=int(input())
2 stop=int(input())
3
4 for i in range (start,stop+1):
5     if i%3==0 and i%5==0 and i%10==0:
6         break
7     elif (i%3==0 and i%5==0) or (i%5==0 and i%10==0) or (i%3==0 and
8         i%10==0):
9         pass
10    elif i%3==0:
11        print("Divisible by 3")
12    elif i%5==0:
13        print("Divisible by 5")
14    elif i%10==0:
15        print("Divisible by 10")
16    else:
17        print(i)
```


Problem 7

Question

Accept the positive integer `n` and display the cube of the number up to a given integer `n` in the following pattern using formatted string.

Input

```
1 | 6
```

Output

```
1 | Current Number is : 1 and the cube is 1
2 | Current Number is : 2 and the cube is 8
3 | Current Number is : 3 and the cube is 27
4 | Current Number is : 4 and the cube is 64
5 | Current Number is : 5 and the cube is 125
6 | Current Number is : 6 and the cube is 216
```

Answer

```
1 | n=int(input())
2 | for i in range(1,n+1):
3 |     print("Current Number is : {} and the cube is {}".format(i,i**3))
```

or

```
1 | n=int(input())
2 | for i in range(1,n+1):
3 |     print(f"Current Number is : {i} and the cube is {i**3}")
```

or

```
1 | n=int(input())
2 | for i in range(1,n+1):
3 |     print("Current Number is : %d and the cube is %d"%(i,i**3))
```

Problem 8

Question

Run the following code and observe the output.

Code

```
1 print("The sum of {} , {} and {} is {}".format(1,2,3,6) )
2 print("The sum of {0} , {1} and {2} is {3}".format(1,2,3,6) )
3 print("The sum of {0} , {1} and {c} is {d}".format(1,2,c=3,d=6) )
4 print("The sum of {a} , {b} and {c} is {d}".format(a=1,b=2,c=3,d=6) )
```

Answer

line 1, if we do not assign any position inside `{}` then the interpreter will assign a position from 0 to 3 in `{}` from left to right in the string.

line 2, we can manually assign position inside `{}` and order is not mandatory.

line3, we can assign position and keyword inside `{}` at the same time. but inside `format()` keyword argument should be defined after positional argument.

line 4, we can manually assign keywords inside `{}` order is not mandatory.

Problem 9

Question

Write a code to accept the positive integer `n` from user and print average of `1 + 11 + 111 + 1111 + ..n terms`.

Input

```
1 | 6
```

so series will be `1 + 11 + 111 + 1111 + 11111 + 111111`

Output

```
1 | 20576.0
```

Answer

```
1 | n = int(input())
2 | num = "1"
3 | total = 0
4 | for i in range(1 , n + 1):
5 |     total += int(num * i)
6 | avg = total / n
7 | print(avg)
```

Problem 10

Question

Place a string and `{}` inside `""` in line number 3 of the code in the appropriate place and fill the argument inside `.format()`'s parenthesis so that the output prints in the following manner.

```
1 name = input()
2 age = input()
3 message="".format()
4 print(message)
```

Input

```
1 | Rahu121
```

Output

```
1 | Hii!, I am Rahu1, I am 21 year's old.
```

Answer

```
1 name = input()
2 age = input()
3 str="Hii!, I am {0}, I am {1} year's old.".format(name,age)
4 print(str)
```

Problem 11

Question

Write a code to accept positive integer `n` from user(`n<10`) and print following pattern.

Input

```
1 | 5
```

Output

```
1 | 5 4 3 2 1 2 3 4 5
2 |  4 3 2 1 2 3 4
3 |    3 2 1 2 3
4 |      2 1 2
5 |        1
```

Answer

```
1 n=int(input())
2 for i in range(0,n):
3     print(" "*2*i,end="")
4     for j in range(n-i,1,-1):
5         print(j,end=" ")
6     for k in range(1,n-i+1):
7         if k == n-i:
8             print(k,end="")
9         else:
10            print(k,end=" ")
11
12     print(" "*2*i,end="")
13     print()
```

Problem 12

Question

Write a code to accept the string of length 10 from the user and print `True` if string has any character occurring 5 times consecutively in it, otherwise print `False`.

Answer

```
1 s=input()
2 valid=False
3 for i in range(0,len(s)-4):
4     count= s.count(s[i])
5     if count > 4 :
6         if s[i:i+5].count(s[i])==5:
7             valid=True
8     if valid==True:
9         break
10 print(valid)
```

or

```
1 s=input()
2 valid=False
3 for i in range(0,len(s)-4):
4     count= s.count(s[i])
5     if count > 4 :
6         valid = True
7         for i in range(i , i+4):
8             if s[i] != s[i+1]:
9                 valid = False
10                break
11     if valid==True:
12         break
13 print(valid)
```

Problem 13

Question

Write a code to accept the positive integer `n` from the user and print the following pattern.

Input

```
1 | 5
```

Output

```
1 | 1
2 | 1 2
3 | 1 2 3
4 | 1 2 3 4
5 | 1 2 3 4 5
```

Answer

```
1 | n= int(input())
2 | for i in range(1,n+1):
3 |     for j in range(1,i+1):
4 |         print(j,end=" ")
5 |     print()
```

Problem 14

Question

Write a code to accept a string as input and reverse it using loop:

Answer

```
1 st = input()
2 reverse = ''
3 for char in st:
4     reverse = char + reverse
5 print(reverse)
```


Problem 15

Question

Write a code to accept a string as input and determine if it is a palindrome or not.

Answer

```
1 st = input()
2 reverse = ''
3 for char in st:
4     reverse = char + reverse
5 if st == reverse:
6     print("Yes,string is palindrome")
7 else:
8     print("No,string is not palindrome")
```

Problem 16

Question

Write a code to accept the name of a person as input and print the initials as output. Assume that the name will be of this form: `<first name> <last name>`. Also assume that the first name and last name will be a single word, and there will be exactly one space between the two names. For example, if the input is `Rohit sharma`, the output should be `RS`.

Answer

```
1 name = input()
2 res = ''
3 first_char = True
4 for char in name:
5     if first_char == True:
6         res = res + char
7         first_char = False
8     if char == ' ':
9         first_char = True
10 print(res)
```

Problem 17

Question

Write a code for the following sequence:

```
1 | |0||0|||0|
```

This sequence should be understood as follows: `| |` represents an empty box. `|0|` represents a box that has an egg in it. These boxes are placed side by side so that the right wall of a box overlaps with the left wall of the box immediately to its right. For any arbitrary sequence given as input, your task is to find:

- total number of boxes
- number of empty boxes
- number of boxes that have eggs in them

In the sequence given above, there are six boxes. Three are empty and the other three are non-empty

Answer

```
1 box = input()
2 total_box = 0
3 egg = 0
4 for char in box:
5     if char == '0':
6         egg = egg + 1
7     if char == "|":
8         total_box = total_box + 1
9 total_box = total_box - 1
10 print("The total number of box =",total_box)
11 print("The total number of empty box =",total_box - egg)
12 print("Tumber of boxes that have eggs in them =",egg)
```

Problem 18

Question

You are given the results of a sequence of matches played by India in ODIs. A win is represented by 'w' and a loss is represented by 'L'. A winning streak is a string of consecutive wins. For example, if India has played five matches with the following results - 'WLWWWL' - then it has a three-match streak. Accept the result-sequence as input and find the longest streak in it.

Answer

```
1 match_result = input()
2 max_streak = 0
3 count_win_streak = 0
4 for char in match_result:
5     if char == 'w':
6         count_win_streak = count_win_streak + 1
7         if max_streak < count_win_streak:
8             max_streak = count_win_streak
9     if char == 'L':
10        count_win_streak = 0
11 print("the longest win streak =",max_streak)
```

Problem 19

Question

Write a code to accept the sequence of positive integers in sorted order(either in non ascending order or non descending order) ending with `-1` and at least two integers must be before `-1`. In Output print the number of distinct elements in the sorted sequence before `-1`.

Sample Input - 1

```
1 | 1
2 | 2
3 | -1
```

Sample Output - 1

```
1 | 2
```

Sample Input - 2

```
1 | 7
2 | 6
3 | 6
4 | 5
5 | 5
6 | 5
7 | -1
```

Sample Output - 2

```
1 | 3
```

Answer

```
1 | curr=int(input())
2 | distinct_num = 1
3 | while ( curr != -1 ):
4 |     prev = curr
5 |     curr=int(input())
6 |     if ( prev != curr and curr != -1):
7 |         distinct_num += 1
8 | print(distinct_num)
```

Problem 20

Question

Write a code to accept the sequence of positive integers ending with `-1` and at least two distinct integers must be before `-1`.

In Output:

- Print `asc` if sequence before `-1` is sorted in ascending order or non descending order.
- Print `desc` if sequence before `-1` is sorted in descending order or non ascending order.
- Print `False` if sequence before `-1` is not sorted in any order.

Sample Input - 1

```
1 | 1
2 | 2
3 | 2
4 | 3
5 | 3
6 | 4
7 | -1
```

Sample Output - 1

```
1 | asc
```

Sample Input - 2

```
1 | 7
2 | 6
3 | 6
4 | 5
5 | 5
6 | 5
7 | -1
```

Sample Output - 2

```
1 | desc
```

Sample Input - 3

```
1 | 3
2 | 4
3 | 4
4 | 5
5 | 6
6 | 2
7 | 8
8 | -1
```

Sample Output - 3

1 | False

Answer

```
1  asc_sort=True
2  desc_sort=True
3  curr=int(input())
4  while ( curr != -1 ):
5      prev = curr
6      curr=int(input())
7      if ( curr != -1 and prev > curr and asc_sort == True) :
8          asc_sort=False
9      if (curr != -1 and prev < curr and desc_sort == True) :
10         desc_sort=False
11  if asc_sort==True:
12      print('asc')
13  elif desc_sort==True:
14      print('desc')
15  else:
16      print('False')
```

Problem 21

Question

Write a program to print the product of the digits of a number entered by the user. Number can be either positive or a negative.

Public

Input	OUTPUT
12345	120
999	729
1000	0
-12345	120

Answer

```
1 num = int(input())
2 if num < 0:
3     num = -num
4 product = 1
5 while(num):
6     remainder = num % 10
7     product = product * remainder
8     num = num // 10
9 print(product)
```


Problem 22

Question

Write a program to find highest common factor (HCF) of two numbers.

Answer

```
1 num_1 = int(input())
2 num_2 = int(input())
3 while num_2 != 0:
4     num_1, num_2 = num_2, num_1 % num_2
5 print(num_1)
```

Problem 23

Question

Write a Program to find the sum of an below series. Consider x and n as positive integers.

$$1 + x^2 + x^3 + \dots + x^n$$

Answer

```
1 num_of_terms = int(input())
2 x = int(input())
3 sum_series = 1
4 for power in range(2, num_of_terms + 1):
5     sum_series = sum_series + (x ** power)
6     #print(sum_series)
7 print("{}".format(sum_series))
```

Problem 24

Question

Write a program for the below scenario:

The sum of a harmonic series approaches infinity when as the number of terms increases.

$$1 + 1/2 + 1/3 + 1/4 + \dots$$

How many terms are required to reach the value near to 10. Consider the value for tolerance = 0.05.

Answer

11764

Solution

```
1 term = 1
2 count = 0
3 sum_series = 0
4 while term:
5     sum_series = sum_series + (1 / term)
6     count += 1
7     term += 1
8     if 10 - sum_series < tolerance:
9         break
10 print("{:.2f}".format(sum_series))
11 print("{}".format(count))
```

Problem 25

Question

Write a program for harmonic mean of first `n` numbers. Accept `n` as an input from the user. Round off the answer to `2` decimal number.

For an example , the harmonic mean for first `5` numbers can be written as.

$$\text{harmonic-mean} = \frac{5}{1/1+1/2+1/3+1/4+1/5}$$

Answer

```
1 num_of_terms = int(input())
2 term = 1
3 count = 0
4 sum_series = 0
5 for term in range(1, num_of_terms + 1):
6     sum_series = sum_series + 1 / term
7     count += 1
8     term += 1
9 print("{:.2f}".format(count / sum_series))
```

Problem 26

Question

Write a program to number guessing game using loops. The program arbitrarily chooses a number in the range 1 to 100 (inclusive) and asks user to enter a guessed number. The program repeatedly asks user to guess the number 5 times. For each guess, the program says `TOO HIGH` or `TOO LOW` or `GOOD` based on the below table.

Difference	output
<code>actual_number - guess_number = 0</code>	<code>EXCELLENT</code>
<code>(actual_number - guess_number <= 10) or (guess_number - actual_number <= 10)</code>	<code>GOOD</code>
<code>guess_number - actual_number > 10</code>	<code>TOO_HIGH</code>
<code>actual_number - guess_number > 10</code>	<code>TOO_LOW</code>

Answer

```
1 import random
2 num_of_guesses = 5
3 actual_number = random.randint(1, 101)
4 #print(actual_number)
5 for count in range(num_of_guesses):
6     guess_number = int(input())
7     if actual_number == guess_number:
8         print("EXCELLENT")
9     elif abs(actual_number - guess_number) <= 10:
10        print("GOOD")
11    elif actual_number - guess_number > 10:
12        print("TOO_LOW")
13    else:
14        print("TOO_HIGH")
```

Problem 27

Question

Write a program to print the Fibonacci series of n terms where n is always greater than or equal to 2.

Answer

```
1 n = int(input("Enter any number: "))
2 a, b = 0, 1
3 print(a, b, end = ' ')
4 for i in range(3, n+1):
5     fib = a + b
6     print(fib, end = ' ')
7     a = b
8     b = fib
```

Problem 28

Question

Two numbers n1 and n2 are said to be same if they have equal number of digits in them. Write a program to check whether n1 and n2 are same. n1 and n2 are positive integers entered by the user without converting the number to string.

Answer

```
1  n1 = int(input("Enter 1st number: "))
2  n2 = int(input("Enter 2nd number: "))
3  count1 = 0
4  count2 = 0
5  while (n1 > 0):
6      count1 = count1 + 1
7      n1 = n1 // 10
8  while (n2 > 0):
9      count2 = count2 + 1
10     n2 = n2 // 10
11  if (count1 == count2):
12     print(True)
13  else:
14     print(False)
```

Problem 29

Question

Write a program to print the first and last digits of a number without converting it to string.

Answer

```
1  n = int(input("Enter any number: "))
2  x = n
3  last_digit = n % 10
4  first_digit = 0
5  while(n > 0):
6      first_digit = n % 10
7      n = n // 10
8  print("first digit is: ",first_digit)
9  print("last digit is: ",last_digit)
```


Below 4 Questions are MCQ/MSQ Type.

Problem 1

Question

You want to make sure that a set of statements are executed at least once before a condition is evaluated. Which loop will be preferred in this situation. This is a Multiple Choice Question (MCQ).

- (a) for
- (b) do-while
- (c) while
- (d) None of these

Answer

- (d)

Problem 2

Question

How many time the loop will run. This is a Multiple Select Question (MSQ).

```
1 while x:  
2     Print("Python")
```

- (a) Will run exactly 1 time for any value of x
- (b) Will run x times where x is a positive integer
- (c) Will run 0 rimes when x = 0
- (d) Will run indefinitely when x is a positive or negative integer
- (e) Will run indefinitely when x = True

Answer

(c), (d), (e)

Problem 3

Question

What will the output of the following code. This is a Multiple Choice Question (MCQ).

```
1 x = 2
2 y = 5
3 example = f'Two plus five is {x + y} and not {3 * (x + y)}'
4 print(example)
```

- (a) Two plus five is {x + y} and not {3 * (x + y)}
- (b) Two plus five is 2 + 5 and not 3 * (2 + 7)
- (c) Two plus five is {2 + 5} and not {3 * (7)}
- (d) Two plus five is 7 and not 21

Answer

- (d)

Problem 4

Question

What will be the output of the following code.

```
1 a = "28"  
2 b = "8"  
3 c = "India"  
4 print("There are {} states and {} union territories in {}".format(a,b,c))  
5
```

- (a) "There are {} states and {} union territories in {}."
- (b) There are {28} states and {8} union territories in {India}.
- (c) There are 28 states and 8 union territories in India.
- (d) "There are 28 states and 8 union territories in India."

Answer

- (c)