Page No: 1

2022-2026-CSE-AIML

Aim:

Write a Java program with a class name [Employee] which contains the data members name (String), age (int), designation (String), salary (double) and the methods setData(), displayData().

The member function **setData()** is used to initialize the data members and **displayData()** is used to display the given employee data.

Write the **main()** method with in the class which will receive four arguments as **name**, **age**, **designation**and **salary**.

Create an object to the class <code>Employee</code> within the main(), call **setData()** with arguments and finally call the method **displayData()** to print the output.

If the input is given as command line arguments to the **main()** as **"Saraswathi"**, **"27"**, **"Teacher"**, **"37250"** then the program should print the output as:

```
Name : Saraswathi
Age : 27
Designation : Teacher
Salary : 37250.0
```

Note: Please don't change the package name.

Source Code:

q11115/Employee.java

```
package q11115;
class Employee{
   String name;
   int age;
    String designation;
    double salary;
    void setData(String a[])
      name=a[0];
      age=Integer.parseInt(a[1]);
      designation = a[2];
      salary = Double.parseDouble(a[3]);
    }
    void displayData()
    {
      System.out.println("Name : "+name);
      System.out.println("Age : "+age);
      System.out.println("Designation : "+designation);
      System.out.println("Salary : "+salary);
    }
    public static void main(String args[])
      Employee e = new Employee();
      e.setData(args);
```

```
e.displayData();
}
}
```

Execution Results - All test cases have succeeded!

Test Case - 1
Jser Output
Name : Ram
Age : 25
Designation : Team member
Salary : 25000.0

	Test Case - 2
User Output	
Name : Ravi	
Age : 36	
Designation : TeamLead	
Salary : 35000.0	