

Oracle

Exam Questions 1Z0-819

Java SE 11 Developer



NEW QUESTION 1

Given:


```
1. public class Test {  
2.     private static class Greet {  
3.         private void print() {  
4.             System.out.println("Hello World");  
5.         }  
6.     }  
7.     public static void main(String[] args) {  
8.         Test.Greet i = new Greet();  
9.         i.print();  
10.    }  
11. }
```

What is the result?

- A. The compilation fails at line 9.
- B. The compilation fails at line 2.
- C. Hello World
- D. The compilation fails at line 8.

Answer: C

Explanation:



The screenshot shows a Java code editor with the following code:

```
1 public class Test {  
2     private static class Greet {  
3         private void print() {  
4             System.out.println("Hello World");  
5         }  
6     }  
7     public static void main(String[] args) {  
8         Test.Greet i = new Greet();  
9         i.print();  
10    }  
11 }
```

Below the code editor, there is a section titled "Execute Mode, Version, Inputs & Arguments" with a dropdown menu showing "JDK 11.0.4". Below this is a section titled "CommandLine Arguments" with an empty text input field.

At the bottom, there is a section titled "Result" showing the output of the code execution:

```
CPU Time: 0.16 sec(s), Memory: 32504 kilobyte(s)  
Hello World
```

NEW QUESTION 2

Given:

```
package b;
public class Person {
    protected Person() {                //line 1
    }
}
```

and

```
package a;
import b.Person;
public class Main {                    //line 2
    public static void main(String[] args) {
        Person person = new Person(); //line 3
    }
}
```

Which two allow a.Main to allocate a new Person? (Choose two.)

- A. In Line 1, change the access modifier to privateprivate Person() {
- B. In Line 1, change the access modifier to publicpublic Person() {
- C. In Line 2, add extends Person to the Main classpublic class Main extends Person {and change Line 3 to create a new Main objectPerson person = new Main();
- D. In Line 2, change the access modifier to protectedprotected class Main {
- E. In Line 1, remove the access modifierPerson() {

Answer: BC

NEW QUESTION 3

Which interface in the java.util.function package will return a void return type?

- A. Supplier
- B. Predicate
- C. Function
- D. Consumer

Answer: D

NEW QUESTION 4

Given:

```
package a;
public abstract class Animal {
    protected abstract void walk();
}
package b;
public abstract class Human extends Animal {
    // line 1
}
```

Which two lines inserted in line 1 will allow this code to compile? (Choose two.)

- A. protected void walk(){}
- B. void walk(){}
- C. abstract void walk();
- D. private void walk(){}
- E. public abstract void walk();

Answer: AE

NEW QUESTION 5

Which two commands are used to identify class and module dependencies? (Choose two.)

- A. jmod describe
- B. java Hello.java
- C. jdeps --list-deps
- D. jar --show-module-resolution
- E. java --show-module-resolution

Answer: CE

NEW QUESTION 6

Given:

```
public static void main(String[] args) {
    final List<String> fruits =
        List.of("Orange", "Apple", "Lemmon", "Raspberry");
    final List<String> types =
        List.of("Juice", "Pie", "Ice", "Tart");
    final var stream =
        IntStream.range(0, Math.min(fruits.size(), types.size()))
            .mapToObj((i) -> fruits.get(i) + " " + types.get(i) );
    stream. forEach(System.out::println);
}
```

What is the result?

- A. Orange Juice
- B. The compilation fails.
- C. Orange Juice Apple Pie Lemmon Ice Raspberry Tart
- D. The program prints nothing.

Answer: C

Explanation:

```
12 public class Person {
13     public static void main (String[] args) {
14         final List<String> fruits =
15             List.of("Orange", "Apple", "Lemmon", "raspberry");
16         final List<String> types =
17             List.of("Juice", "Pie", "Ice", "Tart");
18         final var stream =
19             IntStream.range(0, Math.min(fruits.size(), types.size()))
20                 .mapToObj ((i) -> fruits.get(i) + " " + types.get(i) );
21         stream. forEach(System.out::println);
22     }
23 }
24 }
```

Result

compiled and executed in 1.227 sec(s)

```
Orange Juice
Apple Pie
Lemmon Ice
raspberry Tart
```

NEW QUESTION 7

Given:

```
1. {
2.     Iterator iter = List.of(1,2,3).iterator();
3.     while (iter.hasNext()) {
4.         foo(iter.next());
5.     }
6.     Iterator iter2 = List.of(1,2,3).iterator();
7.     while (iter.hasNext()) {
8.         bar(iter2.next());
9.     }
10. }
11. for (Iterator iter = List.of(1,2,3).iterator(); iter.hasNext(); ) {
12.     foo(iter.next());
13. }
14. for (Iterator iter2 = List.of(1,2,3).iterator(); iter.hasNext(); ) {
15.     bar(iter2.next());
16. }
```

Which loop incurs a compile time error?

- A. the loop starting line 11
- B. the loop starting line 7
- C. the loop starting line 14
- D. the loop starting line 3

Answer: C

NEW QUESTION 8

Which two statements set the default locale used for formatting numbers, currency, and percentages? (Choose two.)

- A. `Locale.setDefault(Locale.Category.FORMAT, "zh-CN");`
- B. `Locale.setDefault(Locale.Category.FORMAT, Locale.CANADA_FRENCH);`
- C. `Locale.setDefault(Locale.SIMPLIFIED_CHINESE);`
- D. `Locale.setDefault("en_CA");`
- E. `Locale.setDefault("es", Locale.US);`

Answer: BD

NEW QUESTION 9

Given:

```
package A;
class Test {
    String name;
    public Test(String name) {
        this.name = name;
    }
    public String toString() {
        return name;
    }
}
```

and

```
package B;
import A.Test;
public class Main {
    public static void main(String[] args) {
        Test test = new Test("Student");
        System.out.println(test);
    }
}
```

What is the result?

- A. null
- B. nothing
- C. It fails to compile.
- D. `java.lang.IllegalAccessException` is thrown.
- E. Student

Answer: C

NEW QUESTION 10

Given:

```
public class Tester {
    static class Person implements /* line 1 */ {
        private String name;
        Person(String name) { this.name = name; }
        /* line 2 */
    }
    public static void main(String[] args) {
        Person[] people = {new Person("Joe"),
                           new Person("Jane"),
                           new Person("John")};
        Arrays.sort(people);
        for(Person person: people) {
            System.out.println(person.name);
        }
    }
}
```

You want the code to produce this output:

John

Joe Jane

Which code fragment should be inserted on line 1 and line 2 to produce the output?

- A. Insert `Comparator<Person>` on line 1. Insert `public int compare(Person p1, Person p2) { return p1.name.compare(p2.name);}` on line 2.
- B. Insert `Comparator<Person>` on line 1. Insert `public int compareTo(Person person) { return person.name.compareTo(this.name);}` on line 2.
- C. Insert `Comparable<Person>` on line 1. Insert `public int compare(Person p1, Person p2) { return p1.name.compare(p2.name);}` on line 2.
- D. Insert `Comparator<Person>` on line 1. Insert `public int compare(Person person) { return person.name.compare(this.name);}` on line 2.

Answer: B

NEW QUESTION 10

Which command line runs the main class com.acme.Main from the module com.example?

- A. java --module-path mods com.example/com.acme.Main
- B. java -classpath com.example.jar com.acme.Main
- C. java --module-path mods -m com.example/com.acme.Main
- D. java -classpath com.example.jar -m com.example/com.acme.Main

Answer: D

NEW QUESTION 15

Given:

```
public class Main {

    public static void checkConfiguration(String filename) {
        File file = new File(filename);
        if(!file.exists()) {
            throw new Error("Fatal Error: Configuration File, "
                + filename + ", is missing.");
        }
    }


    public static void main(String[] args) {
        checkConfiguration("App.config");
        System.out.println("Configuration is OK");
    }
}
```

If file "App.config" is not found, what is the result?

- A. Configuration is OK
- B. The compilation fails.
- C. Exception in thread "main" java.lang.Error:Fatal Error: Configuration File, App.config, is missing.
- D. nothing

Answer: B

Explanation:



NEW QUESTION 16

Given:


```
public class Tester {
    public static void main(String[] args) {
        int x = 4;
        int y = 2;
        System.out.println(x+y+"=(x+y)="+x+y);
    }
}
```

What is the result?

- A. An exception is thrown at runtime
- B. $42=(x+y)=42$
- C. $42=(x+y)=6$
- D. $6=(x+y)=42$
- E. $6=(x+y)=6$

Answer: D

Explanation:



NEW QUESTION 21

Which describes a characteristic of setting up the Java development environment?

- A. Setting up the Java development environment requires that you also install the JRE.
- B. The Java development environment is set up for all operating systems by default.
- C. You set up the Java development environment for a specific operating system when you install the JDK.
- D. Setting up the Java development environment occurs when you install an IDE before the JDK.

Answer: D

NEW QUESTION 25

Given:

```
public static void main(String[] args) {
    try (Reader reader1 = new FileReader("File1.txt");
        Reader reader2 = new FileReader("File2.txt");
        Reader reader3 = new FileReader("File3_txt")) {

    } catch (IOException ex) {
        Logger.getLogger(Main.class.getName()).log(Level.SEVERE, null, ex);
    }
    // Line 1
    System.out.println("Done");
}
```

When run and all three files exist, what is the state of each reader on Line 1?

- A. All three readers are still open.
- B. All three readers have been closed.
- C. The compilation fails.
- D. Only reader1 has been closed.

Answer: C

NEW QUESTION 30

Consider this method declaration:

```
void setSessionUser(Connection conn, String user) throws SQLException {
    Statement stmt = conn.createStatement();
    String sql = <EXPRESSION>;
    stmt .execute();
}
```

- A) "SET SESSION AUTHORIZATION " + user
- B) "SET SESSION AUTHORIZATION " + stmt.enquotIdentifier(user) Is A or B the correct replacement for <EXPRESSION> and why?

- A. A, because it sends exactly the value of user provided by the calling code.
- B. B, because enquoting values provided by the calling code prevents SQL injection.
- C. A and B are functionally equivalent.
- D. A, because it is unnecessary to enclose identifiers in quotes.
- E. B, because all values provided by the calling code should be enquoted.

Answer: A

NEW QUESTION 34

Given:

```
1. public class Secret {
2.     String[] names;
3.     public Secret(String[] names) {
4.         this.names = names;
5.     }
6.     public String[] getNames() {
7.         return names;
8.     }
9. }
```

Which three actions implement Java SE security guidelines? (Choose three.)

- A. Change line 7 to return names.clone();.
- B. Change line 4 to this.names = names.clone();.
- C. Change the getNames() method name to get\$Names().
- D. Change line 6 to public synchronized String[] getNames() {.
- E. Change line 2 to private final String[] names;.
- F. Change line 3 to private Secret(String[] names) {.
- G. Change line 2 to protected volatile String[] names;.

Answer: EFG

NEW QUESTION 38

Given:

```
public class Foo {
    private final ReentrantLock lock = new ReentrantLock();
    private State state;
    public void foo() throws Exception {
        try {
            lock.lock();
            state.mutate();
        }
        finally {
            lock.unlock();
        }
    }
}
```

What is required to make the Foo class thread safe?

- A. No change is required.
- B. Make the declaration of lock static.
- C. Replace the lock constructor call with new ReentrantLock (true).
- D. Move the declaration of lock inside the foo method.

Answer: C

NEW QUESTION 41

Given:

```
import java.io.FileNotFoundException;
import java.io.IOException;

public class Tester {
    public static void main(String[] args) {
        try {
            doA();
        } //line 1
    }
    private static void doA() throws IOException, IndexOutOfBoundsException {
        if (false) {
            throw new FileNotFoundException();
        } else {
            throw new IndexOutOfBoundsException();
        }
    }
}
```

What must be added in line 1 to compile this class?

- A. catch(IOException e) {}
- B. catch(FileNotFoundException | IndexOutOfBoundsException e) {}

- C. catch(FileNotFoundException | IOException e) { }
- D. catch(IndexOutOfBoundsException e) { }catch(FileNotFoundException e) { }
- E. catch(FileNotFoundException e) { }catch(IndexOutOfBoundsException e) { }

Answer: A

NEW QUESTION 43

Which is the correct order of possible statements in the structure of a Java class file?

- A. class, package, import
- B. package, import, class
- C. import, package, class
- D. package, class, import
- E. import, class, package

Answer: B

NEW QUESTION 46

Given:

```
public class DNASynth {
    int aCount;
    int tCount;
    int cCount;
    int gCount;

    DNASynth(int a, int tCount, int c, int g){
        // line 1
    }
    int setCCount(int c){
        return c;
    }
    void setGCount(int gCount){
        this.gCount = gCount;
    }
}
```

Which two lines of code when inserted in line 1 correctly modifies instance variables? (Choose two.)

- A. setCCount(c) = cCount;
- B. tCount = tCount;
- C. setGCount(g);
- D. cCount = setCCount(c);
- E. aCount = a;

Answer: BE

NEW QUESTION 47

Given:

```
class Employee {
    String office;
}
```

and the code fragment:

```
5. public class HRApp {
6.     var employee = new ArrayList<Employee>();
7.     public var display() {
8.         var employee = new Employee();
9.         var offices = new ArrayList<>();
10.        offices.add("Chicago");
11.        offices.add("Bangalore");
12.        for (var office : offices) {
13.            System.out.print("Employee Location"+ office);
14.        }
15.    }
16. }
```

Which two lines cause compilation errors? (Choose two.)

- A. line 12
- B. line 6

- C. line 9
- D. line 8
- E. line 7

Answer: BE

NEW QUESTION 52

You are working on a functional bug in a tool used by your development organization. In your investigation, you find that the tool is executed with a security policy file containing this grant.

```
grant codebase "file:${klib.home}/j2se/home/klib.jar" {  
    permission java.security.AllPermission;  
};
```

What action should you take?

- A. Nothing, because it is an internal tool and not exposed to the public.
- B. Remove the grant because it is excessive.
- C. Nothing, because it is not related to the bug you are investigating.
- D. File a security bug against the tool referencing the excessive permission granted.
- E. Nothing, because listing just the required permissions would be an ongoing maintenance challenge.

Answer: D

NEW QUESTION 55

Given the code fragment:

```
int[] secA = { 2, 4, 6, 8, 10 };  
int[] secB = { 2, 4, 8, 6, 10 };  
int res1 = Arrays.mismatch(secA, secB);  
int res2 = Arrays.compare(secA, secB);  
System.out.print(res1 + " : " + res2);
```

What is the result?

- A. -1 : 2
- B. 2 : -1
- C. 2 : 3
- D. 3 : 0

Answer: B

NEW QUESTION 56

Given:

```
String[][] arr = {  
    {"Red", "White"},  
    {"Black"},  
    {"Blue", "Yellow", "Green", "Violet"}  
};  
for(int row = 0; row < arr.length; row++) {  
    int column = 0;  
    for(; column < arr[row].length; column++) {  
        System.out.println "[" + row + ", " + column + "] = " + arr[row][column];  
    }  
}
```

What is the result?

- A. [0,0] = Red[0,1] = White[1,0] = Black[1,1] = Blue[2,0] = Yellow[2,1] = Green[3,0] = Violet
- B. [0,0] = Red[1,0] = Black[2,0] = Blue
- C. java.lang.ArrayIndexOutOfBoundsException thrown
- D. [0,0] = Red[0,1] = White[1,0] = Black[2,0] = Blue[2,1] = Yellow[2,2] = Green[2,3] = Violet

Answer: D

Explanation:

```
Console 1 Console 2 Console 3

[0,0] =Red
[0,1] =White
[1,0] =Black
[2,0] =Blue
[2,1] =Yellow
[2,2] =Green
[2,3] =Violet

Completed with exit code: 0
```

NEW QUESTION 59

Which code fragment prints 100 random numbers?

- A. `var r= new Random();
new DoubleStream(r::nextDouble).limit(100).forEach(System.out::print);`
- B. `DoubleStream.generate(Random::nextDouble)
.limit (100).forEach(System.out::print);`
- C. `Doublestream.generate(Random.nextDouble).limit(100).forEach(System.out.print);`
- D. `var r = new Random(); DoubleStream.generate(r::nextDouble).limit(100).forEach(System.out::print);`

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

NEW QUESTION 60

Given:

String originalPath = "data\\projects\\a-project\\..\\..\\another-project"; Path path = Paths.get(originalPath); System.out.print(path.normalize());

What is the result?

- A. data\\another-project
- B. data\\projects\\a-project\\another-project
- C. data\\projects\\a-project\\..\\..\\another-project
- D. data\\projects\\a-project\\..\\..\\another-project

Answer: D

Explanation:

```

1  import java.util.*;
2  import java.io.*;
3  import java.nio.file.*;
4
5  public class Test {
6
7      public static void main(String[] args) {
8          String originalPath = "data\\projects\\a-project\\..\\..\\another-project";
9          Path path = Paths.get(originalPath);
10         System.out.print(path.normalize());
11     }
12 }

```

Execute Mode, Version, Inputs & Arguments

JDK 11.0.4 ☐ Interactive Stdin Input

CommandLine Arguments

Execute

Result
 CPU Time: 0.19 sec(s), Memory: 31984 kilobyte(s)

data\projects\a-project\..\..\another-project

NEW QUESTION 63

Given:

```

public class Person {
    private String name = "Joe Bloggs";
    public Person(String name) {
        this.name = name;
    }
    public String toString() {
        return name;
    }
}

```

and

```

public class Tester {
    public static void main(String[] args) {
        Person p1 = new Person(); // line 1
        System.out.println(p1);
    }
}


```

What is the result?

- A. null
- B. Joe Bloggs
- C. The compilation fails due to an error in line 1.
- D. p1

Answer: C

Explanation:



NEW QUESTION 65

Given:

```

try {
    // line 1
    lines.map(l -> l.toUpperCase())
        .forEach (line --> {
            try {
                Files.write(Paths.get("outputFile_to_path"),
line.getBytes(), StandardOpenOption.CREATE);
            } catch (IOException e) {
                e.printStackTrace();
            }
        });
} catch (IOException e) {
    e.printStackTrace();
}

```

You want to obtain the Stream object on reading the file. Which code inserted on line 1 will accomplish this?

- A. var lines = Files.lines(Paths.get(INPUT_FILE_NAME));
- B. Stream lines = Files.readAllLines(Paths.get(INPUT_FILE_NAME));
- C. var lines = Files.readAllLines(Paths.get(INPUT_FILE_NAME));
- D. Stream<String> lines = Files.lines(INPUT_FILE_NAME);

Answer: C

NEW QUESTION 68

Which describes an aspect of Java that contributes to high performance?

- A. Java prioritizes garbage collection.
- B. Java has a library of built-in functions that can be used to enable pipeline burst execution.
- C. Java monitors and optimizes code that is frequently executed.
- D. Java automatically parallelizes code execution.

Answer: C

NEW QUESTION 72

Given:

```

public class Confidential implements Serializable{
    private String data;

    public Confidential(String data) {
        this.data = data;
    }
}

```

Which two are secure serialization of these objects? (Choose two.)

- A. Define the serialPersistentFields array field.
- B. Declare fields transient.
- C. Implement only readResolve to replace the instance with a serial proxy and not writeReplace.
- D. Make the class abstract.
- E. Implement only writeReplace to replace the instance with a serial proxy and not readResolve.

Answer: AC

NEW QUESTION 74

Given:

```
public class DNASynth {
    int aCount;
    int tCount;
    int cCount;
    int gCount;

    int getACount(int aCount){
        return aCount;
    }
    int getTCount(int tCount){
        return this.tCount;
    }
    int getCCount(){
        return getTotalCount() - this.aCount - getTCount(0) - gCount;
    }
    int getGCount(){
        return getGCount();
    }
    int getTotalCount(){
        return aCount + getTCount(0) + this.cCount + this.gCount;
    }
}
```

Which two methods facilitate valid ways to read instance fields? (Choose two.)

- A. getTCount
- B. getACount
- C. getTotalCount
- D. getCCount
- E. getGCount

Answer: CD

NEW QUESTION 76

Given:

```
import java.util.function.BiFunction;
public class Pair<T> {
    final BiFunction<T, T, Boolean> validator;
    T left = null;
    T right = null;
    private Pair() {
        validator=null;
    }
    Pair(BiFunction<T, T, Boolean> v, T x, T y) {
        validator = v;
        set(x, y);
    }
    void set(T x, T y) {
        if (!validator.apply(x, y)) throw new IllegalArgumentException();
        setLeft(x);
        setRight(y);
    }
    void setLeft(T x) {
        left = x;
    }
    void setRight(T y) {
        right = y;
    }
    final boolean isValid() {
        return validator.apply(left, right);
    }
}
```

It is required that if p instanceof Pair then p.isValid() returns true.

Which is the smallest set of visibility changes to insure this requirement is met?

- A. setLeft and setRight must be protected.
- B. left and right must be private.
- C. isValid must be public.
- D. left, right, setLeft, and setRight must be private.

Answer: B

NEW QUESTION 77

Given:

```
public interface A {  
    public Iterable a();  
}  
public interface B extends A {  
    public Collection a();  
}  
public interface C extends A {  
    public Path a();  
}  
public interface D extends B, C {  
}
```

Why does D cause a compilation error?

- A. D inherits a() only from C.
- B. D inherits a() from B and C but the return types are incompatible.
- C. D extends more than one interface.
- D. D does not define any method.

Answer: B

NEW QUESTION 79

Which two statements are true about Java modules? (Choose two.)

- A. Modular jars loaded from --module-path are automatic modules.
- B. Any named module can directly access all classes in an automatic module.
- C. Classes found in -classpath are part of an unnamed module.
- D. Modular jars loaded from -classpath are automatic modules.
- E. If a package is defined in both the named module and the unnamed module, then the package in the unnamed module is ignored.

Answer: AC

NEW QUESTION 80

Which two are functional interfaces? (Choose two.)

- A.

```
@FunctionalInterface  
interface MyRunnable {  
    public void run();  
}
```
- B.

```
@FunctionalInterface  
interface MyRunnable {  
    public void run();  
    public void call();  
}
```
- C.

```
interface MyRunnable {  
    public default void run() {}  
    public void run(String s);  
}
```
- D.

```
@FunctionalInterface  
interface MyRunnable {  
}
```
- E.

```
interface MyRunnable {  
    @FunctionalInterface  
    public void run();  
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D
- E. Option E

Answer: CE

NEW QUESTION 83

Given this requirement:

Module vehicle depends on module part and makes its com.vehicle package available for all other modules. Which module-info.java declaration meets the

requirement?

A

```
module vehicle{
    requires part;
    exports com.vehicle;
}
```

B

```
module vehicle {
    requires part;
    uses com.vehicle;
}
```

C

```
module vehicle{
    requires part;
    exports com.vehicle to part;
}
```

D

```
module vehicle {
    requires com.vehicle;
    exports part;
}
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: A

NEW QUESTION 85

Given:


```
public class Test {
    public static void main(String[] args) {
        AnotherClass ac = new AnotherClass();
        SomeClass sc = new AnotherClass();
        ac = sc;
        sc.methodA();
        ac.methodA();
    }
}
class SomeClass {
    public void methodA() {
        System.out.println("SomeClass#methodA()");
    }
}
class AnotherClass extends SomeClass {
    public void methodA() {
        System.out.println("AnotherClass#methodA()");
    }
}
```

What is the result?

- A. A ClassCastException is thrown at runtime.
- B. AnotherClass#methodA()AnotherClass#methodA()
- C. The compilation fails.
- D. SomeClass#methodA()AnotherClass#methodA()
- E. AnotherClass#methodA()SomeClass#methodA()
- F. SomeClass#methodA()SomeClass#methodA()

Answer: C

Explanation:



```
1 public class Test {
2     public static void main (String[] args) {
3         AnotherClass ac = new AnotherClass();
4
5         ac = sc;
6         sc.methodA();
7         ac.methodA();
8     }
9 }
10 class SomeClass {
11     public void methodA() {
12         System.out.println("SomeClass#methodA()");
13     }
14 }
15
16 class AnotherClass extends SomeClass {
17     public void methodA() {
18         System.out.println("AnotherClass#methodA()");
19     }
20 }
```

NEW QUESTION 86

Which set of commands is necessary to create and run a custom runtime image from Java source files?

- A. java, jdeps
- B. javac, jlink
- C. jar, jlink
- D. javac, jar

Answer: B

NEW QUESTION 88

Which statement about access modifiers is correct?

- A. An instance variable can be declared with the static modifier.
- B. A local variable can be declared with the final modifier.
- C. An abstract method can be declared with the private modifier.
- D. An inner class cannot be declared with the public modifier.
- E. An interface can be declared with the protected modifier.

Answer: B

NEW QUESTION 91

Given:

```
public class Foo {
    private void print() {
        System.out.println("Bonjour le monde!");
    }
    public void foo() {
        print();
    }
}


public class Bar extends Foo {
    private void print() {
        System.out.println("Hello world!");
    }
    public void bar() {
        print();
    }
    public static void main(String... args) {
        Bar b = new Bar();
        b.foo();
        b.bar();
    }
}
```

What is the output?

- A. Hello world!Bonjour le monde!
- B. Hello world!Hello world!
- C. Bonjour le monde!Hello world!
- D. Bonjour le monde!Bonjour le monde!

Answer: C

Explanation:



```
Console 1 x Console 2 x

Bonjour le monde!
Hello world!

Completed with exit code: 0
```

NEW QUESTION 92

Given: Automobile.java

```
public abstract class Automobile { //line 1
    abstract void wheels();
}
```

Car.java

```
public class Car extends Automobile {
    // line 2
    void wheels(int i) { // line 3
        System.out.print(4);
    }
    public static void main(String[] args) {
        Automobile ob = new Car(); // line 4
        ob.wheels();
    }
}
```

What must you do so that the code prints 4?

- A. Remove the parameter from wheels method in line 3.
- B. Add @Override annotation in line 2.
- C. Replace the code in line 2 with Car ob = new Car();
- D. Remove abstract keyword in line 1.

Answer: B

Explanation:

```

1  Car is not abstract and does not override abstract method wheels() in
   Automobile
2  public class Car extends Automobile {
3
4      void wheels(int i) {
5          System.out.print(4);
6      }
7      public static void main(String[] args) {
8          Automobile ob = new Car();
9          ob.wheels();
10     }
11 }

```

NEW QUESTION 96

Given:

/code/a/Test.java containing:

```

package a;
import b.Best;
public class Test {
    public static void main(String[] args) {
        Best b = new Best();
    }
}

```

and

/code/b/Best.java containing: package b;

```
public class Best { }
```

Which is the valid way to generate bytecode for all classes?

- A. java /code/a/Test.java
- B. javac -d /code /code/a/Test
- C. java /code/a/Test.java /code/b/Best.java
- D. java -cp /code a.Test
- E. javac -d /code /code/a/Test.java /code/b/Best.java
- F. javac -d /code /code/a/Test.java

Answer: E

NEW QUESTION 99

Given:

```

public class Employee {
    private String name;
    private String locality;
    /* the constructor, getter and setter methods code goes here */
}

```

and:

```

8. List<Employee> roster = new ArrayList<>();
9. long empCount = roster.stream()
10. /* insert code here */
11. System.out.print(empCount);

```

Which code, when inserted on line 10, prints the number of unique localities from the roster list?

- A. .map(Employee::getLocality).distinct().count();
- B. map(e -> e.getLocality()).count();
- C. .map(e -> e.getLocality()).collect(Collectors.toSet()).count();
- D. .filter(Employee::getLocality).distinct().count();

Answer: D

NEW QUESTION 100

Given the code fragment:

```
Path source = Paths.get("/repo/a/a.txt"); Path destination = Paths.get("/repo"); Files.move(source, destination); // line 1 Files.delete(source); // line 2
```

Assuming the source file and destination folder exist, what is the result?

- A. A java.nio.file.FileAlreadyExistsException is thrown on line 1.
- B. A java.nio.file.NoSuchFileException is thrown on line 2.
- C. A copy of /repo/a/a.txt is moved to the /repo directory and /repo/a/a.txt is deleted.
- D. a.txt is renamed repo.

Answer: C

NEW QUESTION 101

Which interface in the java.util.function package can return a primitive type?

- A. ToDoubleFunction
- B. Supplier
- C. BiFunction
- D. LongConsumer

Answer: A

NEW QUESTION 106

Given:


```
public class Main {
    public static void main(String[] args) {
        try {
            Path path = Paths.get("/u01/work/filestore.txt");
            boolean result = Files.deleteIfExists(path);
            if(result) System.out.println(path + "is deleted.");
            else System.out.println(path + "is not deleted.");
        } catch(IOException e) {
            System.out.println("Exception");
        }
    }
}
```

Assume the file on path does not exist. What is the result?

- A. The compilation fails.
- B. /u01/work/filestore.txt is not deleted.
- C. Exception
- D. /u01/work/filestore.txt is deleted.

Answer: A

Explanation:



NEW QUESTION 110

Given:

List<String> longlist = List.of("Hello","World","Beat"); List<String> shortlist = new ArrayList<>();
 Which code fragment correctly forms a short list of words containing the letter "e"?


```
A. longList.stream()
    .filter(w -> w.indexOf('e') != -1)
    .parallel()
    .forEach(w -> shortList.add(w));

B. longList.parallelStream()
    .filter(w -> w.indexOf('e') != -1)
    .forEach(w -> shortList.add(w));

C. shortList = longList.stream()
    .filter(w -> w.indexOf('e') != -1)
    .parallel()
    .collect(Collectors.toList());

D. longList.stream()
    .filter(w -> w.indexOf('e') != -1)
    .parallel()
    .collect(shortlist);
```

- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: C

NEW QUESTION 113

Given:

```
public class Over {
    public void analyze(Object[] o){
        System.out.println("I am an object array");
    }
    public void analyze(long[] l){
        System.out.println("I am an array");
    }
    public void analyze(Object o){
        System.out.println("I am an object");
    }
    public static void main(String[] args) {
        int[] nums = new int[10];
        new Over().analyze(nums); // line 1
    }
}
```

What is the output?

- A. I am an object array
- B. The compilation fails due to an error in line 1.
- C. I am an array
- D. I am an object

Answer: D

NEW QUESTION 114

Given:

```
List<String> list = ... ;
list.forEach( x -> { System.out.println(x); } );
```

What is the type of x?

- A. char
- B. List<Character>
- C. String
- D. List<String>

Answer: C

NEW QUESTION 118

Given:

```
package test.t1;
public class A {
    public int x = 42;
    protected A() {}           // line 1
}
```

and

```
package test.t2;
import test.t1.*;
public class B extends A {
    int x = 17;                 // line 2
    public B() { super(); }     // line 3
}
```

and

```
package test;
import test.t1.*;
import test.t2.*;
public class Tester {
    public static void main(String[] args) {
        A obj = new B();        // line 4
        System.out.println(obj.x); // line 5
    }
}
```

What is the result?

- A. 42
- B. The compilation fails due to an error in line 4.
- C. 17
- D. The compilation fails due to an error in line 3.
- E. The compilation fails due to an error in line 2.
- F. The compilation fails due to an error in line 1.
- G. The compilation fails due to an error in line 5.

Answer: A

NEW QUESTION 123

Given:


```
public class Tester {
    public static void main(String[] args) {
        byte x = 7, y = 6;
        // line 1
        System.out.println(z);
    }
}
```

Which expression when added at line 1 will produce the output of 1.17?

- A. float z = (float)(Math.round((float)x/y*100)/100);
- B. float z = Math.round((int)(x/y),2);
- C. float z = Math.round((float)x/y,2);
- D. float z = Math.round((float)x/y*100)/(float)100;

Answer: D

Explanation:



NEW QUESTION 127

Given the contents:

MessageBundle.properties file: message=Hello MessageBundle_en.properties file: message=Hello (en) MessageBundle_US.properties file: message=Hello (US) MessageBundle_en_US.properties file: message=Hello (en_US) MessageBundle_fr_FR.properties file: message=Bonjour and the code fragment: Locale.setDefault(Locale.FRANCE);
Locale currentLocale = new Locale.Builder().setLanguage("en").build();
ResourceBundle messages = ResourceBundle.getBundle("MessageBundle", currentLocale); System.out. println(messages.getString("message"));
Which file will display the content on executing the code fragment?

- A. MessageBundle_en_US.properties
- B. MessageBundle_en.properties
- C. MessageBundle_fr_FR.properties
- D. MessageBundle_US.properties
- E. MessageBundle.properties

Answer: C

NEW QUESTION 131

Given:

```
public class Main {  
    public static void main(String[] args) {  
        for(int i = 0; i < args.length; i++) {  
            System.out.println(i + "). " + args[i]);  
            switch(args[i]) {  
                case "one":  
                    continue;  
                case "two":  
                    i--;  
                    continue;  
                default:  
                    break;  
            }  
        }  
    }  
}
```

executed with this command: java Main one two three What is the result?

- A. 0). one
- B. 0). one1). two2). three
- C. The compilation fails.
- D. It creates an infinite loop printing:0). one1). two1). two...
- E. A java.lang.NullPointerException is thrown.

Answer: D

NEW QUESTION 134

Which code fragment compiles?

- A.

```
Comparator comparator = new Comparator<?>() {  
    public int compare(Integer i, Integer j) {  
        return i.compareTo(j);  
    }  
};
```
- B.

```
var comparator = new Comparator<>() {  
    public int compare(Integer i, Integer j) {  
        return i.compareTo(j);  
    }  
};
```
- C.

```
Comparator<> comparator = new Comparator<Integer>() {  
    public int compare(Integer i, Integer j) {  
        return i.compareTo(j);  
    }  
};
```
- D.

```
Comparator<Integer> comparator = new Comparator<>() {  
    public int compare(Integer i, Integer j) {  
        return i.compareTo(j);  
    }  
};
```


- A. Option A
- B. Option B
- C. Option C
- D. Option D

Answer: D

Explanation:

```

1 import java.io.*;
2 import java.util.*;
3 class abc {
4     public static void main(String[] args) {
5
6         Comparator<Integer> comparator = new Comparator<>() {
7             public int compare(Integer i, Integer j) {
8                 return i.compareTo(j);
9             }
10        };
11    }
12 }
13 }
14

```

NEW QUESTION 138

Given:

```

public class Price {
    private final double value;
    public Price(String value) {
        this(Double.parseDouble(value));
    }
    public Price(double value) {
        this.value = value;
    }
    public Price () {}
    public double getValue() { return value; }
    public static void main(String[] args) {
        Price p1 = new Price("1.99");
        Price p2 = new Price(2.99);
        Price p3 = new Price();
        System.out.println(p1.getValue()+" "+p2.getValue()+" "+p3.getValue());
    }
}

```

What is the result?

- A. The compilation fail
- B. 1.99,2.99,0
- C. 1.99,2.99,0.0
- D. 1.99,2.99

Answer: A

Explanation:

```

1
2 public class Price {
3     private final double value;
4     public Price(String value) {
5         this(Double.parseDouble (value));
6     }
7     public Price(double value) {
8         this.value = value;
9
10    }
11    public Price (){}
12    public double getValue() { return value; }
13    public static void main (String[] args) {
14        Price p1 = new Price("1.99");
15        Price p2 = new Price("2.99");
16        Price p3 = new Price();
17        System.out.println(p1.getValue()+" "+p2.getValue()+" "+p3.getValue());
18    }
19 }

```

✖ variable value might not have been initialized

NEW QUESTION 140

Given:

```
var fruits = List.of("apple", "orange", "banana", "lemon");
```

You want to examine the first element that contains the character n. Which statement will accomplish this?

- A. String result = fruits.stream().filter(f -> f.contains("n")).findAny();
- B. fruits.stream().filter(f -> f.contains("n")).forEachOrdered(System.out::print);
- C. Optional<String> result = fruits.stream().filter(f -> f.contains("n")).findFirst();
- D. Optional<String> result = fruits.stream().anyMatch(f -> f.contains("n"));

Answer: B

Explanation:

```
1 import java.io.*;
2 import java.util.*;
3 public class abc {
4     public static void main(String[] args) {
5
6         var fruits = List.of("apple", "orange", "banana", "lemon");
7
8         fruits.stream().filter(f -> f.contains("n")).forEachOrdered(System.out::print);
9
10    }
11 }
12
```

Execute Mode, Version, Inputs & Arguments

JDK 11.0.4



Interactive

Stdin Input

CommandLine Arguments



Execute



Result

CPU Time: 0.19 sec(s), Memory: 33200 kilobyte(s)

orangebanana lemon

NEW QUESTION 144

Given this enum declaration:

```
1. enum Alphabet {
2.     A, B, C
3.
4. }
```

Examine this code: System.out.println(Alphabet.getFirstLetter());

What code should be written at line 3 to make this code print A?

- A. final String getFirstLetter() { return A.toString(); }
- B. static String getFirstLetter() { return Alphabet.values()[1].toString(); }
- C. static String getFirstLetter() { return A.toString(); }
- D. String getFirstLetter() { return A.toString(); }

Answer: C

NEW QUESTION 149

.....

Thank You for Trying Our Product

We offer two products:

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

1Z0-819 Practice Exam Features:

- * 1Z0-819 Questions and Answers Updated Frequently
- * 1Z0-819 Practice Questions Verified by Expert Senior Certified Staff
- * 1Z0-819 Most Realistic Questions that Guarantee you a Pass on Your First Try
- * 1Z0-819 Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

100% Actual & Verified — Instant Download, Please Click
[Order The 1Z0-819 Practice Test Here](#)