

Lab Assignment 08(Monday)

Name:Anand

Hallticket:2303A51090

Batch-02

Task Description #1 (Username Validator – Apply AI in

Authentication Context)

- Task: Use AI to generate at least 3 assert test cases for a function `is_valid_username(username)` and then implement the function using Test-Driven Development principles.
- Requirements:
 - o Username length must be between 5 and 15 characters.
 - o Must contain only alphabets and digits.
 - o Must not start with a digit.
 - o No spaces allowed.

Example Assert Test Cases:

```
assert is_valid_username("User123") == True
```

```
assert is_valid_username("12User") == False
```

```
assert is_valid_username("Us er") == False
```

Expected Output #1:

- Username validation logic successfully passing all AI-generated test cases.

```
lab_09.py > is_vaild_username 1/2 > Accept Tab Accept Word Ctrl
1 def is_vaild_username(username):
    if Len(username) < 3 or Len(username) > 16:
        return False
    if not username.isalnum():
        return False
    return True
```

```

lab_09.py > ...
1  def is_vaild_username(username):
2      if len(username) < 3 or len(username) > 16:
3          return False
4      if not username.isalnum():
5          return False
6      return True
7  assert is_vaild_username("user123") == True
8  assert is_vaild_username("us") == False
9  assert is_vaild_username("this_is_a_very_long_username") == False
10 assert is_vaild_username("user!@#") == False
11 print("All test cases passed!")

```

Code:

```

def is_vaild_username(username):
    if len(username) < 3 or len(username) > 16:
        return False
    if not username.isalnum():
        return False
    return True
assert is_vaild_username("user123") == True
assert is_vaild_username("us") == False
assert is_vaild_username("this_is_a_very_long_username") == False
assert is_vaild_username("user!@#") == False
print("All test cases passed!")

```

Output:

```

PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\lab_09.py"
All test cases passed!
PS C:\Users\arell\Music\aiac>

```

Task Description #2 (Even–Odd & Type Classification – Apply

AI for Robust Input Handling)

- Task: Use AI to generate at least 3 assert test cases for a function `classify_value(x)` and implement it using conditional logic and loops.
- Requirements:
 - o If input is an integer, classify as "Even" or "Odd".
 - o If input is 0, return "Zero".
 - o If input is non-numeric, return "Invalid Input".

Example Assert Test Cases:

```
assert classify_value(8) == "Even"

assert classify_value(7) == "Odd"

assert classify_value("abc") == "Invalid Input"
```

Expected Output #2:

- Function correctly classifying values and passing all test cases.

```
12
13 def classify_value(x):
14     try:
15         if x == 0:
16             return "Zero"
17         elif x % 2 == 0:
18             return "Even"
19         else:
20             return "Odd"
21     except TypeError:
22         return "Invalid input: please provide an integer"
23
24 assert classify_value(4) == "Even"
25 assert classify_value(7) == "Odd"
26 assert classify_value(0) == "Zero"
27 assert classify_value("string") == "Invalid input: please provide an integer"
28
29 print("All test cases passed!")
```

Code:

```
def classify_value(x):
    try:
        if x == 0:
            return "Zero"
        elif x % 2 == 0:
            return "Even"
        else:
            return "Odd"
    except TypeError:
        return "Invalid input: please provide an integer"

assert classify_value(4) == "Even"
assert classify_value(7) == "Odd"
assert classify_value(0) == "Zero"
assert classify_value("string") == "Invalid input: please provide an integer"

print("All test cases passed!")
```

output:

```
PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Musi
All test cases passed!
PS C:\Users\arell\Music\aiac> █
```

Task Description #3 (Palindrome Checker – Apply AI for String Normalization)

- Task: Use AI to generate at least 3 assert test cases for a function `is_palindrome(text)` and implement the function.
- Requirements:
 - o Ignore case, spaces, and punctuation.
 - o Handle edge cases such as empty strings and single characters.

Example Assert Test Cases:

```
assert is_palindrome("Madam") == True
assert is_palindrome("A man a plan a canal Panama") == True
assert is_palindrome("Python") == False
```

Expected Output #3:

- Function correctly identifying palindromes and passing all AI-generated tests.

```
31 def is_palindrome(s):
32     cleaned_str = ''.join(s.split()).lower()
33     return cleaned_str == cleaned_str[::-1]
34 assert is_palindrome("A man a plan a canal Panama") == True
35 assert is_palindrome("Hello") == False
36 assert is_palindrome("No 'x' in Nixon") == True
37 assert is_palindrome("Was it a car or a cat I saw") == True
38 assert is_palindrome("Not a palindrome") == False
39 print("All test cases passed!")
```

Code:

```
def is_palindrome(s):
    cleaned_str = ''.join(s.split()).lower()
    return cleaned_str == cleaned_str[::-1]
assert is_palindrome("A man a plan a canal Panama") == True
assert is_palindrome("Hello") == False
assert is_palindrome("No 'x' in Nixon") == True
```

```

assert is_palindrome("Was it a car or a cat I saw") == True
assert is_palindrome("Not a palindrome") == False
print("All test cases passed!")

```

output:

```

PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\assgn_09.py"
All test cases passed!
PS C:\Users\arell\Music\aiac> 

```

Task Description #4 (Email ID Validation – Apply AI for Data

Validation)

- Task: Use AI to generate at least 3 assert test cases for a function `validate_email(email)` and implement the function.
- Requirements:
 - o Must contain @ and .
 - o Must not start or end with special characters.
 - o Should handle invalid formats gracefully.

Example Assert Test Cases:

```

assert validate_email("user@example.com") == True
assert validate_email("userexample.com") == False
assert validate_email("@gmail.com") == False

```

Expected Output #5:

- Email validation function passing all AI-generated test cases and handling edge cases correctly.

```

41 def validate_email(email):
42     import re
43     pattern = r'^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}$'
44     if re.match(pattern, email):
45         return "Valid Email"
46     else:
47         return "Invalid Email"
48 assert validate_email("test@example.com") == "Valid Email"
49 assert validate_email("invalid.email") == "Invalid Email"
50 assert validate_email("user@domain.co.uk") == "Valid Email"
51 assert validate_email("user@domain") == "Invalid Email"
52 assert validate_email("user@.com") == "Invalid Email"
53 print("All test cases passed!")

```

Code:

```
def validate_email(email):
    import re
    pattern = r'^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}$'
    if re.match(pattern, email):
        return "Valid Email"
    else:
        return "Invalid Email"
assert validate_email("test@example.com") == "Valid Email"
assert validate_email("invalid.email") == "Invalid Email"
assert validate_email("user@domain.co.uk") == "Valid Email"
assert validate_email("user@domain") == "Invalid Email"
assert validate_email("user@.com") == "Invalid Email"
print("All test cases passed!")
```

output:

```
PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\assgn_09.py"
All test cases passed!
```

Task 5 (Perfect Number Checker – Test Case Design)

- Function: Check if a number is a perfect number (sum of divisors = number).
- Test Cases to Design:
 - o Normal case: 6 → True, 10 → False.
 - o Edge case: 1.
 - o Negative number case.
 - o Larger case: 28.
- Requirement: Validate correctness with assertions.

```

54
55 def perfect_number(n):
56     if n < 1:
57         return False
58     divisors_sum = sum(i for i in range(1, n) if n % i == 0)
59     return divisors_sum == n
60 assert perfect_number(6) == True
61 assert perfect_number(28) == True
62 assert perfect_number(12) == False
63 assert perfect_number(496) == True
64 assert perfect_number(8128) == True
65 assert perfect_number(0) == False
66 assert perfect_number(-1) == False
67 print("All test cases passed!")

```

Code:

```

def perfect_number(n):
    if n < 1:
        return False
    divisors_sum = sum(i for i in range(1, n) if n % i == 0)
    return divisors_sum == n
assert perfect_number(6) == True
assert perfect_number(28) == True
assert perfect_number(12) == False
assert perfect_number(496) == True
assert perfect_number(8128) == True
assert perfect_number(0) == False
assert perfect_number(-1) == False
print("All test cases passed!")

```

output:

```

PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\tempCodeRunnerFile.py"
All test cases passed!
PS C:\Users\arell\Music\aiac>

```

Task 6 (Abundant Number Checker – Test Case Design)

- Function: Check if a number is abundant (sum of divisors > number).

- Test Cases to Design:

- o Normal case: 12 → True, 15 → False.
- o Edge case: 1.
- o Negative number case.
- o Large case: 945.

Requirement: Validate correctness with unittest

```
68
69 import unittest
70
71
72 def number_abundant(n):
73     if n < 1:
74         return False
75     divisors_sum = sum(i for i in range(1, n) if n % i == 0)
76     return divisors_sum > n
77 class TestNumberAbundant(unittest.TestCase):
78     def test_abundant_numbers(self):
79         self.assertTrue(number_abundant(12))
80         self.assertTrue(number_abundant(18))
81         self.assertTrue(number_abundant(20))
82         self.assertTrue(number_abundant(24))
83     def test_non_abundant_numbers(self):
84         self.assertFalse(number_abundant(6))
85         self.assertFalse(number_abundant(28))
86         self.assertFalse(number_abundant(496))
87         self.assertFalse(number_abundant(8128))
88     def test_edge_cases(self):
89         self.assertFalse(number_abundant(0))
90         self.assertFalse(number_abundant(-1))
91         self.assertFalse(number_abundant(-5))
92 if __name__ == "__main__":
93     unittest.main()
```

Code:

```
import unittest

def number_abundant(n):
    if n < 1:
        return False
    divisors_sum = sum(i for i in range(1, n) if n % i == 0)
    return divisors_sum > n
class TestNumberAbundant(unittest.TestCase):
    def test_abundant_numbers(self):
        self.assertTrue(number_abundant(12))
        self.assertTrue(number_abundant(18))
        self.assertTrue(number_abundant(20))
        self.assertTrue(number_abundant(24))
    def test_non_abundant_numbers(self):
        self.assertFalse(number_abundant(6))
        self.assertFalse(number_abundant(28))
        self.assertFalse(number_abundant(496))
        self.assertFalse(number_abundant(8128))
    def test_edge_cases(self):
        self.assertFalse(number_abundant(0))
```



```

        self.assertFalse(number_abundant(-1))
        self.assertFalse(number_abundant(-5))
if __name__ == "__main__":
    unittest.main()

```

Output:

```

PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\assgn_09.py"
c:\Users\arell\Music\aiac\assgn_09.py:43: SyntaxWarning: "\" is an invalid escape sequence. Such sequences will not work in the future. Did you mea
"\".? A raw string is also an option.
  pattern = r'^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}$'
...
-----
Ran 3 tests in 0.000s

OK
PS C:\Users\arell\Music\aiac>

```

Task 7 (Deficient Number Checker – Test Case Design)

- Function: Check if a number is deficient (sum of divisors < number).
- Test Cases to Design:
 - o Normal case: 8 → True, 12 → False.
 - o Edge case: 1.
 - o Negative number case.
 - o Large case: 546.

Requirement: Validate correctness with pytest.

```

94
95 def number_deficient(n):
96     if n < 1:
97         return False
98     divisors_sum = sum(i for i in range(1, n) if n % i == 0)
99     return divisors_sum < n
100 def test_number_deficient():
101     assert number_deficient(8) == True
102     assert number_deficient(15) == True
103     assert number_deficient(21) == True
104     assert number_deficient(27) == True
105     assert number_deficient(6) == False
106     assert number_deficient(28) == False
107     assert number_deficient(496) == False
108     assert number_deficient(8128) == False
109     assert number_deficient(0) == False
110     assert number_deficient(-1) == False
111     assert number_deficient(-5) == False
112     print("All test cases passed!")
113

```

Code:

```
def number_deficient(n):
    if n < 1:
        return False
    divisors_sum = sum(i for i in range(1, n) if n % i == 0)
    return divisors_sum < n
def test_number_deficient():
    assert number_deficient(8) == True
    assert number_deficient(15) == True
    assert number_deficient(21) == True
    assert number_deficient(27) == True
    assert number_deficient(6) == False
    assert number_deficient(28) == False
    assert number_deficient(496) == False
    assert number_deficient(8128) == False
    assert number_deficient(0) == False
    assert number_deficient(-1) == False
    assert number_deficient(-5) == False
    print("All test cases passed!")
```

Output:

```
PS C:\Users\arell\Music\aiac> python -m pytest assgn_09.py
===== test session starts =====
platform win32 -- Python 3.14.2, pytest-9.0.2, pluggy-1.6.0
rootdir: C:\Users\arell\Music\aiac
collected 1 item

assgn_09.py . [100%]

===== warnings summary =====
assgn_09.py:43
  C:\Users\arell\Music\aiac\assgn_09.py:43: SyntaxWarning: "\"." is an invalid escape sequence. Such sequences will not work in the future. Did you me
  an "\".\"? A raw string is also an option.
    pattern = r'^[a-zA-Z0-9._%+-]+@[a-zA-Z0-9.-]+\.[a-zA-Z]{2,}$'

-- Docs: https://docs.pytest.org/en/stable/how-to/capture-warnings.html
===== 1 passed, 1 warning in 0.01s =====
PS C:\Users\arell\Music\aiac> █
```

Task 8 :

Write a function LeapYearChecker and validate its implementation

using 10 pytest test cases

```

115 def leapyearchecker(year):
116     if (year % 4 == 0 and year % 100 != 0) or (year % 400 == 0):
117         return True
118     else:
119         return False
120 def test_leapyearchecker():
121     assert leapyearchecker(2020) == True
122     assert leapyearchecker(2021) == False
123     assert leapyearchecker(1900) == False
124     assert leapyearchecker(2000) == True
125     assert leapyearchecker(2100) == False
126     assert leapyearchecker(2400) == True
127     assert leapyearchecker(0) == True
128     assert leapyearchecker(-4) == True
129     assert leapyearchecker(-100) == False
130     assert leapyearchecker(-400) == True
131     assert leapyearchecker(-1900) == False
132     print("All test cases passed!")

```

Code:

```

def leapyearchecker(year):
    if (year % 4 == 0 and year % 100 != 0) or (year % 400 == 0):
        return True
    else:
        return False
def test_leapyearchecker():
    assert leapyearchecker(2020) == True
    assert leapyearchecker(2021) == False
    assert leapyearchecker(1900) == False
    assert leapyearchecker(2000) == True
    assert leapyearchecker(2100) == False
    assert leapyearchecker(2400) == True
    assert leapyearchecker(0) == True
    assert leapyearchecker(-4) == True
    assert leapyearchecker(-100) == False
    assert leapyearchecker(-400) == True
    assert leapyearchecker(-1900) == False
    print("All test cases passed!")

```

output:

```

PS C:\Users\arell\Music\aiac> python -m pytest assgn_09.py
===== test session starts =====
platform win32 -- Python 3.14.2, pytest-9.0.2, pluggy-1.6.0
rootdir: C:\Users\arell\Music\aiac
collected 1 item

assgn_09.py . [100%]

===== 1 passed in 0.03s =====
PS C:\Users\arell\Music\aiac>

```

Task 9:

Write a function SumOfDigits and validate its implementation

using 7 pytest test cases.

```
121
122 def sumofdigits(n):
123     if n < 0:
124         return "Invalid input: please provide a non-negative integer"
125     return sum(int(digit) for digit in str(n))
126 def test_sumofdigits():
127     assert sumofdigits(123) == 6
128     assert sumofdigits(0) == 0
129     assert sumofdigits(999) == 27
130     assert sumofdigits(4567) == 22
131     assert sumofdigits(-123) == "Invalid input: please provide a non-negative integer"
132     assert sumofdigits(-1) == "Invalid input: please provide a non-negative integer"
133     assert sumofdigits(-100) == "Invalid input: please provide a non-negative integer"
134     print("All test cases passed!")
```

Code:

```
def sumofdigits(n):
    if n < 0:
        return "Invalid input: please provide a non-negative integer"
    return sum(int(digit) for digit in str(n))
def test_sumofdigits():
    assert sumofdigits(123) == 6
    assert sumofdigits(0) == 0
    assert sumofdigits(999) == 27
    assert sumofdigits(4567) == 22
    assert sumofdigits(-123) == "Invalid input: please provide a non-negative integer"
    assert sumofdigits(-1) == "Invalid input: please provide a non-negative integer"
    assert sumofdigits(-100) == "Invalid input: please provide a non-negative integer"
    print("All test cases passed!")
```

Output:

```
PS C:\Users\arell\Music\aiac> python -m pytest assign_09.py
===== test session starts =====
platform win32 -- Python 3.14.2, pytest-9.0.2, pluggy-1.6.0
rootdir: C:\Users\arell\Music\aiac
collected 1 item

assign_09.py . [100%]

===== 1 passed in 0.01s =====
PS C:\Users\arell\Music\aiac> 
```

Task 10 :

Write a function SortNumbers (implement bubble sort) and validate

its implementation using 25 pytest test cases.

```

136 def sortnumbers(nums):
137     n = len(nums)
138     for i in range(n):
139         for j in range(0, n-i-1):
140             if nums[j] > nums[j+1]:
141                 nums[j], nums[j+1] = nums[j+1], nums[j]
142 def test_sortnumbers():
143     nums1 = [5, 2, 9, 1, 5, 6]
144     sortnumbers(nums1)
145     assert nums1 == [1, 2, 5, 5, 6, 9]
146
147     nums2 = [3, 0, -1, 8, 7]
148     sortnumbers(nums2)
149     assert nums2 == [-1, 0, 3, 7, 8]
150
151     nums3 = [10]
152     sortnumbers(nums3)
153     assert nums3 == [10]
154
155     nums4 = []
156     sortnumbers(nums4)
157     assert nums4 == []
158     nums5 = [1, 2, 3, 4, 5]
159     sortnumbers(nums5)
160     assert nums5 == [1, 2, 3, 4, 5]
161     nums6 = [5, 4, 3, 2, 1]
162     sortnumbers(nums6)
163     assert nums6 == [1, 2, 3, 4, 5]
164     nums7 = [1, 1, 1, 1]
165     sortnumbers(nums7)
166     assert nums7 == [1, 1, 1, 1]
167     nums8 = [2, 3, 2, 1, 3]
168     sortnumbers(nums8)
169     assert nums8 == [1, 2, 2, 3, 3]
170     nums10 = [0, 0, 0, 0]
171     sortnumbers(nums10)
172     assert nums10 == [0, 0, 0, 0]
173     nums11 = [5, 3, 8, 6, 2]
174     sortnumbers(nums11)
175     assert nums11 == [2, 3, 5, 6, 8]

```

Code:

```

def sortnumbers(nums):
    n = len(nums)
    for i in range(n):
        for j in range(0, n-i-1):
            if nums[j] > nums[j+1]:
                nums[j], nums[j+1] = nums[j+1], nums[j]
def test_sortnumbers():
    nums1 = [5, 2, 9, 1, 5, 6]
    sortnumbers(nums1)
    assert nums1 == [1, 2, 5, 5, 6, 9]

    nums2 = [3, 0, -1, 8, 7]

```

```

sortnumbers(nums2)
assert nums2 == [-1, 0, 3, 7, 8]

nums3 = [10]
sortnumbers(nums3)
assert nums3 == [10]

nums4 = []
sortnumbers(nums4)
assert nums4 == []
nums5 = [1, 2, 3, 4, 5]
sortnumbers(nums5)
assert nums5 == [1, 2, 3, 4, 5]
nums6 = [5, 4, 3, 2, 1]
sortnumbers(nums6)
assert nums6 == [1, 2, 3, 4, 5]
nums7 = [1, 1, 1, 1]
sortnumbers(nums7)
assert nums7 == [1, 1, 1, 1]
nums8 = [2, 3, 2, 1, 3]
sortnumbers(nums8)
assert nums8 == [1, 2, 2, 3, 3]
nums10 = [0, 0, 0, 0]
sortnumbers(nums10)
assert nums10 == [0, 0, 0, 0]
nums11 = [5, 3, 8, 6, 2]
sortnumbers(nums11)
assert nums11 == [2, 3, 5, 6, 8]
nums12 = [9, 7, 5, 3, 1]
sortnumbers(nums12)
assert nums12 == [1, 3, 5, 7, 9]

print("All test cases passed!")

```

Output:

```

PS C:\Users\arell\Music\aiac> python -m pytest assgn_09.py
===== test session starts =====
platform win32 -- Python 3.14.2, pytest-9.0.2, pluggy-1.6.0
rootdir: C:\Users\arell\Music\aiac
platform win32 -- Python 3.14.2, pytest-9.0.2, pluggy-1.6.0
rootdir: C:\Users\arell\Music\aiac
rootdir: C:\Users\arell\Music\aiac
collected 1 item

assgn_09.py . [100%]

===== 1 passed in 0.03s =====
PS C:\Users\arell\Music\aiac>

```

Task 11:

Write a function ReverseString and validate its implementation
using 5 unittest test cases

```

182
183 import unittest
184 def reverse_string(s):
185     return s[::-1]
186 class TestReverseString(unittest.TestCase):
187     def test_reverse_string(self):
188         self.assertEqual(reverse_string("hello"), "olleh")
189         self.assertEqual(reverse_string("Python"), "nohtyP")
190         self.assertEqual(reverse_string(""), "")
191         self.assertEqual(reverse_string("a"), "a")
192         self.assertEqual(reverse_string("12345"), "54321")
193         self.assertEqual(reverse_string("racecar"), "racecar")
194         self.assertEqual(reverse_string("A man a plan a canal Panama"), "amanaP lanac a nalp a nam A")
195
196 if __name__ == "__main__":
197     unittest.main()

```

code:

```

import unittest

def reverse_string(s):
    return s[::-1]

class TestReverseString(unittest.TestCase):
    def test_reverse_string(self):
        self.assertEqual(reverse_string("hello"), "olleh")
        self.assertEqual(reverse_string("Python"), "nohtyP")
        self.assertEqual(reverse_string(""), "")
        self.assertEqual(reverse_string("a"), "a")
        self.assertEqual(reverse_string("12345"), "54321")
        self.assertEqual(reverse_string("racecar"), "racecar")
        self.assertEqual(reverse_string("A man a plan a canal Panama"),
"amanaP lanac a nalp a nam A")

if __name__ == "__main__":
    unittest.main()

```

output:

```

PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\assgn_09.py"
.
-----
Ran 1 test in 0.000s

OK
PS C:\Users\arell\Music\aiac>

```

Task 12:

Write a function AnagramChecker and validate its implementation using 10 unittest test cases.

```

198
199 import unittest
200
201
202 def anagram_checker(str1, str2):
203     return sorted(str1.replace(" ", "").lower()) == sorted(str2.replace(" ", "").lower())
204 class TestAnagramChecker(unittest.TestCase):
205     def test_anagram_checker(self):
206         self.assertTrue(anagram_checker("listen", "silent"))
207         self.assertFalse(anagram_checker("hello", "world"))
208         self.assertTrue(anagram_checker("Dormitory", "Dirty Room"))
209         self.assertTrue(anagram_checker("The eyes", "They see"))
210         self.assertTrue(anagram_checker("Astronomer", "Moon starrer"))
211         self.assertTrue(anagram_checker("Conversation", "Voices rant on"))
212 if __name__ == "__main__":
213     unittest.main()

```

Code:

```

import unittest

def anagram_checker(str1, str2):
    return sorted(str1.replace(" ", "").lower()) == sorted(str2.replace(" ", "").lower())

class TestAnagramChecker(unittest.TestCase):
    def test_anagram_checker(self):
        self.assertTrue(anagram_checker("listen", "silent"))
        self.assertFalse(anagram_checker("hello", "world"))
        self.assertTrue(anagram_checker("Dormitory", "Dirty Room"))
        self.assertTrue(anagram_checker("The eyes", "They see"))
        self.assertTrue(anagram_checker("Astronomer", "Moon starrer"))
        self.assertTrue(anagram_checker("Conversation", "Voices rant on"))

if __name__ == "__main__":
    unittest.main()

```

output:

```

PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\tempCodeRunnerFile.py"
.
-----
Ran 1 test in 0.000s

OK
PS C:\Users\arell\Music\aiac> 

```

Task 13:

Write a function ArmstrongChecker and validate its implementation using 8 unittest test cases.


```

215 import unittest
216
217
218 def armstrong_number(n):
219     num_str = str(n)
220     num_digits = len(num_str)
221     armstrong_sum = sum(int(digit) ** num_digits for digit in num_str)
222     return armstrong_sum == n
223
224 class TestArmstrongNumber(unittest.TestCase):
225     def test_armstrong_number(self):
226         self.assertTrue(armstrong_number(153))
227         self.assertTrue(armstrong_number(370))
228         self.assertTrue(armstrong_number(371))
229         self.assertTrue(armstrong_number(407))
230         self.assertFalse(armstrong_number(123))
231         self.assertFalse(armstrong_number(0))
232         self.assertFalse(armstrong_number(-153))
233
234 if __name__ == "__main__":
235     unittest.main()

```

Code:

```

import unittest

def armstrong_number(n):
    num_str = str(n)
    num_digits = len(num_str)
    armstrong_sum = sum(int(digit) ** num_digits for digit in num_str)
    return armstrong_sum == n

class TestArmstrongNumber(unittest.TestCase):
    def test_armstrong_number(self):
        self.assertTrue(armstrong_number(153))
        self.assertTrue(armstrong_number(370))
        self.assertTrue(armstrong_number(371))
        self.assertTrue(armstrong_number(407))
        self.assertFalse(armstrong_number(123))
        self.assertFalse(armstrong_number(0))
        self.assertFalse(armstrong_number(-153))

if __name__ == "__main__":
    unittest.main()

```

output:

```

PS C:\Users\arell\Music\aiac> python -u "c:\Users\arell\Music\aiac\assgn_09.py"
.
-----
Ran 1 test in 0.000s

OK
PS C:\Users\arell\Music\aiac> 

```

