

Lab Assignment-10.1

Name:D.BHARATH KUMAR

Hallticket:2303A51097

Batch-02

Task Description #1 – Syntax and Logic Errors

Task: Use AI to identify and fix syntax and logic errors in a faulty Python script.

Sample Input Code:


Calculate average score of a student

```
def calc_average(marks):  
    total = 0  
    for m in marks:  
        total += m  
    average = total / len(marks)  
  
    return avrage # Typo here  
  
marks = [85, 90, 78, 92]  
  
print("Average Score is ", calc_average(marks))
```

Expected Output:

- Corrected and runnable Python code with explanations of the fixes.

Privous code:



```
assg_10_1.py > total  
1 def calc_average(marks):  
2     total = 0  
3     for m in marks:  
4         total += m  
5         average = total / len(marks)  
6     return avrage # Typo here  
7     return average # Fixed typo here  
8     marks = [85, 90, 78, 92]  
9     print("Average Score is ", calc_average(marks))
```

Corrected code:

```

assg_10_1.py > ...
1  def calc_average(marks):
2      total = 0
3      for m in marks:
4          total += m
5      average = total / len(marks)
6      return average # Fixed typo here
7  marks = [85, 90, 78, 92]
8  print("Average Score is ", calc_average(marks))

```

```

PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC> & C:\Users\BHARATH\AppData\Local\Programs\Python\Python313\python.exe c:/U
sers/BHARATH/OneDrive/Pictures/Desktop/AIAC/assg_10_1.py
Average Score is 86.25
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC>

```

Task Description #2 – PEP 8 Compliance

Task: Use AI to refactor Python code to follow PEP 8 style guidelines.

Sample Input Code:

```

def area_of_rect(L,B) : return L*B

print(area_of_rect(10,20))

```

Expected Output:

- Well-formatted PEP 8-compliant Python code.

Code:

```

9  #refactor the below code to include error handling and input validation
10 def area_of_rect(L,B) :
    → if not isinstance(L, (int, float)) or not isinstance(B, (int, float)):
        raise TypeError("Length and breadth must be numbers.")
    if L < 0 or B < 0:
        raise ValueError("Length and breadth must be non-negative.")
11     return L*B
12 print(area_of_rect(10,20))
13

```

```

8     print( Average Score is : , calc_average(marks))
9     #refactor the below code to include error handling and input validation
10    def area_of_rect(L,B) :
11        if not isinstance(L, (int, float)) or not isinstance(B, (int, float)):
12            raise TypeError("Length and breadth must be numbers.")
13        if L < 0 or B < 0:
14            raise ValueError("Length and breadth must be non-negative.")
15        return L*B
16    print(area_of_rect(10,20))
17

```

Output:

```

Average Score is : 88.125
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC> & C:\Users\BHARATH\AppData\Local\Programs\Python\Python313\python.exe c:/U
sers/BHARATH/OneDrive/Pictures/Desktop/AIAC/assg_10_1.py
200
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC>

```

Task Description #3 – Readability Enhancement

Task: Use AI to make code more readable without changing its logic.

Sample Input Code:

```

def c(x,y):

    return x*y/100

a=200

b=15

print(c(a,b))

```

Expected Output:

- Python code with descriptive variable names, inline comments, and clear formatting.

Code:

```

18    #refacto the below code discriptive variable names and inline comments to each line and clear formatting
19
20    def c(x,y):
21        return x*y/100
22    a=200
23    b=15
24    print(c(a,b))
25

```

```

def calculate_percentage(value, total):
    """Calculate percentage of a value relative to a total."""
    if total == 0:
        raise ValueError("Total cannot be zero.")
    return (value / total) * 100

a = 200
b = 15
print(calculate_percentage(a, b))

```

```

18  #refacto the below code discriptive variable names and inline comments to each line and clear formatting
19
20  def calculate_percentage(value, total):
21      """Calculate percentage of a value relative to a total."""
22      if total == 0:
23          raise ValueError("Total cannot be zero.")
24      return (value / total) * 100
25
26  a = 200
27  b = 15
28  print(calculate_percentage(a, b))
29
30  |

```

Output:

```

PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC> & C:\Users\BHARATH\AppData\Local\Programs\Python\Python313\python.exe c:/Users/BHARATH/OneDrive/Pictures/Desktop/AIAC/assg_10_1.py
1333.3333333333335
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC> |

```

Task Description #4 – Refactoring for Maintainability

Task: Use AI to break repetitive or long code into reusable functions.

Sample Input Code:

```

students = ["Alice", "Bob", "Charlie"]

print("Welcome", students[0])

print("Welcome", students[1])

print("Welcome", students[2])

```

Expected Output:

- Modular code with reusable functions.

```

30  #refactor the below code with modular code with reusable functions and error handling
31  def add_student(students, student_name):
32      students = ["Alice", "Bob", "Charlie"]
33      print("Welcome", students[0])
34      print("Welcome", students[1])
35      print("Welcome", students[2])
36

```

```

30 #refactor the below code with modular code with reusable functions and error handling
31
32 def validate_name(name):
33     """Validate that name is a non-empty string."""
34     if not isinstance(name, str) or not name.strip():
35         raise ValueError("Student name must be a non-empty string.")
36     return name.strip()
37
38 def welcome_student(student_name):
39     """Welcome a student by name."""
40     try:
41         validated_name = validate_name(student_name)
42         print(f"Welcome {validated_name}")
43     except ValueError as e:
44         print(f"Error: {e}")
45
46 def process_students(students):
47     """Process and welcome a list of students."""
48     if not isinstance(students, list):
49         raise TypeError("Students must be a list.")
50     for student in students:
51         welcome_student(student)
52
53 # Main execution
54 students = ["Alice", "Bob", "Charlie"]
55 process_students(students)
56

```

Output:

```

PS C:\User> & C:\Users\BHARATH\AppData\Local\Programs\Python\Python313\python.exe c:/Users/BHARATH/OneDrive/Pictures/Desktop/AIAC/assg_10_1.py
Welcome Alice
Welcome Bob
Welcome Charlie
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC>

```

Task Description #5 – Performance Optimization

Task: Use AI to make the code run faster.

Sample Input Code:

Find squares of numbers

```
nums = [i for i in range(1,1000000)]
```

```
squares = []
```

```
for n in nums:
```

```
    squares.append(n**2)
```

```
print(len(squares))
```

Expected Output:

- Optimized code using list comprehensions or vectorized

operations.

Code:

```
30 #refactor the below code and optimize the code with the list comprehension and include error handling and input validation
31 nums = [i for i in range(1,1000000)]
32 → squares = []          squares = [n**2 for n in nums]
33 for n in nums:
34     squares.append(n**2)
35 print(len(squares))
36
29
30 # Refactor with list comprehension, error handling, and input validation
31 def calculate_squares(start, end):
32     """Calculate squares of numbers in a range with validation."""
33     if not isinstance(start, int) or not isinstance(end, int):
34         raise TypeError("Start and end must be integers.")
35     if start < 0 or end < 0:
36         raise ValueError("Start and end must be non-negative.")
37     if start > end:
38         raise ValueError("Start must be less than or equal to end.")
39
40     # Use generator expression for memory efficiency
41     squares = [n**2 for n in range(start, end)]
42     return squares
43
44 try:
45     result = calculate_squares(1, 1000000)
46     print(len(result))
47 except (TypeError, ValueError) as e:
48     print(f"Error: {e}")
49
50
51
```

Output:

```
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC> & C:\Users\BHARATH\AppData\Local\Programs\Python\Python313\python.exe c:/Users/BHARATH/OneDrive/Pictures/Desktop/AIAC/assg_10_1.py
999999
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC> █
```

Task Description #6 – Complexity Reduction

Task: Use AI to simplify overly complex logic.

Sample Input Code:

```
def grade(score):
    if score >= 90:
        return "A"
    else:
```

```
    if score >= 80:
        return "B"
    else:
        if score >= 70:
            return "C"
        else:
            if score >= 60:
                return "D"
            else:
                return "F"
```

Expected Output:

- Cleaner logic using elif or dictionary mapping.

Code:

```
49 #refactor the below code and cleaner the logic using elif or dictionary mapping
50 |
51 def grade(score):
52 ↵ if score >= 90: if score >= 90:
53     return "A"         return "A"
54     else:             elif score >= 80:
55     if score >= 80:     return "B"
56     return "B"         elif score >= 70:
57     else:             return "C"
58     if score >= 70:     elif score >= 60:
59     return "C"         return "D"
60     else:             else:
61     if score >= 60:     return "F"
62     return "D"
63     else:
64     return "F"
65
66
67
68
```

```

49 : Refactor with dictionary mapping for cleaner logic
50 def grade(score):
51     if not isinstance(score, (int, float)):
52         raise TypeError("Score must be a number.")
53     if score < 0 or score > 100:
54         raise ValueError("Score must be between 0 and 100.")
55
56     # Dictionary mapping for grade ranges
57     grade_map = {
58         90: "A",
59         80: "B",
60         70: "C",
61         60: "D",
62         0: "F"
63     }
64
65     # Return grade based on score thresholds
66     for threshold in sorted(grade_map.keys(), reverse=True):
67         if score >= threshold:
68             return grade_map[threshold]
69
70 try:
71     print(grade(85))
72 except (TypeError, ValueError) as e:
73     print(f"Error: {e}")
74

```

Output:

```

PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC> & C:\Users\BHARATH\AppData\Local\Programs\Python\Python313\python.exe c:/U
sers/BHARATH/OneDrive/Pictures/Desktop/AIAC/assg_10_1.py
A
PS C:\Users\BHARATH\OneDrive\Pictures\Desktop\AIAC>

```