AI ASSISTED CODING
ASSIGNMENT - 17.1
ROLL NO. 2303A510C8

Task 1 – Customer Data Cleaning
Task:
Use AI to generate a Python script for cleaning a customer dataset.
Instructions:
• Handle missing values in columns (age, income, city).
• Remove duplicate records.
• Standardize text values (e.g., city names in lowercase).
• Encode categorical variables (gender, city).
Sample Code:

```
import pandas as pd
data = pd.read
_
csv("shopping_
trends.csv")
print(data.head())
```

Dataset link:
https://www.kaggle.com/datasets/iamsouravbanerjee/customer-shopping-trends-dataset?select=shopping_
trends.csv
Expected Output:
• A cleaned Pandas data frame ready for analysis

Prompt:
Generate a complete Python script for Google Colab that performs customer dataset cleaning according to these requirements:
Task – Customer Data Cleaning
Instructions:
• Download the dataset using kagglehub:
iamsouravbanerjee/customer-shopping-trends-dataset
• Detect the correct CSV file inside the downloaded folder and load it with pandas.• Clean the dataset with the following steps:
– Handle missing values:
* Age, Annual Income → fill with mean
* Location → fill with mode
– Remove duplicate rows
– Standardize text columns (Location in lowercase)
– Encode categorical variables:
* Gender → label encoding
* Location → one-hot encoding
• After cleaning, output:
– DataFrame info before and after cleaning
– First 10 rows of the cleaned DataFrame
– Number of duplicates removed

– Total missing values handled

Requirements:

• Use only the dataset loaded from kagglehub

• No manual file uploads

• Code only, no explanations

• All steps must run directly in Colab without modification

Produce only the complete Python script.

Code:

```
import pandas as pd
import os
from sklearn.preprocessing import LabelEncoder
# You already downloaded the dataset using kagglehub
# Now load the CSV directly from the downloaded folder
import kagglehub
path =
kagglehub.dataset_download("iamsouravbanerjee/customer-shopping-trends-dat
aset")print("Dataset path:", path)
# Find the CSV file inside the downloaded directory
csv_path = os.path.join(path, "shopping_trends.csv")
# Load the dataset
df = pd.read_csv(csv_path)
print("Dataset loaded from:", csv_path)
print("\n--- Initial DataFrame Info ---")
df.info()
print("\nInitial Head:")
print(df.head())
# ---------------------------------------------
# CLEANING BEGINS
# ---------------------------------------------
initial_rows = len(df)
initial_missing_values = df.isnull().sum().sum()
# 1. Handle missing values
numeric_cols = ["Age", "Annual Income"]
text_cols = ["Location"]
for col in numeric_cols:
if col in df.columns:
df[col] = df[col].fillna(df[col].mean())
for col in text_cols:
if col in df.columns:
df[col] = df[col].fillna(df[col].mode()[0])
# 2. Remove duplicates
before = len(df)
df = df.drop_duplicates()
removed_duplicates_count = before - len(df)
# 3. Standardize text columns
if "Location" in df.columns:df["Location"] = df["Location"].str.lower()
# 4. Encode categorical variables
# Label encode Gender
if "Gender" in df.columns:
le = LabelEncoder()
df["Gender_encoded"] = le.fit_transform(df["Gender"])
# One-hot encode Location (city)
if "Location" in df.columns:
df = pd.get_dummies(df, columns=["Location"], prefix="city",
dtype=int)
```

```python
# Stats after cleaning
final_missing_values = df.isnull().sum().sum()
removed_missing_values = initial_missing_values - final_missing_values
# ---------------------------------------------
# OUTPUT
# ---------------------------------------------
print("\n--- Cleaned DataFrame Info ---")
df.info()
print("\nFirst 10 rows:")
print(df.head(10))
print("\n--- Summary of Cleaning ---")
print(f"Initial rows: {initial_rows}")
print(f"Rows after duplicate removal: {len(df)}")
print(f"Duplicate records removed: {removed_duplicates_count}")
print(f"Missing values handled: {removed_missing_values}")
print("\nCleaned DataFrame ready for analysis.")
```

Output:

```
Using Colab cache for faster access to the 'customer-shopping-trends-dataset'
dataset.
Dataset path: /kaggle/input/customer-shopping-trends-dataset
```

```
Dataset loaded from:
/kaggle/input/customer-shopping-trends-dataset/shopping_trends.csv

--- Initial DataFrame Info ---
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 3900 entries, 0 to 3899
Data columns (total 19 columns):
 #   Column                    Non-Null Count  Dtype
---  ------                    --------------  -----
 0   Customer ID               3900 non-null   int64
 1   Age                       3900 non-null   int64
 2   Gender                    3900 non-null   object
 3   Item Purchased            3900 non-null   object
 4   Category                  3900 non-null   object
 5   Purchase Amount (USD)     3900 non-null   int64
 6   Location                  3900 non-null   object
 7   Size                      3900 non-null   object
 8   Color                     3900 non-null   object
 9   Season                    3900 non-null   object
 10  Review Rating             3900 non-null   float64
 11  Subscription Status       3900 non-null   object
 12  Payment Method            3900 non-null   object
 13  Shipping Type             3900 non-null   object
 14  Discount Applied          3900 non-null   object
 15  Promo Code Used           3900 non-null   object
 16  Previous Purchases        3900 non-null   int64
 17  Preferred Payment Method  3900 non-null   object
 18  Frequency of Purchases    3900 non-null   object
dtypes: float64(1), int64(4), object(14)
memory usage: 579.0+ KB

First 10 rows:
   Customer ID  Age Gender Item Purchased     Category  Purchase Amount (USD)  \
0            1   55   Male         Blouse     Clothing                     53
1            2   19   Male        Sweater     Clothing                     64
2            3   50   Male          Jeans     Clothing                     73
3            4   21   Male        Sandals     Footwear                     90
4            5   45   Male         Blouse     Clothing                     49
5            6   46   Male       Sneakers     Footwear                     20
6            7   63   Male          Shirt     Clothing                     85
7            8   27   Male         Shorts     Clothing                     34
8            9   26   Male           Coat    Outerwear                     97
9           10   57   Male        Handbag  Accessories                     31

  Size      Color  Season  Review Rating  ... city_south dakota  \
0    L       Gray  Winter            3.1  ...                 0
1    L     Maroon  Winter            3.1  ...                 0
```

```
2    S     Maroon  Spring            3.1  ...                0
3    M     Maroon  Spring            3.5  ...                0
4    M  Turquoise  Spring            2.7  ...                0
5    M      White  Summer            2.9  ...                0
6    M       Gray    Fall            3.2  ...                0
7    L   Charcoal  Winter            3.2  ...                0
8    L     Silver  Summer            2.6  ...                0
9    M       Pink  Spring            4.8  ...                0

  city_tennessee city_texas city_utah city_vermont  city_virginia  \
0              0          0         0            0              0
1              0          0         0            0              0
2              0          0         0            0              0
3              0          0         0            0              0
4              0          0         0            0              0
5              0          0         0            0              0
6              0          0         0            0              0
7              0          0         0            0              0
8              0          0         0            0              0
9              0          0         0            0              0

  city_washington city_west virginia  city_wisconsin  city_wyoming
0               0                  0               0             0
1               0                  0               0             0
2               0                  0               0             0
3               0                  0               0             0
4               0                  0               0             0
5               0                  0               0             1
6               0                  0               0             0
7               0                  0               0             0
8               0                  1               0             0
9               0                  0               0             0

[10 rows x 69 columns]

--- Summary of Cleaning ---
Initial rows: 3900
Rows after duplicate removal: 3900
Duplicate records removed: 0
Missing values handled: 0

Cleaned DataFrame ready for analysis.
```

Task 2 – Sales Data Preprocessing

Task:

Preprocess sales transaction data using AI assistance.

Instructions:
• Convert date columns into datetime format.
• Create new features (month, year, day of week).
• Normalize sales amount column.
• Detect and handle outliers in dataset.
Sample Code:
```
import pandas as pd
data = pd.read
_
csv("sales
_
data.csv")
print(data.head())
```
Dataset link:
https://www.kaggle.com/datasets/vinothkannaece/sales-dataset?select=sales
data.csv
_
Expected Output:
• A transformed dataset with time-based features and normalized values
Prompt:
Generate a complete Python script for Google Colab that preprocesses a sales dataset using the following requirements:
Task – Sales Data Preprocessing
Instructions:
• Download the dataset using kagglehub: vinothkannaece/sales-dataset
• Detect the correct CSV file inside the downloaded folder and

load it with pandas.• Convert all date columns into datetime format.

• Create new time-based features:

– Month

– Year

– Day of week

• Normalize the sales amount column.

• Detect outliers in the dataset and handle them appropriately.

• After preprocessing, output:

– A summary of all transformations applied

– The transformed DataFrame

Requirements:

• Script must run directly in Colab.

• Use only the dataset downloaded via kagglehub.

• Do not include explanations, only the complete Python code.

Code:

```
import pandas as pd
import os
import kagglehub
from sklearn.preprocessing import StandardScaler
import numpy as np
# --- 1. Download the dataset using kagglehub ---
dataset_name = "vinothkannaece/sales-dataset"
path = kagglehub.dataset_download(dataset_name)
print(f"Dataset downloaded to: {path}")
# --- 2. Detect the correct CSV file and load it ---
csv_files = [f for f in os.listdir(path) if f.endswith('.csv')]
df = pd.DataFrame()
if not csv_files:
empty DataFrame.")
print("Error: No CSV file found in the downloaded dataset. Creating anelse:
# Try to find a CSV with 'sales' in its name, otherwise pick the first
one
main_csv_file = next((f for f in csv_files if 'sales' in f.lower()),
csv_files[0])
csv_path = os.path.join(path, main_csv_file)
print(f"Loading dataset from: {csv_path}")
df = pd.read_csv(csv_path)
if df.empty:
print("DataFrame is empty after attempting to load CSV. Aborting
further processing.")
else:
print("\n--- Initial DataFrame Info ---")
```

```
df.info()
print("\nInitial Head:")
print(df.head())
# Store initial state for summary
initial_rows = len(df)
transformation_summary = []
# --- 3. Convert all date columns into datetime format and create new
features ---
# Updated date_cols_candidates to include 'Sale_Date'
date_cols_candidates = ['OrderDate', 'Date', 'InvoiceDate',
'SaleDate', 'Order Date', 'Sale_Date'] # Common date column names
converted_date_cols = []
for col in df.columns:
if col in date_cols_candidates:
# Make a copy to avoid SettingWithCopyWarning if original
column is modified later
temp_col = df[col].copy()
# Try to convert to datetime, errors='coerce' will turn
unparseable dates into NaT
df[col] = pd.to_datetime(temp_col, errors='coerce')# Drop rows where date conversion failed (NaT values)
if a
significant portion
# For now, just drop rows with NaT in this specific date
column
initial_count = len(df)
df.dropna(subset=[col], inplace=True)
if len(df) < initial_count:
transformation_summary.append(f"Removed {initial_count -
len(df)} rows due to unparseable dates in '{col}'.")
if not df[col].empty:
converted_date_cols.append(col)
# Create new time-based features from the first
successfully converted date column
# This ensures we don't create multiple 'Month', 'Year'
columns if there are many date cols
if f'{col}_Month' not in df.columns:
df[f'{col}_Month'] = df[col].dt.month
df[f'{col}_Year'] = df[col].dt.year
df[f'{col}_DayOfWeek'] = df[col].dt.dayofweek #
Monday=0, Sunday=6
transformation_summary.append(f"Created 'Month',
'Year', 'DayOfWeek' features from '{col}'.")
transformation_summary.append(f"Converted column '{col}'
to datetime format.")
if not converted_date_cols:
transformation_summary.append("No suitable date columns found or
converted.")
# --- 4. Normalize the sales amount column ---
# Updated sales_col_candidate to include 'Sales_Amount'
sales_col_candidate = ['Sales', 'Amount', 'Purchase Amount', 'Unit
Cost', 'Sales_Amount'] # Common sales amount column names
sales_col = None
for col in df.columns:
if col in sales_col_candidate and
pd.api.types.is_numeric_dtype(df[col]):
sales_col = colbreak
if sales_col:
scaler = StandardScaler()
df[f'{sales_col}_Normalized'] =
```

```
scaler.fit_transform(df[[sales_col]])
transformation_summary.append(f"Normalized column '{sales_col}'
using StandardScaler. New column: '{sales_col}_Normalized'.")
else:
transformation_summary.append("No suitable sales amount column
found for normalization. Skipping normalization.")
# --- 5. Detect outliers in the dataset and handle them appropriately
---
# Using IQR method for the identified sales column
if sales_col and not df[sales_col].empty: # Ensure sales_col exists
and is not empty
Q1 = df[sales_col].quantile(0.25)
Q3 = df[sales_col].quantile(0.75)
IQR = Q3 - Q1
lower_bound = Q1 - 1.5 * IQR
upper_bound = Q3 + 1.5 * IQR
outliers_count = df[(df[sales_col] < lower_bound) | (df[sales_col]
> upper_bound)].shape[0]
# Capping outliers
df[sales_col] = np.where(df[sales_col] < lower_bound, lower_bound,
df[sales_col])
df[sales_col] = np.where(df[sales_col] > upper_bound, upper_bound,
df[sales_col])
transformation_summary.append(f"Handled {outliers_count} outliers
in '{sales_col}' by capping with IQR method. (Lower Bound:
{lower_bound:.2f}, Upper Bound: {upper_bound:.2f})")
else:
transformation_summary.append("Outlier detection and handling
skipped as no suitable sales amount column was found or it was empty.")# --- Remove duplicates (good
practice for preprocessing) ---
initial_rows_before_dedup = len(df)
df.drop_duplicates(inplace=True)
duplicates_removed_count = initial_rows_before_dedup - len(df)
if duplicates_removed_count > 0:
transformation_summary.append(f"Removed {duplicates_removed_count}
duplicate rows.")
else:
transformation_summary.append("No duplicate rows found or
removed.")
# --- Output ---
print("\n--- Summary of all transformations applied ---")
for summary_item in transformation_summary:
print(f"- {summary_item}")
print("\n--- Transformed DataFrame Info ---")
df.info()
print("\nTransformed DataFrame Head:")
print(df.head())
print("\nTransformed DataFrame ready for analysis.")
# Display the full transformed DataFrame (as requested by previous
interactions)
display(df)
print("\n--- Displaying the full transformed DataFrame ---")
```

Output:

```
Using Colab cache for faster access to the
'sales-dataset' dataset.
Dataset downloaded to: /kaggle/input/sales-dataset
Loading dataset from:
/kaggle/input/sales-dataset/sales_data.csv
```

```
--- Summary of all transformations applied ---
- Created 'Month', 'Year', 'DayOfWeek' features from
'Sale_Date'.
- Converted column 'Sale_Date' to datetime format.
- Normalized column 'Sales_Amount' using
StandardScaler. New column:
'Sales_Amount_Normalized'.
- Handled 0 outliers in 'Sales_Amount' by capping
with IQR method. (Lower Bound: -4885.42, Upper
Bound: 14943.17)
- No duplicate rows found or removed.

--- Transformed DataFrame Info ---
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1000 entries, 0 to 999
Data columns (total 18 columns):
 #   Column                  Non-Null Count  Dtype
---  ------                  --------------  -----
 0   Product_ID              1000 non-null   int64
 1   Sale_Date               1000 non-null
datetime64[ns]
 2   Sales_Rep               1000 non-null   object
 3   Region                  1000 non-null   object
 4   Sales_Amount            1000 non-null
float64
 5   Quantity_Sold           1000 non-null   int64
 6   Product_Category        1000 non-null   object
 7   Unit_Cost               1000 non-null
float64
```

```
 8   Unit_Price                1000 non-null
float64
 9   Customer_Type             1000 non-null   object
 10  Discount                  1000 non-null
float64
 11  Payment_Method            1000 non-null   object
 12  Sales_Channel             1000 non-null   object
 13  Region_and_Sales_Rep      1000 non-null   object
 14  Sale_Date_Month           1000 non-null   int32
 15  Sale_Date_Year            1000 non-null   int32
 16  Sale_Date_DayOfWeek       1000 non-null   int32
 17  Sales_Amount_Normalized   1000 non-null
float64
dtypes: datetime64[ns](1), float64(5), int32(3),
int64(2), object(7)
memory usage: 129.0+ KB

Transformed DataFrame Head:
   Product_ID  Sale_Date Sales_Rep Region
Sales_Amount  Quantity_Sold  \
0        1052 2023-02-03       Bob  North
5053.97             18
1        1093 2023-04-21       Bob   West
4384.02             17
2        1015 2023-09-21     David  South
4631.23             30
3        1072 2023-08-24       Bob  South
2167.94             39
4        1061 2023-03-24   Charlie   East
```

```
3750.20             13

  Product_Category  Unit_Cost  Unit_Price
Customer_Type  Discount  \
0        Furniture     152.75      267.22
Returning      0.09
1        Furniture    3816.39     4209.44
Returning      0.11
2             Food     261.56      371.40
Returning      0.20
3         Clothing    4330.03     4467.75
New      0.02
4      Electronics     637.37      692.71
New      0.08

  Payment_Method Sales_Channel Region_and_Sales_Rep
Sale_Date_Month  \
0           Cash        Online            North-Bob
2
1           Cash        Retail             West-Bob
4
2  Bank Transfer        Retail          South-David
9
3    Credit Card        Retail            South-Bob
8
4    Credit Card        Online         East-Charlie
3

   Sale_Date_Year  Sale_Date_DayOfWeek
```

```
Sales_Amount_Normalized
0            2023                    4
0.012197
1            2023                    4
-0.223256
2            2023                    3
-0.136374
3            2023                    3
-1.002094
4            2023                    4
-0.446011

Transformed DataFrame ready for analysis.
```

Task 3 – Healthcare Data Preparation

Task:

Clean and preprocess a healthcare dataset using AI scripts.

Instructions:

• Handle missing values in blood
_pressure, cholesterol.

• Encode categorical features

• Scale numerical features (min-max or standard scaling).

• Split dataset into training and testing sets.

Dataset link :
https://www.kaggle.com/datasets/abdallaahmed77/healthcare-risk
-
factors-dataset

Expected Output:

• A preprocessed dataset ready for machine learning models.

Prompt:Generate a complete Python script for Google Colab that

prepares a healthcare dataset according to these requirements:
Task – Healthcare Data Preparation
Instructions:
• Download the dataset using kagglehub:
abdallaahmed77/healthcare-risk-factors-dataset
• Detect and load the correct CSV file from the downloaded folder using pandas.
• Handle missing values in the following columns:
– blood
_pressure
– cholesterol
• Encode categorical features in the dataset.
• Scale numerical features using either min-max scaling or standard scaling.
• Split the dataset into training and testing sets.
• After preprocessing, output:
– A summary of all preprocessing steps
– The final preprocessed dataset (features and labels)
Requirements:
• Use only the dataset obtained from kagglehub.
• Provide only Python code without explanations.
• The script should run directly in Colab with no additional modifications.
Code:

```
# ---------------------------------------
# Task 3 - Healthcare Data Preparation# ---------------------------------------
import pandas as pd
import numpy as np
import kagglehub
import os
from sklearn.preprocessing import LabelEncoder, MinMaxScaler,
StandardScaler
from sklearn.model_selection import train_test_split
# Download dataset
path =
")
```

```
kagglehub.dataset_download("abdallaahmed77/healthcare-risk-factors-dataset
print("Dataset path:", path)
# Detect CSV file
csv_file = None
for f in os.listdir(path):
if f.endswith(".csv"):
csv_file = os.path.join(path, f)
df = pd.read_csv(csv_file)
print("\nLoaded dataset from:", csv_file)
print("\n--- Initial Data Info ---")
df.info()
print(df.head())
# Store initial info
initial_missing = df.isnull().sum().sum()
# Handle missing values
for col in ["blood_pressure", "cholesterol"]:
if col in df.columns:
if df[col].dtype != "object":
df[col] = df[col].fillna(df[col].mean())
else:
df[col] = df[col].fillna(df[col].mode()[0])# Encode categorical features
for col in df.select_dtypes(include="object").columns:
le = LabelEncoder()
df[col] = le.fit_transform(df[col])
# Scale numerical features
numeric_cols = df.select_dtypes(include=["int64", "float64"]).columns
scaler = MinMaxScaler()
df[numeric_cols] = scaler.fit_transform(df[numeric_cols])
# Split dataset
X = df.drop(df.columns[-1], axis=1) design)
y = df[df.columns[-1]]
# assume last col is target (dataset
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42)
# Output
print("\n--- Summary ---")
print("Initial missing values:", initial_missing)
print("Missing values after cleaning:", df.isnull().sum().sum())
print("Training set shape:", X_train.shape)
print("Testing set shape:", X_test.shape)
print("\n--- Preprocessed DataFrame ---")
df
```

Output:

```
Downloading to
/root/.cache/kagglehub/datasets/abdallaahmed77/healt
hcare-risk-factors-dataset/1.archive...
100%|                    | 1.28M/1.28M [00:00<00:00,
94.6MB/s]Extracting files...
Dataset path:
```

```
/root/.cache/kagglehub/datasets/abdallaahmed77/healt
hcare-risk-factors-dataset/versions/1

Loaded dataset from:
/root/.cache/kagglehub/datasets/abdallaahmed77/healt
hcare-risk-factors-dataset/versions/1/dirty_v3_path.
csv
--- Summary ---
Initial missing values: 22500
Missing values after cleaning: 13500
Training set shape: (24000, 19)
Testing set shape: (6000, 19)

--- Preprocessed DataFrame ---
        Age  Gender  Medical Condition   Glucose
Blood Pressure       BMI  \
0  0.455696     0.5           0.428571  0.391428
0.401144  0.431680
1  0.151899     0.5           0.571429  0.171904
0.256540  0.378609
2  0.506329     1.0           0.142857  0.251249
NaN  0.302155
3  0.594937     1.0           0.857143       NaN
0.369988  0.626271
4  0.708861     0.0           0.714286  0.250947
0.683121  0.476820
5  0.506329     0.5           0.714286  0.290687
0.641251  0.359089
6  0.886076     0.5           0.714286       NaN
```

```
0.659130  0.451403
7  0.506329     0.5           0.285714       NaN
0.406796  0.380236
8  0.632911     0.0           0.857143       NaN
NaN  0.565677
9  0.037975     0.0           0.142857  0.235689
0.345997  0.438593

   Oxygen Saturation  LengthOfStay  Cholesterol
Triglycerides     HbA1c  \
0           0.670348      0.277778     0.518390
0.524877  0.476872
1           0.705592      0.055556     0.265915
0.342102  0.179515
2           0.535714      0.055556     0.453891
0.423050  0.255507
3           0.683506      0.222222     0.388288
0.460844  0.400881
4           0.643562      0.166667     0.623667
0.311561  0.297357
5           0.650846      0.222222     0.523035
0.509358  0.242291
6           0.715461      0.111111     0.576378
0.339535  0.298458
7           0.357378      1.000000     0.432265
0.360977  0.324890
8           0.730968      0.111111     0.643314
0.488052  0.390969
9           0.715461      0.277778     0.372030
```

```
0.419221  0.319383

   Smoking  Alcohol  Physical Activity  Diet Score
Family History  \
0      0.0      0.0           0.216283    0.383056
0.0
1      0.0      0.0           0.733375    0.553946
0.0
2      0.0      0.0           0.540087    0.463432
1.0
3      0.0      0.0           0.425109    0.370746
0.0
4      0.0      1.0           0.449969    0.372918
0.0
5      1.0      0.0           0.540087    0.463432
0.0
6      1.0      1.0           0.348042    0.543809
1.0
7      1.0      0.0           0.560597    0.368573
0.0
8      0.0      0.0           0.331883    0.343230
0.0
9      1.0      0.0           0.556246    0.534395
0.0

   Stress Level  Sleep Hours  random_notes
noise_col
0      0.419788     0.509132      1.000000
0.312605
```

```
1      0.464505     0.699772      0.666667
0.455579
2      0.309111     0.368721      0.666667
0.580072
3      0.304639     0.426941      1.000000
0.518549
4      0.493013     0.576484      1.000000
0.519281
5      0.541643     0.543379      0.666667
0.591527
6      0.597541     0.643836      0.666667
0.476305
7      0.626048     0.382420      0.000000
0.541343
8      0.467859     0.488584      1.000000
0.520445
9      0.532700     0.436073      1.000000
0.416166
```

Task 4 – Employee Salary Data Preprocessing

Task:

Clean and preprocess an employee salary dataset using AI scripts.

Instructions:

- Handle missing values
- Detect and remove salary outliers.
- Standardize department names (lowercase).
- Apply label encoding to job location, department.

Dataset link:https://www.kaggle.com/code/vishantmathur/employee-salary
Expected Output:
• A structured dataset ready for HR analytics.
Prompt:
Generate a complete Python script for Google Colab that preprocesses an employee salary dataset according to the following requirements:
Task – Employee Salary Data Preprocessing
Instructions:
• Download the dataset using kagglehub: vishantmathur/employee-salary
• Detect and load the correct CSV file from the downloaded folder using pandas.
• Handle missing values in the dataset.
• Detect salary outliers and remove them from the data.
• Standardize the department names by converting them to lowercase.
• Apply label encoding to the following categorical columns:
– job location
– department
• After preprocessing, output:
– A summary of all the preprocessing operations performed
– The final cleaned and structured dataset
Requirements:
• Use only the dataset downloaded via kagglehub.
• Output only the Python code with no explanations.• The script must run directly in Google Colab without modifications.
Code:

```
# ------------------------------------------------
# Task 4 - Employee Salary Data Preprocessing
# ------------------------------------------------
import pandas as pd
import numpy as np
import kagglehub
import os
from sklearn.preprocessing import LabelEncoder
# Download dataset
path = kagglehub.dataset_download("vishantmathur/employee-salary")
print("Dataset path:", path)
# Detect CSV file
csv_file = None
for f in os.listdir(path):
if f.endswith(".csv"):
csv_file = os.path.join(path, f)
df = pd.read_csv(csv_file)
print("\nLoaded dataset from:", csv_file)
print("\n--- Initial Data Info ---")
df.info()
print(df.head())
# Store initial missing count
initial_missing = df.isnull().sum().sum()
# Handle missing values
df = df.fillna(df.mode().iloc[0]) # safe generic fill
# Detect & remove salary outliers
if "Salary" in df.columns:Q1 = df["Salary"].quantile(0.25)
Q3 = df["Salary"].quantile(0.75)
IQR = Q3 - Q1
lower = Q1 - 1.5 * IQR
upper = Q3 + 1.5 * IQR
df = df[(df["Salary"] >= lower) & (df["Salary"] <= upper)]
# Standardize department names
if "department" in df.columns:
df["department"] = df["department"].str.lower()
# Label encode job location & department
for col in ["job_location", "department"]:
if col in df.columns:
le = LabelEncoder()
df[col] = le.fit_transform(df[col])
# Output
print("\n--- Summary ---")
print("Initial missing values:", initial_missing)
print("Missing values after cleaning:", df.isnull().sum().sum())
print("Dataset shape after removing outliers:", df.shape)
print("\n--- Final Preprocessed DataFrame ---")
df
```

Output:

```
$ python preprocess_salary.py
Loading dataset...
Dataset shape before cleaning: (1000, 5)

Handling missing values...
Missing values handled.

Detecting and removing salary outliers...
```

```
2    S     Maroon  Spring           3.1  ...                0
3    M     Maroon  Spring           3.5  ...                0
4    M  Turquoise  Spring           2.7  ...                0
5    M      White  Summer           2.9  ...                0
6    M       Gray    Fall           3.2  ...                0
7    L   Charcoal  Winter           3.2  ...                0
8    L     Silver  Summer           2.6  ...                0
9    M       Pink  Spring           4.8  ...                0

  city_tennessee city_texas city_utah city_vermont  city_virginia  \
0              0          0         0            0              0
1              0          0         0            0              0
2              0          0         0            0              0
3              0          0         0            0              0
4              0          0         0            0              0
5              0          0         0            0              0
6              0          0         0            0              0
7              0          0         0            0              0
8              0          0         0            0              0
9              0          0         0            0              0

  city_washington city_west virginia  city_wisconsin  city_wyoming
0               0                  0               0             0
1               0                  0               0             0
2               0                  0               0             0
3               0                  0               0             0
4               0                  0               0             0
5               0                  0               0             1
6               0                  0               0             0
7               0                  0               0             0
8               0                  1               0             0
9               0                  0               0             0

[10 rows x 69 columns]

--- Summary of Cleaning ---
Initial rows: 3900
Rows after duplicate removal: 3900
Duplicate records removed: 0
Missing values handled: 0

Cleaned DataFrame ready for analysis.
```

```
2    S     Maroon  Spring           3.1  ...                0
3    M     Maroon  Spring           3.5  ...                0
4    M  Turquoise  Spring           2.7  ...                0
5    M      White  Summer           2.9  ...                0
6    M       Gray    Fall           3.2  ...                0
7    L   Charcoal  Winter           3.2  ...                0
8    L     Silver  Summer           2.6  ...                0
9    M       Pink  Spring           4.8  ...                0

  city_tennessee city_texas city_utah city_vermont  city_virginia  \
0              0          0         0            0              0
1              0          0         0            0              0
2              0          0         0            0              0
3              0          0         0            0              0
4              0          0         0            0              0
5              0          0         0            0              0
6              0          0         0            0              0
7              0          0         0            0              0
8              0          0         0            0              0
9              0          0         0            0              0

  city_washington city_west virginia  city_wisconsin  city_wyoming
0               0                  0               0             0
1               0                  0               0             0
2               0                  0               0             0
3               0                  0               0             0
4               0                  0               0             0
5               0                  0               0             1
6               0                  0               0             0
7               0                  0               0             0
8               0                  1               0             0
9               0                  0               0             0

[10 rows x 69 columns]

--- Summary of Cleaning ---
Initial rows: 3900
Rows after duplicate removal: 3900
Duplicate records removed: 0
Missing values handled: 0

Cleaned DataFrame ready for analysis.
```