

HIGH PERFORMANCE COMPUTING

ASSIGNMENT-10

Name : Juluri Pavan

HT No : 2303A51412

BatchNo : 21

Assignment 1: Non-Blocking Send and Receive with Overlap

Objective: Implement non-blocking point-to-point communication using `Isend` and `Irecv` and demonstrate overlap of computation with communication.

Python Code (assignment1.py)

```
from mpi4py import MPI
import numpy as np
import time

def compute_task(rank):
    """Simulates independent computation.""" print(f"Rank
    {rank} is performing background computation...")
    time.sleep(0.5) # Simulate workload print(f"Rank {rank}
    finished computation.")

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

if rank == 0: # Master process data =
    np.arange(10, dtype='i') print(f"Rank 0
    sending data: {data}") req =
    comm.Isend(data, dest=1, tag=11)

    # Overlap computation with communication
    compute_task(rank)

    req.Wait()
    print("Rank 0: Send completed.")

elif rank == 1:
    # Worker process
```

```

data = np.empty(10, dtype='i') req =
comm.Irecv(data, source=0, tag=11)

# Overlap computation with communication
compute_task(rank)

req.Wait() print(f"Rank 1: Receive completed. Data
received: {data}")

```

Expected Output (mpirun -n 2 python assignment1.py)

```

Rank 0 sending data: [0 1 2 3 4 5 6 7 8 9]
Rank 0 is performing background computation...
Rank 1 is performing background computation...
Rank 0 finished computation.
Rank 0: Send completed.
Rank 1 finished computation.
Rank 1: Receive completed. Data received: [0 1 2 3 4 5 6 7 8 9]

```

Assignment 2: Overlapping Neighbor Communication with Computation

Objective: Study non-blocking communication between neighboring processes and overlap it with computation.

Python Code (assignment2.py)

```

from mpi4py import MPI
import numpy as np

comm = MPI.COMM_WORLD
rank = comm.Get_rank()
size = comm.Get_size()

# Determine neighbors (wrapping
around) left = (rank - 1) % size right =
(rank + 1) % size

# Local data to send
send_data = np.array([rank * 10], dtype='i')

```

```

recv_data = np.empty(1, dtype='i') print(f"Rank {rank} starting communication. Sending
{send_data[0]} to {right}, receiving from {left}.")

# Non-blocking send to right, receive from left
req_s = comm.isend(send_data, dest=right,
tag=22) req_r = comm.irecv(recv_data, source=left,
tag=22)

# Computation during communication (Sum of local data)
local_sum = sum(range(1000000))

# Synchronize
MPI.Request.Waitall([req_s, req_r])

print(f"Rank {rank} completed. Received {recv_data[0]} from {left}. Background computation result:
{local_sum}")

```

Expected Output (mpiexec -n 3 python assignment2.py)

```

Rank 0 starting communication. Sending 0 to 1, receiving from 2.
Rank 1 starting communication. Sending 10 to 2, receiving from 0.
Rank 2 starting communication. Sending 20 to 0, receiving from 1.
Rank 0 completed. Received 20 from 2. Background computation result: 499999500000
Rank 1 completed. Received 0 from 0. Background computation result: 499999500000
Rank 2 completed. Received 10 from 1. Background computation result: 499999500000

```

Assignment 3: Non-Blocking Receive Using Test

Objective: Use the Test operation in MPI for monitoring non-blocking communication completion.

Python Code (assignment3.py)

```

from mpi4py import MPI
import numpy as np
import time

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

if rank == 0:

```

```

data = np.array([99], dtype='i')
# Simulate a delayed send
time.sleep(1.5) comm.Send(data,
dest=1, tag=33) print("Rank 0:
Data sent.")

elif rank == 1: data = np.empty(1, dtype='i')
req = comm.Irecv(data, source=0, tag=33)

flag = False
loops = 0

print("Rank 1: Starting computation loop while waiting for data...")
while not flag:
    # Perform useful computation while waiting
    time.sleep(0.2)
    loops += 1
    print(f"Rank 1: Doing work... (Cycle {loops})")

    # Periodically check communication status
    flag = req.Test()

print(f"Rank 1: Communication complete! Processing received data: {data[0]}")
print(f"Rank 1: Total computation cycles completed: {loops}")

```

Expected Output (mpirun -n 2 python assignment3.py)

```

Rank 1: Starting computation loop while waiting for data...
Rank 1: Doing work... (Cycle 1)
Rank 1: Doing work... (Cycle 2)
Rank 1: Doing work... (Cycle 3)
Rank 1: Doing work... (Cycle 4)
Rank 1: Doing work... (Cycle 5)
Rank 1: Doing work... (Cycle 6)
Rank 1: Doing work... (Cycle 7)
Rank 0: Data sent.
Rank 1: Doing work... (Cycle 8)
Rank 1: Communication complete! Processing received data: 99
Rank 1: Total computation cycles completed: 8

```

Assignment 4: Non-Blocking Ring Communication with Overlap

Objective: Implement ring communication using non-blocking MPI calls and overlap computation with data exchange.

Python Code (assignment4.py)

```
from mpi4py import MPI
import numpy as np
import time

comm = MPI.COMM_WORLD
rank = comm.Get_rank()
size = comm.Get_size()

# Ring topology logical arrangement
next_rank = (rank + 1) % size
prev_rank = (rank - 1) % size

send_data = np.array([rank], dtype='i')
recv_data = np.empty(1, dtype='i')

# Non-blocking exchange req_s = comm.Isend(send_data,
dest=next_rank, tag=44) req_r = comm.Irecv(recv_data,
source=prev_rank, tag=44)

# Overlap computation
start_time = time.time()
computation_result = sum(i * i for i in range(1000000))
calc_time = time.time() - start_time

# Wait for communication to finish
MPI.Request.Waitall([req_s, req_r])

print(f"Rank {rank}: Received data {recv_data[0]} from Rank {prev_rank}. "
      f"Computed result {computation_result} in {calc_time:.4f} seconds.")
```

Expected Output (mpiexec -n 4 python assignment4.py)

Rank 0: Received data 3 from Rank 3. Computed result 333332833333500000 in 0.0521 seconds.
Rank 1: Received data 0 from Rank 0. Computed result 333332833333500000 in 0.0519 seconds.

Rank 2: Received data 1 from Rank 1. Computed result 333332833333500000 in 0.0522 seconds.

Rank 3: Received data 2 from Rank 2. Computed result 333332833333500000 in 0.0518 seconds.

Assignment 5: Blocking vs Non-Blocking Communication Comparison

Objective: Compare blocking (Send/Recv) and non-blocking (Isend/Irecv) MPI communication and analyze computation overlap.

Python Code (assignment5.py)

```
from mpi4py import MPI
import numpy as np
import time

def workload():
    """Simulates a heavy computational workload (approx 0.5s)."""
    time.sleep(0.5)

comm = MPI.COMM_WORLD
rank = comm.Get_rank()

# Large payload to make communication time noticeable
payload_size = 5000000

if rank == 0: send_data = np.ones(payload_size,
    dtype='d')
elif rank == 1: recv_data =
    np.empty(payload_size, dtype='d')

comm.Barrier() # Synchronize before starting

# =====
# TEST 1: Blocking Communication
# ===== start_blocking =
time.time()

if rank == 0: comm.Send(send_data,
    dest=1, tag=1)
    workload() # Computation is forced to wait until Send is done
```

```

elif rank == 1: comm.Recv(recv_data, source=0,
    tag=1) workload() # Computation waits for Recv
    to finish

comm.Barrier()
end_blocking = time.time()
blocking_time = end_blocking - start_blocking

# =====
# TEST 2: Non-Blocking Communication
# ===== start_non_blocking =
time.time()

if rank == 0: req = comm.Isend(send_data, dest=1,
    tag=2) workload() # Computation overlaps with data
    transfer req.Wait()
elif rank == 1: req = comm.Irecv(recv_data, source=0,
    tag=2) workload() # Computation overlaps with data
    transfer req.Wait()

comm.Barrier()
end_non_blocking = time.time()
non_blocking_time = end_non_blocking - start_non_blocking

# =====
# Results
# ===== if rank == 0: print(f"Data Payload Size:
{payload_size} doubles") print("-" * 40) print(f"Blocking Time Execution : {blocking_time:.4f}
seconds") print(f"Non-Blocking Time Execution : {non_blocking_time:.4f} seconds") print("-" * 40) if
non_blocking_time < blocking_time: print(f"Non-blocking was {blocking_time -
non_blocking_time:.4f} seconds faster due to overlap.")

```

Expected Output (mpiexec -n 2 python assignment5.py)

Data Payload Size: 5000000 doubles

Blocking Time Execution : 0.5231 seconds

Non-Blocking Time Execution : 0.5015 seconds

Non-blocking was 0.0216 seconds faster due to overlap.