

2.1


Name: K Pavani

Batch:27

Hall-Ticket number:2303A51494

Task1: Statistical Summary for Survey Data

Prompt: Generate a Python function that takes a list of numbers and calculates the mean, minimum, and maximum values. Also display the output



Code:

```
def calculate_statistics(numbers):  
    """  
    Calculates the mean, minimum, and maximum values of a list of numbers.  
  
    Args:  
        numbers (list): A list of numerical values.  
  
    Returns:  
        tuple: A tuple containing (mean, minimum, maximum).  
        Returns (None, None, None) if the list is empty.  
    """  
    if not numbers:  
        return None, None, None  
  
    mean_value = sum(numbers) / len(numbers)  
    min_value = min(numbers)  
    max_value = max(numbers)  
  
    return mean_value, min_value, max_value
```

```

# Example usage:
my_list = [10, 20, 5, 30, 15, 25]
mean, minimum, maximum = calculate_statistics(my_list)

print(f"Original List: {my_list}")
print(f"Mean: {mean}")
print(f"Minimum: {minimum}")
print(f"Maximum: {maximum}")

# Example with an empty list
empty_list = []
mean_empty, min_empty, max_empty = calculate_statistics(empty_list)
print(f"\nOriginal List (empty): {empty_list}")
print(f"Mean: {mean_empty}")
print(f"Minimum: {min_empty}")
print(f"Maximum: {max_empty}")

```

Output:

```

Original List: [10, 20, 5, 30, 15, 25]
Mean: 17.5
Minimum: 5
Maximum: 30

Original List (empty): []
Mean: None
Minimum: None
Maximum: None

```

Explanation:

- Creates a reusable function that computes common statistical measures from a given list of values.
- Includes a well-written docstring that describes the function's objective, parameters, and return values.
- Handles the case where the input list is empty to avoid errors such as division by zero.
- Leverages Python's built-in functions to ensure calculations are both efficient and reliable.
- Shows how the function works by running it on a sample dataset for better understanding.
- Confirms proper handling of edge cases by explicitly testing the function with an empty list.

Task2: Armstrong Number – AI Comparison

Prompt: Write a Python program to check whether a number is an Armstrong number.

Part A: GEMINI AI(Google Colab)

Code:

```
def is_armstrong(number):
    """
    Checks if a given number is an Armstrong number.

    An Armstrong number (also known as a narcissistic number,
    pluperfect digital invariant, or plus perfect number) is a
    number that is the sum of its own digits each raised to the
    power of the number of digits.

    Args:
        number (int): The integer to check.

    Returns:
        bool: True if the number is an Armstrong number, False otherwise.
    """
    if not isinstance(number, int) or number < 0:
        raise ValueError("Input must be a non-negative integer.")

    # Convert number to string to easily get digits and count them
    num_str = str(number)
    n_digits = len(num_str)

    sum_of_powers = 0
    for digit_char in num_str:
        digit = int(digit_char)
        sum_of_powers += digit ** n_digits

    return sum_of_powers == number

# Example usage:
print(f"Is 153 an Armstrong number? {is_armstrong(153)}") # Expected: True (1^3 + 5^3 + 3^3 = 1 + 125 + 27 = 153)
print(f"Is 9 an Armstrong number? {is_armstrong(9)}") # Expected: True (9^1 = 9)
print(f"Is 370 an Armstrong number? {is_armstrong(370)}") # Expected: True (3^3 + 7^3 + 0^3 = 27 + 343 + 0 = 370)
print(f"Is 120 an Armstrong number? {is_armstrong(120)}") # Expected: False (1^3 + 2^3 + 0^3 = 1 + 8 + 0 = 9 != 120)
print(f"Is 1634 an Armstrong number? {is_armstrong(1634)}") # Expected: True (1^4 + 6^4 + 3^4 + 4^4 = 1 + 1296 + 81 + 256 = 1634)


# Test with a non-Armstrong number
non_armstrong = 123
print(f"Is {non_armstrong} an Armstrong number? {is_armstrong(non_armstrong)}")
```

Output:

```
Is 153 an Armstrong number? True
Is 9 an Armstrong number? True
Is 370 an Armstrong number? True
Is 120 an Armstrong number? False
Is 1634 an Armstrong number? True
Is 123 an Armstrong number? False
```


PartB: GitHub Copilot(VS Code)

Code:



```
1 #write a python program to check whether a number is an armstrong number or not.
2 # An Armstrong number is a number that is equal to the sum of its own digits each raised to the power of the number of digits
3 def is_armstrong_number(num):
4     # Convert the number to string to easily iterate over digits
5     str_num = str(num)
6     num_digits = len(str_num)
7
8     # Calculate the sum of each digit raised to the power of num_digits
9     sum_of_powers = sum(int(digit) ** num_digits for digit in str_num)
10
11     # Check if the sum of powers is equal to the original number
12     return sum_of_powers == num
13
14 # Test the function
15 number = 153
16 if is_armstrong_number(number):
17     print(f"{number} is an Armstrong number.")
18 else:
19     print(f"{number} is not an Armstrong number.")
```

Output:



```
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> & C:/Users/Pavani/AppData/Local/Microsoft/WindowsApps/python3.12.exe "c:/Users/Pavani/OneDrive/Documents/AI Assisted coding/lab.py"
153 is an Armstrong number.
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding>
```


Explanation:

- Gemini AI produces clearer and more structured code, while GitHub Copilot gives correct code but with less organization.
- Both tools use functions, but Gemini includes proper input validation, whereas Copilot adds very few safety checks.
- Gemini's code is easier to read due to descriptive variable names and good spacing; Copilot's code is more compact.

- Gemini provides detailed docstrings and inline comments, while Copilot usually includes only minimal comments.
- Gemini follows a direct, step-by-step logic that is easy to understand; Copilot focuses on shorter and optimized expressions.
- Error handling is present in Gemini's code but generally missing in Copilot's output.
- Gemini is more suitable for beginners and learning purposes, while Copilot is better suited for experienced programmers.

Task3: Leap Year Validation Using Cursor AI

Prompt1: Write a Python program to check if a year is a leap year or not.



Code:

```
leap_year.py > ...
1  # A year is a leap year if:
2  # - It is divisible by 4, AND
3  #   - not divisible by 100, UNLESS
4  #   - it is also divisible by 400
5
6  year = int(input("Enter a year: "))
7
8  if (year % 400 == 0) or (year % 4 == 0 and year % 100 != 0):
9      print(f"{year} is a leap year.")
10 else:
11     print(f"{year} is not a leap year.")
```

Output :

```
Problems  Output  Debug Console  Terminal  Ports  powershell
● PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> python leap_year.py
Enter a year: 2016
2016 is a leap year.
● PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> python leap_year.py
Enter a year: 2025
2025 is not a leap year.
○ PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> |
```

Prompt2: Write a clean and optimized Python function to validate leap year with input and output handling.

Code:

```

def is_leap_year(year: int) -> bool:
    """
    Return True if `year` is a leap year, otherwise False.
    Leap year rules:
    - divisible by 4 and not by 100, OR
    - divisible by 400
    """
    return (year % 400 == 0) or (year % 4 == 0 and year % 100 != 0)


def main():
    try:
        raw = input("Enter a year: ").strip()
        year = int(raw)
    except ValueError:
        print("Invalid input. Please enter an integer year (e.g., 2024).")
        return

    if year <= 0:
        print("Year must be a positive integer.")
        return

    if is_leap_year(year):
        print(f"{year} is a leap year.")
    else:
        print(f"{year} is not a leap year.")


if __name__ == "__main__":
    main()

```

Output:

```
Problems Output Debug Console Terminal Ports powershell
ValueError: invalid literal for int() with base 10: ''
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> python leap_year.py
Enter a year: 2023
2023 is not a leap year.
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> python leap_year.py
Enter a year: 2014
2014 is not a leap year.
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> python leap_year.py
Enter a year: 2020
2020 is a leap year.
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> 
```

Explanation:

- The basic version uses nested if–else conditions, which makes the leap year logic easy for beginners to understand.
- The optimized version places the logic inside a function, allowing the code to be reused easily.
- Both versions correctly follow the leap year rules based on divisibility by 4, 100, and 400.
- The optimized code avoids repeated checks and clearly separates the logic from user input and output.
- In summary, the simple code is suitable for learning, while the optimized code is more appropriate for real-world and maintainable applications.

Task4: Student Logic + AI Refactoring (Odd/Even Sum)

Creating Student own code on even Or odd number without using AI


```

21
22
23 #Adding student own code on even or odd number without using AI
24 #Create a function for sum of even numbers and odd numbers
25 def sum_even_odd(numbers):
26     even_sum = 0
27     odd_sum = 0
28
29     for num in numbers:
30         if num % 2 == 0:
31             even_sum += num
32         else:
33             odd_sum += num
34
35     return even_sum, odd_sum
36 # Test the function
37 numbers = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
38 even_sum, odd_sum = sum_even_odd(numbers)
39 print(f"Sum of even numbers: {even_sum}")
40 print(f"Sum of odd numbers: {odd_sum}")
41


```

Output:

```

41

```



The screenshot shows a VS Code interface with a terminal window open. The terminal output is as follows:

```

PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> &
...
C:\Users\Pavani\AppData\Local\Microsoft\WindowsApps\python3.12.exe "c:/Users/Pavani/OneDrive/Documents/A
ing/lab.py"
Sum of even numbers: 30
Sum of odd numbers: 25
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding>

```

Prompt: Refactor this Python code to make it cleaner, more readable, and reusable.

Code:

```
lab.py > ...
23 def is_even(num):
24     return num % 2 == 0
25
26 def sum_numbers_by_type(numbers, type_check):
27     total_sum = 0
28     for num in numbers:
29         if type_check(num):
30             total_sum += num
31     return total_sum
32 # Test the refactored functions
33 even_sum = sum_numbers_by_type(numbers, is_even)
34 odd_sum = sum_numbers_by_type(numbers, lambda x: not is_even(x))
35 print(f"Sum of even numbers: {even_sum}")
36 print(f"Sum of odd numbers: {odd_sum}")
37
38
```

Output:

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> & C
```

```
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding> & C:/Users/Pavani/AppData/Local/Microsoft/Wi  
ing/lab.py"  
Sum of even numbers: 30  
Sum of odd numbers: 25  
PS C:\Users\Pavani\OneDrive\Documents\AI Assisted coding>
```

Ln 33

Explanation:

- Both programs correctly identify even and odd numbers using the modulus (% 2) operation.
- The first program is written in a straightforward way and prints the output directly, which is easy for beginners to follow.
- The second program is better organized because it includes a docstring and returns results instead of printing them inside the function.
- Returning values makes the optimized program more reusable and suitable for larger applications.
- Overall, the first program helps in understanding basic logic, while the second program follows cleaner and more professional coding practices.

