SR UNIVERSITY

**School of Computer Science and Artificial Intelligence**

**Lab Assignment # 10**

**Name of Student: GINNE SAI TEJA**
**Enrollment No: 2303A51526**
**Batch No.: 22**

**Task Description -1(Error Detection and Correction)**
**Use AI to analyze a Python script and correct all syntax and logical errors.**
**Sample Input Code:**
**def calculate_total(nums)**
**sum = 0 for n**
**in nums sum**
**+= n**
**return total**
**Expected Output-1:**
**Corrected and executable Python code with brief explanations of the identified syntax and logic errors.**

**Prompt:**generate a python program to correct the code syntax and logical errors in python syntax and print the output to be corrected and executable code with docstring and comments.

**Code:-**

```python
# Task-1
# generate a python program to correct the code syntax and logical errors in
def calculate_total(nums):
    """
    Calculate the total sum of numbers in a list.

    Args:
        nums: A list of numbers to sum.

    Returns:
        The sum of all numbers in the list.
    """
    # Avoid using 'sum' as variable name since it shadows built-in function
    total = 0
    for n in nums:
        total += n
    return total

# Test the function
if __name__ == "__main__":
    numbers = [10, 20, 30, 40, 50]
    result = calculate_total(numbers)
    print(f"Total sum: {result}")
```

**Output:-**

```
.0-win32-x64\bundled\libs\debugp
Total sum: 150
PS C:\Users\saite\Downloads>
```

**Justification:** The original code had a syntax error due to using 'sum' as a variable name, which is a built-in function in Python. By renaming it to 'total', we avoid this conflict and ensure the code runs correctly. Additionally, the function now includes a docstring that explains its purpose, arguments, and return value, improving code readability and maintainability and the test case demonstrates how to use the function and verifies its correctness.

**Task Description -2(Code Style Standardization)**
**Use AI to refactor Python code to comply with standard coding style guidelines.**
**Sample Input Code: def**
**findSum(a,b):return a+b**
**print(findSum(5,10))**
**Expected Output-2:**
**Well-structured, consistently formatted Python code following standard style conventions.**

**Prompt:-**
generate a python program to comply the standard coding Style and well formatted code with proper indentation, spacing, and naming conventions to enhance code readability and maintainability.

**Code:-**

```
# Task-2
# generate a python program to comply t
def find_sum(a, b):
    """
    Find the sum of two numbers.

    Args:
        a: The first number.
        b: The second number.

    Returns:
        The sum of the two numbers.
    """
    return a + b

print(find_sum(5, 10))
```

**Output:-**

```
xtensions\ms-python.debugpy-202
15
PS C:\Users\saite\Downloads>
```

**Justification:**
The code is now compliant with standard coding style, including proper indentation, spacing, and naming conventions. The function name 'find_sum' is descriptive of its purpose, and the

parameters 'a' and 'b' are clear. The docstring provides a clear explanation of the function's purpose, its arguments, and its return value, enhancing code readability and maintainability. The test case demonstrates how to use the function and verifies its correctness.

**Task Description -3(Code Clarity Improvement)**
**Use AI to improve code readability without changing its functionality.**
**Sample Input Code:**
**def f(x,y): return x-**
**y*2**
**print(f(10,3))**
**Expected Output-3:**
**Python code rewritten with meaningful function and variable names, proper indentation, and improved clarity. Prompt:-**
generate a python program to improve the code efficiency and performance and functionality
**Code:-**

```python
# Task-3
# generate a python program to improve the code efficiency and performance and functionality
def calculate_adjusted_difference(base_value, multiplier):
    """
    Calculate the difference between a base value and twice a multiplier.

    Args:
        base_value: The initial value to subtract from.
        multiplier: The value to multiply by 2 before subtracting.

    Returns:
        The result of base_value minus (multiplier * 2).
    """
    return base_value - multiplier * 2

# Test the function
if __name__ == "__main__":
    result = calculate_adjusted_difference(10, 3)
    print(f"Adjusted difference: {result}")
```

**Output:-**

```
xtensions\ms-python.debugpy-20
Adjusted difference: 4
PS C:\Users\saite\Downloads>
```

**Justification:**
The original code had a syntax error due to using 'sum' as a variable name, which is a built-in function in Python. By renaming it to 'total', we avoid this conflict and ensure the code runs correctly. Additionally, the function now includes a docstring that explains its purpose, arguments, and return value, improving code readability and maintainability and the test case demonstrates how to use the function and verifies its correctness.

**Task Description -4(Structural Refactoring)**

**Use AI to refactor repetitive code into reusable functions.**
**Sample Input Code: print("Hello Ram") print("Hello Sita") print("Hello Ravi")**

**Prompt:-**
generate a python program using reusable functions with modular design to break down the code into smaller, reusable functions that perform specific tasks, to improve code organization and maintainability.

**Code:-**

```
# Task-4
# generate a python program using r
def print_greeting(name):
    print(f"Hello {name}")

print_greeting("Ram")
print_greeting("Sita")
print_greeting("Ravi")
```

**Output:-**

```
Hello Ram
Hello Sita
Hello Ravi
PS C:\Users\saite\Downloads>
```

**Justification:**
The code is now organized into a reusable function 'print_greeting' that takes a name as an argument and prints a greeting message. This modular design allows for better code organization and maintainability, as the greeting logic is encapsulated within a single function that can be easily reused with different names. The test cases demonstrate how to use the function with various inputs, verifying its functionality.

**Task Description -5(Efficiency Enhancement) Use AI to optimize Python code for better performance.**
**Sample Input Code:**
**numbers = [ ] for i in range(1, 500000):**
**numbers.append(i * i)**
**print(len(numbers))**
**Expected Output-5:**
**Optimized Python code that achieves the same result with improved performance.**

**Prompt:**generate a python program to optimize the code with improve the performance and efficiency by using appropriate data structures, algorithms, and built-in functions to optimize the code's performance and efficiency, and show the time complexity of the optimized code.

**Code:-**

```python
# Task-5
# generate a python program to optimize the code with improve the performance
def generate_squares(n):
    """
    Generate squares of numbers from 1 to n-1 using a generator.
    Args:
        n: The upper limit (exclusive) for generating squares.
    Returns:
        A generator object that yields squared values.
    Time Complexity: O(1) for creation, O(n) for full iteration
    Space Complexity: O(1) - uses generator instead of storing all values
    """
    return (i * i for i in range(1, n))
# Optimized approach using generator
if __name__ == "__main__":
    # Generator approach - memory efficient
    squares_gen = generate_squares(500000)
    count = sum(1 for _ in squares_gen)
    print(f"Count of squares: {count}")
    # Alternative: Using list comprehension (if storage needed)
    # squares = [i * i for i in range(1, 500000)]
    # print(len(squares))
```

**Output:-**

```
Count of squares: 499999
PS C:\Users\saite\Downloads>
```

**Justification:-**

Generators yield values lazily on-demand, avoiding storage of all n squares in memory (O(1) space vs O(n)), ideal for large n like 500,000 to prevent memory overflow.Iteration over generator is comparably fast to lists here but scales better under memory pressure.