

Gangula Navyasri

2303A51739

TASK-1

Task 1: Word Frequency from Text File

❖ Scenario:

You are analyzing log files for keyword frequency.

❖ Task:

Use Gemini to generate Python code that reads a text file and counts word frequency, then explains the code.

❖ Expected Output:

➢ Working code

➢ Explanation

➢ Screenshot

The screenshot displays a Jupyter Notebook environment with a Gemini AI integration. The top section shows the Gemini interface with a greeting and several interactive buttons. The bottom section shows two code cells. The first cell contains code to create a sample text file, and the second cell shows Gemini generating Python code to read the file and count word frequencies.

```
sample_text = "This is a sample text file. This file contains sample text.\nLater.\n\nWith open('sample.txt', 'w') as f:\n    f.write(sample_text)\n\nprint('Created \'sample.txt\' with sample content.')\n\nCreated 'sample.txt' with sample content.\n\nNow, let's write the Python code to read the text file, count word frequencies, and display the results. We'll use the collections.Counter module for efficient counting.\n\nfrom collections import Counter\nimport re\n\ndef count_word_frequency(filepath):\n    """\n        Reads a text file and returns a Counter object with word frequencies.\n    """\n    with open(filepath, 'r') as file:\n        text = file.read()\n\n    # Convert to lowercase and remove non-alphanumeric characters\n    words = re.findall(r'\b\w+\b', text.lower())
```

```

# Convert to lowercase and remove non-alphanumeric characters
words = re.findall(r'\b\w+\b', text.lower())
return Counter(words)

# Specify the path to your text file
file_path = 'sample.txt' # Change this to your actual file path

word_counts = count_word_frequency(file_path)

print("Word frequencies in '{}':".format(file_path))
for word, count in word_counts.most_common():
    print("{}: {}".format(word, count))

Word frequencies in 'sample.txt':
'this': 2
'sample': 2
'text': 2
'is': 2
'is': 1
'a': 1
'contains': 1

```

Gemini

generate Python code that reads a text file and counts word frequency.

Sure, I can help you with that! Here's the Python code to read a text file and count the frequency of each word.

The code defines a function to read a text file, sample.txt, for processing. It converts the entire text to lowercase and extracts all alphanumeric words using regular expressions. The collections.Counter module is then used to efficiently count the frequency of each extracted word. The function is called with the sample.txt file, which was pre-populated with example text. Finally, the code iterates through the word counts and prints each word along with its frequency.

TASK-2


❖ Scenario:

You are automating basic file operations.

❖ Task:

Use Cursor AI to generate a program that:

- Creates a text file
 - Writes sample text
 - Reads and displays the content
- ❖ Expected Output:
- Functional code
 - Cursor AI screenshots



```
File Edit Selection View Go Run Terminal Help
AI_ASSISTANT_CODING
23.py x
AI_ASSISTANT_CODING
23.py > ...
3 # Step 1: Create and write sample text to a file
4 filename = "sample.txt"
5 sample_text = """Hello, World!
6 This is a sample text file.
7 Python file operations are simple and powerful.
8 We can write, read, and manipulate files easily."""
9
10 # Write the text to the file
11 with open(filename, 'w') as file:
12     file.write(sample_text)
13
14 print(f"Created and wrote sample text to '{filename}'")
15 print()
16
17 # Step 2: Read and display the content
18 with open(filename, 'r') as file:
19     content = file.read()
20
21 print(f"Content of '{filename}':")
22 print("-" * 50)
23 print(content)
24 print("-" * 50)

Problems Output Debug Console Terminal Ports
Content of 'sample.txt':
-----
Hello, World!
This is a sample text file.
Python file operations are simple and powerful.
We can write, read, and manipulate files easily.
-----
```

OUTLINE TIMELINE PS D:\AI_ASSISTANT_CODING Ctrl+K to generate command Cursor Tab Ls 17, Col 99 Spaces: 4 UTF-8 ENG IN 10:25 AM 1/21/2026

Task 3: CSV Data Analysis

❖ Scenario:

You are processing structured data from a CSV file.

❖ Task:

Use Gemini in Colab to read a CSV file and calculate mean, min, and max.

❖ Expected Output:

➢ Correct output

➢ Screenshot

o=x8IEKrop2ZcU

Gemini

◆ Certainly! Here's a 5-line explanation of the code:

1. The code defines a function to read a text file, `sample.txt`, for processing.
2. It converts the entire text to lowercase and extracts all alphanumeric words using regular expressions.
3. The `(collections.Counter)` module is then used to efficiently count the frequency of each extracted word.
4. The function is called with the `(sample.txt)` file, which was pre-populated with example text.
5. Finally, the code iterates through the word counts and prints each word along with its frequency.

Show me the Python code to count word frequency

Run the word frequency counting code

How can I sort the word counts by frequency

read a CSV file and calculate mean, min, and max.

+ Gemini 2.5 Flash ▶

Gemini can make mistakes, so double-check it and use code with caution. [Learn more](#)

✓ 10:11 Python 3

10:34 AM 1/21/2026

The screenshot shows a Jupyter Notebook interface with a sidebar titled "Gemini". The main area contains Python code to create a sample CSV file and calculate its statistics.

```
import pandas as pd

# Create a sample DataFrame
data = {'Category': ['A', 'B', 'A', 'C', 'B', 'A', 'C'],
        'Value': [10, 25, 15, 30, 20, 12, 35],
        'Quantity': [1, 5, 2, 8, 3, 2, 7]}
df_sample = pd.DataFrame(data)

# Save the DataFrame to a CSV file
df_sample.to_csv('sample_data.csv', index=False)

print("Created 'sample_data.csv' with sample content.")
print(df_sample)
```

Output:

Category	Value	Quantity
A	10	5
B	25	2
A	15	2
C	30	8
B	20	3
A	12	2
C	35	7

Next step:

Now, let's read the `sample_data.csv` file into a pandas DataFrame and calculate the mean, min, and max for a numerical column, for example, the `'Value'` column.

The screenshot shows a Jupyter Notebook interface with a sidebar titled "Gemini". The main area contains Python code to read a CSV file and calculate its statistics.

```
import pandas as pd

# Specify the path to your CSV file
csv_file_path = 'sample_data.csv' # Change this to your actual CSV file path

try:
    # Read the CSV file into a pandas DataFrame
    df = pd.read_csv(csv_file_path)

    print(f"Successfully loaded '{csv_file_path}'. Here's the first few rows:")
    display(df.head())

    # Select a numerical column to calculate statistics (e.g., 'Value')
    # You can change 'Value' to any numerical column in your CSV.
    numerical_column = 'Value'

    if numerical_column in df.columns and pd.api.types.is_numeric_dtype(df[numerical_column]):
        # Calculate mean, min, and max
        mean_value = df[numerical_column].mean()
        min_value = df[numerical_column].min()
        max_value = df[numerical_column].max()

        print(f"\nStatistics for column '{numerical_column}':")
        print(f"Mean: {mean_value:.2f}")
        print(f"Min: {min_value:.2f}")
        print(f"Max: {max_value:.2f}")
    else:
        print(f"\nError: Column '{numerical_column}' not found or is not numeric in the CSV file.")
        print("Available columns: ", df.columns.tolist())

```

The screenshot shows a Google Colab notebook titled "Untitled19.ipynb". The code cell contains the following Python script:

```

print("Mean: {:.2f}")
print("Min: {:.2f}")
print("Max: {:.2f}")
else:
    print(f"\nError: Column '{numerical_column}' not found or is not numeric in the CSV file.")
    print("Available columns: ", df.columns.tolist())
except FileNotFoundError:
    print(f"Error: The file '{csv_file_path}' was not found. Please check the path.")
except Exception as e:
    print(f"An error occurred: {e}")

```

The output of the code shows:

- Successfully loaded 'sample_data.csv'. Here's the first few rows:

	Category	Value	Quantity
0	A	10	1
1	B	25	5
2	A	15	2
3	C	30	8
4	B	20	3

- Statistics for column 'Value':
- Mean: 21.00
- Min: 10.00
- Max: 35.00

The sidebar on the right is titled "Gemini" and shows a conversation with Gemini about reading a CSV file. The bottom status bar indicates "Accept and run" and "Accept".

Task 4: Sorting Lists – Manual vs Built-in

❖ Scenario:

You are reviewing algorithm choices for efficiency.

❖ Task:

Use Gemini to generate:

- Bubble sort
- Python's built-in sort()
- Compare both implementations.
- ❖ Expected Output:
- Two versions of code
- Short comparison

The screenshot shows the Gemini AI interface. At the top, there are tabs for "New Tab" and "CSV files". Below the tabs is a toolbar with icons for search, star, copy, download, and more. Further down are sharing and settings options, along with memory usage indicators for RAM and Disk.

Gemini

N read a CSV file and calculate mean, min, and max.

◆ Okay, I can help with that! Here's the Python code to read a CSV file, then calculate and display the mean, minimum, and maximum values for a numerical column. I'll include a step to create a sample CSV first.

Like Dislike

▶ Accept and run ✓ Accept ✖ Cancel

give a python code for bubble sort

+

Gemini 2.5 Flash ▾ ▶

Gemini can make mistakes, so double-check it and use code with caution. [Learn more](#)

✓ 10:35 Python 3

The screenshot shows a Jupyter Notebook interface with a code cell containing a bubble sort algorithm. The code defines a function `bubble_sort` that takes an array `arr` and sorts it in-place. It includes examples of sorting different lists and printing the original and sorted lists.

```

def bubble_sort(arr):
    n = len(arr)
    # Traverse through all array elements
    for i in range(n):
        # Last i elements are already in place
        for j in range(0, n - i - 1):
            # Traverse the array from 0 to n-i-1
            # Swap if the element found is greater than the next element
            if arr[j] > arr[j + 1]:
                arr[j], arr[j + 1] = arr[j + 1], arr[j] # Swap elements

    return arr

# Example usage:
my_list = [64, 34, 25, 12, 22, 11, 90]
print("Original list:", my_list)

sorted_list = bubble_sort(my_list)
print("Sorted list:", sorted_list)

another_list = [5, 1, 4, 2, 8]
print("Original list:", another_list)

sorted_another_list = bubble_sort(another_list)
print("Sorted list:", sorted_another_list)

```

The output of the code cell shows the original lists and their sorted counterparts.

```

... Original list: [64, 34, 25, 12, 22, 11, 90]
Sorted list: [11, 12, 22, 25, 34, 64, 90]
Original list: [5, 1, 4, 2, 8]
Sorted list: [1, 2, 4, 5, 8]

```

N use python built in function for the same question sort()

◆ You're right! Python has very efficient built-in sorting mechanisms. Here's how you can sort lists using `list.sort()` (which sorts the list in-place) and `sorted()` (which returns a new sorted list).

The screenshot shows a Jupyter Notebook interface with a code cell demonstrating the use of Python's built-in sorting functions. It compares the in-place sorting of a list using `list.sort()` and the creation of a new sorted list using `sorted()`.

```

# Using list.sort() (sorts in-place)
list_to_sort_in_place = [64, 34, 25, 12, 22, 11, 90]
print("Original list (for in-place sort):", list_to_sort_in_place)
list_to_sort_in_place.sort()
print("Sorted list (in-place):", list_to_sort_in_place)

print("\n---")

# Using sorted() (returns a new sorted list)
original_list_for_sorted = [5, 1, 4, 2, 8]
print("Original list (for sorted() function):", original_list_for_sorted)
new_sorted_list = sorted(original_list_for_sorted)
print("New sorted list (from sorted() function):", new_sorted_list)
print("Original list remains unchanged:", original_list_for_sorted)

```

The output of the code cell shows the original lists and the results of using each sorting method.

```

... Original list (for in-place sort): [64, 34, 25, 12, 22, 11, 90]
Sorted list (in-place): [11, 12, 22, 25, 34, 64, 90]

---
Original list (for sorted() function): [5, 1, 4, 2, 8]
New sorted list (from sorted() function): [1, 2, 4, 5, 8]
Original list remains unchanged: [5, 1, 4, 2, 8]

```

Short comparison

Bubble Sort: It's a simple sorting algorithm, but generally inefficient for large datasets ($O(n^2)$ complexity). It sorts by repeatedly stepping through the list, comparing adjacent elements and swapping them.

Python's `list.sort()` and `sorted()`: These are highly optimized and implemented in C, using Timsort (a hybrid stable sorting algorithm with $O(n \log n)$ average and worst-case complexity). They are significantly faster and more memory-efficient for most use cases. `list.sort()` sorts in-place, while `sorted()` returns a new sorted list.