

Name: B Nithin

Hall Ticket No: 2303A51803

Batch:26

SCHOOL OF COMPUTER SCIENCE AND ARTIFICIAL INTELLIGENCE		DEPARTMENT OF COMPUTER SCIENCE ENGINEERING																																					
Program Name: B. Tech		Assignment Type: Lab	Academic Year: 2025-2026																																				
Course Coordinator Name		Dr. Rishabh Mittal																																					
Instructor(s)Name		<table border="1"> <tr><td>Mr. S Naresh Kumar</td><td></td></tr> <tr><td>Ms. B. Swathi</td><td></td></tr> <tr><td>Dr. Sasanko Shekhar Gantayat</td><td></td></tr> <tr><td>Mr. Md Sallauddin</td><td></td></tr> <tr><td>Dr. Mathivanan</td><td></td></tr> <tr><td>Mr. Y Srikanth</td><td></td></tr> <tr><td>Ms. N Shilpa</td><td></td></tr> <tr><td>Dr. Rishabh Mittal (Coordinator)</td><td></td></tr> <tr><td>Dr. R. Prashant Kumar</td><td></td></tr> <tr><td>Mr. Ankushavali MD</td><td></td></tr> <tr><td>Mr. B Viswanath</td><td></td></tr> <tr><td>Ms. Sujitha Reddy</td><td></td></tr> <tr><td>Ms. A. Anitha</td><td></td></tr> <tr><td>Ms. M.Madhuri</td><td></td></tr> <tr><td>Ms. Katherashala Swetha</td><td></td></tr> <tr><td>Ms. Velpula sumalatha</td><td></td></tr> <tr><td>Mr. Bingi Raju</td><td></td></tr> <tr><td>Mr. G. Kranthi</td><td></td></tr> </table>		Mr. S Naresh Kumar		Ms. B. Swathi		Dr. Sasanko Shekhar Gantayat		Mr. Md Sallauddin		Dr. Mathivanan		Mr. Y Srikanth		Ms. N Shilpa		Dr. Rishabh Mittal (Coordinator)		Dr. R. Prashant Kumar		Mr. Ankushavali MD		Mr. B Viswanath		Ms. Sujitha Reddy		Ms. A. Anitha		Ms. M.Madhuri		Ms. Katherashala Swetha		Ms. Velpula sumalatha		Mr. Bingi Raju		Mr. G. Kranthi	
Mr. S Naresh Kumar																																							
Ms. B. Swathi																																							
Dr. Sasanko Shekhar Gantayat																																							
Mr. Md Sallauddin																																							
Dr. Mathivanan																																							
Mr. Y Srikanth																																							
Ms. N Shilpa																																							
Dr. Rishabh Mittal (Coordinator)																																							
Dr. R. Prashant Kumar																																							
Mr. Ankushavali MD																																							
Mr. B Viswanath																																							
Ms. Sujitha Reddy																																							
Ms. A. Anitha																																							
Ms. M.Madhuri																																							
Ms. Katherashala Swetha																																							
Ms. Velpula sumalatha																																							
Mr. Bingi Raju																																							
Mr. G. Kranthi																																							
Course Code	23CS002PC304	Course Title	AI Assisted Coding																																				
Year/Sem	III/I	Regulation	R23																																				
Date and Day of Assignment	Week 6 - Thursday	Time(s)	23CSBTB01 To 23CSBTB52																																				
Duration	2 Hours	Applicable to Batches	All Batches																																				
AssignmentNumber: 12.4 (Present assignment number)/24(Total number of assignments)																																							
Q.No.	Question	ExpectedTime to complete																																					
1	Lab 12 – Algorithms with AI Assistance – Sorting, Searching, and Optimizing Algorithms	Week 6																																					

	Lab Objectives • Apply AI-assisted programming to implement and optimize sorting and searching algorithms. • Compare different algorithms in terms of efficiency and use cases. • Understand how AI tools can suggest optimized code and complexity improvements. Learning Outcome After completing this assignment, students will be able to: • Implement classical algorithms with AI assistance • Compare algorithm efficiency using real-world scenarios • Understand when optimization is necessary • Critically evaluate AI-generated suggestions instead of blindly accepting them	
	Task 1: Bubble Sort for Ranking Exam Scores Scenario You are working on a college result processing system where a small list of student scores needs to be sorted after every internal assessment. Task Description • Implement Bubble Sort in Python to sort a list of student scores. • Use an AI tool to: ◦ Insert inline comments explaining key operations such as comparisons, swaps, and iteration passes ◦ Identify early-termination conditions when the list becomes sorted ◦ Provide a brief time complexity analysis Expected Outcome • A Bubble Sort implementation with: ◦ AI-generated comments explaining the logic ◦ Clear explanation of best, average, and worst-case complexity ◦ Sample input/output showing sorted scores	

```
1 def bubble_sort(scores):
2     n = len(scores)
3     for i in range(n - 1):
4         swapped = False
5         for j in range(n - 1 - i):
6             if scores[j] > scores[j + 1]:
7                 scores[j], scores[j + 1] = scores[j + 1], scores[j]
8                 swapped = True
9         if not swapped:
10             break
11     return scores
12
13 scores = [85, 42, 97, 63, 51, 74, 88]
14 print("Before:", scores)
15 print("After:", bubble_sort(scores))
```

Before: [85, 42, 97, 63, 51, 74, 88]
After: [42, 51, 63, 74, 85, 88, 97]

Task 2: Improving Sorting for Nearly Sorted Attendance Records

Scenario

You are maintaining an **attendance system** where student roll numbers are already *almost sorted*, with only a few late updates.

Task Description

- Start with a Bubble Sort implementation.
- Ask AI to:
 - Review the problem and suggest a more suitable sorting algorithm
 - Generate an **Insertion Sort** implementation
 - Explain why Insertion Sort performs better on nearly sorted data
- Compare execution behavior on nearly sorted input

Expected Outcome

- Two sorting implementations:
 - Bubble Sort
 - Insertion Sort
- AI-assisted explanation highlighting efficiency differences for partially sorted datasets

The screenshot shows a VS Code editor with two Python files: `AAC A 12.4.py` and `BUBBLE SORT IMPLEMENTATION FOR S...`. The `AAC A 12.4.py` file contains the following code:

```

1 import time
2 def bubble_sort(arr):
3     n = len(arr)
4     for i in range(n - 1):
5         swapped = False
6         for j in range(n - 1 - i):
7             if arr[j] > arr[j + 1]:
8                 arr[j], arr[j + 1] = arr[j + 1], arr[j]
9                 swapped = True
10        if not swapped:
11            break
12    return arr
13
14 def insertion_sort(arr):
15     for i in range(1, len(arr)):
16         key = arr[i]
17         j = i - 1
18         while j >= 0 and arr[j] > key:
19             arr[j + 1] = arr[j]
20             j -= 1
21         arr[j + 1] = key
22    return arr
23
24 nearly_sorted = [5, 3, 4, 2, 5, 6, 0, 7, 0, 10]
  
```

The terminal output shows the execution of the code:

```

PS C:\Users\shash\Downloads> & 'c:\Users\shash\anaconda3\envs\shashidhar\python.exe' 'c:\Users\shash\vscode\extensions\ms-python.debugpy-2025.18.0-win32-x64\debugpy\launcher' '53307' '-.' 'c:\Users\shash\Downloads\AAC A 12.4.py'
Before: [85, 42, 97, 63, 51, 74, 88]
After: [42, 51, 63, 74, 85, 88, 97]
PS C:\Users\shash\Downloads> cd 'c:\Users\shash\Downloads'; & 'c:\Users\shash\anaconda3\envs\shashidhar\python.exe' 'c:\Users\shash\vscode\extensions\ms-python.debugpy-2025.18.0-win32-x64\debugpy\launcher' '63307' '-.' 'c:\Users\shash\Downloads\AAC A 12.4.py'
Nearly Sorted Input: [1, 2, 4, 3, 5, 6, 8, 7, 9, 10]
Bubble Sort Result: [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
Bubble Sort Time: 0.000178s
Insertion Sort Result: [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
Insertion Sort Time: 0.000124s
  
```

The AI assistant sidebar on the right shows a list of actions: "Reviewed current file and requested simple Python code", "Reviewed and updated AAC A 12.4.py", and "Updated AAC A 12.4.py". It also includes a "give the code again" button and a "Describe what to build next" prompt.

```
Welcome AAC A 12.4.py
C: > Users > shash > Downloads > AAC A 12.4.py > ...
14 def insertion_sort(arr):
17     j = i - 1
18     while j >= 0 and arr[j] > key:
19         arr[j + 1] = arr[j]
20         j -= 1
21     arr[j + 1] = key
22     return arr
23
24 nearly_sorted = [1, 2, 4, 3, 5, 6, 8, 7, 9, 10]
25
26 print("Nearly Sorted Input:", nearly_sorted)
27
28 data1 = nearly_sorted.copy()
29 start = time.perf_counter()
30 print("Bubble Sort Result:", bubble_sort(data1))
31 print(f"Bubble Sort Time: {time.perf_counter() - start:.6f}s")
32
33 data2 = nearly_sorted.copy()
34 start = time.perf_counter()
35 print("Insertion Sort Result:", insertion_sort(data2))
36 print(f"Insertion Sort Time: {time.perf_counter() - start:.6f}s")

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
● PS C:\Users\shash\Downloads> & 'c:\Users\shash\anaconda3\envs\Shashidhar\python
.18.0-win32-x64\bundle\libs\debugpy\launcher' '53307' '--' 'c:\Users\shash\Down
Before: [85, 42, 97, 63, 51, 74, 88]
After: [42, 51, 63, 74, 85, 88, 97]
● PS C:\Users\shash\Downloads> c:; cd 'c:\Users\shash\Downloads'; & 'c:\Users\sh
e\extensions\ms-python.debugpy-2025.18.0-win32-x64\bundle\libs\debugpy\launcher
Nearly Sorted Input: [1, 2, 4, 3, 5, 6, 8, 7, 9, 10]
Bubble Sort Result: [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
Bubble Sort Time: 0.000178s
Insertion Sort Result: [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
Insertion Sort Time: 0.000124s
● PS C:\Users\shash\Downloads> █
```

Task 3: Searching Student Records in a Database

Scenario

You are developing a **student information portal** where users search for student records by roll number.

Task Description

- Implement:
 - **Linear Search** for unsorted student data
 - **Binary Search** for sorted student data
- Use AI to:
 - Add docstrings explaining parameters and return values
 - Explain when Binary Search is applicable
 - Highlight performance differences between the two searches

Expected Outcome

- Two working search implementations with docstrings
- AI-generated explanation of:
 - Time complexity
 - Use cases for Linear vs Binary Search
- A short student observation comparing results on sorted vs unsorted lists

The screenshot shows a VS Code editor with a Python file named 'roll_numbers.py'. The code implements two search functions: `linear_search` and `binary_search`. The `linear_search` function iterates through the list until it finds the target or returns -1. The `binary_search` function uses a while loop to narrow down the search range until the target is found or returns -1. The code also includes test cases for unsorted and sorted lists, and a target value of 115. The terminal output shows the results of these tests, and a performance comparison table is displayed on the right side of the editor.

```

1 def linear_search(roll_numbers, target):
2     for i in range(len(roll_numbers)):
3         if roll_numbers[i] == target:
4             return i
5     return -1
6
7 def binary_search(roll_numbers, target):
8     low, high = 0, len(roll_numbers) - 1
9     while low <= high:
10        mid = (low + high) // 2
11        if roll_numbers[mid] == target:
12            return mid
13        elif roll_numbers[mid] < target:
14            low = mid + 1
15        else:
16            high = mid - 1
17    return -1
18
19 unsorted = [112, 105, 121, 108, 115, 103, 119]
20 sorted_list = [103, 105, 108, 112, 115, 119, 121]
21 target = 115
22
23 print("Unsorted:", unsorted)
24 print("Sorted:", sorted_list)

```

Terminal Output:

```

PS C:\Users\shash\Downloads> cd 'c:\Users\shash\Downloads'; & 'c:\Users\shash\anaconda\envs\Shashidhar\python.exe' 'c:\Users\shash\vscode\extensions\ms-python.debugpy-2025.18.0-win32-x64\lib\debugpy\launcher' '62305' '-c' 'c:\Users\shash\Downloads\AAC A 12.4.py'
Unsorted: [112, 105, 121, 108, 115, 103, 119]
Sorted: [103, 105, 108, 112, 115, 119, 121]
Searching for roll number: 115
Linear Search: Found at index 4
Binary Search: Found at index 4

Searching for roll number: 999
Linear Search: Not Found
Binary Search: Not Found


```

Performance Comparison:

	Linear Search	Binary Search
Best	$O(1)$	$O(1)$
Average	$O(n)$	$O(\log n)$
Worst	$O(n)$	$O(\log n)$
Requires sorted data	No	Yes

When to use which:

- **Linear Search** — works on unsorted data; suitable when data changes frequently and sorting cost is not justified.



Task 4: Choosing Between Quick Sort and Merge Sort for Data Processing

Scenario

You are part of a **data analytics team** that needs to sort large datasets received from different sources (random order, already sorted, and reverse sorted).

Task Description

- Provide AI with partially written recursive functions for:
 - **Quick Sort**
 - **Merge Sort**
- Ask AI to:
 - Complete the recursive logic
 - Add meaningful docstrings
 - Explain how recursion works in each algorithm
- Test both algorithms on:
 - Random data

- Sorted data
- Reverse-sorted data

Expected Outcome

- Fully functional Quick Sort and Merge Sort implementations
- AI-generated comparison covering:
 - Best, average, and worst-case complexities
 - Practical scenarios where one algorithm is preferred over the other

```

1 import time, random
2 def quick_sort(arr):
3     if len(arr) <= 1:
4         return arr
5     pivot = arr[len(arr) // 2]
6     left = [x for x in arr if x < pivot]
7     middle = [x for x in arr if x == pivot]
8     right = [x for x in arr if x > pivot]
9     return quick_sort(left) + middle + quick_sort(right)
10
11 def merge_sort(arr):
12     if len(arr) <= 1:
13         return arr
14     mid = len(arr) // 2
15     left = merge_sort(arr[:mid])
16     right = merge_sort(arr[mid:])
17     return merge(left, right)
18
19 def merge(left, right):
20     result = []
21     i = j = 0
22     while i < len(left) and j < len(right):
23         if left[i] <= right[j]:
24             result.append(left[i])
25             i += 1
26         else:
27             result.append(right[j])
28             j += 1
29     result.extend(left[i:])
30     result.extend(right[j:])
31     return result
32
33 def test_sort(name, sort_func, data):
34     start = time.perf_counter()
35     result = sort_func(data.copy())
36     elapsed = time.perf_counter() - start
37     print(f"{name}: {elapsed:.6f}s -> {result[-5]...{result[-3:]}")
38
39 random_data = random.sample(range(1, 1001), 500)
40 sorted_data = list(range(1, 501))
41 reverse_data = list(range(500, 0, -1))
42 for label, data in [("Random", random_data), ("Sorted", sorted_data), ("Reverse", reverse_data)]:
43     print(f"\n{label} Data:")
44     test_sort("Quick Sort", quick_sort, data)
45     test_sort("Merge Sort", merge_sort, data)
  
```

Random Data:
 Quick Sort: 0.00021s -> [5, 10, 11, 15, 16]...[996, 997, 998]
 Merge Sort: 0.001611s -> [5, 10, 11, 15, 16]...[996, 997, 998]

Sorted Data:
 Quick Sort: 0.000537s -> [1, 2, 3, 4, 5]...[498, 499, 500]
 Merge Sort: 0.001203s -> [1, 2, 3, 4, 5]...[498, 499, 500]

Reverse Data:
 Quick Sort: 0.000677s -> [1, 2, 3, 4, 5]...[498, 499, 500]

```

19 def merge(left, right):
20     while i < len(left) and j < len(right):
21         if left[i] <= right[j]:
22             result.append(left[i])
23             i += 1
24         else:
25             result.append(right[j])
26             j += 1
27     result.extend(left[i:])
28     result.extend(right[j:])
29     return result
30
31 def test_sort(name, sort_func, data):
32     start = time.perf_counter()
33     result = sort_func(data.copy())
34     elapsed = time.perf_counter() - start
35     print(f"{name}: {elapsed:.6f}s -> {result[-5]...{result[-3:]}")
36
37 random_data = random.sample(range(1, 1001), 500)
38 sorted_data = list(range(1, 501))
39 reverse_data = list(range(500, 0, -1))
40 for label, data in [("Random", random_data), ("Sorted", sorted_data), ("Reverse", reverse_data)]:
41     print(f"\n{label} Data:")
42     test_sort("Quick Sort", quick_sort, data)
43     test_sort("Merge Sort", merge_sort, data)
  
```

Random Data:
 Quick Sort: 0.00021s -> [5, 10, 11, 15, 16]...[996, 997, 998]
 Merge Sort: 0.001611s -> [5, 10, 11, 15, 16]...[996, 997, 998]

Sorted Data:
 Quick Sort: 0.000537s -> [1, 2, 3, 4, 5]...[498, 499, 500]
 Merge Sort: 0.001203s -> [1, 2, 3, 4, 5]...[498, 499, 500]

Reverse Data:
 Quick Sort: 0.000677s -> [1, 2, 3, 4, 5]...[498, 499, 500]
 Merge Sort: 0.001405s -> [1, 2, 3, 4, 5]...[498, 499, 500]

Task 5: Optimizing a Duplicate Detection Algorithm

Scenario


You are building a **data validation module** that must detect duplicate user IDs in a large dataset before importing it into a system.

Task Description

- Write a **naive duplicate detection algorithm** using nested loops.
- Use AI to:
 - Analyze the time complexity
 - Suggest an optimized approach using sets or dictionaries
 - Rewrite the algorithm with improved efficiency
- Compare execution behavior conceptually for large input sizes

Expected Outcome

- Two versions of the algorithm:
 - Brute-force ($O(n^2)$)
 - Optimized ($O(n)$)
- AI-assisted explanation showing how and why performance improved



```
Welcome AAC A 12.4.py
C: > Users > shash > Downloads > AAC A 12.4.py > ...

19
20 user_ids = [101, 203, 305, 101, 407, 203, 509, 305, 611, 407]
21 print("User IDs:", user_ids)
22
23 start = time.perf_counter()
24 result1 = find_duplicates_brute(user_ids)
25 t1 = time.perf_counter() - start
26 print(f"\nBrute Force O(n^2): {result1} Time: {t1:.6f}s")
27
28 start = time.perf_counter()
29 result2 = find_duplicates_optimized(user_ids)
30 t2 = time.perf_counter() - start
31 print(f"Optimized O(n): {result2} Time: {t2:.6f}s")
32 large = random.choices(range(1, 5001), k=10000)
33 start = time.perf_counter()
34 find_duplicates_brute(large)
35 t1 = time.perf_counter() - start
36 start = time.perf_counter()
37 find_duplicates_optimized(large)
38 t2 = time.perf_counter() - start
39 print(f"\nLarge dataset (10000 IDs):")
40 print(f"Brute Force: {t1:.4f}s")
41 print(f"Optimized: {t2:.4f}s")

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
PS C:\Users\shash\Downloads> c:; cd 'c:\Users\shash\Downloads'; & 'c:\Users\shash\anaconda\extensions\ms-python.debugpy-2025.18.0-win32-x64\bundled\libs\debugpy\launcher' '5636
● PS C:\Users\shash\Downloads> c:; cd 'c:\Users\shash\Downloads'; & 'c:\Users\shash\anaconda\extensions\ms-python.debugpy-2025.18.0-win32-x64\bundled\libs\debugpy\launcher' '6420
User IDs: [101, 203, 305, 101, 407, 203, 509, 305, 611, 407]

Brute Force O(n^2): [101, 203, 305, 407] Time: 0.000036s
Optimized O(n): [305, 203, 101, 407] Time: 0.000022s

Large dataset (10000 IDs):
Brute Force: 3.2178s
Optimized: 0.0009s
PS C:\Users\shash\Downloads> 
```

Note: Report should be submitted a word document for all tasks in a single document with prompts, comments & code explanation, and output and if required, screenshots