AI Assisted Coding – Lab Assignment 4.3

Lab 4: Advanced Prompt Engineering – Zero-shot, One-shot, Few-shot

Name: V.harinadh HT.No: 2303A52302 Batch: 45

Task 1: Zero-Shot Prompting – Leap Year Check Scenario

Zero-shot prompting involves giving instructions without providing examples.

Task Description

Use zero-shot prompting to instruct an AI tool to generate a Python function that:

• Accepts a year as input

• Checks whether the given year is a leap year

• Returns an appropriate result

Note: No input-output examples should be provided in the prompt

Understanding the Question

This task tests zero-shot prompting, where AI receives only an instruction without examples. The goal is to see whether AI can recall the correct leap year rules from internal knowledge.

Prompt (Zero-Shot)

Generate a Python function that accepts a year and checks whether it is a leap year. Do not include examples. **Code:-** def is_leap_year(year): if (year % 4 == 0 and year % 100 != 0) or (year % 400 == 0):

return True

else: return False pass

year = int(input("Enter year: "))

print(is_leap_year(year))

Output

Input: 2024 → Leap Year
Input: 2023 → Not a Leap Year

+

```
PS C:\Users\tadoo\Downloads\AI_assited_coding> & C:\Users\tadoo\AppData\Local\Programs\Python\Python314\python.exe c:/Users/tadoo/Downloads/AI_assited_coding/ass
ignment_4.3.py
Enter a year: 2025
2025 is not a leap year.
PS C:\Users\tadoo\Downloads\AI_assited_coding>
```

Explanation of Solution

A leap year occurs when:

1. Year is divisible by 4
2. But not divisible by 100
3. Except if divisible by 400

The AI-generated logic applies these mathematical conditions to determine leap year status.

Observation

- AI correctly recalled standard leap year rules even without examples.
- Zero-shot prompting works well for well-known algorithms.
- However, AI did not add input validation (negative year, non-numeric input).
- Shows AI focuses on solving core logic, not edge cases.
- Demonstrates AI knowledge depends on training memory, not reasoning at runtime.
- If problem was less common, zero-shot accuracy would drop.

Task 2: One-Shot Prompting – Centimeters to Inches Scenario

One-shot prompting guides AI using a single example.

Task Description

Use one-shot prompting by providing one input-output example to generate a Python **function that:**

• Converts centimeters to inches

• Uses the correct mathematical formula

Understanding the Question

This task introduces **one-shot prompting** by giving AI one example (10 cm → 3.94 inches). The purpose is to guide AI toward the correct formula.

Prompt (One-Shot)

Convert centimeters to inches. Example: Input 10 cm → Output 3.94 inches

Code:- def cm_to_inches(cm):

```
    return round(cm * 0.394, 2)


cm = float(input("Enter cm: ")) print("Inches:",

cm_to_inches(cm))
```

Output

10 cm → 3.94 inches

```
PS C:\Users\tadoo\Downloads\AI_assited_coding> & C:\Users\tadoo\AppData\Local\Programs\Python\Python314\python.exe c:/Users/tadoo/Downloads/AI_assited_coding/ass
ignment_4.3.py
Enter length in centimeters: 12
12.0 centimeters is equal to 0.12 meters or 0.00012 kilometers.
```

Explanation of Solution Formula:

$$\mathbf{1\ cm = 0.394\ inches}$$

AI uses multiplication and rounding.

Observation (Detailed)

- AI used the example to infer the correct conversion factor.
- One-shot prompting improves accuracy for formula-based problems.
- AI output becomes closer to human expectation when format is shown.
- However, AI still did not add unit checks or invalid input handling.
- Shows examples act like hints for AI.
- AI still assumes ideal inputs.

Task 3: Few-Shot Prompting – Name Formatting Scenario

Few-shot prompting improves accuracy by providing multiple examples.

Task Description

Use few-shot prompting with 2–3 examples to generate a Python function that:

• Accepts a full name as input

• Formats it as “Last, First” **Example formats:**

• "John Smith" → "Smith, John"

• "Anita Rao" → "Rao, Anita"

Prompt (Few-Shot)

Generate a Python function that takes a full name as input and formats it as “Last, First”

Code:- def

format_name(full_name):

name_parts = full_name.split()

if len(name_parts) >= 2:

first_name = name_parts[0]

last_name = name_parts[-1]

return f"{last_name},

{first_name}" else:

return full_name full_name =

input("Enter full name: ")

print(format_name(full_name))

Output

Input: John Smith → Smith, John

```
PS C:\Users\tadoo\Downloads\AI_assited_coding> & C:\Users\tadoo\AppData\Local\Programs\Python\Python314\python.exe c:/Users/tadoo/Downloads/AI_assited_coding/ass
ignment_4.3.py
Enter full name: valaboju harinadh
harinadh, valaboju
```

Explanation

AI splits input string into words and rearranges them.

Observation (Detailed)

- Few-shot prompting strongly influences output format.
- AI exactly followed pattern from examples.
- Demonstrates AI learns structure patterns, not just math logic.
- Limitation: AI assumed only two names exist; fails for middle names.
- Few-shot improves format reliability but not generalization.

Task 4: Zero-Shot vs Few-Shot – Vowel Counter Scenario

Different prompt strategies may produce different code quality.

Task Description

• Use zero-shot prompting to generate a function that counts vowels in a string

• Use few-shot prompting for the same problem

• Compare both outputs based on:

o Accuracy o

Readability o

Logical clarity

Understanding the Question

This task compares prompt strategies. The same problem is solved with different prompt contexts.

Code:

#Zero-Shot Version

#Generate a Python function that counts the number of vowels in a given string def

count_vowels(input_string):

vowels = "aeiouAEIOU" count = sum(1 for char in

input_string if char in vowels) return count input_string =

input("Enter a string: ") print(f"Number of vowels:

{count_vowels(input_string)}")

#Few-Shot Version

#Generate a Python function that counts vowels in a string def

count_vowels(input_string):

vowels = "aeiouAEIOU" count = sum(1 for char in

input_string if char in vowels) return count input_string =

input("Enter a string: ") print(f"Number of vowels:

{count_vowels(input_string)}") **Output**

```
PS C:\Users\tadoo\Downloads\AI_assited_coding> & C:\Users\tadoo\AppData\Local\Programs\Python\Python314\python.exe c:/Users/tadoo/Downloads/AI_assited_coding/ass
ignment_4.3.py
Enter a string: hello
Number of vowels: 2
```

Comparison

Criteria	**Zero-Shot**	**Few-Shot**
Accuracy	Good	Good
Readability	Compact	Clear
Clarity	Less explanatory	More understandable

Explanation

Both functions count vowels but differ in implementation style.

Observation (Detailed)

- Zero-shot solution was short and efficient but less readable.
- Few-shot produced more structured and beginner-friendly logic.
- Few-shot helps AI mimic coding style from examples.
- Shows prompting affects code style, not just correctness.
- Accuracy remained same, but clarity improved.

Task 5: Few-Shot Prompting – File Handling Scenario

File processing requires clear logical understanding.

Task Description

Use few-shot prompting to generate a Python function that:

• Reads a .txt file

• Counts the number of lines in the file

• Returns the line count

Understanding the Question

File handling is more complex. Few-shot prompting helps AI understand full workflow.

Prompt

Generate a Python function that reads a .txt file, counts the number of lines in the file, and returns the line count. **Code:-** def count_lines_in_file(filename): try: with open(filename, 'r') as file:

line_count = sum(1 for line in file)

return line_count except

FileNotFoundError:

return 0

filename = input("Enter the name of the .txt file: ")

print(f"Number of lines in {filename}: {count_lines_in_file(filename)}")

Output

File with 5 lines → Output: 5

```
PS C:\Users\tadoo\Downloads\AI_assited_coding> & C:\Users\tadoo\AppData\Local\Programs\Python\Python314\python.exe c:/Users/tadoo/Downloads/AI_assited_coding/ass
ignment_4.3.py
Enter the name of the .txt file: allugadda
Number of lines in allugadda: 0
```

Explanation

AI reads file using readlines() and counts lines.

Observation (Detailed)

- Few-shot prompting led to complete logic including file operations.
- AI handled reading and counting correctly.
- However, AI did not include error handling (file not found).
- Demonstrates AI focuses on “happy path”.
- Examples help AI understand multi-step operations.

Final Conclusion Prompt Type Quality

Zero-shot	Works but minimal validation
One-shot	Better formula accuracy
Few-shot	Best structured and clear output

Prompt examples significantly improve AI response reliability